



ROUND OR SQUARE BOTTOM
CASTELLATION OPTIONAL

REVIEWER SYMBOLS:
ARMY - AR
AIR FORCE - 82
DLA - 1S

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government operation, the United States Government thereby incurs no responsibility, nor any obligation, and the fact that the Government may have furnished, furnished, or in any way applied the said drawings, specifications, or other data is not to be regarded as an endorsement or approval in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any actual invention that may in any way be related thereto.

AN PART NO.	THREAD T	ULTIMATE TENSILE STRENGTH MINIMUM POUNDS		(a)							
		STEEL	AL ALLOY	A ⑩	B APPROX	E	H	J +1/32 -0	M	R	
AN310-3	NO. 10-32UNF-3B	2,210	1,100	.375 +.002 -.010	7/16	7/64	1/4	5/64	.110	3/32	
AN310-4	1/4 -28UNF-3B	4,080	2,030	.438 +.002 -.010	1/2	1/8	9/32	5/64	.125	3/32	
AN310-5	5/16 -24UNF-3B	6,500	3,220	.500 +.002 -.010	37/64	11/64	21/64	5/64	.172	3/32	
AN310-6	3/8 -24UNF-3B	10,100	5,020	.563 +.002 -.010	21/32	7/32	13/32	1/8	.218	3/32	
AN310-7	7/16 -20UNF-3B	13,600	6,750	.625 +.002 -.011	23/32	17/64	29/64	1/8	.265	3/32	
AN310-8	1/2 -20UNF-3B	18,500	9,180	.750 +.002 -.012	7/8	23/64	9/16	1/8	.359	1/8	
AN310-9	9/16 -18UNF-3B	23,600	11,700	.875 +.002 -.012	1- 1/64	25/64	39/64	5/32	.390	5/32	
AN310-10	5/8 -18UNF-3B	30,100	14,900	1.000 +.002 -.014	1- 5/32	15/32	23/32	5/32	.468	5/32	
AN310-12	3/4 -16UNF-3B	44,000	21,800	1.125 +.002 -.016	1-19/64	9/16	13/16	5/32	.562	3/16	
AN310-14	7/8 -14UNF-3B	60,000	29,800	1.313 +.002 -.017	1-33/64	21/32	29/32	5/32	.656	3/16	
AN310-15	1 -12UNF-3B	80,700	40,000	1.500 +.002 -.017	1-47/64	3/4	1	5/32	.750	3/16	
(b) AN310-16	1 -14NF-3	80,700	40,000	1.500 +.002 -.019	1-47/64	3/4	1	5/32	.750	3/16	
AN310-18	1-1/8-12UNF-3B	101,800	50,500	1.688 +.002 -.021	1-61/64	13/16	1-5/32	5/32	.844	1/4	
AN310-20	1-1/4-12UNF-3B	130,200	64,400	1.875 +.002 -.023	2-11/64	7/8	1-1/4	5/32	.938	1/4	

- (a) FOR ALUMINUM ALLOY NUTS LARGER THAN -5 SIZE, TOLERANCES ON DIMENSION "A" MAY CONFORM TO APPLICABLE MATERIAL SPECIFICATIONS FOR BAR AND ROD.
- (b) 1-14NF THREAD SIZE INACTIVE FOR DESIGN AFTER 27 MARCH 1967.

⑩ FOR CHANGES, SEE PAGE 1

DISTRIBUTION STATEMENT: A - For public release, distribution is unlimited.
NOTE: This drawing is the property of the Air Force and Navy Departments and is loaned to you for your use only. It is not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without the prior written permission of the Air Force and Navy Departments. This drawing is to be used only for the procurement of aeronautical supplies, and the design is not to be used for any other purpose after the latest date of approval shown.
ANSC N/A

P.A NAVY - AS CUSTODIANS: ARMY - AV NAVY - AS AIR FORCE - 99	AIRFORCE NAVY AERONAUTICAL STANDARD		AN 310
	NUT, PLAIN, CASTELLATED, AIRFRAME		
PROCUREMENT SPECIFICATION FF-N-836	SUPERSEDES:	AN355	SHEET 1 OF 2

APPROVED 5 JUL 43 REVISED 8 29 DEC 72 9 25 FEB 91 10 17 MAY 91

REVIEWER SYMBOLS:
ARMY - AR
AIR FORCE - 82
DLA - 15

NOTICE: When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have furnished, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded as implying or otherwise in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

NOTICE: This drawing was approved by joint action of the Air Force and Navy Departments as the Air Force - Navy Standard for this product. This drawing incorporates all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new design not later than 6 months after the latest date of approval shown.

NOTES:

1. MATERIAL: STEEL, ALUMINUM ALLOY AND 300 SERIES CORROSION-RESISTANT STEEL. SEE PROCUREMENT SPECIFICATION. (400 SERIES CRES INACTIVE FOR DESIGN AFTER 1 JAN 1992).
2. FINISH: STEEL-CADMIUM PLATING PER QQ-P-416, TYPE II, CLASS 2. PARTS WITH CLASS 3 PLATING MAY BE FURNISHED FROM SUPPLIER'S STOCK UNTIL 1 JANUARY 1975. ALUMINUM ALLOY-ANODIZE IN ACCORDANCE WITH MIL-A-8625, TYPE II. CORROSION RESISTANT STEEL-PASSIVATE IN ACCORDANCE WITH QQ-P-35.
3. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: FRACTIONS $\pm 1/64$, DECIMALS $\pm .010$, ANGLES $\pm 1^\circ$.
4. REMOVE ALL BURRS.
5. EXAMPLES OF PART NUMBERS: AN310-5 = STEEL NUT, 5/16-24 UNF-3B.
AN310D5 = ALUMINUM ALLOY NUT, 5/16-24UNF-3B.
AN310C5 = CORROSION-RESISTANT STEEL NUT, 5/16-24UNF-3B.
6. ADD D BEFORE DASH NUMBER FOR ALUMINUM ALLOY NUTS.
ADD C BEFORE DASH NUMBER FOR CORROSION-RESISTANT STEEL NUTS.
7. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
8. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THIS ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DDOISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

INTERCHANGEABILITY RELATIONSHIP: AN310 NUTS ARE UNIVERSALLY INTERCHANGEABLE WITH AN355 NUTS. AN355 NUTS ARE NOT INTERCHANGEABLE WITH AN310 NUTS.

INTERCHANGEABILITY TABLE	
CANCELLED	UNIVERSALLY INTERCHANGEABLE
AN355-3	AN310-3
AN355-4	AN310-4
AN355-5	AN310-5
AN355-6	AN310-6
AN355-7	AN310-7
AN355-8	AN310-8
AN355-9	AN310-9
AN355-10	AN310-10
AN355-12	AN310-12

APPROVED 5 JUL 43 REVISED 8 29 DEC 72 9 25 FEB 91 10 17 MAY 91

P.A NAVY - AS CUSTODIANS. ARMY - AY NAVY - AS AIR FORCE - 99	AIRFORCE NAVY AERONAUTICAL STANDARD	AN310
	NUT, PLAIN, CASTELLATED, AIRFRAME	
PROCUREMENT SPECIFICATION FF-N-836	SUPERSEDES: AN355	SHEET 2 OF 2