

User activities: ME, AV
Navy - AS
Air Force - 99
DLA-CS

Review activities: ME, AV
Navy - AS
Air Force - 99
DLA-CS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

FED. SUP. CLASS 4730	
<p>MATERIAL: COPPER ALLOY; ALUMINUM ALLOY; CORROSION RESISTANT STEEL (CRES); TITANIUM ALLOY; BARS, SHAPES OR FORGINGS (SEE PROCUREMENT SPECIFICATION). FINISH: SEE PROCUREMENT SPECIFICATION. NO CODE LETTER IN PART NUMBER FOR COPPER ALLOY.</p> <p>⑦ ADD D AFTER DASH NUMBER FOR ALUMINUM ALLOY (EXCEPT 7075-T73). ADD C AFTER DASH NUMBER FOR CRES, TYPE 302, 303, 304, 316, AND 321. ADD J AFTER DASH NUMBER FOR CRES, TYPE 304. ADD K AFTER DASH NUMBER FOR CRES, TYPE 316. ADD S AFTER DASH NUMBER FOR CRES, TYPE 304 AND 316. PARTS ARE NOT TO BE MANUFACTURED FROM TYPE 304L STEEL AFTER 10 FEBRUARY 1967. ADD T AFTER DASH NUMBER FOR TITANIUM ALLOY.</p> <p>⑦ ADD W AFTER DASH NUMBER FOR 7075-T73 ALUMINUM ALLOY. TITANIUM IS NOT RECOMMENDED FOR USE IN OXYGEN SYSTEMS.</p> <p>⑦ ITEMS CODED C ON PREVIOUS ISSUES OF THIS STANDARD ARE NO LONGER TO BE FURNISHED. PROCURING ACTIVITIES MUST SPECIFY APPLICABLE CRES MATERIAL CODE AS PART OF THE STANDARD PART NUMBER.</p> <p>EXAMPLE OF PART NUMBERS: AN846-6 - ELBOW, 3/8 ID HOSE, COPPER ALLOY. ⑦ AN846-6D - ELBOW, 3/8 ID HOSE, ALUMINUM ALLOY (EXCEPT 7075-T73). AN846-6C - ELBOW, 3/8 ID HOSE, CRES, TYPE 302, 303, 304, 316, OR 321. AN846-6J - ELBOW, 3/8 ID HOSE, CRES, TYPE 304. AN846-6K - ELBOW, 3/8 ID HOSE, CRES, TYPE 316. AN846-6S - ELBOW, 3/8 ID HOSE, CRES, TYPE 316. AN846-6T - ELBOW, 3/8 ID HOSE, TITANIUM ALLOY. ⑦ AN846-6W - ELBOW, 3/8 ID HOSE, 7075-T73 ALUMINUM ALLOY.</p> <p>BREAK ALL SHARP EDGES AND REMOVE ALL HANGING BURRS AND SLIVERS. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: FRACTIONS $\pm 1/64$, DECIMALS $\pm .005$, ANGLES $\pm 1/2^\circ$. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.</p>	
⑦ denotes changes	
P.A. Air Force-99 Other Cust	international interest AIR FORCE-NAVY AERONAUTICAL STANDARD ELBOW, HOSE, 45°
Procurement Specification MIL-F-5509	SUPERSEDES: PAGE 1 OF 2
AN846	

FED. SUP. CLASS
4730User activities: Army - ME, AV
Navy - AS
Air Force - 99Review activities: Army - ME, AV
Navy - AS
Air Force - 99
DLA-CS

Approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

DASH NO.	HOSE ID	A	B	THREAD C (REF)	D +3/64 -0	E	F	H RAD	J DIA	L APPROX
4	1/4	1-15/16	7/16	7/16-20UNJF-3A	2-17/64	5/32	7/16	1/16	7/16	1/4
6	3/8	1-31/32	15/32	9/16-18UNJF-3A	2-13/32	3/16	9/16		9/16	3/8
8	1/2	2	1/2	3/4-16UNJF-3A	2-1/2	7/32	3/4		3/4	7/16
10	5/8	2-1/32	17/32	7/8-14UNJF-3A	2-41/64		7/8	3/32	7/8	1/2
12	3/4	2-1/16	9/16	1-1/16-12UNJ-3A	2-45/64	1/4	1-1/16		1-1/16	9/16
16	1			1-5/16-12UNJ-3A	2-3/4		1-5/16		1-5/16	11/16
20	1-1/4			1-5/8-12UNJ-3A	2-15/16	9/32	1-5/8	1/8	1-5/8	1
24	1-1/2			1-7/8-12UNJ-3A	3		1-7/8		1-7/8	1-1/8

DASH NO.	M +3/64 -0	P APPROX	R RAD	S DIA	U RAD	Y +3/64 -0	Z +3/64 -0	WEIGHT MAX (LBS.)			
								COPPER ALLOY	AL ALLOY	CRES	TI ALLOY
4	1-39/64	7/32	7/32	5/8	1/16	1-41/64	2-19/64				
6	1-21/32	9/32	9/32	13/16		1-23/32	2-15/32				
8	1-11/16	11/32	3/8	1	3/32	1-49/64	2-37/64				
10	1-47/64	7/16	7/16	1-1/4		1-27/32	2-3/4				
12	1-49/64	1/2	17/32	1-7/16	1/8	1-57/64	2-53/64				
16	1-53/64	9/16	21/32	1-11/16		2-1/64	2-15/16				
20	1-59/64	11/16	13/16	2-1/16		2-9/64	3-5/32				
24	1-31/32	3/4	15/16	2-3/8	3/16	2-1/4	3-9/32				

REVISED ⑦ For changes see page 1. 20 MAR 79

APPROVED 20 FEB 42

P.A.
Air Force-99
Other CustInternational
Interest

AIR FORCE - NAVY AERONAUTICAL STANDARD

ELBOW, HOSE, 45°

AN846

Procurement Specification
MIL-F-5509

SUPERSEDES:

PAGE 2 OF 2

DD FORM 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

4730-0968