



DIMENSION TABLE									
DASH NOS.	A	B	C	D	DASH NOS.	A	B	C	D
8	1/2	.063	5/16	1/16	32	2	.080	5/16	3/32
10	5/8	.063	5/16	1/16	34	2-1/8	.080	1/2	3/32
12	3/4	.063	5/16	1/16	36	2-1/4	.080	1/2	3/32
14	7/8	.063	5/16	1/16	38	2-3/8	.080	1/2	3/32
16	1	.063	5/16	1/16	40	2-1/2	.080	1/2	3/32
18	1-1/8	.063	5/16	1/16	44	2-3/4	.090	1/2	3/32
20	1-1/4	.063	5/16	1/16	48	3	.090	1/2	3/32
22	1-3/8	.063	5/16	1/16	52	3-1/4	.090	1/2	3/32
24	1-1/2	.063	5/16	3/32	56	3-1/2	.090	1/2	3/32
26	1-5/8	.080	5/16	3/32	60	3-3/4	.090	1/2	3/32
28	1-3/4	.080	5/16	3/32	64	4	.090	1/2	3/32
30	1-7/8	.080	5/16	3/32	68	4-1/4	.090	1/2	3/32

EXAMPLE OF PART NUMBER: AN996-8 = LOCK RING, WITH 1/2 INCH I.D.

- ① MATERIAL: CARBON, FINISH SPECIFICATION QQ-W-470
- ① FINISH: CADMIUM PLATE, SPECIFICATION QQ-I-416, TYPE II, CLASS 3, OR ZINC PLATE, SPECIFICATION QQ-Z-354, TYPE II, CLASS 3
- DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES DECIMALS ±.010, FRACTIONS ± 1/64.
- ② INACTIVE FOR DESIGN AFTER 15 APRIL 1974
NO SUPERSEDING STANDARD

PROCUREMENT SPECIFICATION
NONE

ARMY-NAVY AERONAUTICAL STANDARD

RING - LOCK

AN996

ARMY AIR FORCES STOCK CLASSIFICATION Q1-A

NOTE: This drawing was approved by Joint Chiefs of Staff and approved by the War and Navy Departments as a standard for the Army, Navy, and Air Force. It is hereby approved for use by the procurement of Government agencies and is hereby approved for use by the procurement of Government agencies. It is hereby approved for use by the procurement of Government agencies. It is hereby approved for use by the procurement of Government agencies.

APPROVED 2-4-72 REVISED ① 15 JUNE 66 2:15 APR 74