INCH-POUND

AN3362 REVISION 6 27 October 1999 SUPERSEDING REVISION 5 30 August 1957

#### **DETAIL SPECIFICATION SHEET**

RELAY, 100 AMP, 2PST, UNSEALED, CLASS O, TYPE II

INACTIVE FOR NEW DESIGN AFTER 30 AUGUST 1957

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-6106.





FIGURE 1. Configurations and dimensions.

# AN3362 REVISION 6



Inches	mm
.010	0.25
.062	1.57
.093	2.36
.250	6.35
.265	6.73
.281	7.14
.375	9.53
.406	10.31
.562	14.27
.594	15.09
1.350	34.29
2.062	52.37
2.100	53.34
2.574	65.38
2.606	66.19
2.656	67.46
2.937	74.60
3.00	76.20
3.406	86.51
3.625	92.08

# NOTES:

- 1. Dimensions are in inches.
- 2. Metric equivalents are given for general information only.
- 3. Unless otherwise specified, tolerance is  $\pm$  .010.

FIGURE 1. Configurations and dimensions - Continued.

### AN3362 REVISION 6

### **REQUIREMENTS:**

Operating cycles: 50,000 minimum.

Contact data:

Contact voltage drop:

Initial: 0.150 volt maximum. After life: 0.175 volt maximum.

Load ratings: See Table I.

TABLE I Rated contact load (per pole).

Type of load	Amperes
Resistive (DC) Resistive (AC 400 Hz, 115 volts) Inductive Motor (DC) Motor (AC 400 Hz, 115 volts)	100 75 80 80 65

### Coil data:

Nominal coil voltage: Rated.

Maximum operating voltage: 29 volts.

Pickup voltage: 20 volts.

Hold voltage: 7 volts.

Dropout voltage: 1.5

Rated duty: Continuous.

Coil current: 0.6 amperes

Physical data:

Weight: 1.5 pounds maximum.

Part or Identifying Number (PIN): AN3362-1

# AN3362 REVISION 6

Custodians: Army - AV Air Force - 11 DLA - CC

Preparing activity: DLA - CC

(Project 5945-1068)