

AN PART NO.	RANGE LB/HR	FUNCTION	RECEPTACLE	POINTERS ANDIOLOL	B ±1/8
AN5528-1	100-1000			-3	
AN5528-2	100-1500	SINGLE	AND10066-145-2P	-3	2-7/8
AN5528-3	100-2000			-3	
an5528-7	300-3000			-3	
AN5528-4-12	100-1000			-11, -12	
AN5528-4-34	100-1000			-13, -1h]
AN5528-5-12	100-1500	DUAL	AND10066-168-1P	-11, -12	4-3/4
AN5528-5-34	100-1500			-13, -1h	
AN5528-6-12	100-2000			-11, -12	
AN5528-6-34	100-2000			-13, -3h	
AN5528-8-12	300-3000			-11, -12	
AN5528-8-34	300-3000			-13, -14	ļ

PART NUMBERS SHOWN ARE FOR INSTRUMENTS WITH ATTACHED HISERT NUTS.

ADD T BEFORE DASH NUMBER FOR INSTRUMENTS WITH REMOVABLE SPRING NUTS.

EXAMPLES OF PART NUMBERS:

AN5528-1 = 100-1000 LB/HR INSTRUMENT WITH ATTACHED INSERT NUTS. AN5528T1 = 100-1000 LB/HR INSTRUMENT WITH REMOVABLE SPRING NUTS. APR

REVISED (A)

<u>ئ</u>

APPROVED

DIMENSIONS IN INCHES.

(A) CANCELED AFTER 6 APRIL 1979 NO SUPERSEDING STANDARD.

PROCUMEMENT SPECIFICATION	AIR FORCE-NAVY AERONAUTICAL STANDARD	ANIEEOO
AN-F-41	INDICATOR - FUEL FLOWMETER, 1-7/8 INCH DIAL	AN5528