NOTE: This drawing was approved by joint action of the War and Navy Departments as the Army-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies, or for use in new design, not later than six months after the latest date of approval shown. It may be put into effect, however, at an earlier date after promulgation.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

NOTICE: No deviation from this drawing permitted except as a war emergency measure and then only after formal authorization from the Air Technical Service Command or the Bureau of Aeronautics through the Procuring Service's District Representative.

PROCUREMENT SPECIFICATION
NONE

ARMY-NAVY AERONAUTICAL STANDARD

ADAPTER - BRITISH TO ARMY OR NAVY SUPPLY OXYGEN UNION

AN6006

SUPERSEDES AAF DRAWING 42A6883

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969 - 341-515/A-4052



MATERIAL: BRASS, COMP. B 1/2 HARD, SPEC. QQ-B-611.

BREAK SHARP EDGES .010 MAXIMUM.

ASSEMBLY MUST BE CLEAN, DRY, AND FREE FROM OIL, GREASE, AND OTHER FOREIGN MATTER.

DIMENSIONS IN INCHES. TOLERANCES: FRACTIONS ±1/64, DECIMALS ±.005, ANGLES ±1/2°, UNLESS OTHERWISE SPECIFIED.

FSC 1660

③ CANCELED AFTER 10 MAY 1968

NO SUPERSEDING STANDARD

APPROVED 4 Apr 42 REVISED ① 11 Feb 44 ② 17 Nov 44 ③ 10 MAY 68

Downloaded from http://www.everyspec.com