



④					
AN PART NO.	TUBING OD	RATED FLOW CAPACITY GPM	A ±1/32	(a) B	C MIN
AN6207-4	1/4	1.2	1-17/32	.688 $\begin{smallmatrix} +.003 \\ -.006 \end{smallmatrix}$	7/8
AN6207-5	5/16	2.3	1-3/4	.813 $\begin{smallmatrix} +.003 \\ -.006 \end{smallmatrix}$	1
AN6207-6	3/8	3.5	1-3/4	.813 $\begin{smallmatrix} +.003 \\ -.006 \end{smallmatrix}$	1
AN6207-8	1/2	6.0	2-7/32	1.063 $\begin{smallmatrix} +.003 \\ -.006 \end{smallmatrix}$	1
AN6207-10	5/8	10.5	2-13/32	1.125 $\begin{smallmatrix} +.003 \\ -.006 \end{smallmatrix}$	1
AN6207-12	3/4	16.0	2-3/4	1.438 $\begin{smallmatrix} +.003 \\ -.006 \end{smallmatrix}$	1
AN6207-16	1	29.0	3-5/16	1.688 $\begin{smallmatrix} +.008 \\ -.016 \end{smallmatrix}$	1

- ④ (a) AT OPTION OF THE MANUFACTURER, DIMENSION "B" MAY BE MADE TO CONFORM TO DIMENSION "E" OF DRAWING AND10056.
DIMENSIONS IN INCHES.
- ④ FOR ACCEPTABLE PRODUCTS SEE ANA BULLETIN NO. 153.