

ON STATEMENT A Approved for public release, distribution is unlimited

NOTE: This drawing was approved by joint action of the Air Force and Navy Departments as the Air Force-Navy standard for this product. This drawing supersedes all standard drawings for the same product and shall be effective for the procurement of commercial supplies, or for use in new design, for later than 6 months after the release date of approval shown.

NOTE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a specific Government operation, the United States Government thereby incurs no responsibility for any obligation whatsoever, and it is hereby authorized that the United States Government may reproduce and distribute reprints for Government purposes, not withstanding any copyright notation that may appear hereon.

NOTE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a specific Government operation, the United States Government thereby incurs no responsibility for any obligation whatsoever, and it is hereby authorized that the United States Government may reproduce and distribute reprints for Government purposes, not withstanding any copyright notation that may appear hereon.

FED. SUP CLASS.  
5306

SECTION THRU THREAD PROFILE

K + .000 -.060	PART NO	L	K + .000 -.060	PART NO	L	K + .000 -.060	PART NO	L	K + .000 -.060	PART NO	
.938	(A)	AN101506	1.875	1.000	AN101520	3.250	2.375	AN101531	5.000	4.125	AN101545
1.000	125	AN101507	2.000	1.125	AN101521	3.375	2.500	AN101532	5.125	4.250	AN101546
1.062	188	AN101508	2.125	1.250	AN101522	3.500	2.625	AN101533	5.250	4.375	AN101547
1.125	250	AN101509	2.250	1.375	AN101523	3.625	2.750	AN101534	5.375	4.500	AN101548
1.188	312	AN101510	2.375	1.500	AN101524	3.750	2.875	AN101535	5.500	4.625	AN101549
1.250	375	AN101511	2.500	1.625	AN101525	3.875	3.000	AN101536	5.625	4.750	AN101550
1.312	438	AN101512	2.625	1.750	AN101526	4.000	3.125	AN101537	5.750	4.875	AN101551
1.375	500	AN101513	2.750	1.875	AN101527	4.125	3.250	AN101538	5.875	5.000	AN101552
1.438	562	AN101514	2.875	2.000	AN101528	4.250	3.375	AN101539	6.000	5.125	AN101553
1.500	625	AN101515	3.000	2.125	AN101529	4.375	3.500	AN101540			
1.562	688	AN101516	3.125	2.250	AN101530	4.500	3.625	AN101541			
						4.625	3.750	AN101542			
						4.750	3.875	AN101543			
						4.875	4.000	AN101544			

(A) THREAD TO HEAD MAXIMUM TWO IMPERFECT THREADS

NOTE (1) SHANK SHALL BE STRAIGHT WITHIN .001 FIR PER INCH OF BOLT LENGTH  
(2) THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR  
(3) THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .023 FIR

MATERIAL. STEEL AMS6322

HARDNESS. ROCKWELL C26-32

FINISH CADMIUM PLATE AMS2400

SURFACE ROUGHNESS AS107

MANUFACTURING SPECIFICATION AMS7450

① INSPECTION ALL PARTS SHALL UNDERGO MAGNETIC INSPECTION IN ACCORDANCE WITH AMS2440.  
BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED

DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED TOLERANCES, LINEAR DIMENSIONS  $\pm .010$ , ANGULAR DIMENSIONS  $\pm 2^\circ$

DO NOT USE UNASSIGNED PART NUMBERS

**INACTIVE FOR NEW DESIGN AFTER 3 MARCH 1969 NO SUPERSEDING STANDARD**

THIS STANDARD WAS DEVELOPED COOPERATIVELY BY THE ENGINE AND PROPELLER UTILITY PARTS COMMITTEE OF THE SAE

PA AF-11 CUST NAVY-AS ARMY-AV	AIR FORCE-NAVY AERONAUTICAL STANDARD	AN101501 THRU AN101600
-------------------------------------	--------------------------------------	------------------------------

APPROVED 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

30 June 1968