Army Regulation 700-82 OPNAVINST 4410.2A MCO 4400.120

Logistics

Joint Regulation
Governing the
Use and
Application of
Uniform Source
Maintenance and
Recoverability
Codes

Headquarters
Departments of the Army,
the Navy,
and the Marine Corps
Washington, DC
10 October 2007

**UNCLASSIFIED** 

# **SUMMARY of CHANGE**

AR 700-82/OPNAVINST 4410.2A/MCO 4400.120

Joint Regulation Governing the Use and Application of Uniform Source Maintenance and Recoverability Codes

This rapid action revision, dated 10 October 2007--

- o Changes meanings of codes (throughout).
- o Makes administrative changes (throughout).

Headquarters
Departments of the Army,
the Navy,
and the Marine Corps
Washington, DC
10 October 2007

\*Army Regulation 700–82 \*OPNAVINST 4410.2A \*MCO 4400.120

Effective 10 November 2007

#### Logistics

## Joint Regulation Governing the Use and Application of Uniform Source Maintenance and Recoverability Codes

By Order of the Secretary of the Army, Navy, and Marine Corps:

GEORGE W. CASEY, JR. General, United States Army Chief of Staff

0.00

M. K. LOOSE

Vice Admiral, CEC, U.S. NAVY Deputy Chief of Naval Operations Fleet Readiness and Logistics

Official:

JOYCÉ E. MORROW Administrative Assistant to the Secretary of the Army R. S. KRAMLICH

Deputy Commandant, U.S. Marine Corps Installations and Logistics

**History.** This publication is a rapid action revision. The portions affected by this rapid action revision are listed in the summary of change.

**Summary.** This regulation prescribes standard policies for the establishment and maintenance of source maintenance and recoverability codes within the Services. It prescribes specific codes and provides associated formats and definitions.

Applicability. This regulation applies to the Active Army, the Army National Guard/Army National Guard of the United States, and the U.S. Army Reserve, unless otherwise stated. This instruction applies to the Army, Navy, and Marine Corps. This regulation also applies to participating agencies and contractors involved with supportability analysis summaries and provisioning/item selection functions by, or for, DOD weapons systems, equipment, publications, software/hardware, training/training devices, and support equipment.

Proponent and exception authority. The proponent of this regulation is the

Deputy Chief of Staff, G-4. The proponent has the authority to approve exceptions or waivers to this regulation that are consistent with controlling law and regulations. The proponent may delegate this approval authority, in writing, to a division chief within the proponent agency or its direct reporting unit or field operating agency, in the grade of colonel or the civilian equivalent. Activities may request a waiver to this regulation by providing justification that includes a full analysis of the expected benefits and must include formal review by the activity's senior legal officer. All waiver requests will be endorsed by the commander or senior leader of the requesting activity and forwarded through their higher headquarters to the policy proponent. Refer to AR 25-30 for specific guidance.

**Army management control process.** This regulation does not contain management control provisions.

**Supplementation.** Supplementation of this regulation and establishment of command and local forms are prohibited without prior approval from the Deputy Chief of Staff, G–4, ATTN: DALO-ZA, 500

Army Pentagon, Washington, DC 20310-0500.

**Suggested improvements.** Users are invited to send comments and suggested improvements on DA Form 2028 (Recommended Changes to Publications and Blank Forms) directly to the Deputy Chief of Staff, G–4, ATTN: DALO–SUS–S, 500 Army Pentagon, Washington, DC 20310–0500.

**Distribution.** This publication is available in electronic media only and is intended for command levels C and D for the Active Army, the Army National Guard/Army National Guard of the United States, and the U.S. Army Reserve. *Navy*: A1, A2A, A4A, A5, A6, B2, B5, C4B, C4F3, C4F10, C4G, C4K, FA, FD, FE, FKA1, FKL, and FKM2. *MCO*: PCN10205240500.

i

<sup>\*</sup>This regulation supersedes AR 700-82/OPNAVINST 4410.2A/MCO 4400.120, dated 31 March 2003.

#### Contents (Listed by paragraph and page number)

#### Chapter 1

```
Introduction, page 1
Purpose • 1–1, page 1
References • 1–2, page 1
Explanation of abbreviations and terms • 1–3, page 1
Responsibilities • 1–4, page 1
```

#### Chapter 2

#### Policy, Implementation, and Format, page 1

Background • 2-1, page 1

General source maintenance and recoverability coding policy • 2–2, page 1

Implementation • 2-3, page 2

Uniform source maintenance recoverability code format • 2-4, page 2

#### **Appendixes**

- A. Reference, page 4
- B. Uniform Source Maintenance Recoverability Format, page 4
- C. Uniform Source Codes, page 5
- **D.** Maintenance Codes, page 7
- **E.** Recoverability Codes, page 9
- **F.** Service Option Codes, page 10

#### **Table List**

```
Table B-1: Service option code, page 4
Table C-1: P series source codes, page 5
Table C-2: K series source codes, page 6
Table C-3: M series source codes, page 6
Table C-4: A series source codes, page 6
Table C-5: X series source codes, page 7
Table D-1: Use (third position), page 7
Table D-2: Repair (fourth position), page 9
Table E-1: Recoverability codes, page 10
Table F-1: Service option codes, page 10
```

#### Figure List

Figure 2-1: Joint Service coding reference chart, page 3

#### **Glossary**

### Chapter 1 Introduction

#### 1-1. Purpose

This regulation establishes uniform source maintenance and recoverability (SMR) codes for all Department of Defense (DOD) Services/participating agencies (PAs) and prescribes policy and interprets guidelines for the initial assignment, changes to and application of these codes. This publication reflects the changes in terminology required by the MIL-PRF-49506, Performance Specification, Logistics Management Information, which replaces MIL-STD-1388-2, DOD Requirements for a Logistics Support Analysis Record. Uniform SMR codes will be used by all DOD Services/PAs. Subject to the Service options contained herein, each Service/PA will ensure that the coding structure and application of these codes are used by their logistics management systems in order to provide uniformity and a means of inter-Service/agency communication of information for multi-Service/agency equipments. All Services/PAs are not required to use every SMR code contained herein. However, only codes contained herein will be used when SMR codes are assigned. A table of approved SMR codes for all Services/PAs is located at appendix B, table B-1.

#### 1-2. References

Required and related publications and prescribed and referenced forms are listed in appendix A.

#### 1-3. Explanation of abbreviations and terms

Abbreviations and special terms used in this pamphlet are explained in the glossary.

#### 1-4. Responsibilities

- a. The Service proponent will provide necessary oversight to implement the development and maintenance of SMR codes defined herein. Logistics wholesale and retail systems will be designed to employ these codes as appropriate.
- b. Service materiel developers and materiel commands will employ the SMR codes as defined herein for developmental and fielded systems. Equipment manufacturers or other contractor support utilized for establishing and maintaining SMR codes will likewise be restricted to the use of codes as defined herein.

## Chapter 2 Policy, Implementation, and Format

#### 2-1. Background

- a. Source maintenance and recoverability codes are used to communicate maintenance and supply instructions to the various logistic support levels and using commands for the logistic support of systems, equipment, and end items. These codes are made available to their intended users by means of technical publications such as allowance lists, illustrated parts breakdown (IPB) manuals, repair parts, and special tools lists (RPSTLs), maintenance manuals and supply documents. These codes are assigned to each support item based on the logistic support planned for the end item and its components.
- b. The primary objective is to establish uniform policies, procedures, management tools, and means of communication that will promote inter-Service and integrated material support within and among the military Services and participating agencies. Thus, the establishment of uniform source maintenance and recoverability codes is an essential step toward improving overall capabilities for more effective inter-Service and integrated support.

#### 2-2. General source maintenance and recoverability coding policy

- a. Uniform SMR codes as established and defined herein will be used to identify the source of spares, repair parts and end items of support equipment, and the levels of maintenance authorized to use, maintain, overhaul, rework, rebuild, condemn, or dispose of them. The initial assignment and subsequent changes to SMR codes significantly impact funding appropriations, requirements determination and all of the elements of logistics. This instruction is to be utilized in the processes of acquiring Logistics Management Information (LMI), SAS, maintenance plan development, MRA, and other provisioning functions.
- b. Uniform SMR codes will be assigned to support items during the initial acquisition phase of end items of material. These codes may also be applied to end items already in the supply system, to support items already in the supply system or to support items entering the supply system after initial acquisition of the end item.
- c. Using military Services/PAs will be responsible for the assignment of SMR codes to end items and support items. Recommendations on the coding of support items may be requested from contractors or vendors. When requested from a contractor, an approving agency for the SMR coding effort shall be identified. Upon approval of the SMR code, no changes to the coding that affect the recoverability (spare to repair part or repair part to spare) will be implemented without a review of the life cycle cost impact considering all required support resources. The using military Services/PAs may delegate coding responsibility to the procuring military Service/PA by mutual written agreement.

- d. The SMR code assigned to each item of supply is a record of a technical decision reflecting adequate consideration of the cost, design, manufacture, application, maintenance, and supply practices and capabilities as related to each support item and the operational missions of the end item.
- e. Particular SMR codes assigned to a specific support item may vary depending on the particular application of the item within an end item and between different end items.
- f. Codes assigned to a specific support item for a particular application to an end item may also vary when the end item has multi-Service/agency usage because of varying maintenance policies and operational missions.
- g. Each military Service or agency will assure that SMR codes are published in applicable maintenance and supply publications and documents. When commercial maintenance and supply publications are adopted for use by the military Services or agencies, SMR codes will be published as required.

#### 2-3. Implementation

Conversion of existing data systems to accommodate uniform SMR codes is mandatory for all Services/agencies as of the date of this regulation. Conversion of existing printed publications/materiels is at the Service/PA discretion. All publications/printed materiels distributed after the date of this regulation will be required to use the uniform SMR Codes.

#### 2-4. Uniform source maintenance recoverability code format

The Uniform SMR code format (see table B-1) is composed of four parts consisting of a two (2) position source code, a two (2) position maintenance code, a one (1) position recoverability code and a one (1) position Service option code as follows:

- a. Source codes (2 positions). Codes entered in the first and second positions of the uniform format indicating the source for acquiring the item for replacement purposes, for example, procured and stocked, manufactured, or assembled (see app C).
- b. Maintenance codes (2 positions). Codes entered in the third and fourth positions of the uniform code format are as follows (see app D):
- (1) Third position. The maintenance code entered in the third position will indicate the lowest maintenance level authorized to remove/replace, and use the item. The decision to code the item for removal and replacement at the indicated maintenance level will require that all the resources necessary to install and assure proper operation after installation of a replacement item (for example, pre-installation inspection, testing and post-installation checkout) are provided.
  - (2) Fourth position.
- (a) The maintenance code entered in the fourth position indicates whether the item is to be repaired and identifies the lowest maintenance level with the capability to perform a complete repair action (see definition of complete repair). The decision to code the item for repair at the indicated maintenance level requires that the proper logistics support (parts, manuals, training, tools, and so on) and all repair capability (remove, replace, repair, assemble, manufacture, and testing for the support item) be provided or be available to that maintenance level. This does not preclude some minor repair which may be accomplished at a lower level of maintenance such as: simple replacement of minor items at the organizational level (fuses, light bulbs, screws, knobs, handles, and so on).
- (b) Because of Service differences in communicating maintenance information; a maintenance code entry in this position is not required by all Services. Therefore this position is for optional use on intra-Service equipment. When a maintenance code is not used a dash (-) sign will be entered. For multi-Service equipment this position will contain a uniform maintenance code assigned by the Service(s) requiring the code.
- c. Recoverability code (1 position). Code entered in the fifth position of the uniform format indicating the desired disposition of the support item (see app E).
- d. Reserved for Service option code (1 position). Code entered in the sixth position of the uniform format used to convey specific information to the logistic community and to the operating forces. This code is unique to each Service and is utilized to disseminate specific instructions to that Service's logistics business processes (see app F).

SOURCE			(REF: AR 700-82/OPNAVIST4410.2/. MCO 4400 MAINTENANCE			RECOVERABILITY		
1ST POS 2ND POSITION		3	3RD POSITION 4TH POSITION		TH POSITION	5TH POSITION		
MEANS (	OF AC	QUIRING SUPPORT						
A ITEM: STOCKED		USE: LOWEST LEVEL		REPAIR: LOWEST		DISPOSITION: WHEN		
	В	ITEM; STOCKED, INSURANCE	AUTHORIZED TO REMOVE/ REPLACE		LEVEL WITH CAPABILITY AND		UNSERVICEABLE OR UNECONOMICALLY	
	C	ITEM: STOCKED, DETERIORATIVE						
	D	ITEM: SUPPORT, INITIAL ISSUE OR OUTFITTING &	TH	THE ITEM.		RESOURCES TO PERFORM		REPARABLE, CONDEMN
		STOCKED ONLY FOR ADD'L INITITIAL ISSUE						DISPOSE.
	102	EQUIPMENT: SUPPORT, STOCKED, INITIAL			C	OMPLETE		
_	E	ISSUE OR OUTFITTING OF SPECIFIED MAINT			REPAIR ACTION.			
P		ACTIVITIES EQUIPMENT: SUPPORT, NON-STOCKED,			_			
	F	CENTRALLY PROCURED ON DEMAND			0	ORG/UNIT O	ORG/UNIT	
		ITEM: STOCKED FOR SUSTAINED SUPPORT.	0	ORG/UNIT		OKGOMII	17	OKGIONII
	G	UNECONOMICAL TO PRODUCE AT LATER TIME				I/DS/AFLOAT		I/DS/AFLOAT
		ITEM; STOCKED, CONTAINS HAZMAT.		**************************************	F	OR THIRD	F	OR THIRD
	H	HMIS/MSDS REPORTING REQUIRED		I/DS/AFLOAT	-	ECHELON	_	ECHELON
i	R	TERMINAL OR OBSOLETE, REPLACED	F	OR THIRD	Н	DOLLEGIN	-	RLHELLIN
				G	ASHORE	_	ASHORE	
	Z	TERMINAL OR OBS, NOT REPLACED			G	AND AFLOAT	G	AND AFLOAT
	D	ITEM: DEPOT O/H & MAINTENANCE KITS	G	BOTH ASHORE	H			
K	F	ITEM: MAINTENANCE KIT, PLACE AT O.F.H.L		AND AFLOAT		I/GS/ASHORE		I/GS/ASHORE
17	В	ITEM; IN BOTH DEPOT REPAIR &MAINT KITS			H	OR FOURTH	H	OR FOURTH
	0	MFG OR FAB AT UNITLEYEL	н	L'CCA CHODE	$\vdash$	ECHELON		ECHELON
	F	MFG OR FAB AT INTERMEDIATE/DS LEVEL		I/GS/ASHORE		CONTRACTOR		CONTRACTOR
T. /	H	MFG OR FAB AT INTERMEDIATE/GS LEVEL		OKTOURIN	к		<b>.</b> ,	
M	L	MFG OR FAB AT SPECIAL REPAIR ACTIVITY (SRA)		ECHELON			<b>~</b>	FACILITY
	G	MFG OR FAB AT BOTH AFLOAT AND ASHORE			L			
	D	MFG OR FAB AT DEPOT MAINTENANCE LEVEL	77	CONTRACTOR	L SRA			NOT AUTHORIZEI
	<u>Q</u>	ITEM: ASSEMBLED AT UNIT	K	FACILITY		SRA	ī.	BELOW DEPOT
	F H	ITEM: ASSEMBLED AT INTERMEDIATE/DS LEVEL					~	LEVEL
Λ		ITEM: ASSEMBLED AT INTERMEDIATE/GS LEVEL ITEM: ASSEMBLED AT SRA			⊢	DEPOT I	┡	
	는 G	ITEM: ASSEMBLED AFLOAT OR ASHORE	· .	SPEC. REPAIR	t D			FLR; CONDEMN
	b	ITEM: ASSEMBLED AT DEPOT MAINTENANCE LYL	L	ACTIVITY			D	OR DISPOSE AT
	A		Ш		<u> </u>			DEPOT
$\mathbf{X}$	A	ITEM: REQUISITION NEXT HIGHER ASSEMBLY	ı		1	z NON- REPARABLE Z	NON-	
	В	ITEM: NOT PROCURED OR STOCKED. AVAILABLE THRU SALVAGE. REQ. BY CAGE/PART NUMBER.	D	DEPOT	Z		Z	REPARABLE
		INSTALLATION DRAWING, DIAGRAM, INSTRUCTION	<u> </u>	ļ	L			
	C	SHEET. IDENTIFY BY CAGE/PART NUMBER		DEFONIS	_		١.	NON-REPARABLE
	D	NON-STOCKED, OBTAIN VIA LOCAL PURCHASE	Z REFONLY		B	RECONDITION	Α	BUT REQUIRES SPECIAL HANDLING

#### Notes:

On Army programs, the following applies:

Figure 2-1. Joint Service coding reference chart

<sup>&</sup>lt;sup>1</sup> Code "O" in the 3rd, 4th, and 5th positions of the maintenance and recoverability codes denotes "field" for Army programs only.

<sup>&</sup>lt;sup>2</sup> Code "F" denotes "field maintenance or Aviation Support Battalion (ASB)" for Army programs only.

<sup>&</sup>lt;sup>3</sup> Code "H" denotes "Below Depot Sustainment or Component Repair Company" for Army programs only.

<sup>&</sup>lt;sup>4</sup> Code "L" denotes "Special Repair Activity or Theater Aviation Sustainment Maintenance Group (TASMG)" for Army programs only.

## Appendix A Reference

#### Section I

#### **Required Publications**

#### MIL-PRF-49506

Logistics Management Information. (Cited in para 1-1.) (Available at http://www.assist.daps.dla.mil/quicksearch.)

#### Section II

#### **Related Publications**

A related publication is a source of additional information. The user does not have to read it to understand this regulation.

#### AR 700-18

Provisioning of U.S. Army Equipment, Internal Control System

#### **NAVSUP Instruction 4423.29**

Naval Uniform Source, Maintenance, and Recoverability (SMR) Codes. (Available at http://logistics.navair.navy.mil.)

#### DOD 4100.39-M

Federal Logistics Information System (FLIS) Procedures Manual

#### DOD 4160.21-M-1

Defense Demilitarization Manual

#### Section III

#### **Prescribed Forms**

This section contains no entries.

#### Section IV

#### **Referenced Forms**

This section contains no entries.

#### Appendix B

#### **Uniform Source Maintenance Recoverability Format**

#### B-1. Description

The uniform SMR format is composed of four parts consisting of a two position source code, a two position maintenance code, a one position recoverability code, and a one position Service option code.

#### B-2. Use

Use the Service option code as follows:

Table B-1 Service option code						
SOURCE CODE	MAINTENANCE CODE		RECOVER- ABILITY CODE	SERVICE OPTION CODE		
Positions (1) and (2)	Position (3) USE CODE	Position (4) REPAIR CODE	Position (5)	Position (6)		

Table B-1 Service option code—Continued						
SOURCE CODE	MAINTENA	NCE CODE	RECOVER- ABILITY CODE	SERVICE OPTION CODE  Reserved, Service Unique. Modifies or clarifies the SM&R code as required by the individual Service. Used to convey Service specific information to the logistics community and/or the operating forces.		
Indicates manner of acquisition for support items.	Indicates the lowest level of maintenance authorized to use, remove, and replace the item.	Indicates whether the item is to be repaired and identifies lowest level of maintenance with the capability to perform a complete repair action. (See Definition: Complete Repair Action)	Indicates the lowest level of maintenance authorized to dispose of the item. If the item is reparable, it also indicates repair as applicable under the progressive maintenance concept.			
(See app C)	(See app D)	(See app D)	(See app E)	(See app F)		

#### Appendix C Uniform Source Codes

#### C-1. Source codes

- a. General. Source codes are assigned to support items to indicate the manner of acquiring support items for maintenance, repair, rework, or overhaul of end items and to identify items requiring special handling (for example, hazardous/precious materials). Source codes are entered in the first and second positions of the uniform SMR code format.
  - b. P series source codes. P series source coded items are items which are centrally procured.

Table C-1 P series source codes			
Code	Application/Explanation		
PA	Item procured and stocked for anticipated or known usage. Items are normally considered for replenishment.		
РВ	Item procured and stocked for insurance purposes because essentiality dictates that a quantity be available in the supply systems.		
PC	Item procured and stocked but is deteriorative in nature.		
PD	Support item, excluding support equipment, procured for initial issue or outfitting and stocked only for subsequent or additional initial issues or out-fittings. Not subject to automatic replenishment.		
PE	End item and/or support equipment procured and stocked for initial issue or outfitting for specific maintenance repair activities.		
PF	Support equipment which will not be stocked but which will be centrally procured on demand.		
PG	Item procured and stocked to provide for sustained support for the life of the equipment. It is applied to an item which, because of probable discontinuance or shutdown of production facilities would prove uneconomical to reproduce at a later time.		
PH	Item procured and stocked and has been identified to contain hazardous material. Item requires recordation in the Hazardous Material Information System (HMIS) and a Material Safety Data Sheet (MSDS).		
PR	End item and/or support item, terminal or obsolete and replaced. No longer authorized for procurement. On hand assets may be issued until exhausted. Then use replacement item.		
PZ	Item terminal or obsolete with no replacement; discontinue use. (Army only. This code will not effect other Services if they are recorded as a user at DLSC.)		

#### C-2. K series source codes

K series source coded items are contained in kits and do not/will not have an NSN assigned.

Note. In those instances where an item is part of a kit and is also an item extraneous to the kit, the P series source code will take precedence.

Table C-2 K series source codes	
Code	Application/Explanation
KD	An item contained in a depot overhaul/repair kit and not purchased separately. Depot kit defined as a kit that provides items required at the time of depot overhaul or repair.
KF	An item contained in a maintenance kit and not purchased separately. Maintenance kit defined as a kit that provides an item that can be replaced at organizational or intermediate levels of maintenance.
КВ	Item included in both a depot overhaul/repair kit and a maintenance kit.

#### C-3. M series source codes

M series source coded items are to be manufactured or fabricated at some level of maintenance. They are normally consumable items or those requiring very limited repair (that is, bending, painting, alignment, and so on). The assignment of this code should be based primarily on the predicted usage of the item over the life cycle of the end item and the practicality and economics of stocking, storing and issuing items. Typical M coded items include hose assemblies, tubing, name plates, decals, wires, and so on, which have minimal likelihood of replacement during the life cycle of the end item. All the publications, manufacturing data, required shop equipment and skills must be available at the specified level of maintenance.

Table C-3 M series source codes			
Code	Application/Explanation		
MO	Item to be manufactured or fabricated at organizational level.		
MF	Item to be manufactured or fabricated at intermediate maintenance level. Marine Corps - 3rd Echelon Army - Direct Support Navy - Afloat		
MH	Item to be manufactured or fabricated at intermediate maintenance level. Marine Corps - 4th Echelon Army - General Support Navy - Ashore		
ML	Item is to be manufactured at a specialized repair facility (for example, environmental considerations).		
MG	Item to be manufactured or fabricated at both afloat and ashore intermediate maintenance levels - Navy use only.		
MD	Item to be manufactured or fabricated at depot maintenance level.		

#### C-4. A series source codes

A series source coded items are authorized for assembly at some level of maintenance. These codes should be assigned when all parts for assembly, the required support equipment and the skills required for the assembly are available at the specified level of maintenance. A source coded items require at least one P coded item in the assembly.

Table C-4 A series source	Table C–4 A series source codes			
Code	Application/Explanation			
AO	Item to be assembled at organizational level.			
AL	Item is to be assembled at a specialized repair activity (that is, item requires specialized tests and fixtures to insure proper assembly).			
AF	Item to be assembled at intermediate maintenance level. Marine Corps - 3rd Echelon Army - Direct Support Navy - Afloat			
AH	Item to be assembled at intermediate maintenance level. Marine Corps - 4th Echelon Army - General Support Navy - Ashore			
AG	Item to be assembled at both afloat and ashore intermediate maintenance levels - Navy use only.			
AD	Item to be assembled at depot maintenance levels.			

#### C-5. X series source codes

X series source coded items are items for which no demand is anticipated.

Table C-5 X series sourc	Table C–5 X series source codes				
Code	Application/Explanation				
XA	Item is not procured or stocked because the requirements for the item will result in the replacement of the next higher assembly.				
ХВ	Support item with low mortality rate, not procured or stocked. Item may/may not be available through salvage Salvage should be considered unless use of salvage item is prohibited by instruction in equipment publication. If prohibited, requisition through normal supply channels using Commercial and Government Entity (CAGE) code and reference number.				
XC	Installation drawing, diagram, instruction sheet, field Service drawing, that is identified by manufacturers' part number.				
XD	Support item with low mortality rate, not stocked. Local purchase or requisition through normal channels using contractor and government entity code (CAGE) and reference number. Not obtainable from salvage/cannibalization.				

#### Notes

For USAF and the USA Safeguard Program, only code F, as used in the third and fourth position of the Uniform SMR Format, will be used to denote intermediate maintenance (see app D). On Joint programs, use of either code F or H by the joining Service will denote intermediate maintenance to USAF and the USA Safeguard Program.

## Appendix D Maintenance Codes

#### D-1. Uniform code format

a. General. Maintenance codes are assigned to indicate the levels of maintenance authorized to USE, REMOVE, REPLACE, or REPAIR support items. The maintenance codes are entered in the third and fourth positions of the Uniform SMR Code Format as follows:

b. Use (third position). The maintenance code entered in the third position will indicate the lowest maintenance level authorized to remove, replace, and use the support item. The decision to code the item for removal and replacement at the indicated maintenance level will require that all the capabilities necessary to install and insure proper operation after installation of a replacement item (for example, pre-installation inspection, testing, and post-installation checkout) are provided. The maintenance code entered in the third position will indicate one of the following levels of maintenance.

Table D-1 Use (third posit	tion)
Code	Application/Explanation
0	Support item is removed, replaced, used at the organizational level of maintenance.  Note (1): To distinguish between the organizational maintenance capabilities on different classes of ships the following codes may be used intra-Navy only. On Joint programs, Navy will receive and transmit an O to indicate organizational maintenance level.  2 - Minesweeper, Yardcraft, Patrol Boat 3 - Submarines 4 - Auxiliary/Amphibious Ships 5 - Major Combatant (Destroyer, Frigate) 6 - Major Combatant (Cruiser, Carrier, Amphibious Assault Ships)  Note (2): On Army programs, a Code "C" may be used in the third position to denote crew or operator maintenance performed within organizational maintenance. On Joint programs, the Army will receive or transmit an "O" to indicate Service Company or Aviation Maintenance Company.

Table D-1 Use (third pos	sition)—Continued
Code	Application/Explanation
F	Support item is removed, replaced, used at the following intermediate levels:
	USAF - Intermediate (*) USA - Field Maintenance or Aviation Support Battalion (ASB) USN - Afloat USMC - Third Echelon
G	Support item is removed, replaced, used at both afloat and ashore intermediate levels. (Navy only)
H	Support item is removed, replaced, used at the following intermediate levels:
	USAF - Intermediate (*) USA - Below Depot Sustainment or Component Repair Company USN - Ashore (only) USMC - Fourth Echelon
	NOTE: For USAF programs and the USA Safeguard Program, Code F will be used to denote intermediate maintenance. On Joint programs, use of either Code F or H by the joining Service will denote intermediate maintenance to USAF and the USA Safeguard Program.
K	Repairable item. Item is removed, replaced, or used at contractor facility.
L	Item is removed, replaced, or used at designated specialized repair activity.
	NOTE: On Army programs, a Code "L" denotes Special Repair Activity or Theater Aviation Sustainment Maintenance Group (TASMG).
D	Support items that are removed, replaced, used at depot only:
	USAF - Depot, Mobile Depot and Specialized Repair Activity USA - Depot, Mobile Depot and Specialized Repair Activity USN - Aviation Rework, Avionics and Ordnance Facilities, and Shipyards USMC - Depot
Z	Item is not authorized to be removed or replaced at any maintenance level. This code is assigned to items not required for support in a specific application and is identified for reference purposes only. (Navy use only.)

#### D-2. Repair

The maintenance code entered in the fourth position indicates whether the item is to be repaired and identifies the lowest maintenance level with the capability to perform complete repair (see definition for complete repair). This code (and subsequent positions of the SMR code) is only used when the first position of the SMR code is a P. The decision to code the support item for repair at the indicated maintenance levels requires that all maintenance capability (remove, replace, repair, assemble, and test) for the support items be provided to that level. This does not preclude some minor repair which may be accomplished at a lower level of maintenance. However, because of Service differences in communicating maintenance repair level information a maintenance code entry in this position is not required by all Services. When a maintenance code is not used a dash (-) sign will be entered. For multi-Service equipment/systems or when a code is entered, this position will contain one of the following maintenance codes as assigned by the Service(s) that require the code:

Table D-2 Repair (fourth	position)	
Code	Application/Explanation	
0	The lowest maintenance level capable of complete repair of the support item is the organizational level.  Note (1): To distinguish between organizational maintenance capabilities on different classes of ships, the following codes may be used intra-Navy only. On Joint programs, Navy will receive or transmit an "O" to indi	
	cate organizational maintenance level and Army will receive or transmit an "O" to indicate organizational/field level.	
	<ul> <li>2 - Minesweeper, Yardcraft, Patrol Boat</li> <li>3 - Submarines</li> <li>4 - Auxiliary/Amphibious Ships</li> <li>5 - Major Combatant (Destroyer, Frigate)</li> </ul>	
	6 - Major Combatant (Cruiser, Carrie, Amphibious Assault Ships)	
F	The lowest maintenance level capable of complete repair of the support item is the following intermediate level:	
	USAF - Intermediate (*) USA - Field Maintenance or ASB	
	USN - Afloat	
	USMC - Third Echelon	
Н	The lowest maintenance level capable of complete repair of the support item is the following intermediate level:	
	USAF - Intermediate (*)	
	USA - Below Depot Sustainment or Component Repair Company USN - Ashore (only) USMC - Fourth Echelon	
	NOTE: For USAF programs and the USA safeguard program, Code F will be used to denote intermediate maintenance. On Joint programs, use of either Code F or H by the joining Service will denote intermediate maintenance to USAF and the USA Safeguard Program.	
K	Repairable support item. Complete repair capability exists at a designated contractor facility.	
G	Both afloat and ashore intermediate levels are capable of complete repair of support item. (Navy only)	
D	The lowest maintenance level capable of complete repair of the support item is the depot level.	
	USAF - Depot, Mobile Depot USA - Depot, Mobile Depot	
	USM - Aviation Rework, Avionics and Ordnance Facilities, and Shipyards USMC - Depot	
L	Repair should be performed at the designated Specialized Repair Activity.	
Z	Non-repairable. No repair is authorized.	
В	No repair is authorized. The item may be reconditioned by adjusting, lubricating, and so on at the No parts or special tools are procured for the maintenance of this item. Inserted when the maintenance is not used.	

#### Appendix E Recoverability Codes

#### E-1. General

Recoverability codes are assigned to support items to indicate the disposition action on unserviceable items.

#### E-2. Fifth position

The recoverability code is entered in the fifth position of the uniform SMR code format as follows:

Table E-1 Recoverability	codes		
Code	Definition		
Z	Non-repairable item. When item becomes unserviceable, condemn and dispose of at authorized level.		
0	Repairable item. When uneconomically repairable, condemn and dispose at organizational level.  NOTE (1): At organizational/field level for Army only.		
F	Repairable item. When uneconomically repairable, condemn and dispose at the following intermediate levels:  USAF - Intermediate (*)  USA - Field Maintenance or ASB  USN - Intermediate Afloat  USMC - Third Echelon F		
G	Field level repairable item. When uneconomically repairable, condemn and dispose at either afloat or asho intermediate levels. (Navy only)		
Н	Repairable item. When uneconomically repairable, condemn and dispose at the following levels:		
	USAF - Intermediate (*) USA - Below Depot Sustainment or Component Repair Company USN - Intermediate Ashore USMC - Fourth Echelon		
	NOTE: For USAF programs and the USA Safeguard Program, Code F will be used to denote intermediate maintenance. On Joint programs, use of either Code F or H by the joining Service will denote intermediate maintenance to USAF and the USA Safeguard Program.		
K	Repairable item. Condemnation and disposal to be performed at contractor facility.		
D	Repairable item. When beyond lower level repair capability, return to depot. Condemnation and disposal not authorized below depot level.		
L	Repairable item. Repair, condemnation, and disposal not authorized below depot level.		
	NOTE (1): Code "L" denotes Special Repair Activity or TASMG.		
A	Non-repairable. Item requires special handling or condemnation procedures because of specific reason example, precious metal content, high dollar value, or critical material). Refer to appropriate manuals tives for specific instructions.		

#### Appendix F Service Option Codes

#### F-1. General

Service option codes are assigned to support items to convey specific information to the Service's logistics community/ operating forces. Each Service uses the code to disseminate specific instructions which add to that Service's internal logistics/practices. Service option codes are entered in the sixth position of the uniform SMR format as follows:

Table F–1 Service option codes	
Code	Application
Α	No demilitarization required.
В	MLI, no demilitarization required.
С	MLI, remove deadly parts in accordance with DOD 4160.21-M-1.
D	MLI, mutilate.

Table F-1 Service option codes—Continued	
Code	Application
E	MLI, burn, shred, or pulp.
F	MLI, contact the item manager.
G	MLI, demil prior to DRMO.
P	MLI, security classified, DECLAS, demilitarize sensitive markings prior to transfer to DRMO. Not used on AEDA items.
Q	SLI, mutilate to preclude normal use, OCONUS only.
N	Throw away, condemn at maintenance use level.
P	Recoverable, condemn at intermediate level.
С	Recoverable, condemn at depot level. (SCARS)
T	Recoverable, Condemn at depot level. (AFRAMS)
S	Support equipment, condemn at depot level. (AFEMS)
U	Support equipment, condemn at O/F level. (AFEMS)
1	Engine intermediate maintenance level - First Degree.
2	Engine intermediate maintenance level - Second Degree.
3	Engine intermediate maintenance level - Third Degree.
6	PA source coded item which is normally procured commercially but organic capability exists to manufacture (source code M series) for emergency stop gap requirements. Organic sources should be reviewed when commercial sources cannot meet demand.
8	Indicates a inter-Service depot non-consumable item that is by the Navy maintenance plan, repairable by second degree engine maintenance level.
9	Indicates a inter-Service depot non-consumable item that is, by the navy maintenance plan, repairable by third degree engine maintenance level.
E	Items which are removed by the O level with no I level repair authorized; however, the I level must perform end to end test to verify failure prior to final disposition. (Beyond Capability of Maintenance)
J	Indicates and inter-Service DLR, that is, by the Navy maintenance plan, considered completely repairable below the depot level.
P	Indicates the item is under a progressive maintenance review. (Item will be coded O in the fourth position and D in the fifth position.) P (sixth position) will then indicate intermediate is authorized between O and D levels. In the unlikely event that two different service option codes apply to the same item, the 'P' progressive maintenance code will take precedence.
R	Indicates Gold Disc repair capability has been developed at the organizational and/or intermediate levels of maintenance. Repair must be performed in a certified Module Test and Repair Facility (MTRF).
T	PD source coded item which has peculiar application to training devices.

#### F-2. Use of codes

Service option codes are entered in the sixth position of the uniform SMR format as follows:

- a. Army Demilitarization code used in accordance with DOD 4160.21-M-1. Identifies unique requirements to be considered when an item is condemned.
  - b. MLI Denotes Military List Team.
  - c. SLI Denotes Strategic List Team.
- d. Navy Service option code. Provides specific data to the maintenance community which cannot be conveyed in the uniform SMR coding format.

#### **Glossary**

#### Section I

#### **Abbreviations**

#### **AFRAMS**

Air Force Recoverable Asset Management System

#### **ASB**

Aviation Support Battalion

#### **CAGE**

commercial and Government entity

#### DOD

Department of Defense

#### **DRMO**

Defense Reutilization and Marketing Office

#### FLIS

Federal Logistics Information System

#### **HMIS**

Hazardous Material Information System

#### **IOM**

install, operate, and maintain

#### **IPB**

illustrated parts breakdown

#### **LMI**

logistics management information

#### MRA

maintenance and repair analysis

#### **MSDS**

material safety data sheet

#### **MTRF**

module test and repair facility

#### **NSN**

national stock number

#### **OCONUS**

outside continental United States

#### PA

participating agency

#### **RFI**

ready for issue

#### **RFU**

ready for use

#### R&R

remove and replace

#### **RPSTL**

repair parts and special tools list

#### SAS

supportability analysis summaries

#### SE

support equipment

#### **SMR**

source, maintenance, recoverability

#### TASMG

Theater Aviation Sustainment Maintenance Group

#### TISA

U.S. Army

#### **USAF**

U.S. Air Force

#### **USMC**

U.S. Marine Corps

#### **USN**

U.S. Navy

#### Section II

Terms

#### Assembled item

A support item which is not stocked, but when required, can be assembled from a combination of sub-items that are individually stocked and/or fabricated. This definition applies to A series source codes.

#### Authorized repair

The maintenance level, identified in the maintenance plan, authorized to perform the preventive or corrective maintenance, and servicing tasks required.

#### Complete repair level

The authorized maintenance level with the capability and resources to perform all maintenance functions identified for a specific level of maintenance and approved by official maintenance documents. It requires that all maintenance capabilities (remove, replace, repair, assemble, and test) for the support item be provided at that level. It requires that all logistics support (parts, publications, tools, test equipment, and so on) be provided to that level of maintenance to perform all assigned maintenance functions.

#### Complete repair action

The authorized performance of one repair action which, when completed as a lone repair, will return the item to serviceable condition. Whether the repaired unit is returned to a ready for use (RFU) or ready for issue (RFI) condition is a matter of which level of maintenance completes the repair and its purpose/ability to place the item in rotable pool stock or certify it for packaging, preservation and shipment. The capability to perform a complete repair action requires that all maintenance functions (remove, replace, repair, assemble, and test) for the support item be provided at that level.

#### Consumable or expendable item

A non-repairable item or repair part which can be discarded more economically than it can be repaired or which is consumed in use. This definition does not include support equipment but does include repair parts for support equipment.

#### End item

A final combination of end products, component parts and/or materials which is ready for its intended use (that is, radar system, control panel, tank, mobile machine shop, aircraft, engine, ground support equipment).

#### Kit

A collection of supporting repair parts packaged and identified as a single item of supply which provides maintenance activities with repair parts necessary to accomplish a specific repair action of component overhaul/rework.

#### **Maintenance Code**

A two position code assigned to support items and end items to indicate the specific maintenance levels authorized to perform the required maintenance functions. The first position indicates the lowest maintenance level authorized to remove and replace (R&R) the item. The second position indicates the lowest maintenance level authorized to perform a complete repair action for the item.

#### Maintenance planning

A concise description of a strategy for achieving, maintaining, and restoring the operational capability of a weapon system/equipment. The plan is the basis on which all elements of logistics are provided. It may also identify repairable components, maintenance significant consumables and level(s) of maintenance authorized to perform preventive or corrective maintenance.

#### Maintenance repair analysis (MRA)

A summary that provides the government with conclusions and recommendations of the contractor's repair analysis which may include overall maintenance plan/concept; identification of reparable and consumable items; level of maintenance activity and life cycle cost. For the system support structure, it may identify operational readiness objectives and supporting logistics considerations such as placement and allocation of spares, support equipment, and personnel.

#### Progressive maintenance

Authorized maintenance which can restore an item to operating condition (RFU) from one or more, but not all, of its identified failure modes at one level of maintenance, but requires progressively higher levels of maintenance until the highest level alone can restore the item to operating condition from any and all identified failure modes. The use of this philosophy will provide the maintenance and logistics activities with the intelligence to know what specific level of maintenance is authorized to accomplish some, but not necessarily all, repair. The logistics support should be provided to those levels to accomplish authorized repair.

#### **Provisioning**

The management process of determining and acquiring the range and quantity of support items necessary to operate and maintain an end item of material for an initial period of Service. Usually refers to first outfitting of a ship, unit or system.

#### Readiness

State of preparedness of a system(s) to meet a mission or conduct warfighting.

#### Repair

The restoration of an unserviceable item to operating condition as necessitated by wear and tear, damage, failure of parts or the like.

#### Repair part

Consumable items or material required for the maintenance, overhaul or repair of a system, equipment, or end item. This definition does not include support equipment but does include repair parts for support equipment.

#### Recoverability Code

A one position code assigned to end items and support items to indicate the recoverability intention and the level of maintenance authorized disposition action on unserviceable support items; and for reparables, it is used to indicate the lowest maintenance level responsible for repair/condemnation and disposition of the item.

#### Source Code

Codes assigned to end items and support items to indicate the manner of acquiring items for the maintenance, repair, or overhaul of end items.

#### Spare parts (spares)

Repairable components or assemblies used for maintenance replacement purposes in the end items of equipment. They are articles identical to or interchangeable with the components of end items on contract which are procured over and above the quantity needed for initial installation for support of a system.

#### Support equipment (SE)

Is that equipment required to make an item, system, or facility operational in its intended environment. This includes all equipment required to install, operate, and maintain (IOM) the item, system,or facility including aerospace ground equipment and ground support equipment.

#### Support items

Items subordinate to or associated with an end item and required to operate, service, repair, or overhaul an end item; for example, spares and repair parts.

#### Supportability analysis summaries (SAS)

The SAS provide information for planning, assessing program status, and decision making by the government relative to various logistics disciplines.

#### Total repair

The authorized maintenance capability to perform all maintenance functions for all identified failure modes which have been previously identified and approved by official maintenance documents. This restores the item to operating condition (RFU). Generally, this occurs at the depot level of maintenance but it may happen at a lower level. It requires that all logistics support (parts, manuals, training, tools, and so on) and maintenance capabilities (remove, replace, repair, assemble, and test) for the support item be provided at that level.

#### Section III

#### **Special Abbreviations and Terms**

This section contains no entries.

# USAPD

## ELECTRONIC PUBLISHING SYSTEM OneCol FORMATTER WIN32 Version 238

PIN: 003799-000

DATE: 10- 9-07 TIME: 15:36:38

PAGES SET: 20

DATA FILE: C:\WinComp\r700-82.fil

DOCUMENT: AR 700-82

SECURITY: UNCLASSIFIED

DOC STATUS: NEW PUBLICATION