A-A-1708 May 20, 1982

COMMERCIAL ITEM DESCRIPTION

ROOFING FELT (ASPHALT SATURATED BASE SHEET)

The General Services Administration has authroized the use of this commercial item description in preference to types I and II of Federal Specification SS-R-501.

This description covers asphalt saturated and coated organic felt base sheet with fine mineral surfacing on one side for use as the first ply of a built up roof.

Salient characteristics:

Shall be in accordance with the requirements of ASTM D2626.

Shall conform to fire resistant requirements of the applicable sections of UL 55A.

Net mass of base sheet shall be no less than 1806 g/m² (37 lb/100 ft²)

Shall be in roll form, width 914 mm (36 in) + 0.7 percent.

Area of rolls shall be as specified.

Shall be plain or perforated, as specified.

The issues of ASTM D2626 and UL 55A in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Workmanship. The finished material shall be free of visible defects such as holes, ragged or untrue edges, breaks, tears, protuberances and indentations, except for intentionally provided perforations and the associated protuberances.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes: Purchaser should specify area of rolls and whether perforated or plain.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

UL standards are available from Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

MILITARY INTERESTS:

Military Coordinating Activity

PREPARING ACTIVITY:

Army - ME

GSA - FSS

Custodians

Army - ME

Navy - YD

Air Force - 99

Review Activity

ARmy - CE

User Activity

Navy - MC