

INCH-POUND

A-A-59326/3B

April 15, 2011

SUPERSEDING

A-A-59326/3A


May 1, 2003

COMMERCIAL ITEM DESCRIPTION SPECIFICATION SHEET

COUPLING HALF, MALE BY EXTERNAL PIPE THREAD, TYPE III

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring couplings described herein shall consist of this document and the latest issue in effect of A-A-59326.

FIGURE 1. Coupling half.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to DAMI_STANDARDIZATION@conus.army.mil or U.S. Army RDECOM, Tank Automotive Research, Development and Engineering Center, ATTN: RDTA-EN/STND/TRANS MS #268, 6501 E. 11 Mile Road, Warren, MI 48397-5000. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at <https://assist.daps.dla.mil>.

AMSC N/A

FSC 4730

Distribution Statement A. Approved for public release; distribution is unlimited.

A-A-59326/3B

1. SCOPE. This specification covers a male cam-locking type coupling half to be used in conjunction with coupling halves having female threaded ends.
2. CLASSIFICATION. The size of the coupling halves is designated in table I.

TABLE I. Coupling half size.

Dash No.	Cam-Lock Nom. Size	Thread NPT-TPI
1	$\frac{1}{2}$	$\frac{1}{2}$ -14
2	$\frac{3}{4}$	$\frac{3}{4}$ -14
3	1	1-11 $\frac{1}{2}$
4	1 $\frac{1}{4}$	1 $\frac{1}{4}$ -11 $\frac{1}{2}$
5	1 $\frac{1}{2}$	1 $\frac{1}{2}$ -11 $\frac{1}{2}$
6	2	2-11 $\frac{1}{2}$
7	2 $\frac{1}{2}$	2 $\frac{1}{2}$ -8
8	3	3-8
9	4	4-8
10	6	6-8

NOTE: Sizes are in inches.

3. SALIENT CHARACTERISTICS. The following characteristics may differ from those listed in the latest issue of A-A-59326.

3.1 Hydrostatic test pressure. The $\frac{1}{2}$ -inch through 6-inch couplings shall withstand a hydrostatic test pressure of 300 pounds per square inch gage (psig).

3.2 Working pressure. The $\frac{1}{2}$ -inch through 6-inch couplings having male cam locking end shall be rated for 150 pounds per square inch working pressure.

3.3 Threads. The coupling threads (male) shall conform to National Tapered Pipe Thread in accordance with ANSI/ASME B1.20.1.

4. NOTES

4.1 Part Identification Number (PIN). The following PIN procedure is for government purposes and does not constitute a requirement for the contractor. This example describes a part numbering system for specification sheet A-A-59326/3

AA59326/3-3-SS; where /3 indicates a Male External Pipe Thread Coupling Half, Type III; -3 indicates a 1-inch nominal size cam locking end; and -SS indicates a stainless steel body.

Material: A - Aluminum Alloy
 B - Copper Alloy (Brass or Bronze)
 BA - Aluminum Bronze
 SS - Stainless Steel

A-A-59326/3B

MILITARY INTERESTS:

Custodians:

Army - AT
Navy - YD
Air Force - 99

Review Activities:

Army - AV, GL
Navy - MC, SH
Air Force - 71
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FAS

Preparing Activity:

Army - AT

(Project 4730-2011-015)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.daps.dla.mil>.