

INCH-POUND

A-A-59655B  
8 September 2011  
SUPERSEDING  
A-A-59655A  
22 May 2006

## COMMERCIAL ITEM DESCRIPTION

BEARINGS, ROLLER, TAPERED, DOUBLE ROW, STEEP ANGLE,  
TWO SINGLE CONES, ONE DOUBLE CUP (TYPE TDOS)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers government acquisition requirements for complete (cone with rollers and cup) double row, tapered, roller bearings with steep angle, two single cones, and one double cup (type TDOS), for general purpose use. These bearings are not intended for use in special precision applications such as on aircraft, precision ordnance, or submarine equipment.
2. CLASSIFICATION. The roller bearings shall be of one type (TDOS) and classified by the size codes listed in [table I](#). The column headings in [table I](#) refer to bearing characteristics defined in [figure 1](#).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: [STDZNMGT@dla.mil](mailto:STDZNMGT@dla.mil) or DLA Aviation VEB, 8000 Jefferson Davis Highway, Richmond, VA 23297-5616. Since contact information can change, you may want to verify the currency of this address information using the ASSIST database at <https://assist.daps.dla.mil/>.

A-A-59655B




FIGURE 1. Bearing characteristics.

TABLE I. Size codes and dimensions.

| Size code | Part number <sup>1</sup> | d      | D                | C                      | T           | R <sup>2</sup>           | r <sup>2</sup>             | d <sub>a</sub>                | D <sub>a</sub> | K factor | Basic dynamic load ratings (lb.) |
|-----------|--------------------------|--------|------------------|------------------------|-------------|--------------------------|----------------------------|-------------------------------|----------------|----------|----------------------------------|
|           |                          | Bore   | Outside diameter | Bearing width over cup | Cones width | Max. shaft fillet radius | Max. housing fillet radius | Recommended shoulder diameter |                |          | Two row radial                   |
|           | Shaft                    |        |                  |                        |             |                          |                            | Housing                       |                |          |                                  |
| 001       | 21063 - 21226D           | 0.6250 | 2.2500           | 1.4375                 | 1.9375      | 0.03                     | 0.03                       | 1.41                          | 2.01           | .99      | 12800                            |
| 002       | 21075 - 21226D           | 0.7500 | 2.2500           | 1.4375                 | 1.9375      | 0.06                     | 0.03                       | 1.24                          | 2.01           | .99      | 12800                            |
| 003       | 43112 - 43319D           | 1.1250 | 3.1875           | 1.5625                 | 2.1875      | 0.03                     | 0.06                       | 1.67                          | 2.91           | .87      | 21500                            |
| 004       | 43125 - 43319D           | 1.2500 | 3.1875           | 1.5625                 | 2.1875      | 0.06                     | 0.06                       | 1.73                          | 2.91           | .87      | 21500                            |
| 005       | 43131 - 43319D           | 1.3125 | 3.1875           | 1.5625                 | 2.1875      | 0.14                     | 0.06                       | 2.01                          | 2.91           | .87      | 21500                            |
| 006       | 43132 - 43319D           | 1.3125 | 3.1875           | 1.5625                 | 2.1875      | 0.08                     | 0.06                       | 1.89                          | 2.91           | .87      | 21500                            |
| 007       | 44131 - 44363D           | 1.3125 | 3.6250           | 1.5625                 | 2.1875      | 0.08                     | 0.06                       | 2.01                          | 3.35           | .75      | 23300                            |
| 008       | 44143 - 44363D           | 1.4375 | 3.6250           | 1.5625                 | 2.1875      | 0.09                     | 0.06                       | 2.13                          | 3.35           | .75      | 23300                            |
| 009       | 44150 - 44363D           | 1.5000 | 3.6250           | 1.5625                 | 2.1875      | 0.09                     | 0.06                       | 2.28                          | 3.35           | .75      | 23300                            |
| 010       | 53150 - 53376D           | 1.5000 | 3.7500           | 1.7500                 | 2.5626      | 0.06                     | 0.03                       | 2.17                          | 3.50           | .79      | 27700                            |
| 011       | 44158 - 44363D           | 1.5625 | 3.6250           | 1.5625                 | 2.1875      | 0.14                     | 0.06                       | 2.28                          | 3.35           | .75      | 23300                            |
| 012       | 44162 - 44363D           | 1.6250 | 3.6250           | 1.5625                 | 2.1875      | 0.09                     | 0.06                       | 2.24                          | 3.35           | .75      | 23300                            |
| 013       | 53162 - 53376D           | 1.6250 | 3.7500           | 1.7500                 | 2.5626      | 0.06                     | 0.03                       | 2.24                          | 3.50           | .79      | 27700                            |
| 014       | 53176 - 53376D           | 1.7500 | 3.7500           | 1.7500                 | 2.5626      | 0.05                     | 0.03                       | 2.32                          | 3.50           | .79      | 27700                            |
| 015       | 53177 - 53376D           | 1.7500 | 3.7500           | 1.7500                 | 2.5626      | 0.14                     | 0.03                       | 2.48                          | 3.50           | .79      | 27700                            |
| 016       | 53178 - 53376D           | 1.7500 | 3.7500           | 1.7500                 | 2.5626      | 0.08                     | 0.03                       | 2.36                          | 3.50           | .79      | 27700                            |
| 017       | 53176 - 53390D           | 1.7500 | 3.8750           | 1.7500                 | 2.5626      | 0.05                     | 0.06                       | 2.32                          | 3.56           | .79      | 27700                            |
| 018       | 55175 - 55433D           | 1.7500 | 4.3300           | 1.6876                 | 2.5000      | 0.14                     | 0.02                       | 2.64                          | 4.13           | .66      | 29500                            |
| 019       | 55187 - 55433D           | 1.8750 | 4.3300           | 1.6876                 | 2.5000      | 0.14                     | 0.02                       | 2.72                          | 4.13           | .66      | 29500                            |
| 020       | 72188C -<br>72488D       | 1.8750 | 4.8750           | 2.1875                 | 3.0625      | 0.03                     | 0.06                       | 2.72                          | 4.53           | .79      | 50000                            |
| 021       | 55200 - 55433D           | 2.0000 | 4.3300           | 1.6876                 | 2.5000      | 0.14                     | 0.02                       | 2.80                          | 4.13           | .66      | 29500                            |
| 022       | 55200 - 55444D           | 2.0000 | 4.4375           | 1.8125                 | 2.5625      | 0.14                     | 0.06                       | 2.80                          | 4.13           | .66      | 29400                            |

<sup>1</sup> Part numbers are for reference only. Part numbers reflect the cup and cone numbers used by industry and the ABMA. Some cones and cups may be used in multiple configurations and are not limited to one bearing assembly.

<sup>2</sup> These maximum fillet radii shall be cleared by the bearing corners.

<sup>3</sup> Minus value indicates load center inside cone backface.

TABLE I. Size codes and dimensions.

| Size code | Part number <sup>1</sup> | d      | D                | C                      | T           | R <sup>2</sup>           | r <sup>2</sup>             | d <sub>a</sub>                | D <sub>a</sub> | K factor | Basic dynamic load ratings (lb.) |
|-----------|--------------------------|--------|------------------|------------------------|-------------|--------------------------|----------------------------|-------------------------------|----------------|----------|----------------------------------|
|           |                          | Bore   | Outside diameter | Bearing width over cup | Cones width | Max. shaft fillet radius | Max. housing fillet radius | Recommended shoulder diameter |                |          | Two row radial                   |
|           | Shaft                    |        |                  |                        |             |                          |                            | Housing                       |                |          |                                  |
| 023       | 66200 - 66462D           | 2.0000 | 4.6250           | 2.1250                 | 2.8750      | 0.14                     | 0.03                       | 2.80                          | 4.37           | .93      | 41200                            |
| 024       | 72200 - 72488D           | 2.0000 | 4.8750           | 2.1875                 | 3.0625      | 0.14                     | 0.06                       | 2.91                          | 4.53           | .79      | 50000                            |
| 025       | 72200C - 72488D          | 2.0000 | 4.8750           | 2.1875                 | 3.0625      | 0.14                     | 0.06                       | 3.03                          | 4.53           | .79      | 50000                            |
| 026       | 72201C - 72488D          | 2.0000 | 4.8750           | 2.1875                 | 3.0625      | 0.03                     | 0.06                       | 3.03                          | 4.53           | .79      | 50000                            |
| 027       | 55206 - 55444D           | 2.0625 | 4.4375           | 1.8125                 | 2.5625      | 0.14                     | 0.06                       | 2.83                          | 4.13           | .66      | 29400                            |
| 028       | 66212 - 66462D           | 2.1250 | 4.6250           | 2.1250                 | 2.8750      | 0.14                     | 0.03                       | 2.87                          | 4.37           | .93      | 41200                            |
| 029       | 72212C - 72488D          | 2.1250 | 4.8750           | 2.1875                 | 3.0625      | 0.14                     | 0.06                       | 3.11                          | 4.53           | .79      | 50000                            |
| 030       | 66584 - 66522D           | 2.1250 | 5.1174           | 1.8750                 | 2.7500      | 0.14                     | 0.03                       | 2.95                          | 4.65           | .88      | 42800                            |
| 031       | 72218C - 72488D          | 2.1875 | 4.8750           | 2.1875                 | 3.0625      | 0.14                     | 0.06                       | 3.15                          | 4.53           | .79      | 50000                            |
| 032       | 66225 - 66462D           | 2.2500 | 4.6250           | 2.1250                 | 2.8750      | 0.14                     | 0.03                       | 2.99                          | 4.37           | .93      | 41200                            |
| 033       | 72225C - 72488D          | 2.2500 | 4.8750           | 2.1875                 | 3.0625      | 0.14                     | 0.06                       | 3.19                          | 4.53           | .79      | 50000                            |
| 034       | 78225 - 78549D           | 2.2500 | 5.5000           | 2.0395                 | 3.0625      | 0.14                     | 0.06                       | 3.27                          | 5.16           | .67      | 55200                            |
| 035       | 66585 - 66522D           | 2.3622 | 5.1174           | 1.8750                 | 2.7500      | 0.14                     | 0.03                       | 3.11                          | 4.65           | .88      | 42800                            |
| 036       | 78250 - 78549D           | 2.5000 | 5.5000           | 2.0395                 | 3.0625      | 0.09                     | 0.06                       | 3.35                          | 5.16           | .67      | 55200                            |
| 037       | 9285 - 9220D             | 3.0000 | 6.3750           | 2.7810                 | 4.1560      | 0.14                     | 0.03                       | 4.06                          | 6.03           | .82      | 81700                            |
| 038       | 9378 - 9320D             | 3.0000 | 7.0000           | 2.9375                 | 4.3125      | 0.14                     | 0.09                       | 4.13                          | 6.46           | .76      | 84200                            |
| 039       | 9380 - 9320D             | 3.0000 | 7.0000           | 2.9375                 | 4.3125      | 0.14                     | 0.09                       | 4.13                          | 6.46           | .76      | 49100                            |
| 040       | 9385 - 9320D             | 3.3125 | 7.0000           | 2.9375                 | 4.3125      | 0.14                     | 0.09                       | 4.37                          | 6.46           | .76      | 84200                            |
| 041       | 9386H - 9320D            | 3.3125 | 7.0000           | 2.9375                 | 4.3125      | 0.14                     | 0.09                       | 4.37                          | 6.46           | .76      | 84200                            |

4

A-A-59655B

<sup>1</sup> Part numbers are for reference only. Part numbers reflect the cup and cone numbers used by industry and the ABMA. Some cones and cups may be used in multiple configurations and are not limited to one bearing assembly.

<sup>2</sup> These maximum fillet radii shall be cleared by the bearing corners.

<sup>3</sup> Minus value indicates load center inside cone backface.

TABLE I. Size codes and dimensions.

| Size code | Part number <sup>1</sup> | d      | D                | C                      | T           | R <sup>2</sup>           | r <sup>2</sup>             | d <sub>a</sub>                | D <sub>a</sub> | K factor | Basic dynamic load ratings (lb.) |
|-----------|--------------------------|--------|------------------|------------------------|-------------|--------------------------|----------------------------|-------------------------------|----------------|----------|----------------------------------|
|           |                          | Bore   | Outside diameter | Bearing width over cup | Cones width | Max. shaft fillet radius | Max. housing fillet radius | Recommended shoulder diameter |                |          | Two row radial                   |
|           | Shaft                    |        |                  |                        |             |                          |                            | Housing                       |                |          |                                  |
| 042       | 98350 - 98789D           | 3.5000 | 7.8750           | 3.1581                 | 4.5625      | 0.14                     | 0.09                       | 4.65                          | 7.40           | .92      | 111700                           |
| 043       | HM921343 - HM921310D     | 3.5400 | 7.4790           | 2.1300                 | 3.3800      | 0.14                     | 0.06                       | 4.61                          | 7.13           | .67      | 79600                            |
| 044       | M919048 - M919010D       | 3.5425 | 6.3740           | 1.7500                 | 2.7500      | 0.14                     | 0.06                       | 4.29                          | 6.06           | .80      | 56700                            |
| 045       | HM821547 - HM821511D     | 3.9362 | 7.7500           | 2.9300                 | 4.0700      | 0.14                     | 0.06                       | 4.84                          | 7.36           | .96      | 103700                           |
| 046       | 98400 - 98789D           | 4.0000 | 7.8750           | 3.1581                 | 4.5625      | 0.14                     | 0.09                       | 5.04                          | 7.40           | .92      | 111700                           |
| 047       | 37425 - 37626D           | 4.2500 | 6.2500           | 1.5625                 | 2.1251      | 0.14                     | 0.03                       | 4.80                          | 5.98           | .96      | 32400                            |
| 048       | 37431 - 37626D           | 4.3125 | 6.2500           | 1.5625                 | 2.1251      | 0.14                     | 0.03                       | 4.84                          | 5.98           | .96      | 32400                            |
| 049       | H924045 - H924010D       | 4.3750 | 8.4375           | 3.3125                 | 4.5625      | 0.14                     | 0.06                       | 5.47                          | 8.07           | .87      | 129100                           |
| 050       | HH924349 - HH924310D     | 4.3750 | 9.5000           | 4.2500                 | 6.2500      | 0.25                     | 0.06                       | 6.18                          | 8.90           | .80      | 184000                           |
| 051       | HM926740 - HM926710D     | 4.5000 | 9.0000           | 3.3125                 | 4.5625      | 0.14                     | 0.09                       | 5.75                          | 8.63           | .79      | 136100                           |
| 052       | 97500 - 97901D           | 5.0000 | 9.0000           | 3.3125                 | 4.5625      | 0.14                     | 0.09                       | 5.94                          | 8.38           | .79      | 102600                           |

5

A-A-59655B

<sup>1</sup> Part numbers are for reference only. Part numbers reflect the cup and cone numbers used by industry and the ABMA. Some cones and cups may be used in multiple configurations and are not limited to one bearing assembly.

<sup>2</sup> These maximum fillet radii shall be cleared by the bearing corners.

<sup>3</sup> Minus value indicates load center inside cone backface.

## A-A-59655B

## 3. SALIENT CHARACTERISTICS

3.1 Dimensions. Bearing dimensions (and dynamic load ratings, see 3.4) shall conform to the requirements specified in table I for each of the bearing part numbers. The listed dimensions conform to the requirements specified in American Bearing Manufacturers Association (ABMA) Standard 19.2, "Tapered Roller Bearings - Radial Inch Design". The bearing size shall be specified in the acquisition order (see 7.3(b)). For any unlisted bearing size codes, the associated dimensional and dynamic load rating requirements should also be specified in the acquisition order.

3.2 Materials.

3.2.1 Cones (inner rings), cups (outer rings), and rollers. The bearing cones, cups, and rollers shall be made of case carburized or through-hardened steel produced in accordance with the ASTM International (ASTM) A295/A295M, "Standard Specification for High-Carbon Anti-Friction Bearing Steel", or ASTM A534, "Standard Specification for Carburizing Steels for Anti-Friction Bearings". The steel shall show a fine fracture grain size in accordance with ASTM E112, "Standard Test Methods for Determining Average Grain Size". Material hardness shall be no less than Rockwell hardness number of 58 on Rockwell C scale (HRC) and no more than 64 HRC as defined in ASTM E18, "Standard Test Methods for Rockwell Hardness of Metallic Materials".

3.2.2 Cage. The bearing cage material shall be impervious to deterioration from any lubricant, preservative, solvent, or other chemical substance expected to contact the bearing during normal use or storage. Similarly, the material shall not cause any chemical deterioration of any other bearing component. The cages shall be made from carbon steel (one piece stamped). Materials shall operate from -65 to 230 °F (-53.9 to 110 °C).

3.3 Tolerance class. The tolerance limits for bearings shall conform to tolerance class 4 as tabulated in ABMA Standard 19.2. Allowable tolerances for bearing components and assembled bearings are listed in tables II through V.

TABLE II. Cone bore tolerance.

| Cone bore (d) |           |           |       |
|---------------|-----------|-----------|-------|
| Size range    |           | Tolerance |       |
| Over          | Inclusive | Plus      | Minus |
| 0.0000        | 3.0000    | 5         | 0     |
| 3.0000        | 8.0000    | 10        | 0     |

Note: Allowable tolerances are in 0.0001 inch.

## A-A-59655B

TABLE III. Cup diameter tolerance.

| Cup diameter (D) |           |           |       |
|------------------|-----------|-----------|-------|
| Size range       |           | Tolerance |       |
| Over             | Inclusive | Plus      | Minus |
| 0.0000           | 12.0000   | 10        | 0     |
| 12.0000          | 24.0000   | 20        | 0     |

Note: Allowable tolerances are in 0.0001 inch.

TABLE IV. Bearing width tolerance.

| Bearing width (T) |           |           |       |
|-------------------|-----------|-----------|-------|
| Bore size range   |           | Tolerance |       |
| Over              | Inclusive | Plus      | Minus |
| 0.0000            | 4.0000    | 160       | 0     |
| 4.0000            | 12.0000   | 280       | 200   |

Note: Allowable tolerances are in 0.0001 inch.

TABLE V. Assembled bearing tolerance.

| Assembled bearing maximum radial runout |           |           |
|---|-----------|-----------|
| Cup outside diameter (D)                |           | Tolerance |
| Over                                    | Inclusive |           |
| 0.0000                                  | 24.0000   | 20        |

Note: Allowable tolerances are in 0.0001 inch.

3.4 Dynamic load rating. The bearing dynamic load rating shall conform to the requirements specified in [table I](#) for each bearing size code. The listed ratings conform to the requirements specified in ABMA Standard 11, "Load Ratings and Fatigue Life for Roller Bearings".

3.5 Lubrication. The bearings shall be furnished without lubrication.

3.6 Contact angle. All bearings are steep angle bearings having a contact angle between 22 and 31 degrees. The contact angle is the angle between the line of action of the roller load and a plane perpendicular to the bearing axis.

## A-A-59655B

## 4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Foreign acquisition restrictions. Unless otherwise indicated in the solicitation and resulting contract, the foreign acquisition restrictions in Section 252.225, Clause 252.225.7016, of the Defense Federal Acquisition Regulation Supplement (DFARS) apply to products described by this CID.

## 5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.


5.2 Market acceptability. The products offered must have been previously sold either to the government or on the commercial market.

## 6. PACKAGING

6.1 Preservation, packing, and marking. Unless otherwise specified in the acquisition order, the bearings shall be preserved, packaged, and marked in accordance with MIL-DTL-197, "Packaging of Bearings, Associated Parts and Subassemblies" (see 7.3(c)).

## 7. NOTES

7.1 Part or identification number (PIN). The following PIN procedure is for government purposes and does not constitute a requirement for the contractor.



AA59655 - 002 indicates: Bearing bore 0.7500 inches; outside diameter 2.2500 inches; width 1.4375 inches.



## A-A-59655B

7.2 Sources of documents.

7.2.1 DFARS and FAR. Copies of DFARS and FAR may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies of DFARS may be obtained from <http://www.acq.osd.mil/dpap/dars/dfarspgi/current/index.html>. Electronic copies of FAR may be obtained from <https://www.acquisition.gov/far/>.

7.2.2 Military specifications. Copies of military specifications may be obtained from Standardization Documents Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. Electronic copies may be obtained from <https://assist.daps.dla.mil/>.

7.2.3 ABMA standards. Copies of ABMA standards may be obtained from the American Bearing Manufacturers Association, 2025 M Street NW, Suite 800, Washington, DC 20036. Electronic copies may be obtained from <http://www.abma-dc.org/>.

7.2.4 ASTM standards. Copies of ASTM standards may be obtained from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959. Electronic copies may be obtained from <http://www.astm.org/>.

7.3 Ordering data. The acquisition order should specify the following information:

- a. CID document number, revision, and CID PIN.
- b. Bearing size (with dimension/load requirements if size is unlisted) (see 3.1).
- c. Preservation, packaging, and marking requirements (see 6.1).

7.4 Cross-reference information. [Table VI](#) relates the original specification slant sheets to the replacement CIDs.

TABLE VI. Federal specification to CID cross-reference.

| FF-B-187B specification sheets | Replacement CID numbers | ABMA types         |
|--------------------------------|-------------------------|--------------------|
| 1                              | A-A-59649               | TS                 |
| 2                              | A-A-59650               | TSF                |
| 3                              | A-A-59651               | TSS                |
| 4                              | A-A-59652               | TSSF               |
| 5                              | A-A-59653               | TDI and TDIS       |
| 6                              | A-A-59654               | TDO                |
| 7                              | A-A-59655               | TDOS               |
| 8                              | A-A-59656               | TNA (normal angle) |
| 9                              | A-A-59657               | TNAS (steep angle) |
| 10                             | A-A-59658               | TNASW              |
| 11                             | A-A-59659               | TNASWE             |

A-A-59655B

7.5 Subject term (key word) listing.

Bore  
Cone  
Cup  
Load  
Width

MILITARY INTERESTS:

Custodians:

Army - AR  
Navy - MC  
Air Force - 99  
DLA - GS

Review Activities:

Navy - OS  
Air Force - 84

CIVIL AGENCY  
COORDINATING ACTIVITY:

GSA - FAS

Preparing Activity:

DLA - GS4

(Project 3110-2011-024)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at <https://assist.daps.dla.mil/>.