DATA ITEM DESCRIPTION

Title: Electromagnetic Interference Test Report (EMITR)

Number: DI-EMCS-80200B Approval Date: 19990820

AMSC Number: F7354 Limitation:

DTIC Applicable: GIDEP Applicable:

Office of Primary Responsibility: F-11

Applicable Forms:

Use/Relationships: The EMITR provides the data and information necessary to evaluate compliance of an equipment or subsystem with its electromagnetic interference (EMI) control requirements based on MIL-STD-461, including the discussion of recommended corrective actions, if needed.

This Data Item Description (DID) contains the format and content preparation instructions for the EMITR required by 5.1 of MIL-STD-461.

This DID is related to DI-EMCS-80199B, Electromagnetic Interference Control Procedures (EMICP), and DI-EMCS-80201B, Electromagnetic Interference Test Procedures (EMITP).

This DID supersedes DI-EMCS-80200A.

Requirements:

- 1. Format. Contractor format is acceptable.
- 2. Content. The EMITR shall contain the following:
- 2.1. Administrative data. The EMITR shall contain an administrative section covering the following:
 - a. Contract number.
 - b. Authentication and certification of performance of the tests by a qualified representative of the procuring activity.
 - c. Disposition of the Equipment Under Test (EUT).
 - d. Description of the EUT, including its function, characteristics, intended installation, actual cable types (characteristics and construction details see 4.3.8.6 of MIL-STD-461), and electrical current usage on each power input line.
 - e. List of tests performed with pass/fail indications.
 - f. Any approved deviations from contractual test procedures or limits previously authorized.
 - g. Identification of Non-Developmental Items (NDI) and Government Furnished Equipment (GFE) that may be part of the EUT.
 - h. Traceability of test equipment calibration.
 - i. A reference to the approved EMI test procedure (EMITP).

DI-EMCS-80200B

- 2.2. Detailed results. A separate appendix shall be prepared for each test. If deviations from an approved test procedure occurred during the test program, an additional appendix shall be provided with the "as run" procedures showing all red-lines and procuring activity concurrence. A separate appendix shall be provided for log sheets. Each test appendix shall contain the following factual data:
- a. Test equipment nomenclature, serial numbers, version of software used (if any), and calibration due date.
 - b. Photographs or diagrams of the actual test set up and EUT, with identification.
 - c. Transfer impedance of current probes.
 - d. Antenna factors.
 - e. Impedance values of Line Impedance Stabilization Networks (LISN).
 - f. Identification of any suppression devices used to meet the contractual requirements, including schematics, performance data, and drawings.
 - g. Sample calculations, such as conversions of measured levels for comparison against the applicable limit.
 - h. The ambient radiated and conducted electromagnetic emission profile of the test facility, when necessary.
 - i. Data, and data presentation, as specified in the "data presentation" sections of the individual test procedures of MIL-STD-461.
 - j. Scan speeds.
 - k. Measurement receiver bandwidths.
 - 1. Antenna polarization.
 - m. Power line voltages, frequencies, and power factor.
 - n. Low-noise amplifiers (LNA) compression points.
 - o. Any thresholds of susceptibility that were determined.
- 2.3. Conclusions and recommendations. Conclusions and recommendations shall be provided, including results of the tests in brief narrative form, a discussion of any remedial actions already initiated, and proposed corrective measures required (if necessary) to assure compliance of the equipment or subsystem with the contractual EMI requirements.
- 3. End of DI-EMCS-80200B.