

Department of Defense Standardization Program



ASSIST UPDATE

(A bi-monthly summary of changes to the ASSIST document database)

1 May 2011

(For the Period 15 April 2011 to 30 April 2011)

ASSIST UPDATE

Documents listed in the ASSIST UPDATE have an indicator of “N” or “M” to describe the last action taken on a listed document.

“N” indicates that a “new” document has been entered into the ASSIST database.

“M” indicates that a document already in ASSIST has been “modified” in some way.

The ASSIST UPDATE is published twice a month and provides a summary of changes to Department of Defense standardization documents for the period indicated. Since changes are processed to the ASSIST database on a daily basis, users should consult the ASSIST web site at <https://assist.daps.dla.mil> for the most current information.

If you need to track changes more frequently, or if you have an interest in specific Federal Supply Classes or individual specifications, standards, or other standardization documents, you may wish to take advantage of the ASSIST Alert Service. This feature lets you establish a list of documents of interest to you, and then the ASSIST will alert you with an E-mail message each day there is a change to one or more documents of interest to you. There is no charge for this service; however, you must have an ASSIST user account. To obtain one, complete the ASSIST online registration form at <https://assist.daps.dla.mil/online/registration/registration.cfm>.

Once you have your account, you can establish your Alert Portal profile. For more information on the ASSIST Alert Service, go to: <https://assist.daps.dla.mil/online/news/AlertService.htm>.

ACTIVE SECTION

ASSIST UPDATE

LAST ACTION			DISTRIBUTION	FSC/AREA	MCA	PREP ACTY	DATE
	DOCUMENT NUMBER	DOCUMENT TITLE					
M	MIL-PRF-62550/2B	Heater Assembly, Combustion Vehicular Compartment, 17.6 kW, Dual Air Type (Metric) [CUST: AT]	A	2540	AT		18-APR-2011
M	MIL-DTL-6193D(3)	Joints, Universal, Plain, Light and Heavy Duty, General Specification for [CUST: AR AS 99 CC] [REVIEW: 71 AV CG CR4 MC SA]	A	3010	CC		14-APR-2011
M	MS20270E	Joint-Universal, Plain, Light Duty, without Lubrication Cover [CUST: AR AS 99 CC] [REVIEW: 71 AV CG CR4 GS MC SA]	A	3010	CC		14-APR-2011
M	MS20271E	Joint-Universal, Plain, Heavy Duty, with Lubrication Cover [CUST: AR AS 99 CC] [REVIEW: 71 AV CG CR4 GS MC SA]	A	3010	CC		14-APR-2011
M	MIL-DTL-81581/5B NOT 1	Hose Assemblies, Breathing Oxygen, Low Pressure, Connector to Regulator [CUST: AS 11]	A	4720	AS		27-APR-2011
M	QPL-25579-58	Hose Assembly, Polytetrafluorethylene, High Temperature, Medium Pressure, General Specification for	A	4720	CC		18-APR-2011
M	MIL-DTL-52525/1D	Fittings, Hose, Screw-on to 37 Degrees Flare Female Swivel, Straight, SAE-J516 Type, for Assembly with SAE-J517, Type 100R2 Hose [CUST: AT SH 99 CC] [REVIEW: AS CG CR4 MC SA YD]	A	4730	CC		21-APR-2011
M	MIL-DTL-52525/3D	Fittings, Hose, Screw-on to 37 Degrees Flare Female Swivel, 90 Degrees Bent Tube, Short Drop [CUST: AT SH 99 CC] [REVIEW: AS CG CR4 MC SA YD]	A	4730	CC		21-APR-2011
M	MIL-DTL-52525/4D	Fittings, Hose, Screw-on to 37 Degrees Flare Female Swivel, 90 Degrees Bent Tube, Long Drop [CUST: AT SH 99 CC] [REVIEW: AS CG CR4 MC SA YD]	A	4730	CC		21-APR-2011
M	MIL-DTL-52525/5D	Fittings, Hose, Screw-on to 37 Degrees Flare Female Swivel, Straight [CUST: AT SH 99 CC] [REVIEW: AS CG CR4 MC SA YD]	A	4730	CC		21-APR-2011
M	MIL-DTL-52525/7D	Fittings, Hose, Screw-on to 37 Degrees Flare Female Swivel, 90 Degrees Bent Tube, Short Drop [CUST: AT SH 99 CC] [REVIEW: AS CG CR4 MC SA YD]	A	4730	CC		21-APR-2011
M	MIL-DTL-52525/10D	Fittings, Hose, Screw-on to 4-Bolt Split-Flange, Straight [CUST: AT SH 99 CC] [REVIEW: AS CG CR4 MC SA YD]	A	4730	CC		21-APR-2011
M	MIL-DTL-52525/12D	Fittings, Hose, Screw on to Split-Flange 90 Degrees Bent [CUST: AT SH 99 CC] [REVIEW: AS CG CR4 MC SA YD]	A	4730	CC		21-APR-2011
M	A-A-59326C	Coupling Halves, Quick-Disconnect, Cam-Locking Type [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	14-APR-2011
M	A-A-59326/2C	Coupling Half, Male by Hose Shank, Type II [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	15-APR-2011
M	A-A-59326/3B	Coupling Half, Male by External Pipe Thread, Type III [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	15-APR-2011
M	A-A-59326/4B	Coupling Half, Male by Flange (TTMA), Type IV [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	20-APR-2011
M	A-A-59326/5B	Coupling Half, Female by Internal Pipe Thread, Type V [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	20-APR-2011
M	A-A-59326/6C	Coupling Half, Female by Hose Shank, Type VI [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	20-APR-2011
M	A-A-59326/7B	Coupling Half, Female by External Pipe Thread, Type VII [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	20-APR-2011
M	A-A-59326/8B	Coupling Half, Female by Flange,(TTMA), Type VIII [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	20-APR-2011
M	A-A-59326/9B	Coupling Half, Female by Flange, Hexagon, Type VIIIA, (for D-1 Nozzle) [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	21-APR-2011
M	A-A-59326/10B	Coupling Half, Cap, Dust, Type IX [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	21-APR-2011
M	A-A-59326/11B	Coupling Half, Plug, Dust, Type X [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	21-APR-2011
M	A-A-59326/12B	Reducer, Male by Female and Female by Male, Type XI [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	21-APR-2011
M	A-A-59326/13B	Reducer, Male by External Pipe Thread, Type XII [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	21-APR-2011
M	A-A-59326/14B	Reducer, External Pipe Thread by Female, Type XIII [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	21-APR-2011
M	A-A-59326/15B	Adapter, 45 Degrees, Female Thread Swivel Collar by Male (Tank Car), Type XV [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	21-APR-2011
M	A-A-59326/16B	Coupling Half, Female by External Straight Threads, Type XVI, (for use with NATO Equipment) [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	22-APR-2011
M	A-A-59326/17B	Coupling Half, Male by Internal Straight Threads, Type XVII (for use with NATO Equipment) [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	22-APR-2011
M	A-A-59326/18B	Coupling Half, Female Reducer by Internal Pipe Thread, Type XVIII [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	22-APR-2011
M	A-A-59326/19B	Coupling Half, Nipple Adapter, Male by External Grooved Pipe, Type XIX [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	22-APR-2011
M	A-A-59326/20B	Y Connection, Flanged, Type XX [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	22-APR-2011
M	A-A-59326/21B	Adapter, Male by Male, Cam Locking Type, Type XXI [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	22-APR-2011
M	A-A-59326/22A	Adapter, Female by Female, CAM Locking Type XXII [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	22-APR-2011
N	A-A-59326/23	Coupling Half, Nipple Adapter, Female by External Groove Pipe, Type XXIII [CUST: AT YD 99] [REVIEW: 71 AV CC GL MC SH]	A	4730	/	AT	22-APR-2011
M	MIL-PRF-12125H	Valve, Gate: Quick-Opening, Class 125 Cast Iron, with Position Lock [CUST: AT CG]	A	4820	AT		27-APR-2011
M	A-A-59828A	Oil Cooling Cart [CUST: 84]	A	4920	/	84	27-APR-2011
M	MS51957D(1)	Screw, Machine, Pan Head, Cross-Recessed, Corrosion Resistant Steel, UNC-2A [CUST: AR YD1 99 IS] [REVIEW: AT AV CR4 GL MC MI NS SH]	A	5305	IS		20-APR-2011
M	MS51960D	Screw, Machine-Flat Countersunk Head, 82 Degree, Cross-Recessed, Corrosion Resistant Steel, UNF-2A [CUST: AV SH 99 IS] [REVIEW: AT EA MC MI OS]	A	5305	IS		20-APR-2011
M	MS90402A	Screw, Captive [CUST: AR AS 11 IS] [REVIEW: AV CC CG MC MI]	A	5305	IS		20-APR-2011
N	NA0077	Nut, Self-Locking, Plate, Fixed, One Lug Reduced Rivet Spacing, Low Height, C'Bored 1100 MPA, Metric, 235 Degrees C [CUST: AR 11 IS] [REVIEW: AV]	A	5310	IS		20-APR-2011
N	NA0078	Nut, Self-Locking, Plate, Fixed, One Lug Reduced Rivet Spacing, Low Height, C'Bored, 900 MPA, Metric, 235 Degrees C, 425 Degrees C [CUST: AR 11 IS] [REVIEW: AV]	A	5310	IS		20-APR-2011

ACTIVE SECTION

ASSIST UPDATE

LAST ACTION			DISTRIBUTION	FSC/AREA	MCA	PREP ACTY	DATE
	DOCUMENT NUMBER	DOCUMENT TITLE					
N	NA0079	Nut, Self-Locking, Plate, Fixed, Two Lug, Steel, Reduced Rivet Spacing, Low Height, C'Bore, 1100 MPA, Metric, 235 Degrees C [CUST: AR 11 IS] [REVIEW: AV]	A	5310	IS		20-APR-2011
N	NA0080	Nut, Self-Locking, Plate, Fixed, Two Lug, CRES, Reduced Rivet Spacing, Low Height, C'Bore, 900 MPA, Metric, 235 Degrees C, and 425 Degrees C [CUST: AR 11 IS] [REVIEW: AV]	A	5310	IS		20-APR-2011
N	NA0081	Nut, Self-Locking, Plate, Fixed, Corner, Steel, Reduced Rivet Spacing, Low Height, C'Bore, 1100 MPA, Metric, 235 Degrees C [CUST: AR 11 IS] [REVIEW: AV]	A	5310	IS		20-APR-2011
N	NA0082	Nut, Self-Locking, Plate, Fixed, Corner, CRES, Reduced Rivet Spacing, Low Height, C'Bore, 900 MPA, Metric 235 Degrees C and 425 Degrees C [CUST: AR 11 IS] [REVIEW: AV]	A	5310	IS		20-APR-2011
N	NA0084	Nut, Self-Locking, Plate, Fixed, Side by Side, CRES Reduced Rivet Spacing, Low Height, C'Bore, 900 MPA, Metric 235 Degrees C and 425 Degrees C [CUST: AR 11 IS] [REVIEW: AV]	A	5310	IS		20-APR-2011
N	NA0095	Nut, Self-Locking, Plate, Corner, Steel, Low Height, C'Bore, 1100 MPA, Metric, 235 Degrees C [CUST: AV 11 IS] [REVIEW: 99]	A	5310	IS		20-APR-2011
N	NA0096	Nut, Self-Locking, Plate, Corner, CRES, Low Height, 900 MPA, Metric 235 Degrees C and 425 Degrees C [CUST: AV 11 IS] [REVIEW: 99]	A	5310	IS		20-APR-2011
M	MIL-PRF-20/27G	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR75 and CC75 [CUST: CR EC 85 CC] [REVIEW: 99 AS MC OS SH]	A	5910	CC		21-APR-2011
M	MIL-PRF-20/28D	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR76 and CC76 [CUST: CR EC 85 CC] [REVIEW: 99 AS AV MC MI OS]	A	5910	CC		21-APR-2011
M	MIL-PRF-20/29E	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR77 and CC77 [CUST: CR EC 85 CC] [REVIEW: 99 AS MC OS SH]	A	5910	CC		21-APR-2011
M	MIL-PRF-20/30D	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR78 and CC78 [CUST: CR EC 85 CC] [REVIEW: 99 AS MC OS SH]	A	5910	CC		21-APR-2011
M	MIL-PRF-20/31C	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR79 and CC79 [CUST: CR EC 85 CC] [REVIEW: 99 AS MC OS SH]	A	5910	CC		21-APR-2011
M	MIL-PRF-20/35K	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR05, CC05, CCR09, and CC09 [CUST: CR EC 85 CC] [REVIEW: 99 AS MC OS SH]	A	5910	CC		21-APR-2011
M	MIL-PRF-20/36G	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR06 and CC06 [CUST: CR EC 85 CC] [REVIEW: 99 AS MC OS SH]	A	5910	CC		21-APR-2011
M	MIL-PRF-20/37F	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR07 and CC07 [CUST: CR EC 85 CC] [REVIEW: 99 AS AV MC OS SH]	A	5910	CC		21-APR-2011
M	MIL-PRF-20/38C	Capacitors, Fixed, Ceramic Dielectric (Temperature Compensating), Established and Non-Established Reliability, Styles CCR08 and CC08 [CUST: CR EC 85 CC] [REVIEW: 99 AS MC OS SH]	A	5910	CC		21-APR-2011
M	MIL-PRF-81/1E	Capacitors, Variable, Ceramic Dielectric, Style CV11 [CUST: CR EC 85 CC] [REVIEW: 19 99 AR MI]	A	5910	CC		19-APR-2011
M	MIL-PRF-81/6F	Capacitors, Variable, Ceramic Dielectric, Styles CV35 and CV36 [CUST: 85 CC] [REVIEW: 19 99]	A	5910	CC		21-APR-2011
M	MIL-PRF-31033B	Capacitors, Fixed, Ceramic Dielectric, High Reliability, Discoidal, General Specification for [CUST: CR EC 85 CC NA] [REVIEW: 19 99 AR AS AT AV MC MI OS SH]	A	5910	CC		29-APR-2011
M	MIL-PRF-39006/30C	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85 Degrees C (Voltage Derated to 125 Degrees C), Established Reliability, Style CLR90 [CUST: CR EC 85 CC] [REVIEW: 19 99 AS MC OS]	A	5910	CC		21-APR-2011
M	MIL-PRF-39006/31C	Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), (Extended Range), 85 Degrees C (Voltage Derated to 125 Degrees C), Established Reliability, Style CLR91 [CUST: CR EC 85 CC] [REVIEW: 19 99 AS MC OS]	A	5910	CC		21-APR-2011
M	MS24523J	Switch, Toggle, One Pole, Environmentally Sealed [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS24524K	Switch, Toggle, Two Pole, Environmentally Sealed [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS24525K	Switch, Toggle, Four Pole, Environmentally Sealed [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS24658G	Switch, Toggle, One Pole, Environmentally Sealed, Lever Lock [CUST: CR AS 85 CC] [REVIEW: 99 AR AT AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS24659G	Switch, Toggle, Four Pole, Environmentally Sealed, Lever Lock [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS24660G	Switch, Toggle, Four Pole, Environmentally Sealed, Lever Lock [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27406E	Switch, Toggle, Four Pole, Environmentally Sealed [CUST: CR AS 85 CC] [REVIEW: 99 AR AV CR4 EC MI]	A	5930	CC		18-APR-2011
M	MS27407E	Switch, Toggle, Two Pole, Environmentally Sealed [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27408E	Switch, Toggle, Two Pole, Environmentally Sealed, Lever Lock [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27409E	Switch, Toggle, Four Pole, Environmentally Sealed, Lever Lock [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27723D	Switch, Toggle, Two Pole, Environmentally Sealed, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27724E	Switch, Toggle, Four Pole, Environmentally Sealed, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27734E	Switch, Toggle, One Pole, Environmentally Sealed, Solder Terminal [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27735E	Switch, Toggle, Two Pole, Environmentally Sealed, Solder Terminal [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27736E	Switch, Toggle, Four Pole, Environmentally Sealed, Solder Terminal [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011

ACTIVE SECTION

ASSIST UPDATE

LAST ACTION			DISTRIBUTION	FSC/AREA	MCA	PREP ACTY	DATE
	DOCUMENT NUMBER	DOCUMENT TITLE					
M	MS27737G	Switch, Toggle, One Pole, Environmentally Sealed, Lever-Lock, Solder Terminal [CUST: CR AS 85 CC] [REVIEW: 99 AV EC]	A	5930	CC		18-APR-2011
M	MS27738F	Switch, Toggle, Two Pole, Environmentally Sealed, Lever Lock, Solder Terminal [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27739F	Switch, Toggle, Four Pole, Environmentally Sealed, Lever Lock, Solder Terminal [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27781D	Switch, Toggle, One Pole, Environmentally Sealed, Lever Lock, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27782D	Switch, Toggle, Two Pole, Environmentally Sealed, Lever Lock, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27783D	Switch, Toggle, Four Pole, Environmentally Sealed, Lever Lock, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27784D	Switch, Toggle, One Pole, Environmentally Sealed, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AV EC]	A	5930	CC		18-APR-2011
M	MS27785D	Switch, Toggle, Two Pole, Environmentally Sealed, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27786D	Switch, Toggle, Two Pole, Environmentally Sealed, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27787D	Switch, Toggle, One Pole, Environmentally Sealed, Lever Lock, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MS27788D	Switch, Toggle, One Pole, Environmentally Sealed, Lever Lock, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI]	A	5930	CC		18-APR-2011
M	MIL-DTL-12883/45D(2)	Sockets, Plug-In Electronic Components, for Relays, for 2-Pole, 5 Amperes (MIL-PRF-6106 and MIL-PRF-83536) [CUST: CR EC 85 CC] [REVIEW: 99 AR AS AT AV CR4 MC OS SH]	A	5935	CC		20-APR-2011
M	MIL-DTL-32139A(2)	Connectors, Electrical, Rectangular, Nanominiature, Polarized Shell, General Specification for [CUST: CR EC 85 CC] [REVIEW: 99 AV MI]	A	5935	CC		13-APR-2011
M	MIL-STD-1669A(1)	Insert Arrangements for MIL-DTL-26482 Environment Resisting, Circular, Electrical Connectors [CUST: CR AS 85 CC] [REVIEW: AR AV EC MI SH]	A	5935	CC		01-APR-2011
M	MIL-PRF-27/155C	Transformers, Power, Stepdown [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS SH]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/164D	Transformers and Inductors (Audio, Power, and High-Power Pulse) Inductors, High Q [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS MC MI OS SH]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/172E	Transformers, Audio Frequency, Micro-Miniature [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC OS]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/240B	Transformers and Inductors (Audio, Power and High-Power Pulse) Inductors, Audio Frequency, High Q [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS MC MI OS SH]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/289B	Transformers and Inductors (Audio, Power and High-Power Pulse) Inductors, Power [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS MC MI OS]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/318C	Transformers, Power, 80 Volt-Amperes, 60 Hertz [CUST: CR EC 85 CC] [REVIEW: 99 AR AS CR4 MC OS SH]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/327D	Transformers, Power, 15 VA, 60 Hertz [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC OS]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/328C	Transformers, Power, 30 VA, 60 Hertz [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC OS]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/340E	Transformers, Power, 15 Voltamperes, 400 HZ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC OS]	A	5950	CC		22-APR-2011
M	MIL-PRF-27/360A	Transformers, Power, 15 VA, Electrostatic Shielded [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC OS]	A	5950	CC		22-APR-2011
M	MIL-STD-1311D	Test Methods for Electron Tubes [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS AV CG CR4 MI OS SH SM]	A	5960	CC		19-APR-2011
M	MIL-PRF-19500/586K	Semiconductor Device, Diode, Silicon, Schottky Barrier, Hermetic Types 1N5817-1, 1N5817UR-1, 1N5819-1, 1N5819UR-1, 1N6761-1, and 1N6761UR-1, JAN, JANTX, JANTXV, JANS, JANHC, and JANKC [CUST: CR EC 85 CC NA] [REVIEW: 19 99 AR AS MC MI SM]	A	5961	CC		22-APR-2011
M	MIL-PRF-19500/620H	Semiconductor Device, Hermetic, Diode, Silicon, Rectifier, Schottky Barrier, Types 1N5822, 1N5822US, 1N6864, 1N6864US, JAN, JANTX, JANTXV, JANS, JANHC, and JANKC [CUST: CR EC 85 CC NA] [REVIEW: 19 AR AS MC MI SM]	A	5961	CC		25-APR-2011
M	IPC-TM650.2.1.1	Microsectioning, Manual Method [CUST: CR EC 85 CC] [REVIEW: 99]	A	5998	CC		06-DEC-1988
M	MIL-PRF-29595A	Batteries and Cells, Lithium, Rechargeable, Aircraft, General Specification for [CUST: CR AS 99 GS] [REVIEW: 11 71 AV]	A	6140	AS		26-APR-2011
N	MIL-PRF-29595/1	Battery, Storage, Aircraft, Maintenance-Free, 26-Volt, 25-Ampere-Hour [CUST: AS]	A	6140	AS		26-APR-2011
M	QPL-24176-33 NOT 1	Cement, Epoxy, Metal Repair and Hull Smoothing (Metric) (Replaced by the Qualified Products Database (QPD) See Notice 1 for Additional Information)	A	8030	SH		26-APR-2011
M	MIL-DTL-32237A	Boot, Combat, Hot Weather Army [CUST: GL CT]	A	8430	CT		15-APR-2011
M	DI-HFAC-81743A	Human Systems Integration Program Plan [AMSC: N9190]	A	HFAC	AS		21-APR-2011
N	SAE-AMS2768	Heat Treatment of Magnesium Alloy Castings [CUST: MR AS 11] [REVIEW: 99 AT MI]	A	MECA	MR		18-APR-2011
M	DI-TMSS-81784A	Army S1000D Project Business Rules [AMSC: A9189]	A	TMSS	TM		19-APR-2011

INACTIVE SECTION

ASSIST UPDATE

LAST ACTION			DISTRIBUTION	FSC/AREA	MCA	PREP ACTY	DATE
	DOCUMENT NUMBER	DOCUMENT TITLE					
M	MIL-PRF-62550/1A NOT 2	Heater Assembly, Combustion Vehicular Compartment, 17.6 kW, Single Air Type (Metric) [CUST: AT]	A	2540		AT	18-APR-2011

CANCELED SECTION

ASSIST UPDATE

LAST ACTION	DOCUMENT NUMBER	DOCUMENT TITLE	DISTRIBUTION	FSC/AREA	MCA	PREP ACTY	DATE
M	ASTM-D295	Cotton Fabrics, Varnished, Used for Electrical Insulation (No S/S Document) [CUST: CR SH 85]	A	2520		SH	18-APR-2011
M	MIL-PRF-62550/3A NOT 2	Heater Assembly, Combustion Vehicular Compartment, 8.8 kW, Single Air Type (Metric) (S/S by MIL-PRF-32222) [CUST: AT]	A	2540		AT	18-APR-2011
M	ASTM-E120	Chemical Analysis of Titanium and Titanium Alloys (No S/S Document) [CUST: MR AS] [REVIEW: AT AV GS MI OS]	A	3439		AS	18-APR-2011
M	NAS526	Gage, Stylus, Flushness for 100 Degrees Countersunk Flush Fasteners (See Notice of Withdrawal for Replacement Information) [CUST: AV AS] [REVIEW: CR CR4]	A	5220		AS	20-APR-2011
M	NAS527	Inspection Procedure for Flash Fasteners (See Notice of Withdrawal for Replacement Information) [CUST: AV AS] [REVIEW: CR CR4]	A	5220		AS	20-APR-2011
M	MS35203B NOT 2	Screw, Machine-Flat Countersunk Head, 82 Degrees, Cross-Recessed, Aluminum Alloy, Anodic Coated, UNF-2A (S/S by NASM35203) [CUST: AR SH 99 IS] [REVIEW: AT AV CR4 EA MC MI]	A	5305		IS	20-APR-2011
M	MS51871 NOT 2	Screw, Tapping-High Performance, Zone Hardened Structural Thread Rolling, Hexagon Washer Head (S/S by NASM51871) [CUST: AR SH 99 IS] [REVIEW: AS AT AV CR4 MC OS]	A	5305		IS	20-APR-2011
M	NA0061	Nut, Self-Locking, Spline Drive, Alloy Steel, 1800 MPA, 235 Degrees C, Metric (No S/S Document) [CUST: AV 11 IS] [REVIEW: 71 99]	A	5310		IS	20-APR-2011
M	NA0077ANDNA0078	Nut, Self-Locking, Plate, Fixed, One Lug Reduced Rivet Spacing, Low Height, C'Bored, 1100 MPA, Metric 235 Degrees C, 425 Degrees C (S/S by NA0077 and NA0078) [CUST: AR 11 IS] [REVIEW: AV]	A	5310		IS	20-APR-2011
M	NA0079ANDNA0080	Nut, Self-Locking, Plate, Fixed, Two Lug, Reduced Rivet Spacing, Low Height, C'Bored, 1100 MPA, Metric, 235 Degrees C, 425 Degrees C (S/S by NA0079 and NA0080) [CUST: AR 11 IS] [REVIEW: AV]	A	5310		IS	20-APR-2011
M	NA0081ANDNA0082	Nut, Self-Locking, Plate, Fixed, Corner, Reduced Rivet Spacing, Low Height, C'Bored, 100 MPA, Metric 235 Degrees C, 425 Degrees C (S/S by NA0081 and NA0082) [CUST: AR 11 IS] [REVIEW: AV]	A	5310		IS	20-APR-2011
M	NA0083ANDNA0084	Nut, Self-Locking, Plate, Fixed, Side by Side Reduced Rivet Spacing, Low Height, C'Bored, 1100 MPA, Metric 235 Degrees C, 425 Degrees C (S/S by NA0084) [CUST: AR 11 IS] [REVIEW: AV]	A	5310		IS	20-APR-2011
M	NA0095ANDNA0096	Nut, Self-Locking, Plate, Corner Low Height, C'Bored, 1100 MPA, Metric 235 Degrees C, 425 Degrees C (S/S by NA0095 and NA0096) [CUST: AV 11 IS] [REVIEW: 99]	A	5310		IS	20-APR-2011
M	ASTM-A687	Steel Bolts and Studs, High-Strength Nonheaded (No S/S Document) [CUST: AR YD IS]	A	53GP		IS	18-APR-2011
M	MIL-DTL-24236/16G NOT 1	Switch, Thermostatic (Metallic), Type II, Overheat Detector, Adjustable, Dual Terminal, 3 Amperes (No S/S Document) [CUST: CR EC 85 CC]	A	5930		CC	13-APR-2011
M	ASTM-F773	Measuring Dose Rate Response of Linear Integrated Circuits (Metric) (No S/S Document) [CUST: CR EC 85 CC NA] [REVIEW: 19 99 AR AS CG MC MI OS SH SM TD]	A	5962		CC	18-APR-2011
M	ASTM-E338	Sheet Materials, High-Strength, Sharp-Notch Tension Testing of (No S/S Document) [CUST: MI AS 99] [REVIEW: GS]	A	6635		MI	18-APR-2011
M	ASTM-D456	Soda (Anhydrous), Caustic (No S/S Document) [CUST: EA SH 68] [REVIEW: GS]	A	6810		EA	18-APR-2011
M	ASTM-D969	Paint, Degree of Bleeding of Traffic, Laboratory Determination of (See Notice of Withdrawal for Replacement Information) [CUST: CR4 SH 99]	A	8010		84	18-APR-2011
M	ASTM-D1963	Oils, Varnishes, Resins, and Related Materials at 25/25 Degrees C, Specific Gravity of (No S/S Document) [CUST: CR4 SH 11]	A	8010		CR4	18-APR-2011
M	ASTM-D585	Paper, Paperboard, Fiberboard and Related Product, Sampling and Accepting a Single Lot of (No S/S Document) [CUST: SM SA 11]	A	8135		SM	18-APR-2011
M	ASTM-D918	Paper and Paperboard, Blocking Resistance of (No S/S Document) [CUST: SM SA 11]	A	8135		SM	18-APR-2011
M	ASTM-D1117	Fabrics, Evaluating Nonwoven (No S/S Document) [CUST: GL SH 99 CT] [REVIEW: 84]	A	8305		CT	18-APR-2011
M	ASTM-D1059	Yarn Number Based on Short-Length Specimens (No S/S Document) [CUST: GL SH 99 CT]	A	8310		CT	18-APR-2011
M	ASTM-D5104	Fibers, Textile (Single-Fiber Test), Shrinkage of (No S/S Document) [CUST: GL NU 99 CT] [REVIEW: 11 CG]	A	83GP		CT	18-APR-2011
M	ASTM-D3337	Greases, Lubricating, in Small Ball Bearings, Determining Life and Torque of (No S/S Document) [CUST: CR4 AS 68] [REVIEW: GS]	A	9150		AS	18-APR-2011
M	ASTM-D590	Petroleum Wax in Paper (No S/S Document) [CUST: GL SH 68] [REVIEW: IS]	A	9160		GL	18-APR-2011
M	ASTM-D1263	Wheel Bearing Greases, Automotive, Leakage Tendencies of (No S/S document) [CUST: AT SH 11] [REVIEW: 68 AR AS]	A	91GP		AT	18-APR-2011
M	ASTM-D689	Paper, Internal Tearing Resistance of (No S/S Document) [CUST: SM AS 11] [REVIEW: 99 AR CR4 GL GS IS MI MR OS SA SH YD]	A	9310		AS	18-APR-2011
M	ASTM-D724	Paper, Surface Wettability of (Angle-of-Contact Method) (No S/S Document) [CUST: SM AS 11] [REVIEW: GS]	A	9310		AS	18-APR-2011
M	ASTM-D726	Paper to Passage of Air, Nonporous, Resistance of (No S/S Document) [CUST: GL SA 99] [REVIEW: GS]	A	9310		MB	18-APR-2011
M	ASTM-D774	Paper, Bursting Strength of (No S/S Document) [CUST: SM AS 11]	A	9310		AS	18-APR-2011
M	ASTM-D779	Water Resistance of Paper, Paperboard, and Other Sheet Materials by the Dry Indicator Method (No S/S Document) [CUST: SM AS 11] [REVIEW: 99 AR CR4 GL GS MI MR OS SA SH YD]	A	9310		AS	18-APR-2011
M	ASTM-D695M	Properties of Compressive Rigid Plastics (Metric) (No S/S Document) [CUST: MR 11] [REVIEW: AR AS AT AV CR4 GL GS IS MI OS SH YD]	A	9330		MR	18-APR-2011
M	ASTM-A525M	Steel Sheet, Zinc-Coated (Galvanized by the Hot-Dip Process (Metric) (See Notice of Withdrawal for Replacement Information) [CUST: MR YD 99] [REVIEW: IS MC SH]	A	9515		YD	18-APR-2011
M	ASTM-A591/A591M	Steel Sheet, Electrolytic Zinc-Coated, for Light Coating Weight (Mass) Applications (See Notice of Withdrawal for Replacement Information) [CUST: MR YD 99] [REVIEW: 84 IS SH]	A	9515		YD	18-APR-2011
M	ASTM-E62	Copper and Copper Alloys, Chemical Analysis of, (Photometric Methods) (No S/S Document) [CUST: MR YD 99] [REVIEW: 84 AS IS OS SH]	A	95GP		YD	18-APR-2011
M	ASTM-E75	Copper-Nickel and Copper-Nickel-Zinc Alloys, Chemical Analysis of (No S/S Document) [CUST: MR SH 99] [REVIEW: IS]	A	95GP		SH	18-APR-2011
M	ASTM-E602	Sharp-Notch Tension Testing and Cylindrical Specimens, Standard Method for (No S/S Document) [CUST: MR AS] [REVIEW: IS SH]	A	95GP		MR	18-APR-2011
M	ASTM-E577	Building Parts and Systems, Rectilinear, Coordination of (No S/S Document) [CUST: CR4 YD 99] [REVIEW: 84 CE MC]	A	FACR		YD	18-APR-2011
M	ASTM-E713	Scales for Metric Building Drawings, Selection of (No S/S Document) [CUST: CR4 YD 99] [REVIEW: 84 CE MC]	A	FACR		YD	18-APR-2011
M	ASTM-E835/E835M	Clay and Concrete Masonry Units, Modular Coordination of (No S/S Document) [CUST: CR4 YD 99] [REVIEW: 84 CE MC]	A	FACR		YD	18-APR-2011
M	MIL-M-6857D NOT 2	Magnesium Alloy Castings, Heat Treatment of (S/S by SAE-AMS2768) [CUST: MR AS 11] [REVIEW: 99 AT MI]	A	MECA		MR	18-APR-2011

CANCELED SECTION

ASSIST UPDATE

LAST ACTION			DISTRIBUTION	FSC/AREA	MCA	PREP ACTY	DATE
	DOCUMENT NUMBER	DOCUMENT TITLE					
M	MIL-PRF-49506 NOT 2	Logistics Management Information (S/S by GEIA-STD-0007) [CUST: TM AS 10 SE] [REVIEW: DC MC NS]	A	SESS		TM	31-MAR-2011
M	MIL-HDBK-514 NOT 2	Operational Safety, Suitability, and Effectiveness for the Aeronautical Enterprise (No S/S Document) [CUST: 11] [REVIEW: 70 71 84]	A	SESS		11	02-MAY-2011