

Department of Defense Standardization Program



ASSIST UPDATE

(A bi-monthly summary of changes to the ASSIST document database)

15 August 2011

(For the Period 1 August 2011 to 14 August 2011)

ASSIST UPDATE

Documents listed in the ASSIST UPDATE have an indicator of “N” or “M” to describe the last action taken on a listed document.

“N” indicates that a “new” document has been entered into the ASSIST database.

“M” indicates that a document already in ASSIST has been “modified” in some way.

The ASSIST UPDATE is published twice a month and provides a summary of changes to Department of Defense standardization documents for the period indicated. Since changes are processed to the ASSIST database on a daily basis, users should consult the ASSIST web site at <https://assist.daps.dla.mil> for the most current information.

If you need to track changes more frequently, or if you have an interest in specific Federal Supply Classes or individual specifications, standards, or other standardization documents, you may wish to take advantage of the ASSIST Alert Service. This feature lets you establish a list of documents of interest to you, and then the ASSIST will alert you with an E-mail message each day there is a change to one or more documents of interest to you. There is no charge for this service; however, you must have an ASSIST user account. To obtain one, complete the ASSIST online registration form at <https://assist.daps.dla.mil/online/registration/registration.cfm>.

Once you have your account, you can establish your Alert Portal profile. For more information on the ASSIST Alert Service, go to: <https://assist.daps.dla.mil/online/news/AlertService.htm>.

ACTIVE SECTION

ASSIST UPDATE

| LAST ACTION | DOCUMENT NUMBER | DOCUMENT TITLE | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|--------------------------|---|--------------|----------|-----|-----------|-------------|
| M | MIL-DTL-2980F | Firing Attachments, Blank Ammunition [CUST: AR OS 99] [REVIEW: 40 70 AS MC MR NP] | D | 1005 | | AR | 17-MAY-2011 |
| M | MIL-DTL-1318D(1) | Cartridge, Caliber .50, Tracer - M17 [CUST: AR OS 99] [REVIEW: 70 AS MC MR NP] | D | 1305 | | AR | 02-AUG-2011 |
| M | MIL-DTL-3066D(1) | Cartridges, Caliber .50: Armor-Piercing Incendiary, M8; and Armor- Piercing Incendiary Tracer, M20 [CUST: AR OS 99] [REVIEW: 40 70 AS MC MR NP] | D | 1305 | | AR | 02-AUG-2011 |
| N | MIL-DTL-32395 | Cartridge, 5.56 Millimeter: Tracer - M856A1 [CUST: AR OS 99] [REVIEW: 40 70 AS MC MR NP] | D | 1305 | | AR | 10-AUG-2011 |
| M | MIL-DTL-45403E | Link, Cartridge, Metallic Belt, 7.62 Millimeter - M13 [CUST: AR OS 99] [REVIEW: 40 70 AS MC MR NP] | D | 1305 | | AR | 12-AUG-2011 |
| M | MIL-STD-636A | Visual Inspection Standards for Small Arms Ammunition through Caliber .50 [CUST: AR OS 99] [REVIEW: 40 70 AS MC MR NP] | D | 1305 | | AR | 29-JUL-2011 |
| M | MIL-DTL-50523A | Charge, Demolition - M112 Parts for and Loading, Assembling and Packing [CUST: AR OS 11] [REVIEW: 70 99 AS NP] | A | 1375 | | AR | 02-AUG-2011 |
| M | MIL-DTL-7034/1A(1) NOT 1 | Pulley, Groove, Secondary Control, Aircraft [CUST: AT AS 99] [REVIEW: 71] | A | 1640 | | GS5 | 03-AUG-2011 |
| M | MIL-DTL-7034/2A(1) NOT 1 | Pulley, Groove, Flight Control, Aircraft [CUST: AV AS 99] [REVIEW: 71] | A | 1640 | | GS5 | 03-AUG-2011 |
| M | MIL-DTL-7034/3A(1) NOT 1 | Pulley, Groove, Heavy Duty, Control, Aircraft [CUST: AV AS 99] [REVIEW: 71] | A | 1640 | | GS5 | 03-AUG-2011 |
| M | A-A-52424B | Caps, Radiator: Pressure Relieving (Metric) [CUST: AT MC 99] [REVIEW: CC CR4] | A | 2930 | / | AT | 03-AUG-2011 |
| M | MS21946E | Body, Cluster Fitting, One-Way, Internal Boss [CUST: AV AS 99 CC] [REVIEW: 71 AR MC SA] | A | 4730 | | CC | 04-AUG-2011 |
| M | MS21958D | Body, Cluster Fitting, Two-Way, 180 Degrees, Internal Boss [CUST: AV AS 99 CC] [REVIEW: 71 AR MC SA] | A | 4730 | | CC | 04-AUG-2011 |
| M | MS21959D | Body,Cluster Fitting, Two-Way, 90 Degrees, Internal Boss [CUST: AV AS 99 CC] [REVIEW: 71 AR MC SA] | A | 4730 | | CC | 04-AUG-2011 |
| M | MS21960D | Body, Cluster Fitting, Three-Way, Internal Boss [CUST: AV AS 99 CC] [REVIEW: 71 AR MC SA] | A | 4730 | | CC | 04-AUG-2011 |
| M | MS9090D | Bolt Machine, Drilled 12 Point Head, Steel, .3125-24 UNF-3A [CUST: AS IS] | A | 5306 | | IS | 04-AUG-2011 |
| M | A-A-59769 NOT 1 | Resistor Networks, Ball Grid Array Terminators General Requirements for [CUST: EC CC] | A | 5905 | / | CC | 08-AUG-2011 |
| M | A-A-59769/1 NOT 1 | Resistor Networks, Ball Grid Array Terminators Thevenin Termination [CUST: EC CC] | A | 5905 | / | CC | 08-AUG-2011 |
| M | MIL-PRF-15160/61G | Fuses, Instrument, Power, and Telephone (Nonindicating), Style F61 [CUST: CR SH 85 CC] [REVIEW: 19 99 AR AS AT CG CR4 MC MI OS YD] | A | 5920 | | CC | 09-AUG-2011 |
| M | MIL-PRF-15160/62G | Fuses, Instrument, Power, and Telephone (Nonindicating), Style F62 [CUST: CR SH 85 CC] [REVIEW: 19 99 AR AS AT CG CR4 MC MI OS YD] | A | 5920 | | CC | 09-AUG-2011 |
| N | A-A-59886 | Circuit Breakers, Miniature, Thermal Magnetic, Shock Enhanced, Trip-Free Series Trip, High Density Design, 35 MM Din Channel Mount, 0.2 to 30 Amperes (A), General Requirements for [CUST: EC CC] | A | 5925 | / | CC | 12-AUG-2011 |
| N | A-A-59886/1 | Circuit Breakers, Miniature, Thermal Magnetic, Shock Enhanced, Trip-Free, Series Trip, High Density Design, 35 MM Din Channel Mount, One Pole, 0.2 to 30 Amperes (A) [CUST: EC CC] | A | 5925 | / | CC | 12-AUG-2011 |
| N | A-A-59886/2 | Circuit Breakers, Miniature, Thermal Magnetic, Shock Enhanced, Trip-Free, Series Trip, High Density Design, 35 MM Din Channel Mount, Two Pole, 0.2 To 30 Amperes (A) [CUST: EC CC] | A | 5925 | / | CC | 12-AUG-2011 |
| N | A-A-59886/3 | Circuit Breakers, Miniature, Thermal Magnetic, Shock Enhanced, Trip-Free, Series Trip, High Density Design, 35 MM Din Channel Mount, Three Pole, 0.2 to 30 Amperes (A) [CUST: EC CC] | A | 5925 | / | CC | 12-AUG-2011 |
| M | MIL-PRF-8805/7H NOT 1 | Switches, Push, Momentary, 2 Circuit or SPST (10 Amperes), Unsealed [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS AV MC NA OS SH] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-8805/27E NOT 1 | Switches, Sensitive, 10 Amperes and Low Level, Unsealed [CUST: CR EC 85 CC] [REVIEW: 19 AR AS AV MC MI] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-PRF-8805/41C NOT 1 | Switches, Sensitive, DPDT, Plunger, 5 Ampere, Hermetic [CUST: CR EC 85 CC] [REVIEW: 19 MC SH] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-PRF-8805/44F NOT 1 | Switches, Sensitive, SPST, 5 Amperes, Resilient Seal [CUST: CR EC 85 CC] [REVIEW: 99 AR AS AV CR4 MC MI OS SH] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-PRF-8805/45G NOT 1 | Switches, Sensitive, SPST, 5 Amperes, Resilient Seal [CUST: CR EC 85 CC] [REVIEW: 99 AR AS AV CR4 MC MI OS SH] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-PRF-8805/46E NOT 1 | Switches, Sensitive, SPST, 4 Amperes, Hermetic [CUST: CR EC 85 CC] [REVIEW: 19 99 AM AS AT AV MC MI OS SH] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-PRF-8805/56G NOT 1 | Switch, Assemblies, Sensitive, Interlock, Unsealed [CUST: CR EC 85 CC] [REVIEW: 19 AS AV MC MI OS] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-PRF-8805/82E NOT 1 | Switches, Sensitive, Leaf, SPDT, 4 Amperes, Hermetic [CUST: CR EC 85 CC] [REVIEW: 19 99 AM AS AT AV MC MI OS SH] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-8805/96E NOT 1 | Switches, Push, Momentary, SPST, 5 Amperes [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS AV MC MI OS SH] | A | 5930 | | CC | 04-AUG-2011 |
| M | MIL-PRF-8805/115 NOT 1 | Switches, Pushbutton, Momentary, Double Pole, 4 Amperes, Low Level, Sealed [CUST: EC CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-PRF-22885/9L NOT 2 | Switch, Push Button, Illuminated, 4-Lamp, Solid Mount, (Modular Constructed) [CUST: CR EC 85 CC] [REVIEW: 19 99 AS AV MC MI OS SH] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/53D NOT 2 | Switch, Push Button, Illuminated, Pushbutton For (With Lamp-Cap Color Filters) [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS SH] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/71C NOT 2 | Switches, Push Button, Illuminated, 7 Amperes and Low Level, 4-Lamp, RFI Shielded, Solid Mount [CUST: CR EC 85 CC] [REVIEW: 70 84 99 MI SA SH] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/75E NOT 2 | Switches, Pushbutton, Illuminated, 4-Lamp, 0.87 Square, 7 Amperes, Electromagnetic Interference Shielded [CUST: CR EC 85 CC] [REVIEW: 99 AR AS AV CR4 MC OS SH] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/82C NOT 2 | Switch, Push Button, Illuminated, Lens Assemblies For, .665 Sq and .916 Lg X .665 Wide [CUST: EC CC] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/85D NOT 2 | Switch, Push Button, Illuminated, Lens Plate for, 1.030 Long X .730 Wide [CUST: CR EC 85] [REVIEW: 19 99 AR AS AV MC MI OS SH] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/86C NOT 2 | Switch, Push Button,Illuminated, 4 Lamp, .870 Square, 2 Amperes, 2PDT and 4PDT, Plug-in Module, EMI/RFI Shielding [CUST: EC CC] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/87C NOT 2 | Switch, Push Button, Illuminated, 4 Lamp, Solid Mount, Modular Constructed, High Impact Shock [CUST: CR EC 85 CC] [REVIEW: 19 99 AS AT AV CR4 MC OS SH] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/88C NOT 2 | Switch, Push Button, Illuminated, High Impact Shock, Modular Switch Assemblies for [CUST: CR EC 85 CC] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/91C NOT 2 | Switch, Push Button, Illuminated, Rocker, Paddle, Solid State Hall Effect, Unsealed [CUST: CR EC 85] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/92B NOT 2 | Switch, Pushbutton, Illuminated, Rocker, Paddle, Power Duty, Unsealed [CUST: EC 85] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-22885/99B NOT 2 | Switch, Push Button, Illuminated, Push Buttons for (Snap-in and Screw-in) [CUST: CR EC 85 CC] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-PRF-24236/24E NOT 1 | Switches, Thermostatic, (Bimetallic), Subminiature, Type I, Hermetically Sealed, Single Pole, Double Throw (SPDT), 2 Amperes and Low Level [CUST: CR EC 85 CC] [REVIEW: AR AT AV CR4 MC MI OS] | A | 5930 | | CC | 02-AUG-2011 |

ACTIVE SECTION

ASSIST UPDATE

| LAST ACTION | DOCUMENT NUMBER | DOCUMENT TITLE | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|-------------------------|---|--------------|----------|-----|-----------|-------------|
| M | MIL-DTL-15291/1B NOT 1 | Switches, Rotary, Snap Action Class 1SR Front Mounted, Back Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/2B NOT 1 | Switches, Rotary, Snap Action Class 1SR Front Mounted, Side Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/3B NOT 1 | Switches, Rotary, Snap Action Class 1SR Base Mounted, Side Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/5B NOT 1 | Switches, Rotary, Snap Action Class 3SR Front Mounted, Back Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/6C NOT 1 | Switches, Rotary, Snap Action Class 3SR Front Mounted, Side Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/7B NOT 1 | Switches, Rotary, Snap Action Class 3SR Base Mounted, Side Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/9B NOT 1 | Switches, Rotary, Snap Action Class 6SR Front Mounted, Back Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/10B NOT 1 | Switches, Rotary, Snap Action Class 6SR Base Mounted, Side Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/12C NOT 1 | Switches, Rotary, Snap Action Class 20SR Front Mounted, Side Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/13B NOT 1 | Switches, Rotary, Snap Action Class 20SR Base Mounted, Side Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MS18150K NOT 1 | Switch, Toggle, 2 Circuit, Sealed Toggle [CUST: CR EC 85 CC] [REVIEW: 99 AS AV] | A | 5930 | | CC | 02-AUG-2011 |
| M | MS18151K NOT 1 | Switch, Toggle, One Pole, Sealed Toggle [CUST: CR EC 85 CC] [REVIEW: 99 AS AV] | A | 5930 | | CC | 02-AUG-2011 |
| M | MS21346F NOT 1 | Switch, Toggle, Positive Break, Lever Lock and Toggle, Miniature, Toggle Sealed, Integrated Wire Terminals, Single Pole, .469 Mounting Bushing [CUST: CR AS 85 CC] [REVIEW: 99 AR EC MI] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS21347K NOT 1 | Switch, Toggle, Positive Break, Miniature, Toggle Sealed, and --Lever Lock-- Miniature, Toggle Sealed, Integrated Wire Terminals, Double Pole, .469 Mounting Bushing [CUST: AS 85 CC] [REVIEW: 19 99 EC] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS21995F NOT 1 | Switch, Rotary, Ammeter - Voltmeter Selector, 115/220 Volts, for 1, 2, or 4 Generator System [CUST: CR AS 85 CC] [REVIEW: 99 AV EC MI] | A | 5930 | | CC | 02-AUG-2011 |
| M | MS24456E NOT 1 | Switch, Sensitive, Sealed, SPDT, Class A5 or B8 [CUST: MI CC] | A | 5930 | | CC | 04-AUG-2011 |
| M | MS25034K NOT 1 | Guard, Switch, 3 Position [CUST: CR AS 85 CC] [REVIEW: 99] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS25125L NOT 1 | Switches, Toggle, Unsealed and Sealed Toggle General Specification for [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS25126L NOT 1 | Switches, Toggle, Unsealed and Sealed Toggle General Specification for [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS25224H NOT 1 | Guard, Switch, 2 Position [CUST: CR AS 85 CC] [REVIEW: 99 AV] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS27752D NOT 1 | Guard, Switch, 3 Position [CUST: CR AS 85 CC] [REVIEW: 99] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS35058K NOT 1 | Switch, Toggle One Pole, Sealed Toggle [CUST: CR AS 85 CC] [REVIEW: 99 AV EC MI] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-J-641/3D NOT 4 | Jacks, Telephone Types JJ-022, JJ-042, JJ-073, JJ-074, JJ-075, JJ-077, and JJ-078 [CUST: CR EC 85 CC] [REVIEW: 19 AS CG MC OS SH] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-J-641/5D NOT 4 | Jacks, Telephone Type JJ-033 [CUST: CR EC 85 CC] [REVIEW: 19 AS CG MC MI OS] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-J-641/6C NOT 4 | Jacks, Telephone Type JJ-034 [CUST: CR EC 85 CC] [REVIEW: 19 MC SH] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-J-641/7C NOT 4 | Jacks, Telephone, Type JJ-048 [CUST: CR EC 85 CC] [REVIEW: 19 MC] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-J-641/19E NOT 3 | Jacks, (Bantam) Telephone, 3 Conductor, Single [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS AV CR4 MC MI] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-DTL-2726/3D NOT 2 | Receptacle, Plug, Electrical, 4-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current, 60-Hertz (Symbol No. 717.1) [CUST: SH CC] | A | 5935 | | CC | 02-AUG-2011 |
| M | MIL-C-28731/32B NOT 3 | Connector, Electrical, Insert (Insulator), Female Rectangular, Polarized, Center Screw Lock, for 117 Removable Type Contacts [CUST: CR EC 85] [REVIEW: 19 99 AR AS AT AV CR4 MC MI OS] | A | 5935 | | CC | 10-AUG-2011 |
| M | MIL-C-28804/2D NOT 3 | Connectors, Plug, Electric, Rectangular, High Density, Polarized Center Jackscrew, Crimp Removable Pin Contacts, Class G [CUST: CR EC 85] [REVIEW: 99 AM AR AS AT CR4 MC MI] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-C-28804/3D NOT 3 | Connectors, Receptacle, Electric, Rectangular, High Density, Polarized Center Jackscrew, Crimp Removable Socket Contacts, Class E [CUST: CR EC 85] [REVIEW: 99 AM AR AS AT CR4 MC MI] | A | 5935 | | CC | 10-AUG-2011 |
| M | MIL-C-28804/4D NOT 3 | Connectors, Plug, Electric, Rectangular, High Density, Polarized Center Jackscrew, Crimp Removable Pin Contacts, Class E [CUST: CR EC 85] [REVIEW: 99 AM AR AS AT CR4 MC MI] | A | 5935 | | CC | 10-AUG-2011 |
| M | MIL-C-28804/5D NOT 3 | Connectors, Receptacle, Electric, Rectangular, High Density, Polarized Center Jackscrew, Crimp Removable Socket Contacts, Class P [CUST: CR EC 85] [REVIEW: 99 AM AR AS AT CR4 MC MI] | A | 5935 | | CC | 10-AUG-2011 |
| M | MIL-C-28804/6D NOT 3 | Connectors, Plug, Electric, Rectangular, High Density, Polarized Center Jackscrew, Crimp Removable Pin Contacts, Class P [CUST: CR EC 85] [REVIEW: 99 AM AR AS AT CR4 MC MI] | A | 5935 | | CC | 10-AUG-2011 |
| M | MIL-C-28804/8D NOT 3 | Connectors, Plug, Electric, Rectangular, High Density, Polarized Center Jackscrew, Solder Pin Contacts, Class S [CUST: CR EC 85] [REVIEW: 99 AM AR AS AT CR4 MC MI] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-C-28804/11D NOT 3 | Connectors, Plug, Electric, Rectangular, High Density, Polarized Center Jackscrew, Interfacial Seal, Solder Pin Contacts, Class SE [CUST: CR EC 85] [REVIEW: 99 AM AR AS AT CR4 MC MI] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-DTL-32385 SUP 1 | Connector, Receptacles, Plugs, Adapter, Used on Electroluminescent, Embedded, and Printed Circuit Board Lamp Lighting Panels [CUST: AV AS 85 GS] [REVIEW: MC SH] | A | 5935 | | GS2 | 14-JUL-2011 |
| M | MIL-DTL-55302/159D(1) | Connectors, Printed Circuit Subassembly and Accessories, Receptacle, 17, 29, 33, 41, 53, and 65 Contact Positions, for Printed Wiring Boards, 2.54 MM X 1.27 MM Offset Grid, Metric [CUST: CR CC] [REVIEW: AR AT AV CR4 MI] | A | 5935 | | CC | 20-JUL-2011 |
| M | MIL-DTL-55302/160D(1) | Connectors, Printed Circuit Subassembly and Accessories, Receptacle, 72, 84, 96, and 120 Contact Positions, for Printed Wiring Boards, 2.54 MM X 1.27 MM Offset Grid, Metric [CUST: CR CC] [REVIEW: AR AT AV CR4 MI] | A | 5935 | | CC | 20-JUL-2011 |
| M | MIL-DTL-55302/161D(1) | Connectors, Printed Circuit Subassembly and Accessories, Receptacle, 160 Contact Positions, for Printed Wiring Boards, 2.54 MM X 1.27 MM Offset Grid, Metric [CUST: CR CC] [REVIEW: AR AT AV CR4 MI] | A | 5935 | | CC | 20-JUL-2011 |
| M | MIL-DTL-55302/162D(1) | Connectors, Printed Circuit Subassembly and Accessories, Plug, 17, 29, 33, 41, 53, and 65 Contact Positions, for Printed Wiring Boards, 2.54 MM X 1.27 MM Offset Grid, Metric [CUST: CR CC] [REVIEW: AR AT AV CR4 MI] | A | 5935 | | CC | 20-JUL-2011 |
| M | MIL-DTL-55302/163D(1) | Connectors, Printed Circuit Subassembly and Accessories, Plug, 72, 84, 96, and 120 Contact Positions, for Printed Wiring Boards, 2.54 MM X 1.27 MM Offset Grid, Metric [CUST: CR CC] [REVIEW: AR AT AV CR4 MI] | A | 5935 | | CC | 20-JUN-2011 |
| M | MIL-DTL-55302/164D(1) | Connectors, Printed Circuit Subassembly and Accessories, Plug and/or Receptacle, 160 Contact Positions, for Printed Wiring Boards, 2.54 MM X 1.27 MM Offset Grid, Metric [CUST: CR CC] [REVIEW: AR AT AV CR4 MI] | A | 5935 | | CC | 20-JUL-2011 |
| M | MIL-S-83505/2B NOT 3 | Socket, (Lead, Electronic Components) (Type II, Printed Circuit) [CUST: CR EC 85] [REVIEW: 99] | A | 5935 | | CC | 09-AUG-2011 |
| M | MIL-C-83527/8 NOT 3 | Connector, Receptacle, Electrical, Rectangular, Rack to Panel, Environment Resisting, 150 Deg. C Continuous Operating Temperature, Multiple Inserts [CUST: CR AS 85] [REVIEW: 19 99 AR EC MC MI OS] | A | 5935 | | CC | 10-AUG-2011 |
| M | DOD-STD-1842 NOT 3 | Insert Arrangements for DOD-C-83527 Rack to Panel Connectors(METRIC) [CUST: CR AS 85] [REVIEW: 19 99 AR EC MC MI OS] | A | 5935 | | CC | 10-AUG-2011 |

ACTIVE SECTION

ASSIST UPDATE

| LAST ACTION | | | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|-------------------------|---|--------------|----------|-----|-----------|-------------|
| | DOCUMENT NUMBER | DOCUMENT TITLE | | | | | |
| M | A-A-55094 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Plug, 24 Position, Discrete Wire Cable Terminating, Bail Locking [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55138 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Receptacle, 24 Position, Cable Terminating, Insulating Displacement, Screw or Bail Locking, Thick Flange [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55139 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Receptacle, 24 Position, Cable Terminating, Insulation Displacement, Screw or Bail Locking, Thin Flange [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55140 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Receptacle, Shielded, 24 Position, Flat Cable Terminating, Insulation Displacement, Screw Locking, Preamsembled Construction [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55142 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Plug, Low Profile, 24 Position, Flat Cable Terminating, Insulation Displacement, Screw Locking [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55144 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Receptacle, Shielded, 24 Position, Vertical Mount, Printed Circuit Board Terminating, Screw Locking [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55148 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, 24 Position, Back to Back Interface Bus, Cable Terminating, Insulation Displacement, Screw Locking [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55151 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Plug and Receptacle, Bail Locking Hardware Kit [CUST: CC] | A | 5935 | / | CC | 09-AUG-2011 |
| M | A-A-55153 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Plug and Receptacle, Metric Jackscrew [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55154 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Rectangular, Low Profile, 24 Position, Flat Cable Terminating, Insulation Displacement, Screw Locking [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55162 NOT 3 | Connectors, Electrical, Sockets Single in Line Memory Module, Single and Dual Vertical Type, 30 or 60 Contacts [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55165 NOT 3 | Connectors, Electrical, Sockets Single in Line Memory Module, Single Vertical Type, 64 Contacts [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55513 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Plug, 24 Position, EMI Shielded, Cable Terminating, Screw Locking [CUST: CC] | A | 5935 | / | CC | 10-AUG-2011 |
| M | A-A-55514 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Plug, 24 Position, Cable Terminating, Insulation Displacement, Screw Locking, Thick Flange [CUST: CC] | A | 5935 | / | CC | 09-AUG-2011 |
| M | A-A-55515 NOT 3 | Connectors, Electrical, IEEE 488 Compatible, Rectangular, Miniature, Polarized Shell, Plug and Receptacle, Snap on Covers, Hardware Kit [CUST: CC] | A | 5935 | / | CC | 09-AUG-2011 |
| M | A-A-55558 NOT 3 | Connector, Receptacle, Electrical, Utility Power, 15 AMP, 125 Volt, 50/60 Hertz with Cover [CUST: CC] | A | 5935 | / | CC | 09-AUG-2011 |
| M | W-C-596/41D NOT 2 | Connector, Receptacle, Electrical, General Purpose, Single, Hospital Grade, Grounding, 2 Pole, 3 Wire, 20 Amperes, 125 Volts, 50/60 Hertz [CUST: CR YD 85 CC] [REVIEW: 19 99 AR AS AV CR4 EC MC MI SH] | A | 5935 | / | CC | 02-AUG-2011 |
| M | W-C-596/64D NOT 2 | Connector, Receptacle, Electrical, General Purpose, Single, General Grade, Grounding, 2 Pole, 3 Wire, 20 Amperes, 250 Volts, 50/60 Hertz [CUST: CR YD 85 CC] [REVIEW: 19 99 AR AS AV CR4 EC MC MI SH] | A | 5935 | / | CC | 02-AUG-2011 |
| M | W-C-596/141C NOT 2 | Connector, Receptacle, Electrical, Male Inlet, General Purpose, Grounding, 2 Pole, 3 Wire, 15 Amperes, 250 Volts, 50/60 Hertz [CUST: CR YD 85 CC] [REVIEW: 19 99 AR AS AV CR4 EC MC MI SH] | A | 5935 | / | CC | 02-AUG-2011 |
| M | W-C-596/142C NOT 2 | Connector, Receptacle, Electrical, Male Inlet, General Purpose, Grounding, 2 Pole, 3 Wire, 20 Amperes, 125 Volts, 50/60 Hertz [CUST: CR YD 85 CC] [REVIEW: 19 99 AR AS AV CR4 EC MC MI SH] | A | 5935 | / | CC | 02-AUG-2011 |
| M | MIL-PRF-27F SUP 1 NOT 2 | Transformers and Inductors (Audio, Power, and High-Power Pulse), General Specification For [CUST: CR EC 85 CC] [REVIEW: AR CR4 MC] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-27/44C NOT 1 | Transformers, Power, 16 Volt Amperes, 400 HZ [CUST: CR EC 85 CC] [REVIEW: 19 AS CR4 MC MI OS SH] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/49D NOT 1 | Transformers, Power, 1.5 Volt Amperes, 400 HZ, Electrostatic Shielded [CUST: CR EC 85 CC] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/51D NOT 1 | Transformers, Power, 3 Volt Amperes, 400 HZ, Electrostatic Shielded [CUST: CR EC 85 CC] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/53D NOT 1 | Transformers, Power, 6 Volt Amperes, 400 HZ, Electrostatic Shielded [CUST: CR EC 85 CC] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-27/55D NOT 1 | Transformers, Power, 16 Volt Amperes, 400 HZ [CUST: CR EC 85 CC] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/57D NOT 1 | Transformers, Power, 50 Volt Amperes, 400 HZ [CUST: CR EC 85] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/58D NOT 1 | Transformers, Power, 75 Volt Amperes, 400 HZ [CUST: CR EC 85] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/59D NOT 1 | Transformers, Power, 100 Volt Amperes, 400 HZ [CUST: CR EC 85] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/61D NOT 1 | Transformers, Power, 16 Volt Amperes, 400 HZ, Electrostatic Shielded [CUST: CR EC 85] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/62D NOT 1 | Transformers, Power, 25 Volt Amperes, 400 HZ, Electrostatic Shielded [CUST: CR EC 85] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-27/63D NOT 1 | Transformers, Power, 50 Volt Amperes, 400 HZ, Electrostatic Shielded [CUST: CR EC 85] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-27/64D NOT 1 | Transformers, Power, 75 Volt Amperes, 400 HZ, Electrostatic Shielded [CUST: CR EC 85] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-27/65D NOT 1 | Transformers, Power, 100 Volt Amperes, 400 HZ, Electrostatic Shielded [CUST: CR EC 85] [REVIEW: 19 99 AS CR4 MC MI OS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-PRF-27/342F NOT 1 | Transformers, Power, 80 Voltamperes, 400 HZ [CUST: CR EC 85] [REVIEW: 19 99 AR AS CR4 MC OS SH] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-27/366 NOT 1 | Transformer, Switching [CUST: CR EC 85 CC] [REVIEW: 19 AR AT AV MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-27/367A NOT 1 | Inductor, Power, High Current, Surface Mount [CUST: CR EC 85 CC] [REVIEW: MI] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-27/368A NOT 1 | Inductor, Power, Surface Mount [CUST: CR EC 85 CC] [REVIEW: MI] | A | 5950 | | CC | 03-AUG-2011 |

ACTIVE SECTION

ASSIST UPDATE

| LAST ACTION | DOCUMENT NUMBER | DOCUMENT TITLE | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|-------------------------|---|--------------|----------|-----|-----------|-------------|
| M | MIL-PRF-27/370A NOT 1 | Inductor, Power, High Current, Surface Mount [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-21038F NOT 1 | Transformers, Pulse, Low Power, General Specification for [CUST: CR EC 85 CC] [REVIEW: 99 AS MI OS SH] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-83446/12A NOT 1 | Coils, Radio Frequency, Chip, Fixed [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/14A NOT 1 | Coils, Radio Frequency, Chip, Fixed [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/15A NOT 1 | Coils, Radio Frequency, Chip, Fixed [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/16A NOT 1 | Coils, Radio Frequency, Chip, Variable [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/17A NOT 1 | Coils, Radio Frequency, Chip, Variable [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/18A NOT 1 | Coils, Radio Frequency, Chip Variable [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/28A NOT 1 | Coils, Radio Frequency, Chip, Fixed, Phenolic Core [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/29A NOT 1 | Coils, Radio Frequency, Chip, Fixed, Iron Core [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/30A NOT 1 | Coils, Radio Frequency, Chip, Fixed, Ferrite Core [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/31A NOT 1 | Coils, Radio Frequency, Chip, Fixed, Phenolic Core [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/32A NOT 1 | Coils, Radio Frequency, Chip, Fixed, Iron Core [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/33A NOT 1 | Coils, Radio Frequency, Chip, Fixed, Ferrite Core [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/34A NOT 1 | Coils, Radio Frequency, Chip, Magnetically Shielded, Iron Core-Iron Sleeve, and Iron Core-Ferrite Sleeve [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/35A NOT 1 | Coils, Radio Frequency, Chip, Fixed, Magnetically Shielded, (Ferrite Core-Ferrite Sleeve) [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/36 NOT 1 | Coils, Radio Frequency, Chip, Open Construction, Surface Mount [CUST: CR EC 85] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-83446/37 NOT 1 | Coils, Radio Frequency, Chip, Open Construction, Surface Mount [CUST: CR EC 85] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-83446/38 NOT 1 | Coils, Radio Frequency, Chip, Fixed Surface Mount [CUST: CR EC 85 CC] [REVIEW: 19 AS MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-PRF-83446/39 NOT 1 | Coils, Radio Frequency, Chip, Fixed, Unshielded, Molded, Surface Mount [CUST: CR EC 85] [REVIEW: 19 AS OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-PRF-83446/40 NOT 1 | Coils, Radio Frequency, Chip, Fixed, Shielded, Molded, Surface Mount [CUST: CR EC 85] [REVIEW: 19 AS OS] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-T-27/140B(1) NOT 4 | Transformers, Power, Step-Down, TF4S03YY [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS SH] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-T-27/141A(1) NOT 4 | Transformers, Power, Step-Down, TF5S03ZZ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS SH] | A | 5950 | | CC | 08-AUG-2011 |
| M | A-A-55096 NOT 2 | Transformer, Printed Circuit Power, 6 Pin [CUST: CC] | A | 5950 | / | CC | 08-AUG-2011 |
| M | A-A-55097 NOT 2 | Transformer, Printed Circuit Power, 8 Pin [CUST: CC] | A | 5950 | / | CC | 08-AUG-2011 |
| M | A-A-55160 NOT 2 | Transformer, Printed Circuit Power, 6 Pin Top Lug Type [CUST: CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-55483A NOT 1 | Shielding Bead, Electronic [CUST: EC CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-55484 NOT 2 | Shielding Beads, Ferrite, Leaded, EMI Suppressor [CUST: CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-55500 NOT 2 | Shielding Bead, Electronic, General Requirements for [CUST: CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-55500/1 NOT 2 | Surface Mount Shielding Bead [CUST: CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59406 NOT 1 | Inductor, Power, Shielded, Surface Mount [CUST: EC CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59408 NOT 1 | Coil, RF, Chip, Fixed, High Current, Surface Mount [CUST: EC CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59696 NOT 1 | Coil, RF, Chip, Fixed, Low Profile, Surface Mount [CUST: EC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59697 NOT 1 | Coil, RF, Chip, Fixed, High Frequency [CUST: EC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59737 NOT 1 | Inductor, Power, Surface Mount [CUST: EC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59738 NOT 1 | Inductor, Power, Low Profile, Surface Mount [CUST: EC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59739 NOT 1 | Coil, RF, Chip, Fixed, High Q, Miniature, Surface Mount [CUST: EC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59740 NOT 1 | Coil, RF, Chip, Fixed, Ceramic, Surface Mount [CUST: EC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59741 NOT 1 | Inductor, Power, Shielded, Ultraminiature, Surface Mount [CUST: EC CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59742 NOT 1 | Inductor, Chip, Power, Low Resistance, Surface Mount [CUST: EC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | A-A-59744 NOT 1 | Choke, Common Mode, Surface Mount [CUST: EC CC] | A | 5950 | / | CC | 04-AUG-2011 |
| M | MIL-PRF-1/1773C(1) | Electron Tube, Magnetron Type DOD-042 [CUST: CR EC 85 CC] [REVIEW: 84 99 AS CG CR4 OS SH] | A | 5960 | | CC | 09-AUG-2011 |
| M | MIL-PRF-19500/108L | Semiconductor Device, Thyristors (Controlled Rectifiers), Silicon, Types 2N682, 2N683, 2N685 through 2N692, 2N692A, 2N5206, JAN and JANTX [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS AV MC MI SM] | A | 5961 | | CC | 08-AUG-2011 |
| M | MIL-PRF-19500/168K | Semiconductor Device, Thyristors (Controlled Rectifiers), Silicon, Types 2N1771A, 2N1772A, 2N1774A, 2N1776A, 2N1777A, 2N1778A, and 2N2619A, JAN, JANTX, and JANTXV [CUST: CR EC 85 CC] [REVIEW: 19 99 AV MI] | A | 5961 | | CC | 15-AUG-2011 |
| M | MIL-PRF-19500/290P | Semiconductor Device, Transistor, PNP, Silicon, Switching, Types, 2N2904, 2N2904A, 2N2904AL, 2N2905, 2N2905A, and 2N2905AL, JAN, JANTX, JANTXV, JANS, JANTXVM, JANTXVD, JANTXVR, JANTXVH, JANS, JANS, JANSR, and JANS [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS MI SM] | A | 5961 | | CC | 12-AUG-2011 |
| M | MIL-PRF-19500/428H | Semiconductor Device, Field-Effect Transistor, N-Channel Silicon, Type 2N4416A and 2N4416AUB, JAN, JANTX, JANTXV, and JANS [CUST: CR EC 85 CC] [REVIEW: 19 99 MC MI] | A | 5961 | | CC | 08-AUG-2011 |
| M | MIL-PRF-19500/511H(1) | Semiconductor Device, Transistor, PNP, Silicon, Switching Type 2N4261, 2N4261UB, 2N4261UBC JAN, JANTX, JANTXV and JANS, JANHC and JANKC [CUST: CR 85 CC NA] [REVIEW: 19 71 99] | A | 5961 | | CC | 06-AUG-2011 |
| M | MIL-DTL-49292/4B NOT 1 | Cable Assemblies, Nonpressure Proof, Fiber Optic, Metric [CUST: CR SH 85 CC] | A | 6020 | | CC | 08-AUG-2011 |
| M | MIL-DTL-49292/7B NOT 1 | Cable Assemblies, Nonpressure Proof, Fiber Optic, Test, Metric [CUST: CR SH 85 CC] [REVIEW: 99 AR AS AV CG EC MC MI] | A | 6020 | | CC | 08-AUG-2011 |
| M | MIL-DTL-83526C NOT 1 | Connectors, Fiber Optic, Circular, Environmental Resistant, Hermaphroditic, General Specification for [CUST: CR AS 85 CC] [REVIEW: 19 99 MI NA SH] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-DTL-55021D | Cable, Electrical, Shielded Singles, Shielded and Jacketed Singles, Twisted Pairs and Triples, Internal Hookup, General Specification for [CUST: MI AS 85 CC] [REVIEW: AR CR] | A | 6145 | | CC | 18-JUL-2011 |

ACTIVE SECTION

ASSIST UPDATE

| LAST ACTION | | | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|--------------------|---|--------------|----------|-----|-----------|-------------|
| | DOCUMENT NUMBER | DOCUMENT TITLE | | | | | |
| M | A-A-50451A | Lamp, Incandescent, RP-11, Bayonet Candelabra, Double Contact [CUST: CR4 SH 99 GS] [REVIEW: 71 IS] | A | 6240 | / | GS2 | 09-AUG-2011 |
| M | MIL-PRF-25017H(1) | Inhibitor, Corrosion/Lubricity Improver, Fuel Soluble (NATO S-1747) [CUST: AT AS 68] [REVIEW: 11 AV GS MD1 PS SH] | A | 6850 | | 68 | 04-AUG-2011 |
| M | MIL-DTL-32237B | Boot, Combat, Hot Weather Army [CUST: GL CT] | A | 8430 | | CT | 11-JUL-2011 |
| M | MIL-DTL-11589/291D | Ribbon, Commander's Award for Public Service, Army [CUST: IH] [REVIEW: CT] | A | 8455 | | IH | 01-AUG-2011 |
| M | MIL-STD-3004C | Quality Assurance/Surveillance for Fuels, Lubricants and Related Products [CUST: AT SA 68 PS] [REVIEW: 11 AS GS OS SH] | A | 91GP | | PS | 10-AUG-2011 |
| M | MIL-PRF-32216A | Evaluation of Commercial Off-the-Shelf (COTS) Manuals and Preparation of Supplemental Data [CUST: TM OS 16 CC] [REVIEW: 01 10 11 13 19 70 84 99 AR AS AT AV CG CR CT EA EC GS MC MD MI OM SA SH TD] [AMSC: A9148] | A | TMSS | | TM | 12-AUG-2011 |
| M | DI-TMSS-80527C | Commercial Off-The-Shelf (COTS) Manuals and Associated Supplemental Data [AMSC: A9207] | A | TMSS | | TM | 12-AUG-2011 |

INACTIVE SECTION

ASSIST UPDATE

| LAST ACTION | DOCUMENT NUMBER | DOCUMENT TITLE | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|-------------------------|--|--------------|----------|-----|-----------|-------------|
| M | MIL-C-48458B(2) NOT 2 | Circuit Card Assembly: 11732392 GCU Electronics [CUST: AR] | C | 1220 | | AR | 11-AUG-2011 |
| M | MIL-DTL-63975A(1) | Primer, Electric, PA520 [CUST: AR] | D | 1305 | | AR | 15-JUL-2011 |
| M | MIL-DTL-63981A(1) | Projectile 30MM, High Explosive Dual Purpose, M789, Metal Parts [CUST: AR] | D | 1305 | | AR | 15-JUL-2011 |
| M | MIL-DTL-45300C | Cap, Fuel Tank: for Military Combat and Tactical Transport Vehicles [CUST: AT MC 99 CC] [REVIEW: 70 GL MI YD] | A | 2910 | | CC | 20-JUL-2011 |
| M | MIL-S-8805/50D NOT 1 | Switches, Sensitive, Roller-Lever, Watertight [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS GL MC MI OS SH] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-S-8805/51D NOT 1 | Switches, Sensitive, Roller-Lever, Watertight [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS GL MC MI OS SH] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-S-8805/53E NOT 1 | Switches, Sensitive, 4 Circuit, Roller-Lever, Watertight [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS MC MI OS SH] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-S-8805/58E NOT 1 | Switch, Actuator, Extended Plunger Type [CUST: CR EC 85 CC] [REVIEW: 19 AR AS AV MC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-S-8805/59D NOT 1 | Switch, Actuator, Roller Leaf [CUST: CR EC 85 CC] [REVIEW: 19 AR AS AV MC MI] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/8B NOT 1 | Switches, Rotary, Snap Action Class 6SR Front Mounted, Back Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MIL-DTL-15291/11B NOT 1 | Switches, Rotary, Snap Action Class 20SR Front Mounted, Back Connected [CUST: SH CC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MS24417K(1) NOT 1 | Guard, Switch, 2 or 3 Position [CUST: CR AS 85 CC] [REVIEW: 99] | A | 5930 | | CC | 02-AUG-2011 |
| M | MS25068K NOT 1 | Switch, Toggle, Four Pole, Sealed Toggle [CUST: CR AS 85 CC] [REVIEW: 99 AV EC] | A | 5930 | | CC | 02-AUG-2011 |
| M | MS25127L NOT 1 | Switches, Toggle, Unsealed and Sealed Toggle General Specification for [CUST: CR AS 85 CC] [REVIEW: 99 AR AV EC MC MI] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS25221G(1) NOT 1 | Guard, Switch, 2 or 3 Position [CUST: CR AS 85 CC] [REVIEW: 99] | A | 5930 | | CC | 02-AUG-2011 |
| M | MS27789D NOT 1 | Switch, Toggle, Four Pole, Environmentally Sealed, Lever Lock, Integrated Wire Terminals [CUST: CR AS 85 CC] [REVIEW: 99 AR AV CR4 EC MC] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS35059K NOT 1 | Switch, Toggle, Two Pole, Sealed Toggle [CUST: CR AS 85 CC] [REVIEW: 99 AV EC MI] | A | 5930 | | CC | 03-AUG-2011 |
| M | MS39058C NOT 1 | Switch, Sensitive-24 Voltage DC (Waterproof) [CUST: AT CC] | A | 5930 | | CC | 03-AUG-2011 |
| M | MIL-DTL-26500G SUP 1 | Connectors, General Purpose, Electrical, Miniature, Circular, Environment Resisting, General Specification for [CUST: 85 CC] [REVIEW: 99] | A | 5935 | | CC | 22-JUL-2011 |
| M | W-C-596/165B NOT 2 | Connector, Plug, Electrical, General Purpose, Grounding, 2 Pole, 3 Wire, 50 Amperes, 250 Volts, 50/60 Hertz [CUST: CR YD 85 CC] [REVIEW: 19 99 AR AS AV CR4 EC MC MI SH] | A | 5935 | / | CC | 02-AUG-2011 |
| M | MIL-R-5757/8F NOT 1 | Relays, Electrical, Hermetically Sealed, DPDT, 2 Amperes [CUST: CR EC 85 CC] [REVIEW: 99 AR AT MI SH] | A | 5945 | | CC | 04-AUG-2011 |
| M | MIL-R-5757/10L NOT 1 | Relays, Electromagnetic, Hermetically Sealed, DPDT, Low Level to 2 Amperes [CUST: CR EC 85 CC] [REVIEW: 19 99 AS AT AV CR4 MC MI NS OS] | A | 5945 | | CC | 03-AUG-2011 |
| M | MIL-R-5757/13H NOT 1 | Relays, Electrical, Hermetically Sealed, DPDT, Low Level to 2 Amperes, (Sensitive, 40 Milliwatts) [CUST: CR EC 85 CC] [REVIEW: 19 99 AS AT AV CR4 MC MI OS SH] | A | 5945 | | CC | 03-AUG-2011 |
| M | MIL-R-5757/29E NOT 1 | Relays, Electrical, 1 PST to 4 PDT Contacts Low-Level to 1/2 Ampere (Dry Reed) [CUST: CR EC 85 CC] [REVIEW: 99 AT AV CR4 MC MI] | A | 5945 | | CC | 04-AUG-2011 |
| M | MIL-R-39016/34F NOT 1 | Relays, Electromagnetic, DPDT, Low Level to 1.0 Ampere, (0.100-Inch Terminal Spacing) [CUST: CR EC 85 CC] [REVIEW: AR AS AT AV CR4 OS SH] | A | 5945 | | CC | 02-AUG-2011 |
| M | MIL-R-39016/40G NOT 1 | Relays, Electromagnetic, 4PDT, Low Level to 2.0 Amperes (0.100-Inch Terminal Spacing) [CUST: CR EC 85 CC] [REVIEW: AS AT AV CR4 OS SH] | A | 5945 | | CC | 03-AUG-2011 |
| M | MIL-R-83407/3D NOT 1 | Relays, Reed (Mercury Wetted), Solder Seal, 0 to 7.5 Volt Amperes [CUST: CR EC 85 CC] | A | 5945 | | CC | 02-AUG-2011 |
| M | MS24577F NOT 1 | Flasher, Solid State, Aircraft Navigational Light [CUST: AV AS 85 CC] [REVIEW: 99 MC] | A | 5945 | | CC | 04-AUG-2011 |
| M | MS25030N NOT 1 | Relay, 50 AMP, 2 PDT (N.O.), Type II, Non-Hermetically Sealed, Mechanically Interlocked [CUST: AS 85 CC] | A | 5945 | | CC | 04-AUG-2011 |
| M | MS25327N NOT 1 | Relays, Electromagnetic, 10 Amperes 4 PDT, Type I, Socket Mounted, Hermetically Sealed [CUST: AS 85 CC] | A | 5945 | | CC | 04-AUG-2011 |
| M | MS25395J(1) NOT 1 | Relays, Electromagnetic, 5 Amperes, 2 PDT, Type I, Hermetically Sealed [CUST: AS 85 CC] | A | 5945 | | CC | 04-AUG-2011 |
| M | MS25918J NOT 1 | Relays, Electromagnetic, 3 Amperes, 6 PDT, Type I [CUST: AS 85 CC] | A | 5945 | | CC | 04-AUG-2011 |
| M | MS27710D NOT 1 | Flasher, Solid State, Aircraft Navigational Light, 28 V DC [CUST: 85 CC] [REVIEW: 99] | A | 5945 | | CC | 04-AUG-2011 |
| M | MIL-PRF-27/235E NOT 1 | Transformers, Power, Isolation, Shielded [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS MC MI OS SH] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-T-27/4 NOT 5 | Transformer, Audio Frequency, TF4R21AJ002 [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/5A NOT 4 | Transformer, Audio Frequency, TF4R21AJ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/8A NOT 5 | Transformer, Audio Frequency, TF4R21AJ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/142C(2) NOT 3 | Transformers and Inductors (Audio, Power and High-Power Pulse) Inductors, Audio Frequency, TF5R20ZZ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS MC OS SH] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-T-27/145 NOT 4 | Transformers and Inductors (Audio, Power and High-Power Pulse) Inductors, Variable, High Q, TF4R20YY [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/148A NOT 4 | Transformer, Power, Step-Down, TF4S03HA [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/153A NOT 4 | Transformer, Power, Step-Down, TF4S03FB [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/154 NOT 4 | Transformer, Power, Step-Down, TF4S03EB [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MI OS SH] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/156A NOT 5 | Transformer, Power, Step-Down, TF4S03AJ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/161A NOT 5 | Transformers and Inductors (Audio, Power and High-Power Pulse), Inductors, Audio Frequency, High Q, TF5R20ZZ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS MC OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/168 NOT 4 | Transformers and Inductors (Audio, Power and High-Power Pulse), Inductors, High Q, TF5R20ZZ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/171C NOT 4 | Transformers and Inductors (Audio, Power and High-Power Pulse), Inductor, Power, TF4S04AG [CUST: CR EC 85 CC] [REVIEW: 19 AR CR4 MC YD] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/183B NOT 4 | Transformer, Power, Step-Down and Step-Up, TF45S03JA [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS SH] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/184B NOT 3 | Transformer, Power, Step-Down, TF4S03AH [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC OS SH] | A | 5950 | | CC | 04-AUG-2011 |

INACTIVE SECTION

ASSIST UPDATE

| LAST ACTION | | | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|-----------------------|--|--------------|----------|-----|-----------|-------------|
| | DOCUMENT NUMBER | DOCUMENT TITLE | | | | | |
| M | MIL-T-27/197B NOT 4 | Transformer, Audio Frequency, TF4R21YY [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS] | A | 5950 | | CC | 04-AUG-2011 |
| M | MIL-T-27/209B NOT 3 | Transformers and Inductors (Audio, Power and High-Power Pulse) Inductor, Power, TF4R04FA [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC MI OS SH] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-T-27/325C NOT 3 | Transformer, Power, TF5S03ZZ [CUST: CR EC 85 CC] [REVIEW: 19 99 AR AS CR4 MC OS SH] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-DTL-28778A NOT 1 | Transformer, Power, Stepup, 3 Phase [CUST: EC] | A | 5950 | | CC | 02-AUG-2011 |
| M | MIL-T-83720/8B NOT 4 | Transformer, Power Step-Up [CUST: 85 CC] | A | 5950 | | CC | 03-AUG-2011 |
| M | MIL-T-83720/13 NOT 4 | Transformer, Power, Step-Up, Step-Down, General Specification for [CUST: 85 CC] [REVIEW: 84 99] | A | 5950 | | CC | 04-AUG-2011 |
| M | MS16403D NOT 3 | Transformer, Power, Step-Down and Step-Up, Type TF4RX03JB221 [CUST: CR EC 85 CC] [REVIEW: 19 AR CG MC MI SH] | A | 5950 | | CC | 04-AUG-2011 |
| M | MS16450F NOT 2 | Transformer, Power, Step-Down, Type TF4RX02HA203 [CUST: CR EC 85 CC] [REVIEW: 19 AR CG MC MI SH] | A | 5950 | | CC | 04-AUG-2011 |
| M | MS16476A NOT 3 | Inductor, (Reactor) Type TF4SX04EB214 [CUST: EC CC] [REVIEW: MI] | A | 5950 | | CC | 04-AUG-2011 |
| M | MS27134B NOT 3 | Transformer, Power, Isolation: Airport Lighting, 300W/6.6A/6.6A/5000V, General Specification for [CUST: 85 CC] [REVIEW: 99 AS YD] | A | 5950 | | CC | 03-AUG-2011 |
| M | MS27286C NOT 3 | Transformer, Power, Isolation: Airport Lighting 200W/20A/6.6A/5000V, General Specification for [CUST: 85 CC] [REVIEW: 99 AS YD] | A | 5950 | | CC | 08-AUG-2011 |
| M | MS27288C NOT 3 | Transformer, Power, Isolation: Airport Lighting, 200W/6.6A/6.6A/5000V, General Specification for [CUST: 85 CC] [REVIEW: 99 AS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MS27289C NOT 3 | Transformer, Power, Isolation: Airport Lighting 30-45W/6.6A/6.6A/5000V, General Specification for [CUST: 85 CC] [REVIEW: 99 AS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MS27302C NOT 3 | Transformer, Power, Isolation: Airport Lighting, 500W/20A/20A/5000V, General Specification for [CUST: 85 CC] [REVIEW: 99 AS] | A | 5950 | | CC | 08-AUG-2011 |
| M | MIL-M-38510/63C NOT 1 | Microcircuits, Digital, ECL, Quad Translator, Monolithic Silicon [CUST: CR EC 85 CC] [REVIEW: 03 19 99 AS CG MC MI SH SM TD] | A | 5962 | | CC | 02-AUG-2011 |
| M | MIL-T-152B(2) NOT 4 | Treatment, Moisture and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment [CUST: CR AS 11 GS] [REVIEW: AR EA EC MI MR] | A | 59GP | | GS3 | 10-AUG-2011 |
| M | MIL-T-29504/10 NOT 3 | Termini, Fiber Optic, Environment Resisting, Class 5, Type II, Style A, Pin Terminus, Size 16, Rear Release MIL-C-83723, Series III, MIL-C-83733, MIL C-26482, Series II [CUST: CR SH 85] [REVIEW: 03 19 33 93 99 AS DI NA] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-T-29504/11 NOT 3 | Termini, Fiber Optic, Environment Resisting, Class 5, Type II, Style A, Socket Terminus, Size 16, Rear Release MIL-C-83723, Series III, MIL-C-83733, MIL-C-26482, Series II [CUST: CR SH 85] [REVIEW: 03 19 33 93 99 AS DI NA] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-C-83522/1F NOT 1 | Connector, Plug, Fiber Optic, Single Terminus, Threaded, (Step-Down Nose Interface), Lensless, Epoxy, for 50/125 um, 62.5/125 um, and 100/140 um [CUST: CR SH 85 CC NA] [REVIEW: 03 19 33 93 99 AS DI] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-C-83522/2G NOT 1 | Connector Plug, Fiber Optic, Single Terminus, Threaded, (Straight Nose Interface), Lensless, Epoxy, for 50/125 mm, 62.5/125 mm, and 100/140 mm [CUST: CR SH 85 CC] [REVIEW: 03 19 33 93 99 AS DI NA] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-C-83522/3G NOT 1 | Connector, Adapter, Fiber Optic, Bulkhead Mount, for Single Fiber [CUST: CR SH 85 CC] [REVIEW: 03 19 33 93 99 AS DI NA] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-C-83522/4F NOT 1 | Connector, Receptacle, Fiber Optic, Single Terminus, Threaded, Receptacle, Low Profile Parallel PC Mount [CUST: CR SH 85] [REVIEW: 03 19 33 93 99 AS DI NA] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-C-83522/5E NOT 1 | Connector, Receptacle, Fiber Optic, Bulkhead Mount, for Single Fiber [CUST: CR SH 85 CC] [REVIEW: 03 19 33 93 99 AS DI NA] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-C-83522/7C NOT 1 | Connector, Receptacle, Fiber Optic, Single Terminus, Threaded, Parallel PC Mount [CUST: CR SH 85 CC] [REVIEW: 03 19 33 93 99 AS DI NA] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-C-83522/8C NOT 1 | Connector, Receptacle, Fiber Optic, Single Terminus, Threaded, Bulkhead, Hex Nut Mount [CUST: CR SH 85 CC] [REVIEW: 03 19 33 93 99 AS DI NA] | A | 6060 | | CC | 08-AUG-2011 |
| M | MIL-DTL-13777/6C | Cable, Special Purpose, Electrical, 60, 65, and 78 Conductors [CUST: AR SH 85 CC] [REVIEW: AT CR CR4 MC MI] | A | 6145 | | CC | 20-JUL-2011 |
| M | MS25216C | Cover, Top and Bottom Fuselage Lights [CUST: AS 99 GS] | A | 6220 | | GS2 | 09-AUG-2011 |
| M | MIL-DTL-6508C | Thermometer, Self-Indicating, Bimetallic, General Specification for [CUST: AR AS 99 GS] [REVIEW: 71] | A | 6685 | | GS1 | 09-AUG-2011 |
| M | MS28028D | Thermometer, Self-Indicating, Bimetallic [CUST: GL AS 99 GS] [REVIEW: 71 CG] | A | 6685 | | GS1 | 09-AUG-2011 |

CANCELED SECTION

ASSIST UPDATE

| LAST ACTION | DOCUMENT NUMBER | DOCUMENT TITLE | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|---------------------|---|--------------|----------|-----|-----------|-------------|
| M | RR-S-001301 NOT 2 | Safety Equipment, Climbing (No S/S Document) [CUST: SH] | A | 4240 | / | SH | 31-MAY-2011 |
| M | EIA364.7 | Contact Axial Concentricity Test Procedure for Electrical Connectors (S/S by EIA/ECA-364-07) [CUST: CR AS 11] | A | 5935 | | AS | 21-JUL-2011 |
| M | EIA364.13 | Mating and Unmating Forces Test Procedure for Electrical Connectors and Sockets (S/S by EIA/ECA-364-13) [CUST: CR AS 11 CC] [REVIEW: 99 AR EC MC MI SH] | A | 5935 | | AS | 21-JUL-2011 |
| M | EIA364.21 | Insulation Resistance Test Procedure for Electrical Connectors, Sockets, and Coaxial Contacts (S/S by EIA/ECA-364-21) [CUST: CR AS 11 CC] [REVIEW: 99 AR EC MC MI SH] | A | 5935 | | AS | 21-JUL-2011 |
| M | EIA364.26 | Salt Spray Test Procedure for Electrical Connectors, Contacts and Sockets (S/S by EIA/ECA-364-26) [CUST: CR AS 11 CC] [REVIEW: 99 AR EC MC MI SH] | A | 5935 | | AS | 21-JUL-2011 |
| M | EIA364.29 | Contact Retention Test Procedure for Electrical Connectors (S/S by EIA/ECA-364-29) [CUST: CR AS 11] | A | 5935 | | AS | 21-JUL-2011 |
| M | EIA364.39 | Hydrostatic Test Procedure for Electrical Connectors, Contacts and Sockets (S/S by EIA/ECA-364-39) [CUST: CR AS 11 CC] [REVIEW: 99 AR EC MC MI SH] | A | 5935 | | AS | 21-JUL-2011 |
| M | EIA359 | Color Identification and Coding, EIA Standard Colors for (No S/S Document) [CUST: CR EC 85] | A | 59GP | | CR | 03-AUG-2011 |
| M | EIA554 | Assessment of Outgoing Non conforming Levels in Parts Per Million (PPM) (No S/S Document) [CUST: CR EC 85] | A | 59GP | | CR | 03-AUG-2011 |
| M | EIA557 | Statistical Process Control Systems (No S/S Document) [CUST: CR EC 85] | A | 59GP | | CR | 03-AUG-2011 |
| M | EIA557.1 | Components, Passive, Guidance for the Selection of Critical Manufacturing Operations for use in Implementing an SPC System for (No S/S Document) [CUST: CR EC 85] | A | 59GP | | CR | 03-AUG-2011 |
| M | W-L-00116D NOT 1 | Lamp, Fluorescent (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/1B NOT 1 | Lamp, Fluorescent Trade No. F6T5/CW, Preheat, 6WATT, T-5 Bulb Cool White, Miniature Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/3C NOT 1 | Lamp, Fluorescent Trade No. F8T5/CW, Preheat, 8 Watt, T-5 Bulb Cool White, Miniature Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/5A NOT 1 | Lamp Fluorescent Trade No. F30T8/CW, Preheat, 30 Watt, T-8 Bulb Cool White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/6C NOT 1 | Lamp Fluorescent Trade No. F8T5/D, Preheat, 8 Watt, T-5 Bulb Daylight, Miniature Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/7B NOT 1 | Lamp Fluorescent Trade No. F14T12/CW, Preheat, 14 Watt, T-12 Bulb (15") Cool White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/8A NOT 1 | Lamp Fluorescent Trade No. F14T12/W, Preheat, 14 Watt, T-12 Bulb White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/9A NOT 1 | Lamp Fluorescent Trade No. F15T8/CW, Preheat, 15 Watt, T-8 Cool White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/10A NOT 1 | Lamp Fluorescent Trade No. F15T8/W, Preheat, 15 Watt, T-8 Bulb White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/11A NOT 1 | Lamp Fluorescent Trade No. F15T8/WW, Preheat, 15 Watt, T-8 Bulb Warm White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/12A NOT 1 | Lamp Fluorescent Trade No. F15R8/D, Preheat, 15 Watt, T-8 Bulb Daylight, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/13A NOT 1 | Lamp Fluorescent Trade No. F15T12/CW, Preheat, 15 Watt, T-12 Bulb Cool White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/14A NOT 1 | Lamp Fluorescent Trade No. F15T12/W, Preheat, 15 Watt, T-12 Bulb White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/15A NOT 1 | Lamp Fluorescent Trade No. F15T12/D, Preheat, 15 Watt, T-12 Bulb Daylight, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/19A NOT 1 | Lamp Fluorescent Trade No. F30T8/W, Preheat, 30 Watt, T-8 Bulb White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/20A NOT 1 | Lamp Fluorescent Trade No. F30T8/D, Preheat, T-8 Bulb Daylight, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/21B NOT 1 | Lamp Fluorescent Trade No. F90T12/CW or F90T17/CW, Preheat, 90 Watt, T-12 or T-17 Bulb (60 In.) Cool White, Mogul Bipin Base (Detail Specification) (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/22B NOT 1 | Lamp Fluorescent Trade No. T90T12/W or F90T17/W, Preheat, 90 Watt, T-12 or T-17 Bulb (60") White, Mogul Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/23B NOT 1 | Lamp Fluorescent Trade No. F90T12/D or F90T17/D, Preheat, 90 Watt, T-12 OR T-17 Bulb (60") Daylight, Mogul Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/24B NOT 1 | Lamp Fluorescent Trade No. FC8T9/CW/RS, Rapid Start, 22 Watt, T-9 Bulb Cool White, 4 Pin Base, Circular 8-1/4 In. Diameter (Detail Specification) (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/25B NOT 1 | Lamp Fluorescent Trade No. FC12T10/CW/RS, Rapid Start, 32 Watt, T-10 Bulb Cool White, 4-Pin Base, Circular 12" Diameter (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/26A | Lamp Fluorescent Trade No. F30T12/CW/RS, Rapid Start, 30 Watt, T-12 Bulb (36") Cool White, Medium Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/27A NOT 1 | Lamp Fluorescent Trade No. F30T12/WW/RS, Rapid Start, 30 Watt, T-12 Bulb (36") Warm white, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/32A NOT 1 | Lamp Fluorescent Trade No. F48T12/CW/NO, Rapid Start, 60 Watt, T-12 Bulb Cool White, Recessed Double Contact Base, High Output (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/34A NOT 1 | Lamp Fluorescent Trade No. F96T12/CW/1500, Rapid Start, 215 Watt, T-12 Bulb (96") Cool White, Recessed Double Contact Base, High Output (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/35A NOT 1 | Lamp Fluorescent Trade No. F40T12/CW/IS, Instant Start, 40 Watt, T-12 Bulb Cool White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/36A NOT 1 | Lamp Fluorescent Trade No. F48T12/CW, Instant Start, 40 Watt, T-12 Bulb Cool White, Single Pin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/38A NOT 1 | Lamp Fluorescent Trade No. F48T12/D, Instant Start, 40 Watt, T-12 Bulb Daylight, Single Pin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/39C NOT 1 | Lamp Fluorescent Trade No. F40T12/CW/IS or F40T17/CW/IS, Instant Start, 40 Watt T-12 or T-17 Bulb (60") Cool White, Mogul Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/40B NOT 1 | Lamp Fluorescent Trade No. F40T12/WW/IS or F40T17/WW/IS, 40 Watt, T-12 or T-17 Bulb (60") Warm White, Mogul Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/41A NOT 1 | Lamp Fluorescent Trade No. F96T8/CW, Instant Start, 50 Watt, T-8 Bulb Cool White, Single Pin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/42A NOT 1 | Lamp Fluorescent Trade No. F72T12/CW, Instant Start, 55 Watt, T-12 Bulb (72") Cool White, Single Pin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |

CANCELED SECTION

ASSIST UPDATE

| LAST ACTION | | | DISTRIBUTION | FSC/AREA | MCA | PREP ACTY | DATE |
|-------------|---------------------|--|--------------|----------|-----|-----------|-------------|
| | DOCUMENT NUMBER | DOCUMENT TITLE | | | | | |
| M | W-L-00116/46A NOT 1 | Lamp Fluorescent Trade No. F96T12/D, Instant Start, 75 Watt, T-12 Bulb(96 Inch) Daylight, Single Pin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/47 NOT 1 | Lamp Fluorescent Trade No. F40CW, Rapid Start, 35 Watt, T-12 Bulb, Cool White Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/48 NOT 1 | Lamp Fluorescent Trade No. F40W, Rapid Start. 35 Watt, T-12 Bulb, White, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/49 NOT 1 | Lamp Fluorescent Trade No. F40WW, Rapid Start, 35 Watt, T-12 Bulb, Warm White, Medium Bipin Base (Detail Specification) (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/50 NOT 1 | Lamp Fluorescent Trade No. F40D, Rapid Start, 35 Watt, T-12 Bulb, Daylight, Medium Bipin Base (No S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | W-L-00116/55 NOT 1 | Lamp Fluorescent Trade No. F96T12/CW/HO, Rapid Start, 95/100 Watt, T-12 Bulb (96") Cool White, Recessed Double Contact Base, High Output (NO S/S Document) | A | 6240 | # | FAS | 31-MAY-2011 |
| M | GG-L-00410 NOT 1 | Line Guide, Lettering, Adjustable (No S/S Document) | A | 6675 | # | FAS | 31-MAY-2011 |
| M | FED-STD-00116 NOT 1 | Mattress, Bed (Felted, Cotton) (No S/S Document) | A | MISC | # | FAS | 31-MAY-2011 |
| M | FED-STD-00160 NOT 1 | Rubber Products, Definitions and Terms for Visible Defects of (No S/S Document) | A | MISC | # | FAS | 31-MAY-2011 |