

METRIC

DOD-C-24556(SH)
AMENDMENT 2
13 February 1984
SUPERSEDING
AMENDMENT 1
12 June 1981

MILITARY SPECIFICATION

CURTAIN, TRACK AND SUSPENSION SYSTEM, BERTH
(SHIPBOARD USE) (METRIC)

This amendment forms a part of Military Specification DOD-C-24556(SH) dated 12 December 1977, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1: Delete and substitute:

* "2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Under "SPECIFICATIONS, MILITARY": Delete reference to "MIL-F-902".

Bottom of page, "Beneficial comment" paragraph, line 3: Delete "Ship Engineering Center, SEC 6124" and substitute "Sea Systems Command, SEA 5523".

PAGE 2

Delete and substitute:

* "(Copies of specifications and standards, required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)"

* 2.2: Add the following:

"ASTM

B 633 - Electrodeposited Coatings of Zinc on Iron and Steel.
(DoD adopted)

B 695 - Coatings of Zinc Mechanically Deposited on Iron and Steel.

FSC 7230

DOD-C-24556(SH)
AMENDMENT 2

(Application for copies should be addressed to the ASTM, 1916 Race Street, Philadelphia, PA 19103.)"

Add as paragraph 2.3:

- * "2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence."

PAGE 3

3.12: Delete last sentence.

PAGE 4

- * TABLE I, across from Type I, under length: Delete "(2 per set) 1020" and substitute "1020 (in 2 sections)".

PAGE 5

3.17: Delete and substitute:

"3.17 Fabric weights. Class 1 curtains shall be fabricated from not less than 210 gram/square meter (7.5 ounces per square yard) material. Classes 2 and 3 curtains shall be fabricated from not less than 140 gram/square meter (5 ounces per square yard) material."

3.18: Delete and substitute:

- * "3.18 Tracks. Curtain tracks shall be style A or B."

PAGE 6

- * 3.18.1, lines 7 and 8: Delete "Tracks for type I curtains shall be 2-meter (m) long. Tracks for type II curtains shall be 710-mm long."
- * Figure 7, under "Assembly Detail": Delete "20 millimeters" and substitute "10 millimeters."

PAGE 7

- * 3.18.2, lines 3 and 4: Delete "Tracks for type I curtains shall be 2-m long. Tracks for type II curtains shall be 710-mm long."

PAGE 7 AND 8

- * 3.19, lines 5 and 6: Delete "cadmium plated" and substitute "steel"; after "channel" add ", zinc-coated in accordance with ASTM B 695, or ASTM B 633, type II, class Fe/Zn 13,".

DOD-C-24556(SH)
AMENDMENT 2

PAGE 8

- * 4.1, first and third sentences: after "contract", add "or purchase order".

4.4.1.1, line 1: After "curtains", add "of the same type and class and curtain track and suspension systems of the same style".

4.4.1.2, line 1: After "curtains", add ", tracks and suspension systems".

4.4.1.2, line 3: Delete "4.5" and substitute "4.0".

4.5: Delete and substitute:

"4.5 Examination. Each of the sample curtains and track and suspension systems selected in accordance with 4.4.1.2 shall be visually and dimensionally examined to verify compliance with the requirements of this specification. Classification of defects shall be conducted as specified (see table II). Any curtain, track and suspension system in the sample containing one or more visual or dimensional defects shall not be offered for delivery, and if the number of defective units of curtains or track and suspension systems in any sample exceeds the acceptance number for that sample, this shall be cause for rejection of the lot represented by the sample."

PAGE 10

5.: Delete and substitute:

- * "5. PACKAGING

(The preparation for delivery requirements specified herein apply only for direct Government acquisition. For the extent of applicability of the preparation for delivery requirements of referenced documents listed in section 2, see 6.4.)"

5.3.1: Delete.

PAGE 11

6.2: Delete and substitute:

- * "6.2 Ordering data.

- * 6.2.1 Acquisition requirements. Acquisition documents should specify the following:"

6.2.1, items (b), (d) and (f): Delete and substitute:

"(b) Type and class of curtain and style of track and suspension systems required (see 1.2.1).

- * "(d) Dimensions if other than standard (see 3.13 and 3.18).

- * "(f) Length of curtain tracks (see 3.18)."

DOD-C-24556(SH)
AMENDMENT 2

6.2.2 Delete and substitute:

- * "6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n)(2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

<u>Paragraph no.</u>	<u>Data requirement title</u>	<u>Applicable DID no.</u>	<u>Option</u>
4.1.1	Certificate of compliance	DI-E-2121	----
4.3.1	First article inspection report	UDI-T-23790	----

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5000.19L., Vol. II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

"6.2.2.1 The data requirements of 6.2.2 and any task in sections 3, 4, or 5 of this specification required to be performed to meet a data requirement may be waived by the contracting/acquisition activity upon certification by the offeror that identical data were submitted by the offeror and accepted by the Government under a previous contract for identical item acquired to this specification. This does not apply to specific data which may be required for each contract regardless of whether an identical item has been supplied previously (for example, test reports)."

6.3 and 6.3.1: Delete and substitute:

- * "6.3 First article inspection. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection as to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract."

PAGE 12

6.4 Delete and substitute:

- * "6.4 Sub-contracted material and parts. The preparation for delivery requirements of referenced documents listed in section 2 do not apply when material and parts are acquired by the contractor for incorporation into the equipment and lose their separate identity when the equipment is shipped."

DOD-C-24556(SH)
AMENDMENT 2

LAST PAGE

- * DD 1426 form, address: Delete in two places "Ships Engineering Center (SEC 6124)" and substitute "Sea Systems Command (SEA 5523)".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 7230-N048)