

**METRIC**

DOD-P-24647A

AMENDMENT 2

7 August 1989

SUPERSEDING

AMENDMENT 1

18 March 1988

**MILITARY SPECIFICATION**

**PAINT, ANTIFOULING, SHIP HULL (METRIC)**

This amendment forms a part of DOD-P-24647A, dated 23 October 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

**PAGE 1**

1.2: Delete "Grade C - For use on neoprene rubber" and substitute: "Grade C - For use on neoprene rubber and steel".

**PAGE 6**

3.7, line 4, after "grade C", add: "when applied to rubber".

3.8.2, line 1, after "eroded", add: "down".

3.8.2, line 2, delete: "(if grade C)".

**PAGE 9**

4.6.9, line 8, add: "when applied to rubber".

**PAGE 11**

\* 4.6.11, line 2: Delete "radius of curvature" and substitute "diameter".

\* 4.6.11, line 7, item (a): Delete and substitute:

"(a) Rotational speed - 320 rpm (15 knots) at periphery of 18 inch drum."

\* 4.6.11, line 11: Delete "6 cycles (1 year)." and substitute "12 cycles (2 years)".

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 8010

DOD-P-24647A  
AMENDMENT 2

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:

Army - ME

Navy - SH

Preparing activity:

Navy - SH

(Project 8010-0179)

Review activity:

Army - MR

User activity:

Navy - CG