

INCH/POUND

FF-B-187B
 SUPPLEMENT 1
 10 September 1993

FEDERAL SPECIFICATION

BEARINGS, ROLLER, TAPERED

This specification is approved by the Administrator,
 Federal Supply Service, General Services Administration,
 for the use of all Federal Agencies.

SPECIFICATION SHEETS

FF-B-187/1	Bearing, Roller, 'Tapered, Single Row, Normal Angle. (Type TS)
FF-B-187/2	Bearing, Roller, Tapered, Single Row, Normal Angle, Flanged Cup. (Type TSF)
FF-B-187/3	Bearing, Roller, Tapered, Single Row, Steep Angle. (Type TSS)
FF-B-187/4	Bearing, Roller, Tapered, Single Row, Steep Angle, Flanged Cup. (Type TSSF)
FF-B-187/5	Bearing, Roller, Tapered, Double Row, One Double Cone, Two Single Cups. (Types TDI and TDIS)
FF-B-187/6	Bearing, Roller, Tapered, Double Row, Normal Angle, Two Single Cones, One Double Cup. (Type TOO)
FF-B-187/7	Bearing, Roller, Tapered, Double Row, Steep Angle, Two Single Cones, One Double Cup. (Type TDOS)
FF-B-187/8	Bearing, Roller, Tapered, Double Row, Normal Angle, Two Single Cones, One Double Cup, Nonadjustable. (Type TNA)
FF-B-187/9	Bearing, Roller, Tapered, Double Row, Steep Angle, Two Single Cones, One Double Cup, Nonadjustable. (Type TNAS)
FF-B-187/10	- Bearing, Roller, Tapered, Double Row, Straight Bore. Two Single Cones with Contacting Front Faces Slotted and Chamfered For Lubrication, One Double Cup with Lubrication, Holes and Groove. (Type TNASW)
FF-B-187/11	- Bearing, Roller, Tapered, Double Row, Straight Bore, Two Single Cones, Cone Back Face Rib Ground on the Outer Diameter For Sealing Purposes, One Double Cup with Lubrication Holes and Groove. (TYPE TNASWE)

AMSC N/A

FSC 3110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.