

QQ-B-575C
AMENDMENT 1

PAGE 3

Delete and substitute: Table I. Dimensions and data.

Table I. Dimensions and data.							
PIN ^{1/}	Strand wire size (AWG)	Tubular inside diameter (inch ^{2/})	Number of carriers	Number of ends	Current rating ^{3/} (amps)	Approx. AWG equivalent	Flat Form width X thickness ^{2/}
QQB575*36*0031	36	0.031	24	24	7.0	22	0.046X0.020
QQB575*36*0062	34	0.062	24	48	11.0	19	0.093X0.031
QQB575*34*0062	34	0.062	16	32	11.0	19	-
QQB575*32*0062	32	0.078	16	16	9.0	20	-
QQB575*36*0078	36	0.109	24	72	16.0	18	0.125X0.020
QQB575*36*0109	36	0.109	24	96	19.0	16	0.156X0.031
QQB575*34*0109	34	0.109	16	64	19.0	16	-
QQB575*32*0109	32	0.125	16	32	18.0	17	-
QQB575*36*0125	36	0.125	24	120	25.0	15	0.187X0.020
QQB575*34*0125	34	0.125	24	72	19.0	16	-
QQB575*32*0125	32	0.156	24	48	25.0	15	-
QQB575*36*0156	36	0.171	24	240	40.0	12	0.250X0.046
QQB575*36*0171	36	0.171	24	168	32.0	14	0.250X0.030
QQB575*34*0171	34	0.171	24	120	36.0	13	-
QQB575*32*0171	32	0.203	24	72	32.0	14	-
QQB575*36*0203	36	0.203	24	312	46.0	11	0.281X0.046
QQB575*34*0203	34	0.203	24	192	46.0	11	-
QQB575*32*0203	32	0.250	24	120	46.0	11	-
QQB575*36*0250	36	0.281	24	384	53.0	10	-
QQB575*30*0281	30	0.375	24	120	60.0	9	-
QQB575*36*0375	36	0.375	48	384	53.0	10	0.625X0.030
QQB575*34*0375	34	0.375	48	240	53.0	10	-
QQB575*32*0375	32	0.375	48	144	46.0	11	-
QQB575*30*0375	30	0.375	24	168 ^{4/}	75.0	8	-
QQB575*30*0437	30	0.437	24	240	90.0	6	0.500X0.093
QQB575*36*0500	36	0.500	48	528	62.0	9	0.625X0.46
QQB575*34*0500	34	0.500	48	336	62.0	9	-
QQB575*32*0500	32	0.500	48	192	62.0	9	-
QQB575*30*0500	30	0.500	24	360	120.0	6	0.625X0.093
QQB575*30*0562	30	0.562	48	480	145.0	3	-
QQB575*30*0656	30	0.656	48	768	190.0	1	-
QQB575*36*0781	36	0.781	48	586	88.0	7	0.750X0.040
QQB575*34*0781	34	0.781	48	428	88.0	7	-
QQB575*32*0781	32	0.781	48	336	88.0	7	-
QQB575*30*0875	30	0.875	48	336	100.0	5	1.375X0.050
QQB575*30*1000	30	1.000	48	384	120.0	4	-
QQB575*30*1125	30	1.125	48	432	130.0	4	-
QQB575*30*1375	30	1.375	48	528	150.0	3	1.500X0.060

1/ The complete PIN will include additional information to indicate the form (first asterisk) and strand coating (second asterisk) (see 1.2.1).

2/Tolerances are as follows:

Dimensions	Tolerances
0.000-0.099	0.010
0.100-0.249	0.016
0.250-0.499	0.031
0.500-0.999	0.063
Over-0.999	0.094

3/ Direct current ratings are given for information only and are not requirements. Values shown are for uninsulated braid in free air at 30°C (80°F). Values should be derated if the braid is insulated or in close contact with other components.

4/ The PIN supersedes the similar construction using 96 ends (NSN 6145-00-191-8402).

QQ-B-575C
AMENDMENT 1

MILITARY INTERESTS:

Custodians:

Army - CR
Navy - AS
Air Force - 85

Preparing Activity:
DLA-IS

(Project 6145-2145)

Review activity:

Army - AR, AT, AV, ME, MI
Navy - MC, OS, SH
DLA - CC
NSA - NS
DNA - DS