

NOT MEASUREMENT
SENSITIVE

VV-L-800C
INTERIM AMENDMENT 2 (ME)
2 December 1993
USED-IN-LIEU-OF
AMENDMENT 1
September 15, 1986

FEDERAL SPECIFICATION

LUBRICATING OIL, GENERAL PURPOSE, PRESERVATIVE

(WATER-DISPLACING, LOW TEMPERATURE)

This interim amendment is approved for use within the US Army Belvoir Research, Development, and Engineering Center, Department of the Army, with VV-L-800C, dated May 11, 1983.

PAGE 1

2.1, under Federal Standard:, add:

"FED-STD-313 - Material Safety Data Sheet, Preparation and the Submission of."

PAGE 2

2.1, after MIL-STD-290, add:

Military specification:

MIL-E-10062 - Engine, Preparation for Shipment and Storage of.

"2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF LABOR (DOL)

OSHA 29 CFR 1910.1200 - Hazard Communication Standard Regarding Lubrication Oils.

(Guideline CPL 2-2.38 may be obtained from OSHA Publication office, Room 5-4203, 200 Constitution Avenue NW, Washington, DC 20210.)"

AMSC N/A

FSC 9150

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

VV-L-800C
INTERIM AMENDMENT 2 (ME)

2.2, under American Society for Testing and Materials (ASTM) Standards, delete "D 270" in its entirety and add:

- * "D 329 - Acetone.
- D 4057 - Manual Sampling of Petroleum and Petroleum Products.
- D 4177 - Automatic Sampling of Petroleum and Petroleum Products."

PAGE 3

3.2, add "The contractor shall certify that no carcinogenic or potentially carcinogenic constituents are present as defined under the Hazard Communication Standard (HCS) 29 CFR 1910.1200. Certification to this effect shall be made to the qualifying activity."

3.4.2, line 2, delete "when viewed under 20-diameter magnification" and substitute "when viewed under 20-power magnification".

PAGE 6

4.3.2, line 2, delete "D 270" and substitute "D 4057 or D 4177".

4.4, add the following:

"The contractor shall provide certification of non-carcinogenicity as specified (i.e. materials are not considered carcinogenic or potential carcinogenic)."

Table II, after test for copper corrosion, add "3/" and at end of table, add:

"3/ At 100 °C for 3 hours."

- * In column "Test", add "4/" after "Corrosiveness and Oxidation Stability".

Table IV, add after "3/":

- * "4/ Metal squares are to be washed at room temperature with aliphatic naphtha conforming to TT-N-95, followed by acetone conforming to ASTM D329, instead of with 1,1,1 trichloroethane, conforming to MIL-T-81533."

PAGE 9

6.1, line 10, delete last sentence in its entirety and substitute: "This preservative oil may also be used to protect the fuel system and combustion chamber of engines conforming to MIL-E-10062."

VV-L-800C
INTERIM AMENDMENT 2 (ME)

However, this material contains a carboxylic acid which could react with certain metals present in the fuel system forming soaps which could contribute to fuel filter plugging."

PAGE 10

6.3 Qualification. Delete paragraph 6.3 and substitute:

"6.3 Qualification. Awards will be made only for products which are qualified for inclusion on the qualified products list at the time set for opening of bids. This qualification shall be approved by the qualifying activity for a period not to exceed five years from the date of original qualification. If a product is submitted for requalification and there has been no change in the specification requirements, the qualifying activity may, at its discretion, waive complete retesting or require only partial retesting of the product to determine its continued acceptability.

"6.3.1 Qualification samples. Samples for qualification shall consist of two gallons hydraulic fluid and one ounce of any additives used as an ingredient in the finished fluid. If additives are supplied as concentrates, an equivalent quantity of the solution shall be furnished. The samples shall be accompanied by Material Safety Data Sheets for each component ingredient of the finished product in accordance with FED-STD-313. A report from the manufacturer or from a commercial laboratory containing complete information concerning the source(s) and type(s) of base stock and each of the additive as well as the composition in exact percentages of the formulation of the finished product and the laboratory report stating quantitative results for all test requirements of the specification shall be furnished with the samples. One gallon of finished product shall be sent to a designated Government Laboratory at the time of qualification. The designated activity shall be determined by U.S. Army Belvoir Research, Development, and Engineering Center. The other samples, reports, and material safety data sheets shall be forwarded to:

* US BELVOIR RDE CTR
ATTN: SATBE-FL
FT BELVOIR VA 22060-5818

The samples shall be plainly identified by durable tags or labels securely attached and containing the following information:

- a. Sample for Qualification Inspection.
- b. Lubricating Oil, General Purpose Preservative (Water-Displacing, Low Temperature).
- c. Name of ingredient (for additive material).
- d. Name of manufacturer.
- e. Product code number.
- f. Date of manufacture.

VV-L-800C
INTERIM AMENDMENT 2 (ME)

Submitted by (name) and (date) for qualification inspection in accordance with the requirements of VV-L-800C under authorization of (reference authorizing letter)."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activities:
Army - AL, AR, AT, MD, MI, SM

Project 9150-A817