

NOTE: MIL-STD-1899(AT) has been redesignated as a handbook, and is to be used for guidance purposes only. This document is no longer to be cited as a requirement. For administrative expediency, the only physical change from MIL-STD-1899(AT) is this cover page. However, this document is no longer to be cited as a requirement. If cited as a requirement, contractors may disregard the requirements of this document and interpret its contents only as guidance.

MIL-HDBK-1899(AT)  
27 March 1998  
SUPERSEDING  
MIL-STD-1899(AT)  
4 June 1987

**DEPARTMENT OF DEFENSE  
HANDBOOK**

**PRESSURE TESTING, 10 PSI THROUGH 200 PSI**



AMSC N/A

AREA NDTI

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

## MIL-STD-1899(AT)

This military standard is approved for use within the U.S. Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE. This standard covers the classifications, requirements, and procedures for air or hydraulic leak testing of castings, parts, or assemblies at 10 through 200 pounds per square inch gage (psig) by using the appropriate documents listed below.

Class	Test limit (psig)	Society of Automotive Engineers/Aerospace Materials specification	Test media
1	10	SAE-AMS 2601	air
2	25	SAE-AMS 2602	air
3	40	SAE-AMS 2604	air
4	55	SAE-AMS 2605	air
5	70	SAE-AMS 2606	air
6	100	SAE-AMS 2607	air
7	200	SAE-AMS 2616	hydraulic

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

2. Subject term (key word) listing.

Air pressure testing

Leak testing

Pressure testing

3. Supersession data. This standard supersedes TCM/M60 PD 62236 dated 18 March 1975.

Custodian:  
Army - AT

Preparing Activity:  
Army - AT

(Project NDTI-A052)