

METRIC

MIL-PRF-27402C  
 01 October 1997  
 Superseding  
 MIL-P-27402B  
 27 May 1969

PERFORMANCE SPECIFICATION  
 PROPELLANT, HYDRAZINE - uns-DIMETHYLHYDRAZINE  
 (50% N<sub>2</sub>H<sub>4</sub> - 50% UDMH)

This specification is approved for use by all  
 Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification covers the requirements for hydrazine -  
 uns-dimethylhydrazine (N<sub>2</sub>H<sub>4</sub> - UDMH) propellant.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in  
 sections 3 and 4 of this specification. This section does not include  
 documents in other sections of this specification or recommended for  
 additional information or as examples. While every effort has been made to  
 ensure the completeness of this list, document users are cautioned that they  
 must meet all specified requirements documents cited in sections 3 and 4 of  
 this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following  
 specifications form a part of this document to the extent specified herein.  
 Unless otherwise specified, the issues of these documents are those listed in  
 the issue of the Department of Defense Index of Specifications and Standards  
 (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-PRF-25604	- Propellant, uns-Dimethylhydrazine
MIL-PRF-26536	- Propellant, Hydrazine
MIL-PRF-27401	- Propellant Pressurizing Agent, Nitrogen
MIL-PRF-27407	- Propellant Pressurizing Agent, Helium

Beneficial comments (recommendations, additions, deletions) and any pertinent  
 data which may be of use in improving this document should be addressed to:  
 Code (68) SA-ALC/SFSP, 1014 Billy Mitchell Blvd/STE 1, Kelly AFB TX 78241-  
 5603, by using the standardization Document Improvement Proposal (DD Form  
 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 9135

DISTRIBUTION STATEMENT A. Approved for public release; distribution is  
 unlimited.

## MIL-PRF-27402C

(Unless otherwise indicated, copies of the above specifications, and standards are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia PA 19111-5094).

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

## AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

- ASTM D 2276 - Test Method for Particulate Contaminant in Aviation Fuel by Line Sampling (DoD adopted)
- ASTM E 29 - Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications (DoD adopted)

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia PA 19103-1187.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

3.1 Chemical and physical properties. The propellants, hydrazine conforming to MIL-P-26536 and uns-dimethylhydrazine conforming to MIL-P-25604, shall be used in this propellant mixture. The chemical and physical properties of the propellant mixture shall conform to those listed in table I when tested according to the applicable test methods.

3.2 Limiting values. The following applies to all specified limits in this specification: For purposes of determining conformance with these requirements, an observed value or a calculated value shall be rounded off "to the nearest unit" in the last right-hand digit used in expressing the specification limit according to the rounding-off method of ASTM Practice E 29 for using Significant Digits in Test Data to Determine Conformance with Specifications.

3.3 Filter. A filter with a 10-micrometer nominal and 40-micrometer absolute rating shall be installed between the manufacturer's plant system and the container to be filled for delivery.

3.4 Qualitative. The propellant shall be colorless, homogeneous liquid when examined visually by transmitted light.

## 4. VERIFICATION

4.1 Classification of inspections. The inspections shall be classified as quality conformance inspections.



## MIL-PRF-27402C

Sample size	1 $\mu$ L
Carrier gas	helium
Carrier gas flow rate	8 mL/min
Initial column temperature	60°C (140°F)
Isothermal hold time	4 min
Gradient heating rate	10°C/min (18°F/min)
Final temperature	140°C (284°F)
Final isothermal hold time	2 min

Condition the column with an injection of a 1  $\mu$ L sample before beginning the analysis. The heating rate and final temperature should be adjusted so that aniline is completely eluted from the column before the end of the analysis. The analyst may vary the temperature, flow rate, column size, and sample size to optimize the procedure.

4.3.2.1.3 Calculations.

$$\% \text{UDMH} = \frac{A_{\text{UDMH}} K_{\text{UDMH}}}{\sum A_i K_i} \times 100$$

$$\% \text{N}_2\text{H}_4 = \frac{A_{\text{N}_2\text{H}_4}}{\sum A_i K_i} \times 100$$

$$\% \text{H}_2\text{O} = \frac{A_{\text{H}_2\text{O}} K_{\text{H}_2\text{O}}}{\sum A_i K_i} \times 100$$

where

$K_{\text{UDMH}}, K_{\text{H}_2\text{O}}$  = the normalization factors for UDMH and H<sub>2</sub>O.

$A_{\text{UDMH}}, A_{\text{N}_2\text{H}_4}, A_{\text{H}_2\text{O}}$  = the measured areas of the UDMH, N<sub>2</sub>H<sub>4</sub>, and H<sub>2</sub>O peaks multiplied by their signal attenuation factors.

$\sum A_i K_i$  = the sum of all the measured peak areas in the chromatogram multiplied by their respective signal attenuation factors and normalization factors.

Assumptions: The normalization factor for N<sub>2</sub>H<sub>4</sub> = 1.000. The normalization factors for trace volatile impurities =  $K_{\text{UDMH}}$ .

4.3.2.1.4 Calibration procedure. Obtain the normalization factors for each component by observing the areas produced by a specially prepared mixture, designated the reference standard. Prepare the standard with freshly distilled components assayed by the gas chromatographic procedure of their respective specifications; for example, N<sub>2</sub>H<sub>4</sub> MIL-P-26536 and UDMH MIL-P-25604. The composition of the mixture should be approximately 51 percent N<sub>2</sub>H<sub>4</sub>, 48 percent UDMH, and one percent H<sub>2</sub>O. Weigh each component to 0.1 milligram. The order of addition in the standard preparation shall be N<sub>2</sub>H<sub>4</sub>, H<sub>2</sub>O, and finally UDMH. Calculate the actual composition as follows:

MIL-PRF-27402C

$$\% \text{UDMH} = \frac{W_{\text{UDMH}} \times \text{assay}_{\text{UDMH}}}{\text{total weight}}$$

$$\% \text{N}_2\text{H}_4 = \frac{W_{\text{N}_2\text{H}_4} \times \text{assay}_{\text{N}_2\text{H}_4}}{\text{total weight}}$$

$$\% \text{H}_2\text{O} = \frac{(W_{\text{H}_2\text{O}} \times 100) + (W_{\text{N}_2\text{H}_4} \times \% \text{H}_2\text{O}) + (W_{\text{UDMH}} \times \% \text{H}_2\text{O})}{\text{total weight}}$$

where

$W_{\text{N}_2\text{H}_4}, W_{\text{UDMH}}, W_{\text{H}_2\text{O}}$  = the weight of each component.

$W_{\text{N}_2\text{H}_4} \times \% \text{H}_2\text{O}$  = the weight of  $\text{N}_2\text{H}_4$  times the percent  $\text{H}_2\text{O}$  determined in the assay as per MIL-P-26536.

$W_{\text{UDMH}} \times \% \text{H}_2\text{O}$  = the weight of UDMH times the percent  $\text{H}_2\text{O}$  determined in the assay as per MIL-P-25604.

Analyze the referenced standard in according to 4.3.2.1.2. Calculate the normalization factors as follows:

$$K_{\text{UDMH}} = \frac{\% \text{UDMH} \times A_{\text{N}_2\text{H}_4}}{\% \text{N}_2\text{H}_4 \times A_{\text{UDMH}}}$$

$$K_{\text{H}_2\text{O}} = \frac{\% \text{H}_2\text{O} \times A_{\text{N}_2\text{H}_4}}{\% \text{N}_2\text{H}_4 \times A_{\text{H}_2\text{O}}}$$

where

$K_{\text{H}_2\text{O}}, K_{\text{UDMH}}$  = the normalization factors for  $\text{H}_2\text{O}$  and UDMH.

$A_{\text{N}_2\text{H}_4}, A_{\text{UDMH}}, A_{\text{H}_2\text{O}}$  = the measured areas of the  $\text{N}_2\text{H}_4$ , UDMH, and  $\text{H}_2\text{O}$  peaks multiplied by their signal attenuation factors.

4.3.2.2 Equipment. The following equipment shall apply as test conditions of 4.3.2.

- a. Gas chromatograph - incorporating a thermal conductivity detector.
- b. Recorder - potentiometric strip chart, 0 - 1 millivolt, 1 second FS response, with integrator.
- c. Column - J&W Scientific fused silica megabore column with a liquid phase of Durabond Wax.
- d. Hypodermic syringe - 1 microliter, fixed needle.

## MIL-PRF-27402C

e. Regulator - helium, to fit the cylinder.

4.3.3 Particulate. The propellant sample shall be tested for contamination in accordance with ASTM D-2276, Method A, with the following exceptions:

4.3.3.1 Mix the sample thoroughly by shaking the sample container. Immediately pour 500 mL of the sample into a clean 500-mL graduated cylinder. Use this 500 mL of propellant for the particulate analysis.

4.3.3.2 Use a solvent resistant filter disc made from such materials as Millipore, LSWP-04700 (Mitex-Teflon), Millipore URWP 04700 (Solvinert), or Gelman VF-6, (Fluoride-Metricel); plain, white, 10±3 microns, 47 mm diameter, or equivalent instead of that specified in ASTM D-2276.

4.3.3.3 The drying oven temperature shall be 70°C (158°F) instead of the 90°C (194°F) specified in ASTM D-2276.

4.3.3.4 Filtered isopropyl alcohol shall be used for rinsing the sample bottle and filter holder instead of petroleum ether specified in ASTM D-2276.

## 5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

## 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The propellant described by this specification is intended for use as a fuel in rocket engines.

6.2 Acquisition requirements. Acquisition documents must specify the following:

- a. Title, number, and date of the specification.
- b. Issue of DoDISS to be cited in the solicitation, and, if required, the specific issue of individual documents referenced (see 2.2.1 and 2.3).
- c. Method of shipment, type and capacity of containers.
- d. Quantity by weight.
- e. When a different sampling plan is required (4.2).

MIL-PRF-27402C

f. Packaging requirements (see 5.1).

6.3 Part or identifying number (PIN). The PIN to be used for propellant acquired to this specification is M27402.

6.4 Subject term (key word listing).

Fuel  
Hydrazine  
Propellant  
Rocket engine  
uns-dimethylhydrazine

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians  
Navy - AS  
Air Force - 68

Review Activities  
Air Force - 19

Preparing Activity  
Air Force - 68

Civil Agency Interest  
NASA

(Project 9135-0141)

## STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

### INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

**NOTE:** This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

<b>I RECOMMEND A CHANGE:</b>	1. DOCUMENT NUMBER MIL-PRF-27402C	2. DOCUMENT DATE (YYMMDD) 97/10/01
3. DOCUMENT TITLE Propellant, Hydrzazine - uns-Dimethylhydrazine (50% N2H4 - 50% UDMH)		
4. NATURE OF CHANGE <i>(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)</i>		
5. REASON FOR RECOMMENDATION		
6. SUBMITTER		
a. NAME <i>(Last, First, Middle Initial)</i>	b. ORGANIZATION	
c. ADDRESS <i>(include Zip Code)</i>	d. TELEPHONE <i>(Include Area Code)</i>	e. DATE SUBMITTED <i>(YYMMDD)</i>
	(1) Commercial (2) AUTOVON <i>(If applicable)</i>	
8. PREPARING ACTIVITY		
a. NAME SA-ALC/SFSP	b. TELEPHONE <i>(Include Area Code)</i>	(2) AUTOVON
	(1) Commercial (210) 925-7847	945-7847
c. ADDRESS <i>(Include Zip Code)</i> 1014 Billy Mitchell Blvd, STE 1 Kelly AFB, TX 78241-5603	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	