

| |
|------------|
| INCH-POUND |
|------------|

MIL-PRF-39006E
SUPPLEMENT 1
23 January 1998

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE),
TANTALUM, ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39006E, dated 15 January 1998

| | | |
|-------------------|---|---|
| MIL-C-39006/9 | - | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR65. |
| MIL-C-39006/18 | - | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR10. |
| MIL-C-39006/19 | - | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR14. |
| MIL-C-39006/20 | - | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR17. |
| MIL-C-39006/21 | - | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR69. |
| MIL-PRF-39006/22- | | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR79. |
| MIL-PRF-39006/25 | | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR81. |
| MIL-PRF-39006/28 | | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), High Reliability, Style CLR79. |
| MIL-PRF-39006/29 | | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), High Reliability, Style CLR81. |
| MIL-PRF-39006/30 | | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR90 |
| MIL-PRF-39006/31 | | Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug), (Extended Range), 85°C (Voltage Derated to 125°C) Established Reliability, Style CLR91 |
| MIL-PRF-39006/32 | | Capacitors, Fixed, Electrolytic (Non-Solid Electrolyte) Tantalum, (Non-Polarize, Sintered Slug) 85°C (Voltage Derated to 125°C), Established, Reliability, Style CLR82 |

Preparing activity:
DLA - CC

(Project 5910-1916-99)

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5910