

INCH-POUND  
MIL-PRF-39006G  
SUPPLEMENT 1  
7 December 2006

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE),  
TANTALUM, ESTABLISHED RELIABILITY,  
GENERAL SPECIFICATION FOR

This supplement forms a part of [MIL-PRF-39006G](#), dated 22 November 2006.

- [MIL-PRF-39006/9](#) - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR65.
- [MIL-PRF-39006/21](#) - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR69.
- [MIL-PRF-39006/22](#) - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR79.
- [MIL-PRF-39006/25](#) - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) (Extended Range), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR81.
- [MIL-PRF-39006/30](#) - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug), 85°C (Voltage Derated to 125°C), Established Reliability, Style CLR90
- [MIL-PRF-39006/31](#) - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug), (Extended Range), 85°C (Voltage Derated to 125°C) Established Reliability, Style CLR91

Custodians:  
Army - CR  
Navy - EC  
Air Force - 11  
DLA - CC  
NASA - NA

Preparing activity:  
DLA - CC  
  
(Project 5910-2007-003)

Review activities:  
Army - AR  
Navy - AS, MC, OS, SH  
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at <http://assist.daps.dla.mil> .