

INCH-POUND

MIL-PRF-83726C
 SUPPLEMENT 1A
 15 February 2000

 SUPERSEDING
 SUPPLEMENT 1
 15 June 1999

PERFORMANCE SPECIFICATION

RELAYS, HYBRID AND SOLID STATE, TIME DELAY,
GENERAL SPECIFICATION FOR

This supplement forms part of MIL-PRF-83726C, dated
 15 June 1999.

SPECIFICATION SHEETS

- | | | |
|----------------------|---|---|
| MIL-R-83726/7 | - | Relays, Hybrid, Time Delay, On Pickup, Type I, Class A, 2 Amperes, 2PDT, Fixed Time, .06 to 300 Seconds. |
| MIL-R-83726/8 | - | Relays, Hybrid, Time Delay (On Release), Type IIA, Class A, 2 Amperes, 2PDT, Fixed Time, 0.100 to 300. |
| MIL-R-83726/12(USAF) | - | Relays, Hybrid, Time Delay (On Release), Type IIA, Class B, 10 Amperes, 4PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds. |
| MIL-R-83726/13 | - | Relays, Solid State, Time Delay, (On Operate), Type I, Class C, SPSTNO, 300 Milliamperes, Fixed Time, 0.05 to 600 Seconds, Hermetically Sealed. |
| MIL-R-83726/14(USAF) | - | Relays, Hybrid, Time Delay (On Operate), Type I, Class B, 10 Amperes, 4PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds. |
| MIL-R-83726/18(USAF) | - | Relays, Hybrid, Time Delay (On Release), Track Mounted, Type IIA, Class B, 10 Amperes, 2PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds. |
| MIL-R-83726/19(USAF) | - | Relays, Hybrid, Time Delay (On Operate), Track Mounted, Type I, Class B, 10 Amperes, 2PDT, Hermetically Sealed, Fixed Time, 0.100 to 300. |
| MIL-PRF-83726/20 | - | Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPST, 250 Milliamperes, Fixed Time, .05 to 500 Seconds. |
| MIL-PRF-83726/21 | - | Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPST, 250 Milliamperes, Variable Time, .05 to 500 Seconds. |
| MIL-R-83726/22(USAF) | - | Relays, Hybrid, Time Delay, Type IIB, Class B, 10 Amperes, 4PDT, Hermetically Sealed (Inactive for new design after 10 November 93). |
| MIL-R-83726/23(USAF) | - | Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPST, 250 Milliamperes, Variable Time, .05 to 500 Seconds. |

MIL-PRF-83726C
SUPPLEMENT 1A

- MIL-R-83726/24(USAF) - Relays, Solid State, Time Delay (On Operate), Track Mounted, Type I, Class C, SPST, 150 Milliampere, Fixed Time, 50 Milliseconds to 500 Seconds.
- MIL-R-83726/25(USAF) - Relays, Solid State, Time Delay (On Release) Track Mounted, Type IIA, Class C, SPST, 150 Milliampere, Fixed Time, .050 to 500 Seconds.
- MIL-R-83726/27(USAF) - Relays, Hybrid, Time Delay, Voltage Sensitive, Delay On Drop-Out, Class A, Type V, Hermetically Sealed (Potted), SPDT, 2 Ampere, Track Mounted.
- MIL-PRF-83726/28 - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 500 Seconds.
- MIL-PRF-83726/29 - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 500 Seconds.
- MIL-PRF-83726/30 - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor), 0.1 to 500 Seconds.
- MIL-PRF-83726/31 - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor) 0.1 to 500 Seconds.
- MIL-PRF-83726/35 - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, 4PDT, 10 Amperes, Fixed Time Delay, 0.1 to 600 Seconds
- MIL-PRF-83726/36 - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, 4PDT, 10 Amperes, Fixed Time Delay, 0.1 to 600 Seconds

Preparing activity:
DLA - CC

(Project 5945-1090)