

INCH-POUND

MIL-PRF-83726C  
 SUPPLEMENT 1A  
 15 February 2000  


---

 SUPERSEDING  
 SUPPLEMENT 1  
 15 June 1999

## PERFORMANCE SPECIFICATION

RELAYS, HYBRID AND SOLID STATE, TIME DELAY,  
GENERAL SPECIFICATION FOR

This supplement forms part of MIL-PRF-83726C, dated  
 15 June 1999.

## SPECIFICATION SHEETS

- |                      |   |   |
|----------------------|---|---|
| MIL-R-83726/7        | - | Relays, Hybrid, Time Delay, On Pickup, Type I, Class A, 2 Amperes, 2PDT, Fixed Time, .06 to 300 Seconds.  |
| MIL-R-83726/8        | - | Relays, Hybrid, Time Delay (On Release), Type IIA, Class A, 2 Amperes, 2PDT, Fixed Time, 0.100 to 300.  |
| MIL-R-83726/12(USAF) | - | Relays, Hybrid, Time Delay (On Release), Type IIA, Class B, 10 Amperes, 4PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds.                |
| MIL-R-83726/13       | - | Relays, Solid State, Time Delay, (On Operate), Type I, Class C, SPSTNO, 300 Milliamperes, Fixed Time, 0.05 to 600 Seconds, Hermetically Sealed.     |
| MIL-R-83726/14(USAF) | - | Relays, Hybrid, Time Delay (On Operate), Type I, Class B, 10 Amperes, 4PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds.                  |
| MIL-R-83726/18(USAF) | - | Relays, Hybrid, Time Delay (On Release), Track Mounted, Type IIA, Class B, 10 Amperes, 2PDT, Hermetically Sealed, Fixed Time, 0.100 to 300 Seconds. |
| MIL-R-83726/19(USAF) | - | Relays, Hybrid, Time Delay (On Operate), Track Mounted, Type I, Class B, 10 Amperes, 2PDT, Hermetically Sealed, Fixed Time, 0.100 to 300.           |
| MIL-PRF-83726/20     | - | Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPST, 250 Milliamperes, Fixed Time, .05 to 500 Seconds.                              |
| MIL-PRF-83726/21     | - | Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPST, 250 Milliamperes, Variable Time, .05 to 500 Seconds.                           |
| MIL-R-83726/22(USAF) | - | Relays, Hybrid, Time Delay, Type IIB, Class B, 10 Amperes, 4PDT, Hermetically Sealed (Inactive for new design after 10 November 93).                |
| MIL-R-83726/23(USAF) | - | Relays, Solid State, Time Delay (On Operate), Type I, Class C, SPST, 250 Milliamperes, Variable Time, .05 to 500 Seconds.                           |

MIL-PRF-83726C  
SUPPLEMENT 1A

- MIL-R-83726/24(USAF) - Relays, Solid State, Time Delay (On Operate), Track Mounted, Type I, Class C, SPST, 150 Milliampere, Fixed Time, 50 Milliseconds to 500 Seconds.
- MIL-R-83726/25(USAF) - Relays, Solid State, Time Delay (On Release) Track Mounted, Type IIA, Class C, SPST, 150 Milliampere, Fixed Time, .050 to 500 Seconds.
- MIL-R-83726/27(USAF) - Relays, Hybrid, Time Delay, Voltage Sensitive, Delay On Drop-Out, Class A, Type V, Hermetically Sealed (Potted), SPDT, 2 Ampere, Track Mounted.
- MIL-PRF-83726/28 - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 500 Seconds.
- MIL-PRF-83726/29 - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Fixed Time, 0.1 to 500 Seconds.
- MIL-PRF-83726/30 - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor), 0.1 to 500 Seconds.
- MIL-PRF-83726/31 - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, DPDT, 10 Amperes, Adjustable Time Delay (External Resistor) 0.1 to 500 Seconds.
- MIL-PRF-83726/35 - Relays, Hybrid, Time Delay (On Operate), Class B, Type I, Hermetically Sealed, 4PDT, 10 Amperes, Fixed Time Delay, 0.1 to 600 Seconds
- MIL-PRF-83726/36 - Relays, Hybrid, Time Delay (On Release), Class B, Type IIA, Hermetically Sealed, 4PDT, 10 Amperes, Fixed Time Delay, 0.1 to 600 Seconds

Preparing activity:  
DLA - CC

(Project 5945-1090)