

MIL-A-85046(AS)
7 September 1976

MILITARY SPECIFICATION

ACTUATOR, LINEAR, ELECTROMECHANICAL

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for the manufacture and inspection of one type of electromechanical linear actuator. The test limits in this specification define minimum acceptable capabilities.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-T-7743	Testing, Store Suspension and Release Equipment, General Specification for
MIL-E-17555	Electronic and Electrical Equipment, Accessories and Repair Parts, Packaging and Packing of

STANDARDS

Military

MIL-STD-100	Engineering Drawing Practices
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-454	Standard General Requirements for Electronic Equipment

FSC-1095

MIL-A-85046(AS)

MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Military Standard, Electromagnetic Interference Characteristics, Measurement of
MIL-STD-704	Electric Power, Aircraft, Characteristics and Utilization of
MIL-STD-810	Environmental Test Methods
MIL-STD-831	Test Reports, Preparation of
MIL-STD-1250	Corrosion, Prevention and Deterioration, Control in Electronic Components and Assemblies

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Order of precedence of specifications and standards. Should a conflict exist between any requirement in this specification and any requirement in the applicable documents referenced herein, the requirements of this specification shall take precedence over the referenced (applicable) document.

3. REQUIREMENTS

3.1 First article. The actuator furnished under this specification shall be a product which has been inspected and passed the first article inspection specified herein (see 4.3).

3.2 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3 Design and construction. The design and construction of the actuator shall be in accordance with the requirements specified herein. The actuator shall be capable of meeting all the requirements of this specification after undergoing a room temperature shelf life of 48 months. There shall be no repair of the actuator permitted to meet this requirement.

3.3.1 Materials. The materials shall be entirely suitable for the purpose intended. Materials shall be selected on the basis of strength, workability and compatibility with other materials in the item so as to minimize galvanic action (see MIL-STD-1250). Mounting interfaces shall be constructed of materials that are compatible with the cadmium plated steel pin pivots and stainless steel nuts on the actuating ram.

3.3.2 Finishes. Finishes shall be applied to all materials, whenever applicable, and shall be entirely suitable for the purpose intended, such as corrosion resistance and increased durability.

3.3.3 Surface texture. Surface texture shall not exceed 250 microinches (6.35×10^{-8} centimeters) and there shall be no sharp edges or burrs.

MIL-A-85046(AS)

3.3.4 Interchangeability. All actuators having the same part number shall be internally and externally identical.

3.3.5 Identification of parts. All parts shall be marked as specified on the applicable drawing or in accordance with MIL-STD-130 if not specified on the drawing. The item identification and part number requirements of MIL-STD-100 shall govern the part numbers and changes thereto.

3.3.6 Nameplates. Identification and wiring schematic plates for actuators shall be in accordance with the applicable drawing for the actuator being procured.

3.3.7 Envelope.

3.3.7.1 Dimensions. The actuator envelope dimensions shall be in accordance with the applicable drawing for the actuator being procured.

3.3.7.2 Electrical interface. The actuator cable interface shall be in accordance with color coding of the applicable drawing for the actuator being procured.

3.3.8 Weight. The maximum weight of the actuator shall be 1 pound (0.4536 kilograms).

3.3.9 Lubrication. If lubricants are used they shall not be of a toxic nature or of such a nature to cause injury to personnel.

3.3.10 Manual operation. The actuator shall incorporate provisions for a manual operation. The ratio of turns of the manual input shaft to the actuating ram stroke shall be a maximum of 20 turns of manual input shaft rotation for linear movement of output shaft from fully extended to fully retracted position. The torque required to manually operate the actuators shall be a maximum of 10 inch pounds (1.13 N•m).

3.3.11 Input power requirements. The rated voltage of the actuator shall be 28 VDC. The actuator shall operate from a 28 VDC power source with the characteristics and limits defined in MIL-STD-704, except that the actuator shall operate over a range of 18 to 30 volts with a normal operating load applied.

3.3.12 Electromagnetic interference control. The electrical portion of the system shall be designed for electromagnetic interference free operation in accordance with 4.6.5.

3.3.13 Operating stroke. The operating stroke shall be as specified in the applicable drawing for the actuator being procured.

3.3.14 Manual torque. The torque required to manually operate the actuator (no external load applied) when the actuating ram is positioned approximately mid-stroke, shall be:

- a. 10 inch pounds (1.13 N•m) maximum (breakaway)
- b. 6 inch pounds (0.677 N•m) maximum (run)

3.3.15 Operating loads. The normal operating load shall be 90 ± 10 pounds (40.82 ± 4.54 kilograms) in a direction opposing the travel of the actuator shaft in both the extend and retract modes. The maximum operating load shall be 180 pounds (81.65 kilograms) applied in the same manner as a normal load.

MIL-A-85046(AS)

3.3.16 Reversibility. The actuator shall not mechanically reverse as a result of an externally applied load of 200 pounds (90.72 kilograms) with the actuator electrically unpowered.

3.3.17 Static load. The maximum static load shall be 200 pounds (90.72 kilograms) tension or compression.

3.3.18 Overriding loads. The overriding load for the actuator (90 ± 10 pounds, 40.82 ± 4.54 kilograms) shall not cause sufficient overspeeding of the actuator during operation to cause failure or damage in the actuating system. Overriding loads shall not increase the stopping distance beyond that allowed in the applicable drawing for the actuator being procured.

3.3.19 End play. At any point in the electrical cycle, the actuating ram end play shall not exceed 0.010 inch (0.0254 centimeters) TIR (total indicated reading) when measured under a 10 pound (4.54 kilogram) reversing load.

3.3.20 Duty cycle. The duty cycle of the actuator shall be 30 seconds on and 5 minutes off.

3.3.21 Operating life. The operating life of the actuator shall be 5000 cycles at normal operating load, rated voltage and at room temperature. The duty cycle (see 3.3.20) shall be applicable during the 5000 cycles.

3.3.22 Bend test. The actuator cable shall maintain electrical and mechanical integrity after being subjected to the bend test of 4.6.11.

3.3.23 Pull test. The actuator shall remain functional while sustaining a tensile load in accordance with 4.6.12.

3.3.24 Performance (see 4.6.8).

3.3.24.1 Current. The normal operating current shall not exceed 1.0 ampere. Starting and stall current shall not exceed 2.1 amperes at 28 VDC and room temperature.

3.3.24.2 Electrical limit. The actuator shall contain internal limit devices set to limit the stroke as shown on the applicable drawings for the actuator being procured.

3.3.24.3 Mechanical stops. The actuator shall contain internal, non-jamming, mechanical stops. Mechanical stops shall limit the stroke as shown in the applicable drawings for the actuator being procured.

3.3.24.4 Direction of operation. The actuator shall be electrically reversible when energized in accordance with the basic wiring schematic of the applicable drawing.

3.3.24.5 Instantaneous reversal (plugging). With no external load applied, the actuator shall be capable of repeated electrical polarity reversals (rated voltage), instantaneously reversing the direction of the actuating ram, without damage to the actuator.

3.3.24.6 Anti-rotation device. The actuator shall contain an anti-rotation device to prevent rotation of the actuating ram.

3.3.24.7 Position indicator. The actuator shall incorporate two devices for position indication in accordance with the applicable drawings for the actuator being procured.

MIL-A-85046(AS)

3.3.24.8 Operating time. Under normal operating load, rated voltage and room temperature ($25 \pm 10^{\circ}\text{C}$) the actuating ram shall operate at a rate of 1 inch (2.54 centimeters) per 2.2 to 4.5 seconds.

3.3.25 Operating environment. The actuator performance shall comply with the requirements of the applicable conditions specified in MIL-STD-810 and MIL-T-7743 and other conditions specified herein (see Tables I and II).

3.3.26 Workmanship The workmanship displayed in fabrication and assembly of the actuator shall be such as to assure, within design limitations, ability of the actuator to meet performance requirements under all applicable environmental conditions specified herein. Unauthorized repair, welding, heavy burrs, or parts assembled by introduction of high stresses not prescribed in design, are typical signs of inferior workmanship and shall be cause for rejection. The standards of workmanship exhibited in the approved first article sample, subject to any qualification stated in the government's notice of approval, shall be determinative of the requirements of the contract relative to workmanship. All electrical components and wiring shall be installed in accordance with MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS (see 6.4)

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification, where such inspections are deemed necessary to assure the supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection of the actuator shall be classified as follows:

- a. First article inspection (see 4.3).
- b. Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall consist of all the inspections listed in Table I. First article inspection report format shall be in accordance with MIL-STD-831 (see 6.3).

4.3.1 Sampling for first article inspection. First article actuator samples shall consist of the first nine actuators manufactured on contract. The actuators shall be permanently labelled A, B and C for ease of identification. Failure of the actuators to pass any of the first article inspections shall be cause for rejection (see 6.2.1h).

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the following inspections:

- a. Individual inspections (4.4.1).
- b. Sampling inspections (4.4.2).

Quality conformance inspection report format shall be in accordance with MIL-STD-831 (see 6.3).

MIL-A-85046(AS)

4.4.1 Individual inspections. Individual inspections are those inspections conducted on each actuator in accordance with the inspections listed in Table II, Group 1. Failure to pass any of these inspections shall be cause for rejection of the actuator.

4.4.2 Sampling inspections. A random sampling of actuators shall be selected by the procuring activity from each production lot in accordance with Table III and shall be subjected to the inspections listed in Table II, Groups 1 and 2. Group 1 inspections shall be conducted prior to Group 2 inspections. Failure of any sample to pass any of these inspections shall be cause for rejection of the entire lot (see 6.2.1i).

4.5 Inspection conditions. Unless otherwise specified, all inspections shall be performed under the following conditions:

- a. Room temperature. Room ambient of $25 \pm 10^{\circ}\text{C}$ ($77 \pm 18^{\circ}\text{F}$) indicated.
- b. Test temperature. All parts of the test item shall be stabilized at the specified temperature $\pm 2.8^{\circ}\text{C}$ ($\pm 5^{\circ}\text{F}$) indicated prior to conducting any tests. Unless otherwise specified, temperature stabilization will have been attained when the indicated temperature of the surface of the largest mass of the test item does not change more than $\pm 2.8^{\circ}\text{C}$ ($\pm 5^{\circ}\text{F}$) per hour.

4.6 Inspection methods.

4.6.1 Actuator inspection. The actuator shall be inspected as follows.

4.6.1.1 Individual inspections. Each actuator shall be inspected to ensure that it has been properly assembled and that the workmanship is as specified herein (see 3.3.26).

4.6.1.2 First article and quality conformance inspections.

- a. Each actuator shall be thoroughly examined to determine conformance to all of the requirements specified herein (see 3.3).
- b. The actuator shall be examined to ascertain that the packaging conforms to contract requirements (see 5).

4.6.2 Manual torque. Disconnect the actuator from all external electrical circuits. The torque measurements to manually operate the actuator (no external load applied) when the actuating ram is positioned approximately mid-stroke, shall conform to 3.3.14.

4.6.3 End play. At any point in the electrical cycle, the actuator end play shall conform to 3.3.19.

MIL-A-85046(AS)

TABLE I

FIRST ARTICLE INSPECTIONS - SCHEDULE AND SEQUENCE 1/

TESTS	TEST PARA.	SAMPLE		
		A	B	C
Actuator Inspection	4.6.1	1	1	1
Manual Torque	4.6.2	2	2	2
End Play	4.6.3	3	3	3
Functional Test	4.6.4	4	4	4
Electromagnetic Compatibility	4.6.5	5	5	X
Maximum Operating Load	4.6.6	6	6	5
Overriding Loads	4.6.7	7	7	6
Combined Altitude and	4.6.8.1	8	8	7
Low Temperature				
High Temperature	4.6.8.2	9	9	8
Temperature Shock	4.6.8.3	10	10	9
Salt Fog	4.6.8.4	11	11	10
Humidity	4.6.8.5	12	12	11
Dust	4.6.8.6	13	13	12
Fungus	4.6.8.7	14	X	X
Shock	4.6.8.8	X	14	13
Explosive Atmosphere	4.6.8.9	15	X	X
Acceleration	4.6.8.10	X	15	14
Vibration	4.6.8.11	16	16	X
Endurance	4.6.8.12	X	17	15
Static Load	4.6.9	17	X	16
Mechanical Stops	4.6.10	18	X	X
End Play	4.6.3	19	18	17
Bend Test	4.6.11	20	19	18
Pull Test	4.6.12	21	20	19

1/ Inspection sequence is denoted by the numbers in the sample columns. An X denotes inspection not required.

MIL-A-85046(AS)

TABLE II

QUALITY CONFORMANCE INSPECTIONS - SCHEDULE AND SEQUENCE 1/

TESTS	TEST PARA.	SAMPLE		
		A	B	C
<u>GROUP 1</u>				
Actuator Inspection	4.6.1		<u>2/</u>	
Manual Torque	4.6.2		<u>2/</u>	
Functional Test	4.6.4		<u>2/</u>	
<u>GROUP 2</u>				
End Play	4.6.3	1	1	1
Electromagnetic Compatibility	4.6.5	2	2	X
Maximum Operating Load	4.6.6	3	3	2
Overriding Loads	4.6.7	4	4	3
Combined Altitude and Low Temperature	4.6.8.1	5	5	4
High Temperature	4.6.8.2	6	6	5
Temperature Shock	4.6.8.3	7	7	6
Salt Fog	4.6.8.4	8	8	7
Humidity	4.6.8.5	9	9	8
Dust	4.6.8.6	10	10	9
Fungus	4.6.8.7	11	X	X
Shock	4.6.8.8	X	11	10
Explosive Atmosphere	4.6.8.9	12	X	X
Acceleration	4.6.8.10	X	12	11
Vibration	4.6.8.11	13	13	X
Endurance	4.6.8.12	X	14	12
Static Load	4.6.9	14	X	13
Mechanical Stops	4.6.10	15	X	X
End Play	4.6.3	16	15	14
Bend Test	4.6.11	17	16	15
Pull Test	4.6.12	18	17	16

1/ Inspection sequence is denoted by the numbers in the sample columns. An X denotes inspection not required.

2/ Inspect all actuators to the requirements of the test paragraph.

MIL-A-85046(AS)

TABLE III
SAMPLING TEST ITEMS

PRODUCTION LOT SIZE	NUMBER OF SAMPLES
500 or Less	3
501 to 1000	6 $\frac{1}{2}$
1001 or More	$\frac{2}{3}$

- 1/ Actuators shall be inspected as two groups of three units each, in accordance with Table II.
- 2/ Number of samples shall be in multiples of 3. The procuring activity shall specify the number of samples and the sequence of inspections each unit shall be subjected to for lots in excess of 1000 units (see 6.2.1g).

4.6.4 Functional test. The actuator shall be subjected to the following operational checks.

4.6.4.1 Direction of operation. Operate the actuator in the retract direction with 18 VDC applied. The output shaft shall move in the retract direction. Subsequently, operate the actuator in the extend direction with 18 VDC applied. The output shaft shall move in the extend direction.

NOTE

The actuating ram shall move in the extend direction with 18 VDC applied if the positive (+) potential is applied to pin A (Black) and the negative (-) potential is applied to pin C. During any operational check, a negative (-) potential must be applied to pin B to allow dynamic braking at the electrical limits.

4.6.4.2 Electrical stroke and position indication. The actuator shall be subjected to the following checks:

- a. The actuator shall be operated in a no-load condition to ascertain compliance with the mechanical and electrical extend and retract limits on the applicable drawings.
- b. The actuator shall be operated to ensure that both extend and retract indicator devices are actuated prior to, but within 0.120 inch (0.305 centimeters) maximum travel of their respective limit devices.

4.6.4.3 Mechanical stop. The actuating ram shall be operated with 30 VDC into the retract mechanical stop by bypassing the electrical limit device. The actuator shall then be operated with 18 VDC in the extend direction. The actuator shall pull off the retract mechanical stop. The actuating ram shall be operated with 30 VDC into the extend mechanical stop by bypassing the electrical limit device. The actuator shall then be operated with 18 VDC in the retract direction. The actuator shall pull off the extend mechanical stop.

MIL-A-85046(AS)

4.6.4.4 Normal load. The actuator shall be operated for a full stroke with 28 VDC in the retract direction against a load of 90 ± 10 pounds (40.82 ± 4.54 kilograms). The time to complete the stroke shall be based on a rate of 1 inch (2.54 centimeters) per 2.2 to 4.5 seconds. The running current during operation shall not exceed 1.0 ampere. Starting and stall current shall not exceed 2.1 amperes at 28 VDC and room temperature. The actuator shall be operated for a full stroke with 28 VDC in the extend direction against a load of 90 ± 10 pounds (40.82 ± 4.54 kilograms). The time to complete the stroke shall be based on a rate of 1 inch (2.54 centimeters) per 2.2 to 4.5 seconds. The running current during operation shall not exceed 1.0 ampere.

4.6.4.5 Manual shaft torque. With no load applied, the actuating ram shall be positioned at approximately mid-stroke. The breakaway and running torques shall then be measured. The torque shall meet the requirements of 3.3.14 without any slipping or binding.

4.6.5 Electromagnetic compatibility. The actuator shall be tested in accordance with MIL-STD-461, Class 1D using the methods described in MIL-STD-462. The following tests are applicable: CE01, CE02, CE03, CE04, RE02, CS01, CS02, CS06, RS01, RS02, and RS03. The following shall apply:

- a. Conducted and radiated emission levels emitted by the actuator shall not exceed those values depicted in Figures 1 through 3.
- b. The power line configuration during conducted emission testing shall include a 7 microhenry choke in series with each power lead.
- c. The actuator shall be loaded with a 0.030 ampere suppressed inductive load across pins E and D in series with a 28 VDC power source. Pins G and F shall be loaded by a 0.010 ampere resistive load in series with a 28 VDC power source.

NOTE

In cases where an electrical connector is not required by the applicable drawing, the suppressed inductive load shall be across the blue and green lines and the yellow and brown lines shall be loaded by the resistive load.

- d. The actuator shall not be mechanically loaded during this test.
- e. In addition to the requirements specified in MIL-STD-461, the actuator shall meet the following requirements:
 1. The actuator shall not emit radiated magnetic fields exceeding those values depicted in Figure 4 of this document, when tested in accordance with test method RE01 of MIL-STD-462.
 2. The actuator shall operate without degradation when subjected to a near-linear-steady-state magnetic field of 1 oersted.

MIL-A-85046(AS)

3. Static magnetic fields. The actuator shall not generate a static magnetic field intensity (H), due to DC, exceeding 1.2×10^{-1} oersteds, at a point 12.0 inches (30.48 centimeters) from the center of the actuator magnetic sources. A static magnetic field is defined as a field which does not change in magnitude or direction.
4. Dynamic magnetic fields. The actuator shall not generate a dynamic magnetic field intensity (H) over the frequency range from DC to 30 Hz exceeding 7.2×10^{-3} oersteds. A dynamic field is defined as a field which can change. The measurement distance shall be 12.0 inches (30.48 centimeters) from the center of the actuator magnetic sources.

4.6.6 Maximum operating load. The actuator shall be operated utilizing the input power and maximum operating loads (see 3.3.11 and 3.3.15) respectively. The actuator shall operate satisfactorily under these conditions.

4.6.7 Overriding loads. The actuator shall be operated utilizing the input power and overriding load conditions (see 3.3.11 and 3.3.18 respectively). The load shall be applied in the same direction as the actuating ram direction and shall not cause sufficient over-speeding of the actuator during operation to cause failure or damage to the actuator. Overriding loads shall not increase the stopping distance beyond that allowed in 3.3.18.

4.6.8 Environmental tests. The actuators shall be subjected to the following environmental tests. Where required, the actuator shall be subjected to an operational check as follows:

The actuator shall be operated for seven cycles in the following sequence. A normal full stroke cycle shall consist of starting at a point on the stroke and going to the electrical limits on both ends of the stroke before returning to that point. Each cycle shall be conducted using rated voltage (see 3.3.11) except as noted in e. below and normal operating loads (see 3.3.15) except as noted in b. below. Data shall be obtained to verify compliance to 3.3.24 except as noted in e. below.

- a. Two normal full stroke cycles shall be performed.
- b. One cycle shall be an instantaneous reversal of the actuating ram direction (no external applied load) when at the midpoint of the stroke.
- c. One cycle shall be performed with the limit devices by-passed. The actuating ram shall be driven into the mechanical stops corresponding to each direction of the ram. The limit devices shall be by-passed by opening the common ground wire. The actuator will be electrically isolated from grounding through the case. The stall current shall not exceed 2.1 amperes at 28 VDC at room temperature.
- d. One normal full stroke cycle shall be performed.
- e. Two cycles shall be performed utilizing the full electrical stroke of the actuator and the input power shall be 18 VDC for one cycle and 30 VDC for the remaining cycle.

4.6.8.1 Altitude and low temperature. The actuator shall be subjected to a low temperature altitude test. The temperature shall be -54°C (-65°F) and the altitude shall be 50,000 feet (15,240 meters). The actuator shall be maintained under these conditions for 1 hour. The operational checks of 4.6.8 shall be performed while the altitude and temperature conditions are maintained. The actuator shall then be returned to room temperature and the operational checks repeated.

MIL-A-85046(AS)

4.6.8.2 High temperature. The actuator shall be subjected to a temperature of 93°C (+200°F) for a period of 4 hours. The operational checks of 4.6.8 shall be performed while the temperature condition is maintained. The actuator shall then be returned to room temperature and the operational checks repeated.

4.6.8.3 Temperature shock. The actuator shall be subjected to the temperature shock test in accordance with MIL-STD-810, Method 503, Procedure I. At the completion of testing, the actuator shall be tested in accordance with 4.6.8.

4.6.8.4 Salt fog. The actuator shall be subjected to the salt fog test in accordance with MIL-STD-810, Method 509, Procedure I. The exposure period shall be 50 hours. The operational checks of 4.6.8 shall be performed within 1 hour after completion of the test.

4.6.8.5 Humidity. The actuator shall be subjected to the humidity test in accordance with MIL-STD-810, Method 507, Procedure I. At the completion of testing, the actuator shall be tested in accordance with 4.6.8.

4.6.8.6 Dust. The actuator shall be subjected to the dust test in accordance with MIL-STD-810, Method 510, Procedure I. At the completion of testing, the actuator shall be tested in accordance with 4.6.8.

4.6.8.7 Fungus. The actuator shall be subjected to the fungus test in accordance with MIL-STD-810, Method 508, Procedure I. At the completion of testing, the actuator shall be tested in accordance with 4.6.8.

4.6.8.8 Shock. The actuator shall be subjected to the shock test in accordance with MIL-STD-810, Method 516, Procedure I. The actuator shall be mounted on rigid plate utilizing its mounting points only and the actuating ram shall be extended to the mid-stroke position. At the completion of testing, the actuator shall be tested in accordance with 4.6.8.

4.6.8.9 Explosive atmosphere (vapor-safe). The actuator shall be subjected to the explosive atmosphere test in accordance with MIL-STD-810, Method 511, Procedure I. While under explosive conditions, the actuator will only be mechanically loaded in one direction of the stroke. At the completion of testing, the actuator shall be tested in accordance with 4.6.8.

4.6.8.10 Acceleration. The actuator shall be subjected to the acceleration test in accordance with MIL-STD-810, Method 513, Procedure II. Accelerations equivalent to 10g's shall be applied in such directions as are likely to cause malfunctions, such as lifted brushes or switch contacts. Each acceleration vector shall be maintained for the period required to perform the operational checks of 4.6.8.

4.6.8.11 Vibration. The actuator shall be subjected to the vibration test in accordance with MIL-T-7743. The actuator shall be attached to the vibration table by means of a rigid fixture on which it is attached by its normal mount fittings. During the resonant and destructive vibration tests, the actuator shall be operated, with no external applied mechanical loading, for two normal full stroke operating cycles (as defined in 4.6.8) at each resonant frequency in each axis. At the completion of each axis of testing, the actuator shall be tested in accordance with 4.6.8.

4.6.8.12 Endurance. The actuator shall be subjected to 5,000 normal full stroke cycles (as defined in 4.6.8) at room temperature. The operational check of 4.6.8 shall be performed after every 500 cycles.

MIL-A-85046(AS)

4.6.9 Static load. As specified in 3.3.17, the actuator shall withstand a static load of 200 pounds (90.72 kilograms) when applied as a tension and compression load. The actuator shall be irreversible with these applied loads and no permanent deformation shall occur. The loads shall be applied at any position of the actuating ram, other than at the mechanical stops.

4.6.10 Mechanical stops. The actuator shall be subjected to 100 jams into each mechanical stop with the limit devices bypassed to determine compliance with 3.3.24.3. Each jam will consist of:

- a. With no load applied and an input voltage of 30 VDC, the actuator shall be jammed into one of the mechanical stops.
- b. With maximum operating load (see 3.3.15) applied and an applied voltage of 18 VDC, the actuator shall pull off the stop.

NOTE

The test method for this test shall not provide any rotational restraint to the actuator to ensure that the requirements of the anti-rotation device (see 3.3.24.6) are satisfied.

4.6.11 Bend test. The actuator cable shall be subjected to a bend test. The actuator shall be suspended in a temperature conditioning chamber at least 6 inches (15.24 centimeters) above a mandrel which is 1.9 inches (4.8 centimeters) in diameter. The cable shall be allowed to hang down tangent to the mandrel. A 5 ± 1 pound ($2.27 \pm .45$ kilogram) load shall be secured to the end of the cable. The temperature of the chamber shall be lowered to -54°C (-65°F) and maintained for 4 hours. At the end of this period and while the actuator and mandrel are still at temperature, the cable shall be wrapped once around the mandrel and subjected to the 5 pound (2.27 kilogram) load. The actuator and mandrel shall then be returned to room temperature. The actuator shall be removed from the mandrel, visually inspected and subjected to an operational check in accordance with the requirements of 4.6.8 and 4.6.12.

4.6.12 Pull test. The actuator cable shall be subjected to a pull test. A 15 to 20 pound (6.8 to 9.07 kilogram) inline tensile load shall be applied to the cable connector. While under this load, the actuator shall be subjected to one normal full stroke cycle. The load shall be removed and the operational check of 4.6.8 shall be performed.

5. PACKAGING

5.1 General. All major units and parts of the equipment shall be packaged, packed and marked for the level of shipment specified in the contract in accordance with MIL-E-17555.

6. NOTES

6.1 Intended use. The actuator covered by this specification is used as a safe-lock mechanism on armament type equipment.

MIL-A-85046(AS)

6.2 Ordering data. Procurement documents shall specify the following.**6.2.1 Procurement requirements.**

- a. Title, number and date of this specification.
- b. Applicable detail drawing specification.
- c. Selection of applicable levels of packaging and packing required (see 5.1).
- d. Samples subjected to sampling inspection shall not be considered or accepted as part of the contract (see 4.4.2).
- e. Sampling inspection selection (see 4.4.2).
- f. A statement which requires the contractor to notify the procuring activity of any changes in design and construction after the actuator has passed first article inspection. In all cases, configuration control of the actuator shall be governed by the requirements of MIL-STD-480 and as directed by the procuring activity.
- g. Number of samples and inspection sequence for production lots in excess of 1,000 units (see Table III).
- h. A requirement that prior to submission, the contractor shall inspect the first article samples to the degree necessary to assure that they conform to the requirements of the contract and submit an inspection report with the samples, including statements of findings and certificates of conformance of materials and tests of paragraphs 4.6.1, 4.6.2, 4.6.3, 4.6.4 and 4.6.6 as listed in Table I.
- i. Name and location of government representative responsible for random selection of inspection samples (see 4.4.2).
- j. Items of data required (see 6.3).
- k. Name and location of government approved test laboratory.

6.2.2 Contract provision. Contracts shall specify the following provision for first article inspection.

6.2.2.1 First article. When a first article is required for inspection and approval (see 3.1, 4.3, 6.2 and 6.3), the contract shall specify the following provision for first article inspection. When a contractor is in continuous production of actuators from contract to contract, consideration should be given to waive the first article inspections. If inspection is required, indicate:

- a. If first article inspections are conducted at the contractor's plant or a government approved laboratory, an inspection report shall be forwarded for verification to the procuring activity.
- b. That the approval of first article samples or the waiving of the first article inspection shall not relieve the contractor of his obligation to fulfill all other requirements of the specification and contract.

MIL-A-85046(AS)

6.3 Contract data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of 7-104.9(n) of the Armed Services Procurement Regulations, the data requirements identified below will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of ASPR-7-104.9(n) are not invoked, the data specified below will be delivered by the contractor in accordance with the contract requirements. Deliverable data required by this specification is cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
4.3	First Article Inspection Reports	DI-T-5329 - Inspection Test Reports
4.4	Quality Conformance Inspection Reports	DI-T-5329 - Inspection Test Reports

(Copies of data item descriptions required by the contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

6.4 Quality assurance definitions. Definitions for quality assurance terms are in accordance with MIL-STD-109.

Preparing Activity
NAVY-AS
DOD Project No. 1095-N075




Figure 1. Specification Limit for CE01 and CE02 Broadband Emissions




Figure 2. Specification Limit for CE03 and CE04 Broadband Emissions

MIL-A-85046 (AS)




Figure 3. Specification Limit for RE02 Broadband Emissions




Figure 4. Specification Limit for RE01 Magnetic Field Emissions

MIL-A-85046 (AS)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL		OMB Approval No. 22-R255	
<p>INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.</p>			
DOCUMENT IDENTIFIER AND TITLE MIL-A-85046(AS) ACTUATOR, LINEAR, ELECTROMECHANICAL			
NAME OF ORGANIZATION AND ADDRESS		CONTRACT NUMBER	
		MATERIAL PROCURED UNDER A <input type="checkbox"/> DIRECT GOVERNMENT CONTRACT <input type="checkbox"/> SUBCONTRACT	
<p>1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? A. GIVE PARAGRAPH NUMBER AND WORDING.</p> <p>B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES</p>			
2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID			
<p>3. IS THE DOCUMENT RESTRICTIVE? <input type="checkbox"/> YES <input type="checkbox"/> NO (If "Yes", in what way?)</p>			
4. REMARKS			
SUBMITTED BY (Printed or typed name and address - Optional)		TELEPHONE NO.	
		DATE	

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Lakehurst, NJ 08733

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DOD 316



Engineering Specifications and Standards Department (Code 93)
Naval Air Engineering Center
Lakehurst, NJ 08733

FOLD