

MIL-A-8591G
1 December 1983
SUPERSEDING
MIL-A-8591F
30 January 1979

MILITARY SPECIFICATION

AIRBORNE STORES, SUSPENSION EQUIPMENT AND AIRCRAFT-STORE INTERFACE (CARRIAGE PHASE); GENERAL DESIGN CRITERIA FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification sets forth general structural and mechanical design criteria to which airborne stores, suspension equipment and their associated interfaces shall be designed. Provisions are included to promote cross-utilization and servicing capability among military aircraft of all services of the Department of Defense and various NATO country aircraft. Guidance is provided for design, analysis, test, and documentation of airborne stores, suspension equipment and the aircraft-store interface during captive operations. Acquisition of airborne stores and related suspension and release equipment shall be covered by a detail specification or drawing to be prepared by the contractor or acquiring activity.

1.2 Extent. This specification contains general criteria that shall be used to design, analyze, test and document the development of airborne stores, suspension equipment and other details of the interface between the store and the aircraft suspension equipment.

1.3 Conforming requirements. Airborne stores and associated suspension equipment shall conform to this specification and shall perform in service with minimum possible restriction on the aircraft flight envelope.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Engineering Specifications and Standards Department (Code 93), Naval Air Engineering Center, Lakehurst, NJ 08733, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

MIL-A-8591G

SPECIFICATIONS

MILITARY

MIL-T-7743	Testing, Store Suspension and Release Equipment, General Specification for.
MIL-M-8856	Missile, Guided, Strength and Rigidity, General Specification for.
MIL-A-8860	Airplane Strength and Rigidity, General Specification for.
MIL-A-8868	Airplane Strength and Rigidity, Data and Reports.
MIL-A-8870	Airplane Strength and Rigidity, Vibration, Flutter, and Divergence.

STANDARDS

MILITARY

MIL-STD-210	Climatic Extremes for Military Equipment.
MIL-STD-810	Environmental Test Methods.
MIL-STD-2088	Bomb Rack Unit (BRU), Aircraft, General Design Criteria for.
MS3314	Lug, Suspension (1000 Pound Class) Airborne Equipment.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

NAVAL AIR SYSTEMS COMMAND

1555268	MK 14 Mod 0 Lug.
1380540	MK 3 Mod 0 Lug.

PUBLICATIONS

NATO STANDARDIZATION AGREEMENTS

STANAG 3441AA	Design of Airborne Stores for Fixed Wing Aircraft and Helicopters.
STANAG 3558AA	Location of the Electrical Control Connection for Aircraft Stores other than Missiles for Fixed Wing Aircraft.
STANAG 3575AA	Requirements for Aircraft Store Ejector Racks for Fixed Wing Aircraft.
STANAG 3726AA	Bail (Portal) Lugs for the Suspension of Airborne Stores for Fixed Wing Aircraft and Helicopter.

MIL-A-8591G

AIR STANDARDIZATION COORDINATING COMMITTEE - AIR STANDARDS

AIR STD 20/10	Ejector Racks for Conventional Munitions.
AIR STD 20/13	Suspension Lugs, Reinforced Areas, and Design Load Criteria for Droppable Aircraft Stores.
AIR STD 20/15	Suspension Lugs for 1000 Pound Class and 2000 to 5000 Pound Class Stores.
AIR STD 20/17	Mechanical Arming Wire Connections Between Airborne Armament Stores and Associated Suspension Equipment.

AIR FORCE LOGISTICS COMMAND REGULATION

AFSCR/AFLCR 80-28	Aircraft/Stores Compatibility Program.
-------------------	--

NAVAL AIR SYSTEMS COMMAND

NAVAIRINST 3710.7	Aircraft/Store/Suspension Equipment Compatibility, Store Handling-Loading Equipment Compatibility, and Flight Operating Limitations for Aircraft Carrying Stores.
-------------------	---

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI Y10.7-1954	American Standard Letter Symbols for Aeronautical Sciences.
-----------------	---

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

MIL-A-8591G

3. REQUIREMENTS

3.1 Terms and nomenclatures. U.S. Standard Atmosphere, normal atmospheric property variations, design analysis, test and reporting nomenclatures to be used shall be those equivalent to appropriate and applicable terms and nomenclature used in the related basic airplane design specification MIL-A-8860 or as specified in the contract documents by the acquiring activity. Definitions and symbols shall be in accordance with 6.3.

3.2 Design strength. The airborne store and associated suspension equipment shall have the strength and rigidity to support the forces and moments resulting from the loading conditions specified herein (see 3.11). For limit, yield, and ultimate conditions, stress analysis and tests shall demonstrate that allowable stresses are not exceeded. The service life of the structure must equal or exceed the specified life required in the applicable contractual document.

3.2.1 Limit loads. Unless otherwise specified, the maximum loads expected in normal operational employment of stores and suspension equipment, designated herein as the limit loads, are used in this specification and referenced specifications and formulas.

3.2.2 Yield loads. Unless specific yield loads are delineated, yield loads are obtained herein by multiplying limit loads by 1.15, which is denoted the yield factor of safety (yield factor of safety is 1.0 for Army applications). The effects of deformation remaining after application and removal of yield loads shall not exceed those prohibited in 3.3.

3.2.3 Ultimate loads. Except when specific ultimate loads are delineated, ultimate loads for suspension equipment or airborne stores while in the captive phase (store is within the sphere of influence of the aircraft as defined in MIL-M-8856) are obtained by multiplying the limit loads by 1.50, which is the ultimate factor of safety for the captive phase. The airborne store or associated suspension equipment shall not fail during application of ultimate loads. Failure is constituted by unintended separation of the store from the suspension equipment, separation of any part of the store or suspension equipment at ultimate or lower loads, or a material fracture of the store or suspension equipment.

3.3 Deformation. The permanent deformations resulting from flight or structural test articles being loaded statically, cyclically, or dynamically with yield loads shall be combined with any thermal deformation due to application of design temperature. If the thermal deformation should be in a manner which would relieve the yield deformation, the more critical deformation shall be considered. The deformation considered shall not:

- a. Inhibit or degrade the mechanical operation of the store or suspension equipment, or of the carriage aircraft.
- b. Adversely affect the aerodynamic characteristics of the store, suspension equipment or the carriage aircraft.
- c. Require repair or replacement of parts.

MIL-A-8591G

3.4 Design loads. The design loads shall include thermal effects and aeroelastic structural deformation. Magnitudes and distribution of loads shall also include effects of structural dynamic response resulting from transient or suddenly applied loads as defined by the acquiring agency or derived by the contractor in a rational manner acceptable to the acquiring agency.

3.5 Store classification. This specification shall be used for both ejected stores and rail launched stores. Detailed characteristics of each of these stores are given in the following paragraphs.

3.5.1 Ejected stores. The maximum gross weights of ejected stores shall include all disposable items. This actual weight, and any attainable lesser weight, shall be used in the determination of design loads and establishment of the store weight class for selection of suspension lugs. Store weight classes, approved lug types and spacing for each class are listed in Table I.

3.5.2 Rail launched stores. The maximum gross weight and other characteristics of rail launched stores are listed in Table II. Each class has unique hanger/rail mechanical interfaces. Table III illustrates the typical hanger configuration for each class of rail launched stores. Generally the hangers are either an internal T-shaped hanger (Figure 10) or an external U-shaped shoe (Figure 11).

TABLE I. Approved lug configuration for aircraft stores.

Weight class	Weight range	Number of lugs	Spacing, inches	Lug figures	Remarks
100	20 to 100	2	14 (see figure 4)	1	-
1,000	101 to 1,450	2	14 or 30 or both (see Figures 4, 5 or 6)	2 or 3	<u>1/</u>
2,000	1,451 to 3,500	2	30 (see Figure 6)	3	-
12,000	3,501 to 12,500	-	(see Figure 7)	-	<u>2/</u>
Over 12,500	12,501 and up	-	(see Figure 7)	-	<u>2/</u>

1/ Stores in this weight category may require 14-inch or 30-inch spacing, or both. The decision as to which spacing will be required will be found in the store detail specification and will be a function of store weight, length, diameter, moments of inertia, and types of aircraft on which it will be carried. Only Figure 3 lugs shall be used for 30-inch spacing. Only Figure 2 lugs shall be used for 14-inch spacing.





2/ In most instances, stores in this weight category will be sling suspended in bomb bays.

MIL-A-8591G

TABLE II. Typical rail launched store characteristics.

Weight class	Weight (lb)	Diameter (in.)	Type	Range	Launch type
300	< 300	< 7	Air-to-air	Short	Rail
600	300	< 10	Air-to-air	Medium	Rail/eject
600	1000	> 10	Air-to-surface	Medium	Rail/eject

TABLE III. Rail launched store configurations.

Weight class	Forward hanger <u>1/</u>	Aft hanger <u>1/</u>
300		
600		

1/ Dimensions are in inches.

3.5.3 Center of gravity. The center of gravity (cg) positions to be considered for design shall be the maximum forward and aft positions for the gross weights of 3.5, including all distributions of mass items for the store during ground use, captive flight, and operational conditions. Additional center of gravity positions within this range that produce critical loadings shall be examined.

3.6 Thermal criteria. The design of the store and suspension equipment shall provide for the cumulative heating effects from the internal and external thermal environments as defined in 3.6.1 and 3.6.2.

MIL-A-8591G

3.6.1 Internal. Heating effects shall be considered for internal thermal environmental areas of the store and suspension equipment caused by, but not limited to, operation of electronic systems and ejection cartridges prior to, during, and after separation.

3.6.2 External. The external thermal environment shall be considered which results from cooling and heating effects on external areas of the store and suspension equipment caused by, but not limited to, aerodynamic heating and operation in ambient atmospheres consistent with both the cold and hot atmospheres prevalent at the specified operational altitudes, as covered in MIL-STD-210, or the system specification.

3.7 Service life. Service life shall be defined. Service life design shall be a function of external loads resulting from pressure, oscillatory forces, shock and transient loadings, temperature effects, transportation, and storage consistent with the specified or intended operational use. Appropriate durability and damage tolerance analyses shall be performed to document that the required service life is satisfied for the planned operational use. A qualification test program shall be conducted which shall adequately demonstrate such analyses.

3.8 Suspension design criteria. This section defines the mechanical interface requirements for both ejected and rail launched stores.

3.8.1 Suspension lugs. Suspension lugs shall conform to drawings listed in Figures 1, 2 and 3 and shall be applicable to the weight class shown in Table I. If variations from these requirements are considered necessary for certain kinds of stores, formal justification and request are needed, and written approval by the acquiring activity shall be obtained prior to use.

3.8.1.1 Lug strength. The minimum strength of suspension lugs shall be as specified in Figures 1, 2 and 3. The weight class, as determined in accordance with 3.5, shall be used for selection of the type of suspension lugs to be used on the store. Other suspension lug designs shall comply with the load requirements specified in 3.11.

3.8.1.2 Lug number and location. Tandem two-lug suspension shall be the minimum lug configuration. Any other means of suspension shall require that the acquiring activity designate or approve a suspension configuration. The number of suspension lugs and the spacing, by weight class, shall be as specified in Table I. Lug location with respect to the store cg shall be the most practical location consistent with the characteristics of the airborne store carriage aircraft, and separation and handling requirements. The store cg shall be centered on the lugs within ± 3.0 -inches unless otherwise approved by the acquiring activity. All lug locations, dimensions, and allowable tolerances are specified in Figures 4, 5, 6 and 7.

3.8.1.3 Lug well details. The lug wells for the 1000 and 2000 pound class stores shall conform to the requirements specified in Figures 8 and 9 respectively. The lug well axis shall be within the store reinforced areas (see 3.9) and perpendicular to the longitudinal axis of the store within a tolerance of ± 0.5 degree.

MIL-A-8591G

3.8.1.4 Design acceptance. Appropriate drawings, illustrations, proposed store designs and data describing and substantiating the use of suspension lug dimensions, strengths and locations specified herein shall be submitted to the acquiring activity for acceptance prior to incorporating the lugs in stores for use on standard suspension equipment. The design shall not conflict with NATO STANAGs 3441AA, 3558AA, 3575AA and 3726AA and AIR STDS 20/10, 20/13, 20/15 and 20/17 (see 6.4).

3.8.2 Rail launched hangers. Two types of hangers are used to support rail launched stores. These are either an internal T-shaped hanger or an external U-shaped shoe. Figures 10 and 11 illustrate the general configuration of each. Detail dimensions and material types shall be provided by the acquiring activity.


3.9 Store reinforced areas. Store reinforced areas shall conform to the dimension, location, and load requirements of 3.9.1, 3.9.2 and 3.9.3. Strength requirements shall conform to 3.9.4.

3.9.1 Sway brace areas. The sway brace area for stores with 14-inch lug spacing shall be as specified in Figures 4 and 5; for stores with 30-inch spacing shall be as specified in Figure 6; and for heavy stores shall be as specified in Figure 7.

3.9.2 Ejector areas. Both internal and external carriage stores shall have ejector areas as specified in Figures 4, 5, 6 and 7. The store ejection velocities, store attitude control, and the load time histories on the ejector area of the store shall be as specified in the detail specification or by the acquiring activity.

3.9.3 Cradling and handling areas. As a minimum, all stores shall have cradling and handling area(s) of the size specified in Figures 4, 5 and 6 for the applicable store category. The store in Figure 7 shall sustain cradling and handling loads on any parts of the skin beneath the strongback region.


MIL-A-8591G



NAVAIRSYSCOM DWG 1555268, MK 14 MOD 0 LUG, DEFINES THE EXACT DETAIL REQUIREMENTS OF THE 100-LB CLASS LUG. THESE DATA PROVIDED AS INFORMATION ONLY. DIMENSIONS ARE IN INCHES.

FIGURE 1. Lugs for stores in 100-lb weight class.


MIL-A-8591G



MS3314 DEFINES THE EXACT DETAIL REQUIREMENTS OF THE 1000-LB CLASS BOMB LUG.
THESE DATA PROVIDED AS INFORMATION ONLY.
DIMENSIONS ARE IN INCHES.

FIGURE 2. 14-inch spaced lugs for stores in 1000-lb weight class.


MIL-A-8591G



NAVAIRSYSCOM DWG 1380540 MX 3 MOD 0 DEFINES THE EXACT DETAIL REQUIREMENTS OF THE 2000-LB CLASS BOMB LUG. THESE DATA PROVIDED AS INFORMATION ONLY. DIMENSIONS ARE IN INCHES.

FIGURE 3. 30-inch spaced lugs for stores up to 2,000-lb weight class.

MIL-A-8591G




NOTES:

- A MINIMUM 0.625 INCH CLEARANCE SHALL BE PROVIDED BETWEEN THE RACK LOWER SURFACE AND THE STORE UPPER SURFACE. THIS CLEARANCE SHALL NOT APPLY TO RACK HOOKS, BRACES, EJECTORS, STORE LUGS OR SERVICE CONNECTIONS.
- LUG AND LUG WELL AXES SHALL BE NORMAL TO THE STORE LONGITUDINAL AXIS WITHIN $\pm 1/2^\circ$ AND IN THE SAME PLANE WITHIN $\pm 1/2^\circ$.
- THIS LOCATION MAY BE INCOMPATIBLE WHEN OLDER STORES OR AIRCRAFT ARE MIXED WITH NEW ONES. IF SO, DUAL CONNECTORS SHOULD BE PROVIDED.
- DIMENSIONS ARE IN INCHES.

FIGURE 4. Location of store case components, 14-inch lug stores, for carriage on 14-inch lug racks.

MIL-A-8591G




NOTES:

- A MINIMUM 0.625 INCH CLEARANCE SHALL BE PROVIDED BETWEEN THE RACK LOWER SURFACE AND THE STORE UPPER SURFACE. THIS CLEARANCE SHALL NOT APPLY TO RACK HOOKS, BRACES, EJECTORS, STORE LUGS OR SERVICE CONNECTIONS.
- LUG AND LUG WELL AXES SHALL BE NORMAL TO THE STORE LONGITUDINAL AXIS WITHIN $\pm 1/2^\circ$ AND IN THE SAME PLANE WITHIN $\pm 1/2^\circ$.
- THIS LOCATION MAY BE INCOMPATIBLE WHEN OLDER STORES OR AIRCRAFT ARE MIXED WITH NEW ONES. IF SO, DUAL CONNECTORS SHOULD BE PROVIDED.
- DIMENSIONS ARE IN INCHES.

FIGURE 5. Location of store case components, 14-inch lug stores, for carriage on 14 or 30-inch lug racks.

MIL-A-8591G




NOTES:

- A MINIMUM 0.625 INCH CLEARANCE SHALL BE PROVIDED BETWEEN THE RACK LOWER SURFACE AND THE STORE UPPER SURFACE. THIS CLEARANCE SHALL NOT APPLY TO RACK HOOKS, BRACES, EJECTORS, STORE LUGS OR UMBILICAL CONNECTIONS.
- LUG AND LUG WELL AXES SHALL BE NORMAL TO THE STORE LONGITUDINAL AXIS WITHIN $\pm 1/2^\circ$ AND IN THE SAME PLANE WITH $\pm 1/2^\circ$.
- THIS LOCATION MAY BE INCOMPATIBLE WHEN OLDER STORES OR AIRCRAFT ARE MIXED WITH NEW ONES. IF SO, DUAL CONNECTORS SHOULD BE PROVIDED.
- DIMENSIONS ARE IN INCHES.

FIGURE 6. Location of store case components, 30-inch lug stores, for carriage on 30-inch lug racks.

MIL-A-8591G



NOTES:

- a. IF USED, LUG AND LUG WELL AXES SHALL BE NORMAL TO THE STORE LONGITUDINAL AXIS WITHIN $\pm 1/2^\circ$ AND IN THE SAME PLANE WITHIN $\pm 1/2^\circ$.
- b. DIMENSIONS ARE IN INCHES.

FIGURE 7. Sway brace and ejector areas for heavy stores (ref Table I).

MIL-A-8591G




TABLE OF DIMENSIONS		
*	A	0.624 in. minimum full thread
	B	1.870 D in.
	C	1.750 in. 12 UN-2B Thread
*	D	0.177 $\begin{matrix} +0.010 \\ -0.010 \end{matrix}$ in.
*	E	0.749 $\begin{matrix} +0.141 \\ -0.000 \end{matrix}$ in.

* These dimensions are mandatory for the U.S. and advisory for other participating nations that have agreed to STANAG 3441AA and AIR STD 20/13.

FIGURE 8. Threaded lug well for 1000 lb class stores.

MIL-A-8591G




TABLE OF DIMENSIONS

•	A	1.14 in. minimum full thread	
	B	2.620 D in.	
	C	2.500 in. 12 UN-2B Thread	
•	D	0.210	+0.010 in. -0.010
•	E	1.350	+0.000 in. -0.020

- These dimensions are mandatory for the U.S., and advisory for other participating nations that have agreed to STANAG 3441AA and AIR STD 20/13.

FIGURE 9. Threaded lug well for 2000 lb class stores.

MIL-A-8591G




FIGURE 10. Example of internal T-shaped hanger.

MIL-A-8591G




FIGURE 11. Example of external U-shaped shoe.

MIL-A-8591G

3.9.4 Reinforced area strength. Unless otherwise specified by the acquiring activity, stores with reinforced areas described in 3.9 shall be capable of withstanding the loads specified in 3.11 without failure.

3.9.4.1 Sway brace pad areas and span. Reinforced sway brace pad areas shall be provided in the store design for a minimum of 2.5 inches circumferentially on either side of the lug centerline for 100-pound weight class stores, a minimum of 4.0 inches circumferentially on either side of the lug centerline for 1000-pound weight class stores, and a minimum of 5.0 inches circumferentially on either side of the lug centerline for heavier weight class stores (see Figures 4 through 7).

3.9.4.2 Cradling and handling area strength. The strong area on the bottom of the store shall be capable of withstanding loads equal to three times the weight of the store without permanent deformation (see 3.11.7.3).

3.10 Store/suspension equipment interface design. This specification defines procedures for use in developing loads for the design of stores and associated suspension equipment. When this specification is used for the design of suspension and release equipment, it shall be applied in conjunction with the appropriate design specifications/standards for bomb racks (see MIL-STD-2088), launchers, and pylons. The following method of application shall be followed for suspension equipment design.

- a. Use appropriate appendices given in this specification to determine loads generated at the store/suspension equipment interface. This step should consider all stores scheduled for carriage on the new suspension equipment.
- b. If the suspension equipment being designed is a multiple-store type, the worst case loads shall be examined to determine maximum shear/moment conditions for various critical design structural points within the suspension equipment.
- c. Use the loads generated at the store/suspension equipment interface to perform stress analysis of the new suspension equipment.

3.10.1 Ejector foot areas. For design purposes, each ejector foot area must be capable of withstanding a minimum of 15,000 psi.

3.10.2 Sway brace pad areas. For store design purposes, it shall be assumed that suspension equipment design shall provide a minimum area of 2 square inches per sway brace pad. Sway brace pad areas for 100-pound class stores are an exception to this rule, however, and suspension equipment design shall be as specified by the acquiring activity.

3.11 Carriage design limit load. Design data for weapon carriage is to be generated by one of three procedures. These procedures have been developed to cover a variety of aircraft/store situations; including high and low speed fixed wing aircraft; helicopter aircraft; stores mounted at fuselage, wing pylon and wing-tip station; rack-mounted and rail-mounted stores. A summary of the various procedures and their applications are given in the following

MIL-A-8591G

paragraphs. Detailed descriptions of these procedures are contained in Appendices A, B and C. Procedure A shall be used unless one of the alternate procedures is approved by the acquiring activity. The method for determining lug and sway brace reactions, excluding preload, shall be approved by the acquiring activity.

3.11.1 Procedure descriptions. The following paragraphs 3.11.1.1 and 3.11.1.2 delineate the general and specific cases for fixed wing aircraft and 3.11.1.3 for helicopter aircraft.

3.11.1.1 Procedure A - carriage design limit loads - general case. This procedure, defined in Appendix A, includes the use of general inertial load factor envelopes along with free stream aerodynamic data to develop conservative design loads for application to a broad spectrum of aircraft. It shall be employed when flow field data is not available and the provisions of other procedures do not apply. Since the actual aircraft aerodynamic characteristics are not available, procedures outlined in Appendix A shall be used to calculate store angles of attack and side slip.

3.11.1.2 Procedure B - carriage design limit loads - stores carried on a specific aircraft. This procedure, defined in Appendix B, is intended to provide conservative loads that are representative of the actual loads the store will encounter on specific aircraft, excluding helicopter aircraft which are covered in Procedure C. Alternative methodologies are presented to allow the proper combination of aerodynamic loads and inertial loads to represent particular flight conditions, rather than following the more general approach defined in Procedure A. Stores that are designed using Procedure B are not intended for application on several classes of aircraft, since this procedure will generally produce less conservative loads than Procedure A.

3.11.1.3 Procedure C - carriage design limit loads - stores carried on helicopter aircraft. This procedure, defined in Appendix C, is intended to provide the methodology for determining the carriage loads on stores mounted on helicopter aircraft only. When stores may be carried on both helicopter and fixed-winged aircraft, it shall be necessary to evaluate the fixed-winged aircraft loads using Procedure A or B, as well as determining the helicopter aircraft loads as defined in Procedure C.

3.11.2 Installation preloads. The preloads imposed by the sway braces shall be included in the calculation of the total design loads. However, it is possible that under certain conditions of high vertical loading, the sway braces will cease to touch the store, thereby reducing the preload effect to zero. For the specific installation being considered, the contractor shall determine an appropriate distribution of preloads by sway brace torquing procedures and present this to the acquiring activity for approval.

3.11.3 Dynamic magnification.


3.11.3.1 Dynamic magnification factors. Allowances for dynamic magnification of accelerations imposed on the store by aircraft catapult take-offs and arrested landings, which result from structural flexibilities

MIL-A-8591G

of the aircraft or the store installation, are included in the load factor envelopes in Appendices A and B. Magnification factors for flight loads resulting from structural flexure of any or all of the aircraft, store or suspension equipment, are also included in the envelopes provided in Appendices A and B. For application of the remaining procedure, the dynamic magnification requirements are specifically stated in the appropriate appendix.

3.11.3.2 Time rates. For those cases where the functioning of store and suspension equipment internal components may be affected by the dynamic application of load, and when specific data are not available, the time histories of application of critical combinations of load factors and rotational accelerations shall be as shown in Figure 12.

FOR FLIGHT:	$t = 0.20 \text{ SEC TO } 1.0 \text{ SEC}$
FOR ARRESTED LANDING:	$t = 0.03 \text{ SEC TO } 0.10 \text{ SEC}$
(WITH LONGITUDINAL LOAD FACTORS UP TO ± 2.0)	
FOR ARRESTED LANDING:	$t = 0.15 \text{ SEC TO } 0.50 \text{ SEC}$
(WITH LONGITUDINAL LOAD FACTORS ABOVE 2.0)	
FOR CATAPULTING:	$t = 0.02 \text{ SEC TO } 0.40 \text{ SEC}$
FOR NON-ARRESTED LANDINGS	$t = 0.03 \text{ SEC TO } 1.0 \text{ SEC}$



FOR ALL CASES ABOVE, n = LOAD FACTOR

FIGURE 12. Time-load factor curve.

3.11.4 Vibratory loads. The vibration environment to which a store and its internal equipment shall be designed is defined in MIL-STD-810, (Methods 514.2 and 515.2). The vibration environment to which the suspension and release equipment shall be designed is defined in MIL-T-7743. If actual measured vibration environments are available, these may be used by the store designer, provided such use is approved by the acquiring activity. When specific aircraft are designated for the application, the equipment designer and aircraft contractor(s), with approval of the acquiring agency, shall coordinate the definition of the vibration criteria to be used in the design. For stores intended for carriage on helicopters, refer to Appendix C.

MIL-A-8591G

3.11.5 Fatigue strength. Oscillatory forces associated with pressures and load spectra representative of excitations which include turbulent airflow, inlet hammer shock, radiated jet engine exhaust noises, boundary layers, wakes, and similar sources, shall be considered in identifying and analyzing resonant vibratory stresses which subsequently shall be used to estimate fatigue strength in the design. When specific carriage-aircraft are designated, and the forces described above are known, these forces, with a scatter factor of two, shall be used for analyses and testing. If no carriage aircraft are specified, nor a broad spectrum of aircraft designated, and the forces defined above are not known, values shall be estimated and used after acceptance by the acquiring activity. See 3.7 for comments that also apply.

3.11.6 Liquid-slosh loads. If the store contains liquids, strength shall be provided for the pressures and dynamic response associated with liquid-slosh and liquid-surge loads. Strength shall be provided for all capacities of varying-capacity stores.

3.11.7 Shock loads.

3.11.7.1 Employment loads. Strength shall be provided for transient loading occurring during employment by ejection and jettisoning.

3.11.7.2 Shipping loads. Strength shall be provided to withstand the shipping environmental loads specified by MIL-STD-810 or as designated by the acquiring activity.

3.11.7.3 Cradling and handling loads. Sufficient strength shall be provided at the designated support points to withstand loads equal to 3.0 times the weight of the store (in both directions of the three major axes depicted in Figure 13) without unacceptable deformation (see 3.3).

3.12 Flutter and divergence. Flutter, buzz or other related dynamic instabilities of any or all of the store, the suspension equipment, the weapon station, the related aircraft structures and components, shall be accounted for in accordance with 3.13 of MIL-M-8856. The store designer, the suspension equipment contractor and the designated carriage-aircraft contractor shall coordinate with each other, as appropriate, and in accordance with acquiring activity direction, to exchange pertinent inertia, dynamic and other data necessary to define, by analytical and test methods, the aircraft/store flutter and divergence characteristics. These data shall be used to establish test requirements for the store during carriage and separation conditions in accordance with MIL-A-8870.

3.13 Recycled, virgin and reclaimed materials. There is no exclusion to the use of recycled or reclaimed materials and no mandate for the use of virgin materials provided it meets the requirements of this specification.

MIL-A-8591G

4. QUALITY ASSURANCE

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless otherwise disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Test procedures. Design verification test procedure requirements for store design, operational structural capability, and employment characteristics shall be as specified in detail by the acquiring activity or by reference to applicable parts of the designated related specifications. Quality conformance and qualification testing for store and store-mounted equipment shall be in accordance with appropriate MIL-STD-810 requirements. The requirements in these documents shall be as defined in the equipment detail specifications. The acquiring activity shall approve the test plans and reserves the right to modify the tests, revise the limit values or specify the degree of testing, if considered necessary to determine compliance with the requirements herein or in the contract.

4.3 Ground tests. A program of static, dynamic, repeated load, environmental, wind tunnel, and other ground tests required for proof of structural and operational design shall be performed as specified by the acquiring activity in the contract, purchase order or other applicable contractual document. For Air Force applications, unless otherwise directed, static testing is required if margins of safety are less than 0.20 for forged components and 0.33 for cast components. This requirement does not supersede any requirements of MIL-M-8856.

4.4 Flight tests. Operational flight tests, including carrier or shipboard suitability testing, if applicable, to demonstrate the structural and functional adequacy of the store shall be performed as specified by the acquiring activity in the contract, purchase order, or other applicable contractual document.

4.5 Design data. The structural reports and design data required to substantiate the strength and rigidity of the store design shall be specified by the acquiring activity in appropriate contractual documents. The form and extent of information required for design, analysis, test data, and reports shall be equivalent to such appropriate and applicable parts of airplane design specifications, MIL-A-8868 and MIL-A-8870, as they relate to the store. Submittal data schedules shall be as proposed by the contractor and accepted by the acquiring activity.

4.5.1 Symbols and axes systems. Except as otherwise specified herein, the symbols, axes systems designations, signs and angular relationships required for the structural reports, shall be those outlined in ANSI Y10.7-1954.

5. PACKAGING

This section is not applicable to this specification.

MIL-A-8591G

6. NOTES

6.1 Intended use. The requirements of this specification shall be used for the design of entire stores and suspension systems. The primary purpose of this specification is for the design of the total store and its components, not merely the generation of interface loads. Design of store components usually requires generation of distributed shear and moment diagrams using the information provided in 3.11. These diagrams are then used for detailed design of the store or its components.

6.2 Data.

6.2.1 Data requirements. For the information of contractors and contracting officers, the data to be furnished hereunder shall be listed on DD Form 1423 (Contractor Data Requirements List), which shall be attached to and made a part of the contract or order.

6.2.2 Store certification data. For the information of contractors, contracting officers, program managers, project officers, and project engineers in stores and suspension equipment, U.S. Navy certification and data requirements are set forth in NAVAIRINST 3710.7. For the U.S. Air Force, these requirements are contained in AFSCR/AFLCR 80-28. These requirements shall be met prior to authorizing stores/suspension equipment to be carried on an aircraft.

6.3 Definitions and symbols.

6.3.1 Weight class. The designation given stores within a specified weight range, used herein and in Table I for ejectable store and Table II for rail launched stores, is a nominal weight within that range. The nominal weight is not necessarily a mid-range or extreme range value.

6.3.2 Store. Any device intended for internal or external carriage and mounted on aircraft suspension and release equipment, whether or not the item is intended to be separated in flight from the aircraft. Stores include missiles, rockets, bombs, nuclear weapons, mines, torpedos, pyrotechnic devices, detachable fuel and spray tanks, line-source disseminators, dispensers, pods (refueling, thrust augmentation, gun, electronic-countermeasures, etc), targets, cargo drop containers and drones.

6.3.3 Suspension equipment. All airborne devices used for carriage, suspension, employment and jettison of stores, such as racks, adapters, launchers and pylons.

6.3.4 Missile launcher. An item rigidly attached to an aircraft to carry, service, launch and jettison air-launched missiles.

6.3.5 Air-launched missile. A guided, self-propelled store designed to be launched from an airborne vehicle and whose target is either airborne, on the ground or under the water surface.

6.3.6 Rail launcher. A launcher containing rails on which the missile is carried, and along which the missile travels after initiation of the missile's self-propulsion system.

6.3.7 Ejection launcher. A launcher which provides an initial source of energy to adequately displace the missile from the aircraft prior to the initiation of the missile's self-propulsion system.

6.3.8 Pylon. A pylon is a suspension device externally attachable on the wing or fuselage of an aircraft, with provisions for attaching aircraft stores.

6.3.9 Sway bracing. That mechanism within the physical triaxial restraint system which partially or totally reacts to store yaw and pitching moment in addition to lateral store loads.

6.3.10 Carriage. The conveying of a store or suspension equipment by an aircraft under all flight and ground conditions including taxi, takeoff, and landing. The store or suspension equipment may be located either external or internal to the aircraft. Carriage shall include time in flight up to the point of complete separation of the store or suspension equipment from the aircraft.

6.3.11 Separation. The terminating of all physical contact between a store or suspension equipment, or portions thereof, and an aircraft; or between a store, or portions thereof, and suspension equipment. This shall include the parting of items or submunitions from a dispenser.

6.3.12 Ejection. Separation of a store with the assistance of a force imparted from a device, either external or internal to the store.

6.3.13 Employment. The use of a store for the purpose and in the manner for which it was designed, such as releasing a bomb, launching a missile, firing a gun or dispensing submunitions.

6.3.14 Jettison.

6.3.14.1 Selective jettison. The intentional separation of stores or suspension equipment, or portions thereof (such as expended rocket pods), no longer required for the performance of the mission in which the aircraft is engaged.

6.3.14.2 Emergency jettison. The intentional simultaneous, or nearly simultaneous separation of all stores or suspension equipment from the aircraft in a pre-set, programmed sequence and normally in the safe condition.

6.3.15 Symbols. This section provides a partial list of symbols for use with this specification. Additional symbols are defined in the individual appendices as required.

W_A - Aircraft basic flight design gross weight, pounds

W_S - Store weight, including all disposable items, pounds

I_{xx} , I_{yy} , I_{zz} - Store moments of inertia, slug-ft², at store cg

MIL-A-8591G

I_{xy}, I_{xz}, I_{yz} - Store products of inertia, slug-ft², at store cg

cg - Center of gravity

S_A - Aircraft reference area, ft²

S_S - Store reference area, ft²

l - Store reference length, ft

g - Acceleration of gravity - 32.17 ft/sec²

q - Dynamic pressure, lbs/ft² = $1/2 \rho V^2$

ρ - Air density, slugs/ft³

V - Aircraft forward velocity, ft/sec

V_L - Limiting aircraft speed, ft/sec

α_A - Aircraft angle of attack, degrees

α_S - Store local angle of attack, degrees

β_A - Aircraft angle of sideslip, degrees

β_S - Store local angle of sideslip, degrees

a_x - Aircraft axial acceleration, g's

a_y - Aircraft side acceleration, g's

a_z - Aircraft normal acceleration, g's

n_x - Fore and aft load factor (+ aft)

n_y - Side load factor (+ right looking forward)

n_z - Normal load factor (+ up)

ϕ - Roll attitude, degrees

θ - Pitch attitude, degrees

ψ - Yaw attitude, degrees

$\dot{\phi}, \dot{\omega}_x$ - Aircraft roll rate, rad/sec

$\dot{\theta}, \dot{\omega}_y$ - Aircraft pitch rate, rad/sec

$\dot{\psi}, \dot{\omega}_z$ - Aircraft yaw rate, rad/sec

$\ddot{\phi}, \ddot{\omega}_x$ - Aircraft roll acceleration, rad/sec²

$\ddot{\theta}, \ddot{\omega}_y$ - Aircraft pitch acceleration, rad/sec²

$\ddot{\psi}$, $\ddot{\omega}_z$ - Aircraft yaw acceleration, rad/sec²

M - Mach number

C_x - Store airload axial force coefficient

C_y - Store airload side force coefficient

C_z - Store airload normal force coefficient

C_l - Store airload roll moment coefficient

C_m - Store airload pitch moment coefficient

C_n - Store airload yaw moment coefficient

C_{L_α} - Aircraft lift curve slope, $\frac{1}{\text{degree}}$

C_{Y_β} - Aircraft side force curve slope, $\frac{1}{\text{degree}}$

P_x - Store air, inertia, or net axial force

P_y - Store air, inertia, or net side force

P_z - Store air, inertia, or net normal force

M_x - Store air, inertia, or net roll moment

M_y - Store air, inertia, or net pitch moment

M_z - Store air, inertia, or net yaw moment

R - Distance from aircraft roll center to aircraft store station, inches

X - Aircraft fuselage station, ft

Y - Aircraft butt line, ft

Z - Aircraft waterline, ft

6.3.16 Sign convention. The reference axes for the aircraft or store are shown in Figure 13. Loads, load factors, and dimensions are positive when acting aft, to the right (looking forward) and up. Angles, moments, angular accelerations and angular velocities about axes parallel to the reference axes follow the right-hand rule.

6.4 International standardization agreements. Certain provisions of this specification are the subject of the following international standardization agreements; STANAGs 3441AA, 3558AA, 3726AA, and portions of STANAG 3575AA and AIR STD 20/13, 20/15 and parts of AIR STD 20/10 and 20/17. When an amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations.

MIL-A-8591G




FIGURE 13. Coordinate system, sign convention, and a typical load factor envelope.

MIL-A-8591G

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - AV
Navy - AS
Air Force - 18

Preparing activity:

Navy - AS
(Project No. 15GP-0045)

Review activities:

Air Force - 11, 15

Applicable International Organizations:

Standardization Agreement North Atlantic Treaty Organization (STANAG)
Air Standardization Coordinating Committee (ASCC)

MIL-A-8591G

APPENDIX A

PROCEDURE A

CARRIAGE DESIGN LIMIT LOADS, GENERAL CASE

10. SCOPE

10.1 Scope. Appendix A details procedures for either of the following conditions:

- a. When no individual carriage aircraft is specified.
- b. When a broad spectrum of carriage aircraft is being considered.

This appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

20. APPLICABLE DOCUMENTS

This section is not applicable to this appendix.

30. DESIGN LOADS

30.1 Aerodynamic loads. The airloads to be used for wing or sponson-mounted stores shall be developed from store free stream aerodynamic data using the angles of attack and sideslip computed in accordance with the equations shown in Figure A-1. Corresponding angles of attack and sideslip to be used for calculation of airloads on fuselage-mounted stores are shown in Figure A-2. Values of dynamic pressure, q , shall be determined for all critical conditions of velocity, V , to which the store is intended to be subjected. This information shall be furnished by the acquiring activity.

30.2 Inertia loads.

30.2.1 Limit inertia load factors. The limit inertia flight load factor diagram for wing or sponson-mounted stores is shown in Figure A-3. The corresponding diagram for fuselage-mounted stores is shown in Figure A-4. These load factor envelopes shall be applied at the store cg.

30.2.2 Limit inertia catapult and arrested landing load factors. The limit inertia catapult and arrested landing load factor diagram for wing or sponson mounted stores is shown in Figure A-3. The corresponding diagram for fuselage-mounted stores is shown in Figure A-4.

MIL-A-8591G

APPENDIX A

For all points, the stores shall be considered to be mounted at incidence angles of 0 or -3 degrees, whichever is more critical in each case, to be added to the values of α_S given below:

POINTS (1) AND (2):


$$\alpha_S = 0 \text{ to } + \frac{38000}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{3000}{q} \text{ DEGREES}$$

POINTS (3) AND (4):

$$\alpha_S = 0 \text{ to } - \frac{22800}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{3000}{q} \text{ DEGREES}$$



POINT (5):

$$\alpha_S = + \frac{100}{q^{1/2}} \text{ to } - \frac{15200 + 100 q^{1/2}}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{13000}{q} \text{ DEGREES}$$

POINT (6):

$$\alpha_S = 0 \text{ to } + \frac{30400 + 100 q^{1/2}}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{13000}{q} \text{ DEGREES}$$

FIGURE A-1. Store angles of attack and sideslip at specific load envelope points for wing or spouson-mounted stores.

MIL-A-8591G

APPENDIX A

For all points, the stores shall be considered to be mounted at incidence angles of 0 or -3 degrees, whichever is more critical in each case, to be added to the values of α_S given below:

POINTS (1) AND (2):

$$\alpha_S = 0 \text{ to } + \frac{38000 \text{ DEGREES}}{q}$$

$$\beta_S = \pm \frac{13000 \text{ DEGREES}}{q}$$

POINTS (3) AND (4):

$$\alpha_S = 0 \text{ to } - \frac{30400 \text{ DEGREES}}{q}$$

$$\beta_S = \pm \frac{13000 \text{ DEGREES}}{q}$$




FIGURE A-2. Store angles of attack and sideslip at specific load envelope points for fuselage-mounted stores.




FIGURE A-3. Design inertia limit load factors for wing or sponson-mounted stores.

MIL-A-8591G

APPENDIX A




FIGURE A-4. Design inertia limit load factors for fuselage-mounted stores

MIL-A-8591G

APPENDIX B

PROCEDURE B

CARRIAGE DESIGN LIMIT LOADS, STORES CARRIED ON SPECIFIC AIRCRAFT, A GROUP OR CLASS OF AIRCRAFT

10. SCOPE

10.1 Scope. Appendix B details procedures to be used when specific aircraft, except helicopters, are designated for carriage.

This procedure defines analysis methods that may be used as an alternative to Appendix A for cases where consideration is being given to specific aircraft/store combinations for which detailed information is available, including wing tip mounted stores, heavy stores and low performance aircraft carriage.

The procedures herein are intended to provide loads that are conservative, but as close as possible to the actual loads the store will encounter. Aerodynamic loads for a particular flight condition shall be combined with inertia loads representing the same flight condition. Alternative methodologies are included because the type and amount of data available for a specific aircraft cannot be predicted.

This appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

20. APPLICABLE DOCUMENTS

This section is not applicable to this appendix.

30. DESIGN LOADS

30.1 Aerodynamic loads. The aerodynamic loading on the store shall be determined assuming the flow field to be quasi-static at the instant that the inertia loading is being applied. Actual test data for store aerodynamic loads may be used for airloads, otherwise, the method to be used may be selected from those described below. The first two methods involve free stream aerodynamic data and uniform flow angles; whereas, the latter two methods involve the utilization of local flow effects and distributed angles. The actual method that is to be used shall be approved by the acquiring activity.

MIL-A-8591G

30.1.1 Method of Appendix A. The method of Appendix A shall be used to determine the store angles of attack and sideslip. These angles shall be used with wind tunnel data for the store alone in a uniform flow, together with q , to obtain aerodynamic loads. If appropriate store aerodynamic coefficient data is unavailable, analytical or empirical methods may be used to obtain the load coefficients for the store in a uniform onset flow.

30.1.2 Method using aircraft angles. An approximate method based on aircraft aerodynamic characteristics shall be used to calculate store loads. For wing or sponson-mounted stores, use Figure B-1 to compute the aircraft static angles of attack and sideslip. For fuselage-mounted stores, use Figure B-2 to compute the aircraft static angles. If the actual aircraft aerodynamic characteristics are unavailable, representative values for the type of aircraft may be obtained from Table B-1. The store angles of attack and sideslip shall be assumed to be the same as the aircraft angles, except for an incidence angle correction which shall be made in accordance with the notes on Figures B-1 and B-2. If the aircraft motion includes angular rates, incremental angles of attack and sideslip shall be calculated using the products of angular rate and distance of the store from the aircraft center of rotation and added to the store angles. The overall store loads shall be calculated assuming the store to be in a uniform onset flow by using the store angles of attack and sideslip determined above with wind tunnel data for the store in a uniform onset flow. If appropriate store aerodynamic coefficient data is unavailable, analytical or empirical methods may be used to obtain the load coefficients for the store in a uniform flow. This method does not take account of the variations in flow field along the store length and its influence on the store load distribution.

TABLE B-1. Representative values for parameters of Figures B-1 and B-2.

Type of aircraft	n_z	n_y	$\dot{\phi}$	C_{L_α}	C_{Y_β}
Fighter, Attack	8.00	1.0	4.70	0.05	0.010
Antisubmarine, Patrol	3.00	0.5	1.60	0.10	0.017

MIL-A-8591G

APPENDIX B

For all points, the stores shall be considered to be mounted at incidence angles of 0 or -3 degrees, whichever is more critical in each case, to be added to the values of α_A given below:

POINTS (1) AND (2):

$$\alpha_A = 0 \text{ to } \alpha_{MAX} \text{ DEGREES}$$

$$\beta_A = \pm 0.2 \beta_{MAX} \text{ DEGREES}$$

POINTS (3) AND (4):

$$\alpha_A = 0 \text{ to } -0.6 \alpha_{MAX} \text{ DEGREES}$$

$$\beta_A = \pm 0.2 \beta_{MAX} \text{ DEGREES}$$

POINT (5):


$$\alpha_A = +\alpha_R \text{ to } -(0.4 \alpha_{MAX} + \alpha_R) \text{ DEGREES}$$

$$\beta_A = \pm \beta_{MAX} \text{ DEGREES}$$

POINT (6):

$$\alpha_A = 0 \text{ to } (0.8 \alpha_{MAX} + \alpha_R) \text{ DEGREES}$$

$$\beta_A = \pm \beta_{MAX} \text{ DEGREES}$$



WHERE: $\alpha_{MAX} = \pi_Z \frac{W_A}{S_A} \left(\frac{1}{C_{L_{\alpha}} q} \right)$

$$\alpha_R = \frac{1.98 R \phi}{\sqrt{q}}$$

$$\beta_{MAX} = \pi_Y \frac{W_A}{S_A} \left(\frac{1}{C_{Y\beta} q} \right)$$

FIGURE B-1. Aircraft angles of attack and sideslip at specific load envelope points for wing or sponson-mounted stores.

MIL-A-8591G

APPENDIX B

For all points, the stores shall be considered to be mounted at incidence angles of 0 or -3 degrees, whichever is more critical in each case, to be added to the values of α_A given below:

POINT (1):

$$\alpha_A = 0 \text{ to } \alpha_{MAX} \text{ DEGREES}$$

$$\beta_A = \pm 0.2 \beta_{MAX} \text{ DEGREES}$$

POINT (2):

$$\alpha_A = 0 \text{ to } 0.8 \alpha_{MAX} \text{ DEGREES}$$

$$\beta_A = \pm \beta_{MAX} \text{ DEGREES}$$

POINT (3):


$$\alpha_A = 0 \text{ to } -0.6 \alpha_{MAX} \text{ DEGREES}$$

$$\beta_A = \pm 0.2 \beta_{MAX} \text{ DEGREES}$$

POINT (4):

$$\alpha_A = 0 \text{ to } -0.4 \alpha_{MAX} \text{ DEGREES}$$

$$\beta_A = \pm \beta_{MAX} \text{ DEGREES}$$



WHERE: $\alpha_{MAX} = n_z \frac{w_A}{s_A} \left(\frac{1}{c_{L_o}^q} \right)$

$$\beta_{MAX} = n_y \frac{w_A}{s_A} \left(\frac{1}{c_{Y\beta}^q} \right)$$

FIGURE B-2. Aircraft angles of attack and sideslip at specific load envelope points for fuselage-mounted stores.

MIL-A-8591G

APPENDIX B

30.1.3 Method using flow field data. Appropriate interference flow field data shall be used from wind tunnel tests or flight tests. These flow field data shall be combined with velocity to obtain the local flow field distribution over the length of the store. If the parent aircraft is undergoing angular rates in pitch, yaw or roll, the induced flow field due to the aircraft rates shall be combined with the measured interference flow field and velocity to obtain the local flow distribution along the store. The resulting flow field shall then be used with appropriate load distribution methods to obtain the force distribution acting along the length of the store. The force distribution shall then be summed to obtain the overall store aerodynamic loads.

30.1.4 Analytical method. Analytical prediction methods shall be used to calculate the overall aerodynamic loads on the store when the store is under the influence of the aircraft flow field. The methods shall be capable of including angular rates and predicting disturbances in the flow field due to the aircraft components, including, but not limited to, the fuselage, wing, pylon, rack, and adjacent stores, and shall predict the influence of these disturbances on the load distribution along the length of the store.

30.1.5 Method for low speed carriage. For aircraft with a maximum carriage speed of 350 knots equivalent air speed (KEAS) or less, airloads shall be developed using store angles of attack and sideslip computed in accordance with the equations of Figure B-3 (wing or sponson-mounted stores) or Figure B-4 (fuselage-mounted stores). The store overall loads shall be determined using the store angles with wind tunnel data for the store in a uniform onset flow. If appropriate store aerodynamic coefficient data is not available, analytical or empirical methods may be used to obtain the load coefficients for the store in a uniform flow.


30.2 Inertia loads. Inertia loads shall be determined from a knowledge of the aircraft performance capabilities and the location of the store on the aircraft. Each combination of aircraft and carriage location defined by the acquiring activity shall be considered in determining the critical loads. When the performance capability of the aircraft is affected by the presence of the store, the performance with the store present shall be used. These load factor envelopes shall be applied at the store cg.

It shall be noted that the store load factors are equal in magnitude, but opposite in direction to the accelerations in g's experienced by the store, during a particular maneuver.

MIL-A-8591G

APPENDIX B

For all points, the stores shall be considered to be mounted at incidence angles of 0 or -3 degrees, whichever is more critical in each case, to be added to the values of α_S given below:



POINTS (1) AND (2)

$$\alpha_S = 0 \text{ to } \frac{15000}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{500}{q} \text{ DEGREES}$$

POINTS (3) AND (4)

$$\alpha_S = 0 \text{ to } -\frac{9000}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{500}{q} \text{ DEGREES}$$

POINT (5)

$$\alpha_S = \pm \frac{600}{q} \text{ to } -\frac{8000}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{6000}{q} \text{ DEGREES}$$

POINT (6)

$$\alpha_S = 0 \text{ to } \frac{15000}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{6000}{q} \text{ DEGREES}$$

FIGURE B-3. Store angles of attack and sideslip at specific load envelope points for wing or sponson-mounted stores (low speed aircraft).

MIL-A-8591G

APPENDIX B

For all points, the stores shall be considered to be mounted at incidence angles of 0 or -3 degrees, whichever is more critical in each case, to be added to the values of α_S given below:

POINTS (1) AND (2)

$$\alpha_S = 0 \text{ to } \frac{1600}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{6000}{q} \text{ DEGREES}$$

POINTS (3) AND (4)

$$\alpha_S = 0 \text{ to } -\frac{1500}{q} \text{ DEGREES}$$

$$\beta_S = \pm \frac{6000}{q} \text{ DEGREES}$$




FIGURE B-4. Store angles of attack and sideslip at specific load envelope points for fuselage-mounted stores (low speed aircraft).

MIL-A-8591G

APPENDIX B

30.2.1 Load factor calculations. The load factors shall be computed using the relations given below.

$$n_{x_s} = -a_x + \frac{1}{g} [\ddot{w}_z \Delta Y - \ddot{w}_y \Delta Z + (\dot{w}_y^2 + \dot{w}_z^2) \Delta X - \dot{w}_x \dot{w}_y \Delta Y - \dot{w}_x \dot{w}_z \Delta Z]$$

$$n_{y_s} = -a_y + \frac{1}{g} [\ddot{w}_x \Delta Z - \ddot{w}_z \Delta X + (\dot{w}_x^2 + \dot{w}_z^2) \Delta Y - \dot{w}_x \dot{w}_y \Delta X - \dot{w}_y \dot{w}_z \Delta Z]$$

$$n_{z_s} = -a_z + \frac{1}{g} [\ddot{w}_y \Delta X - \ddot{w}_x \Delta Y + (\dot{w}_y^2 + \dot{w}_x^2) \Delta Z - \dot{w}_x \dot{w}_z \Delta X - \dot{w}_y \dot{w}_z \Delta Y]$$

$$\Delta X = X_{\text{store cg}} - X_{\text{aircraft cg}}$$

$$\Delta Y = Y_{\text{store cg}} - Y_{\text{aircraft cg}}$$

$$\Delta Z = Z_{\text{store cg}} - Z_{\text{aircraft cg}}$$

30.2.2 Total inertia loads at store cg. The total inertial loads at the store cg shall be computed from the following relations:

$$P_{x_{\text{inertia}}} = n_{x_s} W_s$$

$$P_{y_{\text{inertia}}} = n_{y_s} W_s$$

$$P_{z_{\text{inertia}}} = n_{z_s} W_s$$

$$\begin{aligned} M_{x_{\text{inertia}}} = & -I_{xx} \ddot{w}_x + (I_{yy} - I_{zz}) \dot{w}_y \dot{w}_z - I_{yz} (\dot{w}_y^2 - \dot{w}_z^2) \\ & + I_{xz} (\ddot{w}_z + \dot{w}_x \dot{w}_y) + I_{xy} (\ddot{w}_y - \dot{w}_z \dot{w}_x) \end{aligned}$$

$$\begin{aligned} M_{y_{\text{inertia}}} = & -I_{yy} \ddot{w}_y + (I_{zz} - I_{xx}) \dot{w}_z \dot{w}_x + I_{xz} (\dot{w}_z^2 - \dot{w}_x^2) \\ & + I_{xy} (\ddot{w}_x + \dot{w}_y \dot{w}_z) + I_{yz} (\ddot{w}_z - \dot{w}_x \dot{w}_y) \end{aligned}$$

$$\begin{aligned} M_{z_{\text{inertia}}} = & -I_{zz} \ddot{w}_z + (I_{xx} - I_{yy}) \dot{w}_x \dot{w}_y + I_{xy} (\dot{w}_x^2 - \dot{w}_y^2) \\ & + I_{xy} (\ddot{w}_y + \dot{w}_x \dot{w}_z) + I_{xz} (\ddot{w}_x - \dot{w}_y \dot{w}_z) \end{aligned}$$

MIL-A-8591G

APPENDIX B

30.2.3 Catapult and arrested landing load factors. For wing or sponson-mounted stores on carrier-based aircraft, use Figure B-5 for catapult and arrested landing load factors. The corresponding diagram for fuselage-mounted stores is shown in Figure B-6.

30.2.4 Low-speed fixed-wing aircraft. For aircraft with a maximum carriage speed of 350 KEAS or less, inertia load factors may be taken from Figure B-7 (wing-mounted stores) or Figure B-8 (fuselage-mounted stores).

30.2.5 Wingtip mounted air-to-air missiles. For air-to-air missiles mounted at wingtip locations (outboard of the wing pylon stations) on high performance (fighter/attack type) aircraft, the inertia loads shall be determined from the aircraft flight conditions given in Table B-2 if specific aircraft data is not available.

30.2.6 Forces of interaction. The forces of interaction between the store and aircraft may be computed by various means. For stores with unusual or unique configurations, finite-element models utilizing flexible beam-type elements may be necessary to obtain a proper set of store loads. For this situation, a computer code, such as NASTRAN, may be used to obtain not only the forces of interaction, but also the distributed moments and shears along the store. Procedures employed for these interaction force calculations shall be approved by the acquiring activity.

30.3 Coordinate system and sign convention. The airplane reference axes are shown in Figure 13. Loads, load factors and dimensions are positive when acting up, aft and to the right. Moments, angular accelerations, and angular velocities about axes parallel to the airplane reference axes follow the right-hand rule.

MIL-A-8591G

APPENDIX B




FIGURE B-5. Catapult and arrested landing inertial limit load factors for wing or sponson-mounted stores.

MIL-A-8591G

APPENDIX B





FIGURE B-6. Catapult and arrested landing inertia limit load factors for fuselage-mounted stores.




WHERE:

- (A) Has a value of $n_y = 0$, $n_z = 1.5 \times \text{max negative } g$ which clean aircraft can attain (n_z must be at least 1.0 up).
- (B) Has a value of $n_z = n_z$ at Point (A), $n_y = 1.0$.
- (C) Has a value of $n_z = 0$, $n_y = 1.5 \times \text{max } g$ as read in cockpit, which can be attained during unsymmetric maneuver.
- (D) Has a value of $n_z = n_y = 1.5 \times \text{max } g$ as read in cockpit, which can be obtained during an unsymmetric maneuver.
- (E) Has a value of $n_z = n_z$ at Point (F), $n_y = 1.0$.
- (F) Has a value of $n_y = 0$, $n_z = 1.5 \times \text{max positive } g$ which the clean aircraft can attain.

FIGURE B-7. Design Inertia limit load factors for wing or sponson-mounted stores (low speed aircraft).

APPENDIX B



(A) Has a value of $n_y = 0$, $n_z = 1.5 \times \text{max negative } g$ which clean aircraft can attain (n_z must be at least 1.0 up).

(B) Has a value of $n_y = 0$, $n_z = 1.5 \times \text{max positive } g$ which clean aircraft can attain.

FIGURE B-8, Design inertia limit loads for fuselage-mounted stores (low speed aircraft).

TABLE B-2 Aircraft flight conditions for design of stores on high performance aircraft (limit loads).

Condition	Dynamic pressure (psf)	Aircraft angles (deg)		Linear accelerations (g's)			Peak angular rates ^{1/} (rad/sec)			Peak angular accelerations ^{1/} (rad/sec ²)		
		Attack α	Sideslip β	a_x	a_y	a_z	$\dot{\omega}_x$	$\dot{\omega}_y$	$\dot{\omega}_z$	$\ddot{\omega}_x$	$\ddot{\omega}_y$	$\ddot{\omega}_z$
1. Pullout	2500	5	0	± 1.5	± 1.0	+7.0	± 0.25	± 0.5	0
2. Pullout	1000	13	0	± 1.5	± 1.0	+8.5	± 0.5	± 0.5	0
3. Pullout	500	25	0	± 1.5	± 1.0	+10.0	± 0.5	± 0.5	0
4. Rolling-pullout	650	6	22	± 1.5	± 0.5	+7.0	± 5.0	± 11.0	± 3.0	± 2.0
5. Rolling-pullout	2500	3	± 1	± 1.5	± 0.25	+6.5	± 4.5	± 13.0	± 1.0	± 1.0
6. Rolling-pullout	2500	2	± 1	± 1.5	± 0.25	+6.0	± 4.5	± 17.0	± 1.0	± 1.0
7. Barrier engagement	150	0	0	-4.0	± 1.0	+2.0	0	± 6.0	± 4.0
8. Max sink rate landing	150	0	0	-1.0	± 1.0	+4.0	0	± 4.0	± 2.0
9. Bank-to-bank roll	2500	3	± 1	± 1.5	± 1.0	+6.0	± 13.0	± 0.5	± 1.0
10. Rudder-kick release (19)	400	2	± 10	± 1.5	± 1.5	1.0	± 1.0	0	± 1.5
11. Pushover	2500	-2	0	± 1.5	± 1.0	-1.0	0	0	0
12. Pushover	1800	-4	0	± 1.5	± 1.0	-3.0	0	0	0
13. Pushover	1000	-6	0	± 1.5	± 1.0	-6.0	± 0.5	0	0

^{1/} Note that these values are peak values and do not occur simultaneously.

APPENDIX C

PROCEDURE C

GENERAL DESIGN CRITERIA FOR HELICOPTERS

10. SCOPE

10.1 Scope. Appendix C sets forth general and specific criteria to which airborne stores and related suspension and release equipment, intended for use on helicopters, shall be designed. The requirements set forth herein shall be used except where additional or differing criteria are specified by the acquiring activity.

This appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

20. APPLICABLE DOCUMENTS

This section is not applicable to this appendix.

30. DESIGN REQUIREMENTS

30.1 General requirements. External stores, suspension and release equipment, and the associated interfacing hardware, shall be designed to withstand the most critical combinations of aerodynamic, dynamic and inertial loadings occurring in any specified aircraft configuration. All applicable combinations of external store/suspension, ground or flight conditions (rotor speeds, altitudes and temperatures), and the effects of blast pressure and recoil during weapon firing, launch, or jettison shall be considered. The dynamic interaction or coupling of the combined stores/suspension/aircraft, and any possible resonant amplification, shall be investigated. There shall be no degradation of the basic aircraft with regard to ground and air resonance phenomena, or the occurrence of dynamic instabilities, including flutter and divergence, within the prescribed margins which define the operating envelope of the aircraft. Where critical to successful projectile/missile launch and target capture (seeker lock-on), the design shall provide acceptable launch tip-off attitudes and rates. Evaluation of these system integration requirements shall be accomplished as specified by the acquiring activity and made available to the store contractor as necessary.

30.2 Loads.

30.2.1 Aerodynamic loads. A general method for determination of aerodynamic loads on a store, similar to Appendix A, is not presented. The detail store loads shall be computed by one of the methods described below and approved by the acquiring activity.

- a. Measured force and moment data from wind tunnel or flight tests properly scaled with respect to dynamic pressure or size will be used.
- b. Analytical force and moment data computed by an appropriate rotorcraft flight simulation program during maneuvers performed in accordance with the applicable structural specification.

APPENDIX C

- c. Analytical force and moment data computed by an appropriate three-dimensional flow field program modeling either the complete airframe and store or only the store and those portions of the airframe in the immediate vicinity of the store.
- d. Forces and moments calculated using non-dimensional aerodynamic co-efficients determined by appropriate analytical methods and conditions of dynamic pressure, angle of attack, and sideslip approved by the acquiring activity.

30.2.2 Inertia loading. Methods for calculating store load factors associated with flight and landing are presented here.

30.2.2.1 Flight load factors. The methods for calculating load factors are:

- a. When the helicopter performance parameters and the specific location and weight of the store are known, the equations presented in 30.2.1 and 30.2.2 of Appendix B shall be used to calculate flight inertia load factors and store inertia loads, respectively.
- b. When the helicopter performance parameters are not known, the limit load factors, angular velocities and accelerations at the aircraft cg presented in 30.2.2.4 of this appendix, shall be used with the equations presented in 30.2.1 and 30.2.2 of Appendix B. If the location and weight of the store are unknown, reasonable estimates of these parameters shall be made based upon knowledge obtained from similar store configurations. Estimated data shall be approved by the acquiring activity.

30.2.2.2 Landing load factors. Methods for calculating landing inertia load factors are the same as those presented in 30.2.2.1a and 30.2.2.1b of this appendix. Landing loads shall not be combined with aerodynamic loads.

30.2.2.3 Crash. Load factors presented in Table C-1 shall be used to determine store loads associated only with Navy helicopter crash conditions. These factors are not additive and are to be applied separately at the store center of gravity. For Army helicopters, the store and store support structure, as a minimum, shall be designed to separate from the aircraft prior to failure of the primary structure.

TABLE C-1. Navy helicopter store ultimate crash load factors (at store cg).

n_{x_s}	n_{y_s}	n_{z_s}
-9.00	± 3.75	-9.0
+2.25	. . .	+4.5

MIL-A-8591G

APPENDIX C

30.2.2.4 Aircraft parameters. The aircraft parameters shall be as specified in Table C-2.

TABLE C-2. Aircraft parameters.

Condition	a_x	a_y	a_z	$\dot{\omega}_x$	$\dot{\omega}_y$	$\dot{\omega}_z$	\ddot{u}_x	\ddot{u}_y	\ddot{u}_z
Symmetrical flight	± 1.0	± 0.2	3.5	± 1.0	± 1.0	± 0.1	± 1.0	± 4.0	± 0.5
Unsymmetrical flight	± 0.5	± 0.5	2.8	± 1.0	± 1.0	± 0.9	± 8.0	± 1.5	± 2.5
Landing with roll	± 0.5	0	1.8	-	-	-	± 12.0	± 2.5	± 1.5
Landing with pitch	± 0.5	± 0.5	2.2	-	-	-	± 7.0	± 5.5	± 0.3

30.2.3 Dynamic loading. The store shall be designed for all dynamic loads including those resulting from ground, airborne, weapons and countermeasures firing, weapons jettison and rotor excitation conditions in combination with the appropriate inertial and aerodynamic loads. The store contractor and the designated carriage-aircraft contractor shall coordinate with each other as appropriate and in accordance with acquiring activity direction, to exchange dynamic and vibration data and information. These dynamic characteristics, associated with the specific helicopter(s), shall be accounted for in the design of the aircraft/store system, to preclude adverse response characteristics that would degrade the basic helicopter handling qualities, riding comfort, and aircraft component fatigue lives.

30.2.4 Fatigue loading. Steady state and oscillatory loads which are imposed on the stores installation shall be determined for the full range of the operating environment of the specified helicopter. Fatigue life substantiation shall be accomplished using these loads and a flight spectrum approved by the acquiring activity.

30.3 Dynamic requirements. The vibratory response characteristics of the store, suspension equipment, or store/interface system, shall be calculated or measured for all conditions below. The frequency response shall range from, 1/rev of the main rotor through 4b/rev of the main rotor or 2b/rev of the tail rotor, whichever is higher (b = number of blades). For weapons firing conditions, the frequency range shall extend from the fundamental firing frequency through the 10th harmonic. In addition to excitations at frequencies producing highest loads or accelerations, other rotor and weapons-fire harmonics shall be considered when their frequency is within ± 10 percent of a known component resonance. Resonances are defined as amplification of the input level by greater than 2:1. Therefore, design consideration shall include, but not necessarily be limited to, the following conditions:

APPENDIX C

- a. Ground operations including handling and taxiing.
- b. Airborne flight including hover IGE and OGE, level flight, normal maneuvers, tactical maneuvers and autorotation.
- c. Weapon and countermeasure firing from small and large caliber guns, rockets, missiles, grenades, chaff dispensers and flares.
- d. Take off and landing.
- e. Stores jettison.

30.3.1 Rotor induced harmonic excitation. Main and tail rotor induced vibrations are the significant sources of dynamic loading for helicopters. The coupled dynamic response of the rotor(s), fuselage, wing (if applicable), suspension equipment, and stores, induced either aerodynamically or through the structure, shall be determined. As a goal, the system shall be designed to avoid main and tail rotor resonances within the normal power-on and power-off speeds at all gross weights, centers of gravity, and aircraft loadings, and for all applicable stores loading and dispensing configurations, including that of other store locations. Freedom from nb/rev resonance (n = an integer) is highly desirable. Where more than one store is mounted on the same suspension hardware, or where more than one store/suspension combination is located on a structure(s) cantilevered from the fuselage, then all specified loading combinations shall be considered. Margins from 1/rev and b/rev of 0.25/rev shall be observed, or alternately, it shall be conservatively demonstrated that the combined static and dynamic loadings are acceptable.

30.3.2 Frequency placement. The following structural and dynamic factors which control frequency placements shall be considered:

- a. Fuselage attachment and supporting structure including wings or other cantilevered structure for support of external stores.
- b. Wing or cantilevered structural stiffness.
- c. Flexibility of suspension and release equipment.
- d. Stores or launcher structural flexibility.
- e. Sway brace stiffness.
- f. Coupling of system modes in close proximity.

30.3.3 Store response. Factors affecting the prediction of store response magnitude shall include, but not necessarily be limited to, the following:

- a. Strength of the rotor wake impinging on the stores and stores support structure, and the resulting harmonic excitation.
- b. Magnitude of forcing functions at the rotor hub.

MIL-A-8591G

APPENDIX C

- c. Proximity of natural frequencies to rotor excitation frequencies and weapon firing rates.
- d. Transmissibility from rotor to support structure as a result of modal response distributions.
- e. Amplification or attenuation of stores relative to support structure (suspension/stores dynamics).
- f. Modal coupling.
- g. System and local damping.
- h. Free play in suspension/release mechanisms.
- i. Effective damping of stores, such as fuel.

30.4 Flutter and divergence. The requirements of 3.12 of the basic document shall be met.

30.5 Mechanical instability. The total weapons system shall be free of mechanical instability with the required margin of safety at all rotor speeds during all ground and flight operating conditions. The store designer, the suspension equipment contractor, and the designated carriage-aircraft contractor shall coordinate with each other, as appropriate, and in accordance with acquiring activity direction, to exchange pertinent inertia, dynamic, and other data necessary to define, by analytical or test methods, the aircraft/store mechanical instability characteristics.

30.6 Store/aircraft interface. The interaction forces between the store and the aircraft shall be determined by a method approved by the acquiring activity. Finite-element models utilizing flexible beam-type elements may be necessary to obtain a proper set of store loads. For this situation, a computer code, such as NASTRAN, may be used to obtain not only forces of interaction, but also the distributed moments and shears along the store.

MIL-A-8591G

INDEX		
CONTENTS	PARAGRAPH	PAGE
<u>APPENDIX</u>		
A	-	31 thru 35
B	-	36 thru 49
C	-	50 thru 54
<u>APPLICABLE DOCUMENTS</u>	2.	1
<u>CARRIAGE DESIGN LIMIT LOAD</u>	3.11	20
Dynamic magnification:	3.11.3	21
Dynamic magnification factors	3.11.3.1	21
Time rates	3.11.3.2	22
Fatigue strength	3.11.5	23
Installation preloads	3.11.2	21
Liquid-slosh loads	3.11.6	23
Procedure descriptions:	3.11.1	21
Procedure A - carriage design limit loads general case	3.11.1.1	21
Procedure B - carriage design limit loads - stores carried on a specific aircraft	3.11.1.2	21
Procedure C - carriage design limit loads - stores carried on helicopter aircraft	3.11.1.3	21
Shock loads:	3.11.7	23
Cradling and handling loads	3.11.7.3	23
Employment loads	3.11.7.1	23
Shipping loads	3.11.7.2	23
Vibratory loads	3.11.4	22
<u>CHANGES FROM PREVIOUS ISSUE</u>	6.5	30
<u>CUSTODIANS</u>	-	30
<u>DATA</u>	6.2	25
Data requirements	6.2.1	25
Store certification data	6.2.2	25
<u>DEFINITIONS AND SYMBOLS</u>	6.3	25
Air-launched missile	6.3.5	25
Carriage	6.3.10	26
Ejection	6.3.12	26
Ejection launcher	6.3.7	26
Employment	6.3.13	26

MIL-A-8591G

INDEX - Continued		
CONTENTS	PARAGRAPH	PAGE
Jettison:	6.3.14	26
Emergency jettison	6.3.14.2	26
Selective jettison	6.3.14.1	26
Missile launcher	6.3.4	25
Pylon	6.3.8	26
Rail launcher	6.3.6	26
Separation	6.3.11	26
Sign convention	6.3.16	28
Store	6.3.2	25
Suspension equipment	6.3.3	25
Sway bracing	6.3.9	26
Symbols	6.3.15	26 thru 28
<u>DEFORMATION</u>	3.3	4
<u>DESIGN DATA</u>	4.5	24
Symbols and axes	4.5.1	24
<u>DESIGN STRENGTH</u>	3.2	4
Limit loads	3.2.1	4
Ultimate loads	3.2.3	4
Yield loads	3.2.2	4
<u>FIGURES</u>		
1 through 11	-	9 thru 19
12	-	22
13	-	29
A-1 through A-4	-	32 thru 35
B-1	-	38
B-2	-	39
B-3	-	41
B-4	-	42
B-5 through B-8	-	45 thru 48
<u>FLIGHT TESTS</u>	4.4	24
<u>FLUTTER AND DIVERGENCE</u>	3.12	23
<u>INTENDED USE</u>	6.1	25
<u>INTERNATIONAL ORGANIZATIONS</u>	-	30
<u>INTERNATIONAL STANDARDIZATION AGREEMENTS</u>	6.4	28
<u>NOTES</u>	6.	25

INDEX - Continued		
CONTENTS	PARAGRAPH	PAGE
<u>PACKAGING</u>	5.	24
<u>PREPARING ACTIVITY</u>	-	30
<u>QUALITY ASSURANCE</u>	4.	24
<u>RECYCLED, VIRGIN AND RECLAIMED MATERIALS</u>	3.13	23
<u>REQUIREMENTS</u>	3.	4
<u>RESPONSIBILITY FOR INSPECTION</u>	4.1	24
<u>REVIEW ACTIVITY</u>	-	30
<u>SCOPE</u>	1.	1
Conforming requirements	1.3	1
Extent	1.2	1
Scope	1.1	1
<u>SERVICE LIFE</u>	3.7	7
<u>STORE CLASSIFICATION</u>	3.5	5
Center of gravity	3.5.3	6
Ejected stores	3.5.1	5
Rail launched stores	3.5.2	5
<u>STORE DESIGN LOADS</u>	3.4	5
<u>STORE REINFORCED AREAS</u>	3.9	8
Cradling and handling areas	3.9.3	8
Ejector areas	3.9.2	8
Reinforced area strength:	3.9.4	20
Cradling and handling		
area strength	3.9.4.2	20
Sway brace pad		
areas and span	3.9.4.1	20
Sway brace areas	3.9.1	8
<u>STORE/SUSPENSION EQUIPMENT INTERFACE DESIGN</u>	3.10	20
Ejector float areas	3.10.1	20
Sway brace pad areas	3.10.2	20
<u>SUSPENSION DESIGN CRITERIA</u>	3.8	7
Rail launched hangers	3.8.2	8
Suspension lugs:	3.8.1	7
Design acceptance	3.8.1.4	8
Lug number and location	3.8.1.2	7
Lug strength	3.8.1.1	7
Lug well details	3.8.1.3	7

MIL-A-8591G

INDEX - Continued		
CONTENTS	PARAGRAPH	PAGE
<u>TABLES</u>		
I	-	5
II and III	-	6
B-1	-	37
B-2		49
C-1		51
<u>TERMS AND NOMENCLATURES</u>	3.1	4
<u>THERMAL CRITERIA</u>	3.6	6
External	3.6.2	7
Internal	3.6.1	7
<u>APPENDIX A</u>		
<u>APPLICABLE DOCUMENTS</u>	20.	31
<u>DESIGN LOADS</u>	30.	31
Aerodynamic loads	30.1	31
<u>FIGURES</u>		
A-1 through A-4	-	32 thru 35
<u>INERTIA LOADS</u>	30.2	31
Limit inertia catapult and arrested landing load factors	30.2.2	31
Limit inertia load factors	30.2.1	31
<u>SCOPE</u>	10.	31
<u>APPENDIX B</u>		
<u>APPLICABLE DOCUMENTS</u>	20.	36
<u>DESIGN LOADS</u>	30.	36
Aerodynamic loads:	30.1	36
Analytical method	30.1.4	40
Method for low speed carriage	30.1.5	40
Method of Appendix A	30.1.1	37
Method using aircraft angles	30.1.2	37
Method using flow field data	30.1.3	40

MIL-A-8591G

INDEX - Continued

CONTENTS	PARAGRAPH	PAGE
Coordinate system and sign convention	30.3	44
Inertia loads:	30.2	40
Catapult and arrested		
landing load factors	30.2.3	44
Forces of interaction	30.2.6	44
Load factor calculations	30.2.1	43
Low speed fixed-wing aircraft	30.2.4	44
Total inertia loads at store cg	30.2.2	43
Wingtip mounted air-to-air missiles	30.2.5	44
<u>FIGURES</u>		
B-1	-	38
B-2	-	39
B-3	-	41
B-4	-	42
B-5 through B-8	-	45 thru 48
<u>SCOPE</u>	10.	36
<u>TABLES</u>		
B-1	-	37
B-2	-	49
<u>APPENDIX C</u>		
<u>APPLICABLE DOCUMENTS</u>	20.	50
<u>DESIGN REQUIREMENTS</u>	30.	50
Dynamic requirements:	30.3	52
Frequency placement	30.3.2	53
Rotor induced harmonic excitation	30.3.1	53
Store response	30.3.3	53
Flutter and divergence	30.4	54
General requirements	30.1	51
Loads:	30.2	50
Aerodynamic loads	30.2.1	50
Dynamic loading	30.2.3	52
Fatigue loading	30.2.4	52
Inertia loading:	30.2.2	51
Aircraft parameters	30.2.2.4	52
Crash	30.2.2.3	51
Flight load factors	30.2.2.1	51
Landing load factors	30.2.2.2	51
Mechanical instability	30.5	54
Store/aircraft interface	30.6	54

MIL-A-8591G

INDEX - Continued		
CONTENTS	PARAGRAPH	PAGE
<u>SCOPE</u>	10.	50
<u>TABLES</u>		
C-1	-	51
C-2	-	52

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER MI-A-8591G		2. DOCUMENT TITLE Airborne Stores, Suspension Equipment	
3a. NAME OF SUBMITTING ORGANIZATION		4. TYPE OF ORGANIZATION (Mark one) <input type="checkbox"/> VENDOR <input type="checkbox"/> USER <input type="checkbox"/> MANUFACTURER <input type="checkbox"/> OTHER (Specify): _____	
b. ADDRESS (Street, City, State, ZIP Code)			
5. PROBLEM AREAS			
a. Paragraph Number and Wording:			
b. Recommended Wording:			
c. Reason/Rationale for Recommendation:			
6. REMARKS			
15			
7a. NAME OF SUBMITTER (Last, First, MI) - Optional		b. WORK TELEPHONE NUMBER (Include Area Code) - Optional	
c. MAILING ADDRESS (Street, City, State, ZIP Code) - Optional		8. DATE OF SUBMISSION (YYMMDD)	