

~~MIL-B-85667A~~  
 SUPPLEMENT 1  
 28 January 1991  
 SUPERSEDING  
 MIL-B-85667(AS)  
 SUPPLEMENT 1  
 14 March 1986

# MILITARY SPECIFICATION

## BOLT, SLEEVE, STRAIGHT SHANK, PROTRUDING AND FLUSH HEAD GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-B-85667A, dated 28 January 1991.

MIL-B-85667/1A (Supersedes MIL-B-8831/1)	Bolt, Sleeve, Straight Shank, Reliability and Maintainability Requirements for
MIL-B-85667/2A	Bolt, Sleeve, 100° Reduced Flush Head, Straight Shank, Expandable Cres 304 Sleeve, Cres PH13-8Mo Pin, 125 KSI Fsu
MIL-B-85667/3A	Bolt, Sleeve, Protruding Head, Straight Shank, Expandable Cres 304 Sleeve, Cres PH13-8Mo Pin, 220 KSI Ftu
MIL-B-85667/4A	Bolt, Sleeve, 100° Reduced Flush Head, Straight Shank, Titanium Alloy Pin, 95 KSI Fsu
MIL-B-85667/5A	Bolt, Sleeve, Protruding Head, Straight Shank, Titanium Alloy Pin, 160 KSI Ftu
MIL-B-85667/6A	Bolt, Sleeve, 100° Reduced Flush Head, Straight Shank, Expandable Cres 304 Sleeve, Nickel Alloy 718 Pin, 125 KSI Fsu, 450°F
MIL-B-85667/7A	Bolt, Sleeve, Protruding Head, Straight Shank, Expandable Cres 304 Sleeve, Nickel Alloy 718 Pin, 220 KSI Ftu, 125 KSI Fsu, 450°F
MIL-B-85667/8	Bolt, Sleeve, 100° Reduced Flush Head, Straight Shank, Expandable Cres 304 Sleeve, Cres A-286 Pin, 95 KSI Fsu, 450°F
MIL-B-85667/9	Bolt, Sleeve, Protruding Head, Straight Shank, Expandable Cres 304 Sleeve, Cres A-286 Pin, 95 KSI Fsu, 160 KSI Ftu, 450°F

AMSC N/A

FSC 5306

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MIL-B-85667A

SUPPLEMENT 1

MIL-B-85667/10	Bolt, Sleeve, 100° Tension Flush Head, Straight Shank, Expandable Cres 304 Sleeve, Cres A-286 Pin, 160 KSI Ftu, 450°F
MIL-B-85667/11	Bolt, Sleeve, 100° Tension Flush Head, Straight Shank, Expandable Nickel-Cres 304 Sleeve, Nickel Alloy 718 Pin, 220 KSI Ftu, 450°F
MIL-B-85667/12	Bolt, Sleeve, 100° Tension Flush Head, Straight Shank, Expandable Cres 304 Sleeve, Titanium Alloy Pin, 95 KSI Fsu, 160 KSI Ftu
MIL-B-85667/13	Bolt, Sleeve, 100° Tension Flush Head, Straight Shank, Expandable Aluminum Alloy Sleeve, Titanium Alloy Pin, 95 KSI Fsu, 160 KSI Ftu
MIL-B-85667/14 (Supersedes MIL-B-8831/2)	Bolt, Sleeve, 100° Reduced Flush Head, Straight Shank, Expandable Aluminum Alloy Sleeve, Alloy Steel Pin, 108 KSI Fsu
MIL-B-85667/15 (Supersedes MIL-B-8831/3)	Bolt, Sleeve, Protruding Head, Straight Shank, Expandable Aluminum Alloy Sleeve, Alloy Steel Pin, 180 KSI Ftu
MIL-B-85667/16 (Supersedes MIL-B-8831/4)	Bolt, Sleeve, 100° Reduced Flush Head, Straight Shank, Expandable Aluminum Alloy Sleeve, Alloy Steel Pin, Low Interference, 108 KSI Fsu
MIL-B-85667/17 (Supersedes MIL-B-8831/5)	Bolt, Sleeve, Protruding Head, Straight Shank, Expandable Aluminum Alloy Sleeve, Alloy Steel Pin, Low Interference, 180 KSI Ftu

Preparing Activity:  
Navy - AS  
(Project No. 5306-1379)