

INCH-POUND

MIL-B-8906C
AMENDMENT 2
5 FEBRUARY 1998

MILITARY SPECIFICATION

BOLT, ALLOY STEEL, SHEAR AND TENSILE (132 KSI MIN FSU AND 220 KSI MIN FTU),
450°F, SPLINE DRIVE

This amendment forms a part of MIL-B-8906C, dated 18 APRIL 1988,
and is approved for use by all Departments and Agencies of the
Department of Defense.

PAGE 3

- * Delete paragraph 3.2

Rewrite paragraph 3.2 to read: "3.2 This paragraph left intentionally
blank."

PAGE 11

Paragraph 3.10.3: Delete "average" and substitute "minimum," i.e. average
fatigue life of 65,000 cycles should be minimum fatigue life of 65,000
cycles.

PAGE 13

- * Delete paragraph 4.2

Rewrite paragraph 4.2 to read: "4.2 Classification of inspections. The
examination and testing of bolts shall be classified as quality conformance
inspection (see 4.4)."

- Delete paragraph 4.3 and Table VI.

•

PAGE 14

- * Delete paragraph 4.3.1, 4.3.2 and 4.3.3

AMSC N/A

FSC 5306

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

**MIL-B-8906C
AMENDMENT 2**

PAGE 20

*** Delete paragraph 6.3 and 6.3.1 and replace with the following:**

"6.3 This paragraph left intentionally blank."

"6.3.1 This paragraph left intentionally blank."

Custodians:

Army - AV

Navy - AS

Air Force - 99

Preparing Activity:

DLA-IS

(Project 5306-2019)

Review activity:

Army - AR, MI

Air Force - 82