

MIL-C-27072/29A
 24 September 1987
 SUPERSEDING
 MIL-C-27072/29(USAF)
 10 September 1965

MILITARY SPECIFICATION SHEET

CABLE, SPECIAL PURPOSE, ELECTRICAL, MULTICONDUCTOR,
 (12 CONDUCTORS) AND SINGLE SHIELDED
 N27072/29MACA*

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the cable described herein shall consist of this specification and the latest issue of MIL-C-27072.




FIGURE 1. Cable configuration.

* The complete part number requires a color code designator (see table I).

MIL-C-27072/29A

DESIGN DATA:

Design and construction: See figure 1.
Number of conductors: Twelve.
Conductor size and stranding: See table I.
Wire: M16878/17BFB* (see table I).
Jacket undershield: Not applicable.
Shielding: Tinned copper.
Sheath: Polyvinyl chloride.
Temperature rating: 105°C.

REQUIREMENTS:

Visual and dimensional:

Components:

Basic wire: Tinned copper.

Dimensions: See table I.

Primary insulation:

Material: Polyvinyl chloride.

Wall thickness: .009 ±.003 inch.

Colors:

- White with black tracer.
- White with brown tracer.
- White with red tracer.
- White with orange tracer.
- White with green tracer.
- White with blue tracer.
- White with violet tracer.
- White with two black tracers.
- White with black and brown tracers.
- White with black and red tracers.
- White with black and orange tracers.
- White with black and green tracers.

Spark test voltage: 3,400 V rms.

Inspection test voltage: 2,000 V rms.

Impulse dielectric test: 8,000 V peak.

Jacket over insulation: Polyamide.

MIL-C-27072/29A

Color: Natural.

Filler:

Material: Not applicable.

Lay: 3.0 inches maximum.

Tape material: Not applicable.

Cabling:

Number of conductors: Twelve.

Maximum pitch or lay: 3.0 inches.

Shield:

Material: Tinned copper.

Gauge: 36 AWG.

Braid angle: 20 to 40 degrees.

Workmanship: In accordance with MIL-C-27072.

Sheath:

Material: Polyvinyl chloride.

Wall thickness: .030 inch nominal.

Tensile strength: In accordance with table V of MIL-C-27072.

Elongation: In accordance with table V of MIL-C-27072.

Tension set: Not applicable.

Tear strength: Not applicable.

Accelerated aging: In accordance with table V of MIL-C-27072.

Oil resistance: Not applicable.

Color: See table IV of MIL-C-27072.

Finished cable:

Weight: For future consideration.

Diameter: See table I.

Conductor resistance: In accordance with MIL-W-16878/17.

Dielectric strength: In accordance with MIL-W-16878/17.

Cold bend: Mandrel size in accordance with table XIII of MIL-C-27072.

Ozone: Mandrel size in accordance with table XIV of MIL-C-27072.

Marking durability: In accordance with MIL-C-27072.

Heat stability: Not applicable.

MIL-C-27072/29A

TABLE I. Construction data.

Part number M27072/29	Conductor			Nominal diameter (in.)	Finished cable diameter (in.) ±10%	Basic wire M16878/17
	Wire size (AWG)	Number of strands	Strand size (AWG)			
MACA*	22	7	30	.056	.310	BFB***

Asterisks (*) shall be replaced by the appropriate color designator.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:

Army - CR
Navy - SH
Air Force - 85

Review activities:

Air Force - 99
DLA - ES, IS

Preparing activity:

Air Force - 85

Agent:

DLA - ES

(Project 6145-0909-10)