INCH-POUND

MIL-C-52950A AMENDMENT 2 <u>27 November 1991</u> SUPERSEDING AMENDMENT 1 18 September 1991

#### MILITARY SPECIFICATION

### CRATES, WOOD, OPEN AND COVERED

This amendment forms a part of Military Specification MIL-C-52950A, dated 20 March 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

#### PAGE 1

\* Change document identifier to read as follows:

INCH-POUND

MIL-C-52950A 20 March 1991 SUPERSEDING MIL-C-52950 10 April 1978

#### PAGE 2

\* Table I, above first column and to left of "load" add "Type."

Table I, delete last row of numbers (Type V), and replace with the following:

V 2/ 2500 12 6 6 4000 32 6 10

PAGE 22

Project number: Delete "PACK-0793" and substitute "8115-0513."

Under "User Activities" delete "MU" and insert "AR."

AMSC N/A

### 1 of 2

FSC 8115

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


MIL-C-52950A AMENDMENT 2


### PAGE 23 THRU PAGE 40

Add figures 1 thru 18.


The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians: Army - ME Navy - YD Air Force - 69 Review Activities:	Preparing Activity: Navy - YD (Project 8115-0533)		
		Army - CR, SM, GL, EA	
		Navy - SA	
		User Activities:	
Army - AR, AT			
Navy - MC			





Α



В

Nailing patterns. (All widths are nominal. Similar patterns shall be used when boards cross at angles other 90°.). FIGURE 1.







FIGURE 2. <u>Splicing of members; A, splice of 4-by-4 inch</u> or 4-by-6 inch skids; B, splice of 2-inch member; <u>C, splice of 1-inch member; D, lamination of skid</u>.








- STRUT


SIDE

TOP





# FIGURE 3. Type I, style A crate assembly.







FIGURE 4. Type I, style B crate assembly.







FIGURE 5. Type II, style A, crate assembly.








FIGURE 6. <u>Type II, crate with exterior side cleats</u>: <u>A, complete crate; B, two panel; C, three panel;</u> and D, four panel.

MIL-C-52950A





# FIGURE 7. Type III, style B, crate assembly.




SIDE

TOP











FIGURE 9. Type V, style A crate assembly.







FIGURE 10. Bases for type V, style B crates: A, up through 42 inches wide; B, over 42 inches wide.






FIGURE 11. Single - panel sides for Type V, style B crates: A, side of long crate; B, side of short crate; C, covered side.





FIGURE 12. Double - panel sides for type V, style B crates for heights through 96 inches: A, open side; B, covered side.






FIGURE 13. <u>Triple - panel sides for type V, style B crates</u> for heights over 96 inches: A, open side; <u>B, covered side</u>.




FIGURE 14. Ends for type V, style B crates: A, two - panel horizontal; B, single - panel (covered); C, four - panel; D, two - panel vertical.







FIGURE 15. <u>Ends for type V, style B crates: A, wide</u> and narrow double - panel ends; B, wide and narrow triple - panel ends.








FIGURE 16. <u>Tops for type V, style B crates:</u> <u>A, narrow top; B, medium - wide top;</u> <u>C, wide top</u>.





# FIGURE 17. Type V, style B crate assembly (open).




FIGURE 18. Type V, style B crate assembly (covered).

Downloaded from http://www.everyspec.com

MIL-C-52950A