

INCH-POUND

MIL-C-81511F(AS)
 SUPPLEMENT 1
 30 September 1992

MILITARY SPECIFICATION
 CONNECTORS, ELECTRICAL, CIRCULAR, HIGH DENSITY, QUICK
 DISCONNECT, ENVIRONMENT RESISTING: AND ACCESSORIES
 GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-C-81511F(AS) dated 30 September 1992.

SPECIFICATION SHEETS

- | | |
|----------------|---|
| MIL-C-81511/1 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Receptacle, Flange Mount, Crimp-Type Contacts, Class A, F, E and W (Series 2). |
| MIL-C-81511/3 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: And Accessories: Receptacle, Jam Nut Mount, Crimp-Type Contacts, Class A, F, E, and W (Series 2). |
| MIL-C-81511/5 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: And Accessories: Receptacle, Cable Connecting, Crimp-Type Contacts, Class A, F, E, and W (series 2). |
| MIL-C-81511/6 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: And Accessories Plug, Crimp-Type Contacts, Class A, F, E and W (Series 2). |
| MIL-C-81511/13 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: F Adapter, Rotatable, Type I (Series 1 or 2) |
| MIL-C-81511/14 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; And Accessories. Adapter, Straight |
| MIL-C-81511/15 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; And Accessories: Plug, Sealing Contact (Series 1 or 2) |
| MIL-C-81511/16 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting and Accessories: Cap, Protective Locking |

MIL-C-81511F(AS)
SUPPLEMENT 1

- | | |
|----------------|---|
| MIL-C-81511/17 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories. Cover, Protective, Plug (Series 2). |
| MIL-C-81511/18 | - Connectors, Electrical Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories Cover, Protective, Receptacle (Series 1 or 2). |
| MIL-C-81511/19 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories; Receptacle, Dummy Stowage, For Series 2 Connectors. |
| MIL-C-81511/20 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; And Accessories: Nut, Slotted Hexagon, Connector Mounting, For Series 1 and 2 |
| MIL-C-81511/21 | - Connectors, Electrical, Circular, High Density Quick Disconnect, Environment Resisting; and Accessories: Receptacle, Flange Mount, Crimp-Type Contacts, Class A, F, E and W (Series 1). |
| MIL-C-81511/23 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Receptacle, Jam Nut Mount, Crimp-Type Contacts, Class A, F, E and W (Series 1). |
| MIL-C-81511/25 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Receptacles, Cable Connecting, Crimp-Type Contacts, Class A, F, E and W (Series 1) |
| MIL-C-81511/26 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories: Plug, Crimp-Type Contacts, Class A, F, E and W (Series 1). |
| MIL-C-81511/41 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Flange Mount, Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 3). |
| MIL-C-81511/45 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Cable Connecting, Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 3). |
| MIL-C-81511/49 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting Receptacle, Jam Nut Mount, Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 3) |

MIL-C-81511F(AS)
SUPPLEMENT 1

- | | |
|----------------|---|
| MIL-C-81511/51 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Flange Mount, Individual Release, Crimp-Type Contacts. Class A, W, and F (Series 4). |
| MIL-C-81511/53 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Jam Nut Mount, Individual Release, Crimp-Type Contacts. Class A, F and W (Series 4). |
| MIL-C-81511/54 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Jam Nut Mount. Solder-Type Contacts, Pins Only. Class D (Series 4). |
| MIL-C-81511/55 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Cable Connecting, Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 4). |
| MIL-C-81511/56 | - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Plug. Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 4). |
| MS3425 | - Insert Arrangements, MIL-C-81511 Electric Connector, Size 8 |
| MS3426 | - Insert Arrangements, MIL-C-81511 Electric Connector, Size 10 |
| MS3428 | - Insert Arrangements, MIL-C-81511 Electric Connector, Size 14 |
| MS3429 | - Insert Arrangements, MIL-C-81511 Electric Connector, Size 16 |
| MS3430 | - Insert Arrangements, MIL-C-81511 Electric Connector, Size 18 |
| MS3431 | - Insert Arrangements, MIL-C-81511 Electric Connector, Size 20 |
| MS3432 | - Insert Arrangements, MIL-C-81511 Electric Connector, Size 22 |
| MS3433 | - Insert Arrangements, MIL-C-81511 Electric Connector, Size 24 |
| MS3482 | - Tool, Connector Assembly; for MIL-C-81511 Connectors |

Preparing activity.
Navy - AS