

MIL-C-83503A(USAF)
 SUPPLEMENT 1
 21 JUNE 1984

MILITARY SPECIFICATION

CONNECTORS, ELECTRICAL, FLAT CABLE, NONENVIRONMENTAL,
 GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-C-83503A(USAF), dated 1 July 1983.

SPECIFICATION SHEETS

- MIL-C-83503/6(USAF) - Connector, electrical, flat cable, nonenvironmental, dual-in-line plug for terminating round conductors on .050 centers, for mating with standard dip sockets, .100 x .300 contact spacing, .100 X .400 contact spacing and .100 x .600 contact spacing.
- MIL-C-83503/7(USAF) - Connectors, electrical, flat cable, nonenvironmental, plug with dual polarization, round conductor, insulation displacing, non-removable socket contacts (.100 x .100 spacing).
- MIL-C-83503/20(USAF) - Connectors, electrical, flat cable, nonenvironmental, header, right angle (.100 spacing) with polarizing feature solderless wrappost or PWB termination.
- MIL-C-83503/21(USAF) - Connectors, electrical, flat cable, nonenvironmental, header, straight thru (.100" spacing) with polarizing feature solderless wrappost or PWB termination.
- MIL-C-83503/22(USAF) - Connectors, electrical, flat cable, nonenvironmental, socket insulation displacement.
- MIL-C-83503/23(USAF) - Connectors, electrical, flat cable, nonenvironmental, printed wiring board solder transition for terminating round conductors on .050 inch centers.
- MIL-C-83503/24(USAF) - Connectors, electrical, flat cable, nonenvironmental, four wall header, right angle (.100 spacing) with polarizing feature, solderless wrappost or PWB termination.
- MIL-C-83503/25(USAF) - Connectors, electrical, flat cable, nonenvironmental, four wall header, straight thru (.100 spacing) with polarizing feature, solderless wrappost or PWB termination.

Agent:
 DLA - ES

Preparing activity:
 Air Force - 85

(Project 5935-F241)