

MIL-D-3954C
 SUPPLEMENT 1
 24 March 1976

MILITARY SPECIFICATION

DUMMY LOADS, ELECTRICAL WAVEGUIDE,
 GENERAL SPECIFICATION FOR

This supplement forms a part of Military
 Specification MIL-D-3954C, 19 November 1973.

Specification Sheets

MIL-D-3954/11	- Dummy Loads, Electrical, Waveguide (Frequency Range 7.05 to 10.0 Gigahertz).
MIL-D-3954/12	- Dummy Loads, Electrical, Waveguide (Frequency Range 26.5 to 40.0 Gigahertz).
MIL-D-3954/13	- Dummy Loads, Electrical, Waveguide (Frequency Range 12.4 to 18.0 Gigahertz).
MIL-D-3954/14	- Dummy Load, Electrical, Waveguide (Frequency Range 18.0 to 26.5 Gigahertz).
MIL-D-3954/15	- Dummy Loads, Electrical, Waveguide (Frequency Range 1.12 to 1.70 Gigahertz).
MIL-D-3954/16	- Dummy Loads, Electrical, Waveguide (Frequency Range 5.85 to 8.20 Gigahertz).
MIL-D-3954/17	- Dummy Loads, Electrical, Waveguide (Frequency Range 3.95 to 5.85 Gigahertz).
MIL-D-3954/18	- Dummy Loads, Electrical, Waveguide (Frequency Range 2.6 to 3.95 Gigahertz).
MIL-D-3954/19	- Dummy Loads, Electrical, Waveguide (Frequency Range 8.2 to 12.4 Gigahertz).
MIL-D-3954/20	- Dummy Loads, Electrical, Waveguide, Class II, (Frequency Range 5.4 to 5.9 GHz).
MIL-D-3954/21	- Dummy Loads, Electrical, Waveguide, Class II, Frequency Range 10.25 to 10.50 Gigahertz, 7KW.
MIL-D-3954/22	- Dummy Loads, Electrical, Waveguide, Class II, (Frequency Range 8.2 to 12.4 Gigahertz).

Preparing activity:
 Navy - EC

Agent:
 DSA - ES

★U.S. GOVERNMENT PRINTING OFFICE: 1976-603-766/5788

(Project 5985-0838)

FSC 5985