

INCH-POUND

MIL-D-9129D
AMENDMENT 1
9 Nov 1990MILITARY SPECIFICATION
DISCHARGERS, ELECTROSTATIC
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-D-9129D, dated 30 September 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.6.6, delete and substitute:

"3.6.6 Direct current resistance. The resistance of dischargers measured from discharge points to discharger mounting base shall be at 25°C (see 4.7.4).

- a. Trailing edge mounted = 6 to 200 megohms.
- b. Tip mounted = 6 to 120 megohms.
- c. Resistance shall be measured with a 500 volt minimum megohmmeter."

PAGE 9

TABLE III, delete and substitute:

"TABLE III. Group B inspection.

| Inspection | Requirement paragraph | Test method paragraph |
|---------------------------------|-----------------------|-----------------------|
| (4 sample units) | | |
| Direct current resistance | 3.6.6 | 4.7.4 |
| High discharge current | 3.6.4 | 4.7.2.4 |
| Discharge current | 3.6.1 | 4.7.2.1 |
| Radio frequency discharge noise | 3.6.2 | 4.7.2.2 |

AMSC N/A

1 of 2

PSC 5920

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.

MIL-D-9129D
AMENDMENT 1

4.6.3.1.2, delete and substitute:

"4.6.3.1.2 Failures. If one or more sample units fails to pass group C inspections, the sample lot shall be considered to have failed. In that event the cognizant inspection activity and the qualifying activity shall be notified immediately (see 4.4.4)."

CONCLUDING MATERIAL

Custodians:

Army - ER
Navy - AS
Air Force - 85

Review activities:

Army - CE, MI
Air Force - 17, 99
DLA - ES

User activities:

Navy - MC
Air Force - 14, 19

Preparing activity:

Air Force - 85

Agent:

DLA - ES

(Project 5920-0462)