

INCH-POUND

MIL-DTL-16878G
SUPPLEMENT 1
11 August 2000

DETAIL SPECIFICATION

WIRE, ELECTRICAL, INSULATED,
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-16878G, dated 11 August 2000.

SPECIFICATION SHEETS

MIL-DTL-16878/1	-	Wire, Electrical, Polyvinyl Chloride (PVC) Insulated, 105 °C, 600 Volts (Not For Navy Shipboard Use)
MIL-DTL-16878/2	-	Wire, Electrical, Polyvinyl Chloride (PVC) Insulated, 105 °C, 1000 Volts (Not For Navy Shipboard Use)
MIL-DTL-16878/3	-	Wire, Electrical, Polyvinyl Chloride (PVC) Insulated, 105 °C, 3000 Volts (Not For Navy Shipboard Use)
MIL-DTL-16878/7	-	Wire, Electrical, Silicone Rubber Insulated, 200 °C, 600 Volts
MIL-DTL-16878/8	-	Wire, Electrical, Silicone Rubber Insulated, 200 °C, 1000 Volts
MIL-DTL-16878/10	-	Wire, Electrical, Polyethylene Insulated, 75 °C, 600 Volts
MIL-DTL-16878/14	-	Wire, Electrical, Crosslinked, Modified Polyethylene (XLPE) Insulated, 125 °C, 600 Volts
MIL-DTL-16878/15	-	Wire, Electrical, Crosslinked, Modified Polyethylene (XLPE) Insulated, 125 °C, 1000 Volts
MIL-DTL-16878/16	-	Wire, Electrical, Crosslinked, Modified Polyethylene (XLPE) Insulated, 125 °C, 3000 Volts
MIL-DTL-16878/17	-	Wire, Electrical, Polyvinyl Chloride (PVC) Insulated, Polyamide Jacket, 105 °C, 600 Volts (Not For Navy Shipboard Use)
MIL-DTL-16878/18	-	Wire, Electrical, Polyvinyl Chloride (PVC) Insulated, Polyamide Jacket, 105 °C, 1000 Volts (Not For Navy Shipboard Use)
MIL-DTL-16878/19	-	Wire, Electrical, Polyvinyl Chloride (PVC) Insulated, Polyamide Jacket, 105 °C, 3000 Volts (Not For Navy Shipboard Use)
MIL-DTL-16878/29	-	Wire, Electrical, Silicone Rubber Insulated, 150 °C, 600 Volts
MIL-DTL-16878/30	-	Wire, Electrical, Silicone Rubber Insulated, 150 °C, 1000 Volts
MIL-DTL-16878/31	-	Wire, Electrical, Silicone Rubber Insulated, 150 °C, 1000 Volts, Glass Braid Covering, Abrasion Resistant
MIL-DTL-16878/32	-	Wire, Electrical, Silicone Rubber Insulated, 200 °C, 1000 Volts, Glass Braid Covering, Abrasion Resistant
MIL-DTL-16878/33	-	Wire, Electrical, Polyethylene Insulated, 75 °C, 600 Volts, Polyamide Covering, Abrasion Resistant
MIL-DTL-16878/36	-	Wire, Electrical, Low Smoke, Crosslinked Polyolefin (XLPO) Insulated, 105 °C, 600 Volts

MIL-DTL-16878G
SUPPLEMENT 1

- MIL-DTL-16878/37 - Wire, Electrical, Ethylene-Propylene Diene Elastomer (EPDM) Insulated,
125 °C, 600 Volts, Extruded Insulation
- MIL-DTL-16878/38 - Wire, Electrical, Ethylene-Propylene Diene Elastomer (EPDM) Insulated,
125 °C, 5000 Volts, Extruded Insulation

CONCLUDING MATERIAL

Preparing activity:
DLA - CC

(Project 6145-2193)