

INCH-POUND
------------

MIL-DTL-25427B  
SUPPLEMENT 1  
08 December 2009

## DETAIL SPECIFICATION

### COUPLING ASSEMBLY, HYDRAULIC, SELF-SEALING, QUICK DISCONNECT, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-25427B, dated 15 May 2009.

## SPECIFICATION SHEETS

### 600, 3000 PSI

MS24333	Coupling Assembly, Hydraulic, Self-Sealing, Quick Disconnect, Flared Fitting To Internal Thread Boss
MS24334	Coupling Assembly, Hydraulic, Self-Sealing, Flareless Fitting To Internal Thread Boss
MS24335	Flange, Bulkhead Mounting, Hydraulic, Self-Sealing Coupling

### 1000, 3000, 5000 PSI

MIL-DTL-25427/1	Coupling Assembly, Aircraft Hydraulic, Self-Sealing, Quick Disconnect, Ground Support
MIL-DTL-25427/2	Coupling Half, Aircraft Mounting, Hydraulic, Self-Sealing, Quick Disconnect
MIL-DTL-25427/3	Coupling Half, Hose Attachment, Hydraulic, Self-Sealing, Ground Support, Quick Disconnect, Type I and Type II
MIL-DTL-25427/4	Coupling Cap, Aircraft Hydraulic, Self-Sealing, Ground Support Quick Disconnect
MIL-DTL-25427/5	Coupling Plug, Hose Attachment, Hydraulic, Self-Sealing, Ground Support, Quick Disconnect
MIL-DTL-25427/6	Coupling Nut, Aircraft Hydraulic, Self-Sealing, Ground Support, Quick Disconnect, Type I and Type II
MIL-DTL-25427/7	Coupling Flange, Aircraft Mounting, Hydraulic, Self-Sealing

AMSC N/A

FSC 4730

MIL-DTL-25427B

CONCLUDING MATERIAL

Custodians:

Army-AV  
Navy-AS  
Air Force-99

Preparing activity:

Navy-AS

Review activities:

Army-AT, MI  
Navy-SA  
Air Force-11, 71  
DLA-CC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.daps.dla.mil>.