

INCH-POUND
MIL-DTL-2726C
SUPPLEMENT 1
14 February 2006

DETAIL SPECIFICATION

RECEPTACLES, RECEPTACLE PLUGS, SWITCH AND RECEPTACLES, AND OUTLETS (ELECTRICAL), GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-2726C, dated 14 February 2006.

SPECIFICATION SHEETS

MIL-DTL-2726/1	- Receptacle, Plug, Electrical, 2-Pin, 40-Ampere, 125-Volt, Direct Current (Symbol No. 715.1).
MIL-DTL-2726/2	- Receptacle, Plug, Electrical, 3-Pin Grounded, 50-Ampere, 250-Volt, Direct Current (Symbol No. 716.1).
MIL-DTL-2726/3	- Receptacle, Plug, Electrical, 4-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current, 60-Hertz (Symbol No. 717.1).
MIL-DTL-2726/5	- Receptacle, Plug, Electrical, 3-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current (Symbol No. 1140.1).
MIL-DTL-2726/6	- Receptacle, Plug, Electrical, 3-Pin Grounded, 40-Ampere, 125-Volt, Alternating Current (Symbol No. 1143.1).
MIL-DTL-2726/7	- Receptacle, Electrical, 2-Pin, 40-Ampere, 125-Volt, Direct Current (Symbol Nos. 756.1 and 756.2).
MIL-DTL-2726/8	- Receptacle, Electrical, 3-Pin Grounded, 50-Ampere, 250-Volt, Direct Current (Symbol Nos. 757.1 and 757.2).
MIL-DTL-2726/9	- Receptacle, Electrical, 4-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current (Symbol Nos. 758.1 and 758.2).
MIL-DTL-2726/11	- Receptacle, Electrical, 3-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current (Symbol Nos. 1141.1 and 1141.2).
MIL-DTL-2726/12	- Receptacle, Electrical, 3-Pin Grounded, 40-Ampere, 125-Volt, Alternating Current (Symbol Nos. 1144.1 and 1144.2).
MIL-DTL-2726/13	- Receptacle, Cap Assembly, Electrical (Symbol No. 1142.1).
MIL-DTL-2726/14	- Receptacle, Electrical, Enclosed, 3-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current (Symbol Nos. 1145.1, 1145.2 and 1145.3).
MIL-DTL-2726/15	- Receptacle, Electrical, Enclosed, 3-Pin Grounded, 50-Ampere, 250-Volt, Alternating Current (Symbol Nos. 1146.1, 1146.2 and 1146.3).
MIL-DTL-2726/16	- Receptacle, Electrical, Enclosed, 4-Pin Grounded, 40-Ampere, 450-Volt, Alternating Current (Symbol Nos. 1147.1, 1147.2 and 1147.3).
MIL-DTL-2726/17	- Receptacle, Electrical, Enclosed, 3-Pin Grounded, 40-Ampere, 125-Volt, Alternating Current (Symbol Nos. 1148.1, 1148.2 and 1148.3).
MIL-DTL-2726/18	- Receptacle, Electrical, Triple, 50-Ampere, 250 Volt, Direct Current 3-Pole Grounded (Symbol No. 1105.1).
MIL-DTL-2726/19	- Receptacle witch Switch, Electrical, 30-Ampere, 450-Volt, Alternating Current, 60-Hertz, 3-Phase, Interlocking, Grounded (Symbol No. 915.1).
MIL-DTL-2726/20	- Receptacle witch Switch, Electrical, 30-Ampere, 450-Volt, 1-Phase, Interlocking, Grounded (Symbol No. 916.1).
MIL-DTL-2726/21	- Receptacle witch Switch, Electrical, 30-Ampere, 250-Volt, Direct Current, Interlocking, Grounded (Symbol No. 917.1).

MIL-DTL-2726C SUPPLEMENT 1

- MIL-DTL-2726/22 - Receptacle, Outlet, Electrical, Welding, 200-Ampere, Direct Current, Constant Potential (Symbol No. 770.2).
- MIL-DTL-2726/23 - Receptacle, Electrical, Enclosed, 100-Ampere, 250-Volt, Direct Current, Bulkhead Mounted (Symbol No. 726.1).
- MIL-DTL-2726/24 - Receptacle, Plug, Electrical, Connector, 25-Ampere, 500-Volt, 3-Phase Grounded (Symbol No. 707.1).
- MIL-DTL-2726/25 - Receptacle, Electrical Connector, 25-Ampere, 500-Volt, 3-Phase Grounded (Symbol No. 722.1).
- MIL-DTL-2726/26 - Receptacle, Plug, Electrical, 4-Pin, 60-Ampere, 208/117-Volt, 3-Phase (Symbol No. 728.1).
- MIL-DTL-2726/27 - Receptacle with Switch, Electrical, 60-Ampere, 208/117-Volt, 3-Phase, Interlocking, Grounded (Symbol No. 776.1).
- MIL-DTL-2726/28 - Receptacle, Electrical, 4-role Grounded, 100-Ampere, 450-Volt, 3-Phase (Symbol No. 1221).
- MIL-DTL-2726/29 - Receptacle, Plug, Electrical, 4-Pole Grounded, 100-Ampere, 450-Volt, 3-Phase (Symbol No. 1222).
- MIL-DTL-2726/30 - Receptacle, Plug, Electrical, 10-Ampere, 125-Volt, Single Pole, Male (Symbol No. 727.1-Red; Symbol No. 727.2-Black).
- MIL-DTL-2726/31 - Receptacle, Plug, Electrical, 10-Ampere, 125-Volt, Double Pole, Male (Symbol No. 729.1).
- MIL-DTL-2726/32 - Receptacle, Electrical, 10-Ampere, 125-Volt, Single Pole, Panel Mounted (Symbol No. 775.1-Black; Symbol No. 775.2-Red).
- MIL-DTL-2726/33 - Receptacle, Plug, Electrical, 40-Ampere, 125-Volt, Single Pole, Male (Symbol No. 1214.2-Red; Symbol No. 1214.5-Black).
- MIL-DTL-2726/34 - Receptacle, Plug, Electrical, 40-Ampere, 125-Volt, Single Pole, Female Type (Symbol No. 1214.3-Red; Symbol No. 1214.4-Black).
- MIL-DTL-2726/35 - Receptacle, Electrical, 40-Ampere, 125-Volt, Single Pole, Panel Mounted, Female (Symbol No. 1213.2-Red; Symbol No. 1213.4-Black).
- MIL-DTL-2726/36 - Receptacle, Electrical, 40-Ampere, 125-Volt, Single Pole, Panel Mounted, Male Type (Symbol No. 1213.3-Red; Symbol No. 1213.5-Black).
- MIL-DTL-2726/37 - Receptacle, Electrical, 15-Ampere, 125-Volt, 60-Hertz, Bladed Type, Grounded (Symbol No. 1099.1).
- MIL-DTL-2726/38 - Receptacle, Plug, Electrical, 15-Ampere, 125-Volt, Bladed Type, Grounded (Symbol No. 1218.3).
- MIL-DTL-2726/39 - Receptacle and Switch, Electrical, 15-Ampere, 125-Volt, Bladed Type, Grounded (Symbol No. 919).
- MIL-DTL-2726/40 - Receptacle Channel, Electrical, 15-Ampere, 125-Volt, Bladed Type, Grounded (Symbol No. 730.4).
- MIL-DTL-2726/41 - Receptacle, Electrical, Enclosed, 15-Ampere, 125-Volt (Symbol No. 1098.1).
- MIL-DTL-2726/42 - Receptacle, Electrical, Enclosed, .60-Ampere, 500-Volt, 3-Phase, Grounded (Symbol No. 746.2).
- MIL-DTL-2726/43 - Receptacle, Electrical, (Bladed) 15-Ampere with 3-Ampere Switch, Type DPST, 125-Volt, Grounded, Totally Enclosed (Symbol 918.1).
- MIL-DTL-2726/44 - Receptacle, Portable Triple Outlet, Electrical, 60Ampere, 500-Volt, 3-Phase Grounded (Symbol No. 765.3).
- MIL-DTL-2726/45 - Receptacle, Outlet Switch, Electrical, 100-Ampere, 125-Volt, 60-Ampere, 250-Volt, Interlocking, Grounded (Symbol No.772.1).
- MIL-DTL-2726/46 - Receptacle, Plug, Electrical, 100-Ampere, 250-Volt, Direct Current, 3-Pole (Symbol No. 721.1).
- MIL-DTL-2726/47 - Receptacle, Electrical, Enclosed, 15-Ampere, 125-Volt, 2-Pole, Grounded (Symbol No. 735.3).

MIL-DTL-2726C
SUPPLEMENT 1

- MIL-DTL-2726/48 - Receptacle and Switch, Electrical, Enclosed, 15-Ampere, 125-Volt, Interlocking, Grounded (Symbol No. 900.1).
- MIL-DTL-2726/49 - Receptacle, Outlet, Triple, Electrical, 40-Ampere, 450-Volt, 60-Hertz, Alternating Current, 4-Pole, Portable, Plastic, Grounded (Symbol Nos. 765.6, 765.7 and 765.8).
- MIL-DTL-2726/50 - Receptacle, Plug, Electrical, 15-Ampere, 125/250-Volts, 2-Pole, Grounded (Symbol No. 720.3).
- MIL-DTL-2726/51 - Receptacle, Adapter, Electrical, 15-Ampere, 125-Volt, Alternating Current, Grounded (Symbol No. 2440.2).
- MIL-DTL-2726/52 - Receptacle, Plug, Electrical, 3-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, Single Phase (Symbol No. 1257).
- MIL-DTL-2726/53 - Receptacle, Plug, Electrical, 4-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, 3-Phase (Symbol No. 1258).
- MIL-DTL-2726/54 - Receptacle, Plug, Electrical, 3-Pin Grounded, 10-Ampere, 450-Volt, 400-Hertz, Single Phase (Symbol No. 1259).
- MIL-DTL-2726/55 - Receptacle, Plug, Electrical, 4-Pin Grounded, 10-Ampere, 450-Volt, 400-Hertz, 3-Phase (Symbol No. 1260).
- MIL-DTL-2726/56 - Receptacle, Plug, Electrical, 4-Pole Grounded, 60-Ampere, 450-Volt, 3-Phase (Symbol No. 1261).
- MIL-DTL-2726/57 - Receptacle, Electrical, 3-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, Single Phase (Symbol No. 1262).
- MIL-DTL-2726/58 - Receptacle, Electrical, 4-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, Alternating Current (Symbol No. 1263).
- MIL-DTL-2726/59 - Receptacle, Electrical, 3-Pin Grounded, 10-Ampere, 450-Volt, 400-Hertz, Single Phase (Symbol No. 1264).
- MIL-DTL-2726/60 - Receptacle, Electrical, 4-Pin Grounded, 10-Ampere, 450-Volt, 400-Hertz, 3-Phase (Symbol No. 1265).
- MIL-DTL-2726/61 - Receptacle, Electrical, 4-Pole Grounded, 60-Ampere, 450-Volt, 3-Phase (Symbol No. 1266).
- MIL-DTL-2726/62 - Receptacle, Electrical, Enclosed, 3-Pin Grounded, 10-Ampere, 450 Volt, 60-Hertz, Single Phase (Symbol No. 1267).
- MIL-DTL-2726/63 - Receptacle, Electrical, Enclosed, 4-Pin Grounded, 10-Ampere, 450-Volt, 60-Hertz, Alternating Current (Symbol No. 1268).
- MIL-DTL-2726/64 - Receptacle, Electrical, Enclosed, 3-Pin Grounded, 10-Ampere, 450-Volt, 400-Hertz, Single Phase (Symbol No. 1269).
- MIL-DTL-2726/65 - Receptacle, Electrical, Enclosed, 4-Pin Grounded, 10-Ampere, 450-Volt, 400-Hertz, 3-Phase (Symbol No. 1272).
- MIL-DTL-2726/67 - Receptacle, Electrical, Enclosed, 10-Ampere, 125-Volt, 3-Phase, Grounded (Symbol No. 741.2).
- MIL-DTL-2726/68 - Receptacle, Plug, Connector, Electrical, 10-Ampere, 125-Volt, 3-Phase, Grounded (Symbol No. 706.1).
- MIL-DTL-2726/69 - Receptacle, Outlet, Triple, Electrical, Portable, 15-Ampere, 125-Volt, Alternating Current, Double Pole, Grounded, 25-Foot Cable Extension (Symbol No. 779).
- MIL-DTL-2726/72 - Receptacle Adapter, Electrical, 15-Ampere, 125-Volt, Alternating Current, 60 to 400-Hertz, Grounded (Symbol No. 2439).
- MIL-DTL-2726/73 - Receptacle, Electrical, 15-Ampere, 125-Volt, Bladed Type, Grounded (Portable) (Symbol No. 1215).

MIL-DTL-2726C
SUPPLEMENT 1

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - SH
DLA - CC

Preparing activity
DLA-CC

(Project 5935-2005-120)

Review activities:
Army - AR

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information Above using the ASSIST Online database at <http://assist.daps.dla.mil>.