

INCH-POUND

MIL-DTL-28731E
11 October 2000
SUPERSEDING
MIL-C-28731D
4 June 1985

DETAIL SPECIFICATION

CONNECTORS, ELECTRICAL, RECTANGULAR, REMOVABLE CONTACT, FORMED BLADE, FORK TYPE (FOR RACK AND PANEL AND OTHER APPLICATIONS)

GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers rectangular, electrical connectors with removable formed blade, fork type contacts intended for use in electronic and electrical equipment (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

- | | |
|----------|--|
| QQ-N-290 | - Nickel Plating (Electrodeposited). |
| QQ-P-416 | - Plating, Cadmium (Electrodeposited). |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Supply Center Columbus, P.O. Box 3990 Attn: VAI, Columbus, Ohio, 43216-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5935

MIL-DTL-28731E

DEPARTMENT OF DEFENSE

- MIL-F-14072 - Finishes for Ground Based Electronic Equipment.
- MIL-C-22520/17 - Crimping Tools, Terminal, Hand, Wire Termination For Crimp Type Removable Contacts, Electric Connectors.
- MIL-W-22759/9 - Wire, Electric, Fluoropolymer-Insulated, Extruded TFE, Silver-Coated Copper Conductor, 1000-Volt.
- MIL-M-24519 - Molding plastics, Electrical, Thermoplastic.
- MIL-C-28731/20 - Connector, Electrical, Contact, Fork Type, Crimp Removable (8.5 Amperes).
- MIL-C-28731/25 - Connector, Electrical, Contact, Fork Type, Wire Hole Removable.
- MIL-C-28731/35 - Connector, Electrical, Contact, Fork Type, Crimp Removable (5.0 Amperes).
- MIL-I-81969/4 - Installing and Removal Tools, Connector Electrical Contact, (Fork Type Wrappost/Crimp, Removable Contacts), Electrical Connectors, Type II, Class I, Composition C.
- MIL-I-81969/5 - Installing and Removal Tools, Connector Electrical Contact, (Fork Type Crimp, Removable), Type I, Class 1, Composition A.
- MIL-I-81969/11 - Installing and Removal Tools, Connector Electrical Contacts, (Type CR), Type II, Class 1, Composition C.
- MIL-I-81969/13 - Installing and Removal Tools, Connector Electrical Contact, (Type CR), Type I, Class 1, Composition A.

(See supplement 1 for list of associated specifications).

STANDARDS

FEDERAL

- FED-STD-66 - Steel: Chemical Composition and Hardenability.

DEPARTMENT OF DEFENSE

- MIL-HDBK-454 - General Guidelines for Electronic Equipment.
- MIL-STD-202 - Tests Methods for Electronic and Electrical Component Parts.
- MIL-STD-889 - Dissimilar Metals.
- MIL-STD-1285 - Marking of Electrical and Electronic Parts.
- MIL-STD-1344 - Test Methods for Electrical Connectors.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Other Government documents, drawing, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation. The following documents form a part of this specification to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

- ASTM A 342 - Materials, Feebly Magnetic, Permeability of.
- ASTM A 484 - General Requirements for Stainless and Heat-Resisting Wrought Steel Products (Except Wire).
- ASTM A 582 - Free-Machining Stainless and Heat-Resisting Steel Bars, Hot Rolled or Cold Finished.
- ASTM B85 - Standard Specification for Aluminum Alloy Die Castings.
- ASTM B139 - Standard Specification for Phosphor Bronze Rod, Bar, and Shapes.
- ASTM B488 - Standard Specification of Gold for Engineering Uses.
- ASTM D5948 - Standard Specification for Molding Compounds, Thermosetting.

(Application for copies should be addressed to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

MIL-DTL-28731E

AMS-P-81728 - Plating, Tin Lead (Electrodeposited).

(Application for copies should be addressed to the SAE World Headquarters, 400 Commonwealth Drive, Warrendale, PA 15096-0001)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Specification sheets. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheet. In the event of any conflict between the requirements of this specification and the specification sheet, the latter shall govern. (If a specific requirement specified herein is not required for an item, it shall be so indicated on the specification sheet; for example, "Shock - N/A").

3.2 First article. When specified (see 6.2) connectors and contacts furnished under this specification shall be subjected to first article inspection (see 6.3) in accordance with 4.5.

3.3 Materials. Example reference materials are identified herein. However, when an example reference material is not identified, a material shall be used which will enable the sockets and accessories to meet the performance requirements of this specification. Acceptance or approval of a constituent material shall not be construed as a guaranty of acceptance of the finished product.

3.3.1 Reference materials, plating, and processes. The identified reference material, plating, and processes have been established to provide assurances that connectors manufactured to this specification will properly interface to similar industry standard or government specified connector systems without problems of electrochemical contamination of critical electrical or mechanical interfaces or generation of incompatible mechanical interface surface wear products. The manufacturer of connectors supplied to this specification are allowed to use alternate recognized industry standard materials, plating, and processes from those identified in paragraph 3.3 of this specification. Use of alternates to those referenced guidance items by the supplier must not result in inferior short or long term performance or reliability of supplied connectors as compared with connectors manufactured using the referenced materials, plating, or processes. Short or long term failures or reliability problems due to use of these alternates shall be the responsibility of the supplier.

3.3.2 Recycled, recovered, or environmentally preferable material. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.3.3 Nonmagnetic materials. All parts, with the exception of screws, washers, and mounting hardware, shall be made from materials, which are classified, as nonmagnetic and the permeability of the basic connector shall be less than 2.0. The permeability shall be checked by the instrument described in ASTM A342 or equivalent (see 4.7.2).

3.3.4 Dissimilar metals. When dissimilar metals are used in intimate contact with each other, protection against electrolysis and corrosion shall be provided as specified in MIL-STD-889.

3.3.5.1 Contacts. Contacts shall be made of phosphor bronze in accordance with ASTM B139.

3.3.5.1.1 Plating. Unless otherwise specified, the contacts shall be plated as follows.

3.3.5.1.2 Contact mating area. The contact mating area shall be gold plated in accordance with ASTM B488, type 2, code C, class 1.27 μm (50 microinches minimum) over a nickel underplate in accordance with QQ-N-290, class 2, 50 microinches (1.27 μm) minimum.

3.3.5.1.3 Terminations.

MIL-DTL-28731E

3.3.5.1.3.1 Wrappost terminations. Wrappost terminations shall be gold plated in accordance with ASTM B488, type 2, code C, class 1.27 μm (50 microinches minimum) over a nickel underplate in accordance with QQ-N-290, class 2, 30 microinches (0.76 μm) minimum.

3.3.5.1.3.2 Solder terminations. Solder terminations shall be tin-lead plated in accordance with AMS-P-81728, .00010 inch (0.0025 mm) minimum thickness, over a nickel underplate in accordance with QQ-N-290, class 2, 50 microinches (1.27 μm) minimum.

3.3.5.1.3.3 Crimp terminations. Crimp terminations shall be gold plated, 50 microinches (1.27 μm) minimum over a nickel underplate in accordance with QQ-N-290, class 2, 50 microinches (1.27 μm) minimum.

3.3.5.1.3.4 Remaining areas of the contact. Those areas of the contact not included in 3.3.1.1.1 and 3.3.1.1.2 shall be nickel plated in accordance with QQ-N-290, class 2 with a minimum thickness of 50 microinches (1.27 μm). Overplating is not required in this area.

3.3.5.1.3.5 Contacts furnished in strip form. If contacts are furnished in strip form, when the contact is separated from the carrier strip, the absence of the nickel or other plating at the broken edge of the contact is acceptable, provided it is in a nonfunctional area of the contact and any corrosion formed as a result of the salt spray test does not creep into the contact mating area.

3.3.6 Connector shields and clamps. Shields and clamps shall be die-cast aluminum or corrosion-resistant steel. Die-cast aluminum, if used, shall conform to composition number 13, A13, A380, or 360 or ASTM B85, and workmanship in accordance with ASTM B85. Sheet metal shall conform to FED-STD-66. All shields and clamps (except nylon strap) shall be plated in accordance with finish no. M225 of MIL-F-14072.

3.3.7 Engaging hardware. All stress bearing hardware shall be type 303 or 416 corrosion-resistant steel in accordance with ASTM A 484 and ASTM A 582. All hardware shall be passivated in accordance with finish no. E300 of MIL-F-14072. Actuating hardware shall be dry film lubricated.

3.3.8 Other hardware. Nonstress bearing hardware shall be type 303 or 416 corrosion resisting steel in accordance with ASTM A 484 and ASTM A 582, or noncorrosion resisting metal parts which shall be plated with cadmium in accordance with QQ-P-416, class 3, type II. All finishes shall be conductive unless otherwise specified (see 3.1).

3.3.9 Insert material. Unless otherwise specified (see 3.1), insert material shall be a diallyl phthalate in accordance with ASTM D5948, type SDG-F, GDI-30F, or polyester thermoplastic conforming to MIL-M-24519, (reground material shall not be used).

3.3.10 Dissimilar metals. When dissimilar metals are employed in intimate contact with each other, protection against electrolytic corrosion should be provided as specified in requirement 16 of MIL-HDBK-454.

3.4 Design, construction, and physical dimensions.

3.4.1 Connectors. Connectors shall be of the design, construction, and physical dimensions specified (see 3.1). The temperature range shall be from -65°C to $+125^{\circ}\text{C}$. The connector shall permit individual insertion and removal of the contacts with the insertion and removal tools in accordance with 3.4.2.3. Wire conductors shall be attached to the applicable contacts by crimping, soldering, or wrapping as specified herein (see 3.1).

3.4.1.1 Insert design. Inserts shall be on one-piece construction and shall be such that they will not crack, chip, or break in normal service or assembly. Split or hollow inserts glued or bonded together shall not be used. The insert dimensions and contact hole shall be as specified on the individual specification sheet. The contact hole configuration for the contacts shall conform to the dimensions (see 3.1). Contacts when assembled in the male or female plug shall be recessed a minimum of .020 inch (0.51 mm) below the outer protective flange. Contacts when assembled in the female or male receptacle shall be recessed a minimum of .020 inch (0.51 mm) below the face of the plastic insert.

3.4.2 Contacts. Contact configuration shall be as specified (see 3.1).

3.4.2.1 Contact design. Contact design shall provide for crimp, solder, or wrappost termination's and be designed so

MIL-DTL-28731E


that they will not be damaged by mating or unmating with the connectors. The contact, for use in both the plug and the receptacle, shall be of the formed blade, fork type. Mating contacts shall be 90° to each other when assembled and provide for positive spring contact wiping action. Each contact shall contain a means of firmly locking itself when installed in the insert. The locking feature shall be such that insertion and removal of the contact may be accomplished using tools as specified in 3.4.2.3.

3.4.2.2 Crimping tool. The crimping tool shall be in accordance with MIL-C-22520/17.

3.4.2.3 Insertion and removal tools. Insertion and removal tools shall be used to assemble and disassemble contacts. These tools shall be in accordance with MIL-I-81969/11, MIL-I-81969/13, MIL-I-81969/4 and MIL-I-81969/5.

3.4.2.4 Wire inspection. Subsequent to crimping of the wire to the contact, visual inspection shall be made to ascertain that the wire fully engages the wire crimp tabs.

3.4.2.5 Wrappost geometry. Wrappost geometry shall be in accordance with figures 1 and 2.



Minimum wrappable length, -E, inches. 1/


Number Of wrapped Connections	Wire Gage						
	30 (mm)	28 (mm)	26 (mm)	24 (mm)	22 (mm)	20 (mm)	18 (mm)
1	.185 (4.70)	.219 (5.56)	.226 (5.74)	.258 (6.55)	.303 (7.69)	.327 (8.31)	.391 (9.93)
2	.320 (8.13)	.388 (9.85)	.402 (10.21)	.466 (11.83)	.556 (14.12)	.604 (15.34)	.732 (18.59)
3	.455 (11.56)	.557 (14.15)	.578 (14.68)	.674 (14.43)	.809 (20.55)	.881 (22.37)	1.073 (27.25)

1/ Minimum wrappable length shall have the wrappost geometry in accordance with figure 2.

FIGURE 1. Wrappable Length.

3.4.2.6 Parallelism. See figure 2 and associated table.

MIL-DTL-28731E



Wrappost geometry.

A (mm)	B (mm)	B (mm)	Parallelism (mm)	Straightness inch/inch (mm)
.025 (0.63) nominal .022 (0.56) Min	.025 (0.63) nominal .022 (0.56) Min	.0355 (0.902) Max .0325 (0.825) Min	.002 (0.05)	.005 (0.13)
.045 (1.14) nominal .042 (1.07) Min	.045 (1.14) nominal .042 (1.07) Min	.066 (1.68) Max .059 (1.50) Min	.005 (0.13)	.005 (0.13)
.030 (0.76) nominal .027 (0.69) Min	.060 (1.52) nominal .057 (1.45) Min	.070 (1.78) Max .063 (1.60) Min	.005 (0.13)	.005 (0.13)

FIGURE 2. Wrappost geometry.

3.4.3 Polarization. Polarization of the plug with its receptacle shall be accomplished by mechanical means such as the protective shell, bosses, guide pins, guide sockets, or jackscrews (see 3.1).

3.4.4 Mating. Unless otherwise specified (see 3.1), connector plugs and receptacles shall be capable of being mated and unmated by hand without the aid of special tools, within the temperature range.

3.4.5 Mounting accessories. Guide pins, guide sockets, shields, and other hardware shall be as specified (see 3.1).

3.4.6 Actuating hardware design. To aid in the engagement of connectors, actuating hardware shall be used as required. This hardware shall be categorized as follows and be denoted by their associated type.

3.4.6.1 Type C jackscrew. Rotatable actuating member with a male thread (engages with a type F fixed socket). The actuating knob includes a screwdriver slot.

3.4.6.2 Type D jacksocket. Rotatable actuating member with a female thread (engages with a type E fixed screw).

3.4.6.3 Type E fixed screw. Fixed actuating member with a male thread (engages with a type D or H jacksocket).

3.4.6.4 Type F fixed socket. Fixed actuating member with a female thread (engages with a type C or G jackscrew).

3.4.6.5 Type G jackscrew. Rotatable actuating member with a male thread (engages with a type F fixed socket). Actuating knob is for hand tightening only.

3.4.6.6 Type H jacksocket. Rotatable actuating member with a female thread (engages with type E fixed screw). Actuating knob includes a screwdriver slot.

MIL-DTL-28731E

3.5 Interchangeability. All contacts shall be capable of being assembled in the molded insulators (see 3.1) and be completely interchangeable with each other with respect to installation (physical) and performance (function) as specified herein. All complete connectors including their complement of contacts, having the same Part or Identifying Number (PIN) shall be completely interchangeable with each other with respect to installation (physical) and performance (function) as specified herein. Tools shall be capable of properly inserting and removing the contacts from the molded inserts. Evidence, such as dimensional data, may be required by the Government in order to assure that contacts, complete connector assemblies, and tools, will be interchangeable and meet the requirements of this specification.

3.5.1 Plugs and receptacles. Plugs and receptacles of a given size and design, manufactured by one source to the requirements of this specification, shall be capable of mating with associated plugs and receptacles manufactured to the requirements of this specification by other sources. The connector assemblies having the same PIN shall be directly and completely interchangeable with respect to installation and performance.

3.5.2 Loose crimp contacts. Removable contacts are to be included with the connector. For connectors supplied with loose crimp contacts, the quantity of crimp contacts to be supplied with each connector shall consist of a full complement of contacts plus one spare contact for connectors using 26 contacts of each size used shall be supplied.

3.6 Performance. Connectors shall be designed to meet the performance requirements specified herein.

3.6.1 Insulation resistance. When tested as specified in 4.7.2, the resistance shall be not less than 5,000 megohms, except after humidity exposure the resistance shall be not less than 1,000 megohms.

3.6.2 Temperature cycling. When tested as specified in 4.7.3, the connectors shall not show evidence of physical damage.

3.6.3 Dielectric withstanding voltage. When tested as specified in 4.7.4, the connectors shall withstand 1,500 volts without flashover.

3.6.4 Contact retention. When tested as specified in 4.7.5, individual contacts shall withstand an axial load of 10 pounds (4.54 kilograms) without damage to the contact, insert or contact retaining clip.

3.6.5 Vibration. When the complete connector assembly, wired with the appropriate size wire, is tested as specified in 4.7.6 (10G, 10 to 500 Hz), there shall be no cracking, breaking, or loosening of parts. There shall be no loss of electrical continuity with any of the contact circuits for more than 1 microsecond with 100 milliamperes flowing in each circuit.

3.6.6 Mechanical shock. When tested as specified in 4.7.7, there shall be no evidence of failure of metallic or dielectric materials, nor shall the mated portions of the connector become disengaged. For connectors exposed to the high impact shock test, there shall be no loss of electrical continuity for more than 20 milliseconds to any of the contact circuits, or 1 microsecond for connectors tested for compliance to the specified pulse shock test.

3.6.7 Mating and unmating forces (connector assembly). When tested as specified in 4.7.8, the force and torque required to either engage or separate any pair of mated connectors (plug and receptacle) shall not exceed the maximum force and torque specified (see 3.1).

3.6.8 Humidity. When tested as specified in 4.7.9, the connectors shall meet the following requirements:

- a. Insulation resistance - Shall not be less than 1,000 megohms.
- b. Dielectric withstanding voltage - 50 percent of specified voltage (see 3.8).

3.6.9 Durability. When tested as specified in 4.7.10, the connector assembly shall withstand the test without evidence of electrical or mechanical damage that impairs the normal operation of the connector.

3.6.10 Salt spray (corrosion). When tested as specified in 4.7.11, there shall not be sufficient corrosion on the connectors to interfere with mating or unmating, or cause exposure of base metal on contact sets when inspected under 10 power magnification. Following the test, the contacts only shall meet the following requirement:

- a. Low level circuits - Shall not exceed the potential drop values specified in 3.6.15.

MIL-DTL-28731E

3.6.10.1 Contacts supplied in reels. When contacts are separated from the carrier strip, base metal may be exposed. Following the salt spray test, any corrosion that may occur in the region of the separation, shall not interfere with the ability of the contacts to meet the subsequent test requirements, either for contacts tested separately, or as part of the connector, including the ability to mate or unmate the connectors.

3.6.11 Contact resistance. When tested as specified in 4.7.12, the contact resistance of each mated pair of contacts shall not exceed the potential drop requirements in table I.

TABLE I. Contact resistance.

Wire size AWG	Test current (amperes)	Maximum potential Drop (mV)	Contact resistance (maximum) (mW)
18	8.5	51.0	6.0
20	7.5	45.0	6.0
22	5.0	40.0	8.0
24	3.0	26.0	8.7
26	2.0	24.0	12.0
28	1.5	22.0	14.7
30	1.0	20.0	20.0

3.6.12 Crimp tensile strength (crimp contact) (when specified, see 3.1). When tested as specified in 4.7.13, the contact to wire crimp shall not break or pull out at less than the minimum tensile strength specified in table II.

TABLE II. Crimp tensile strength.

Wire size AWG (7 or 19 strand)	Minimum tensile strength pounds
18	40.0
20	25.0
22	15.0
24	10.0
26	5.0
28	3.0
30	1.5

3.6.13 Crimp tensile strength (adapter to crimp contact). When tested as specified in 4.7.13.1, the adapter to contact crimp shall not break or pull out at less than the minimum tensile strength specified (see 3.1).

3.6.14 Contact separating forces (contacts). When contacts are tested as specified in 4.7.14, unless otherwise specified (see 3.1), the forces required to disengage the contacts shall be 12 ounces per contact.

3.6.15 Low level circuit resistance (contacts). When tested as specified in 4.7.15, the values of contact resistance shall not exceed the potential drop in table III.

TABLE III. Low level circuit.

Wire size AWG	Contact resistance (maximum) <u>1</u> /	Maximum potential drop (mV)
------------------	--	--------------------------------

MIL-DTL-28731E

	(mw)	
18	7	7.0
20	9	9.0
22	15	15.0
24	20	20.0
26	25	25.0
28	40	40.0
30	50	50.0

1/ Test current shall be milliamperes.

3.6.16 Resistance to soldering heat. Connectors shall withstand the tests specified in 4.7.16.

3.7 Marking.

3.7.1 Connectors. Each connector shall be legibly and permanently marked, die cast, or stamped in accordance with MIL-STD-1285. The marking shall be placed on a side of the connector parallel to the long dimension. Wherever possible, the marking information shall be located such that it is not obscured by the subsequent addition of a connector shield.

3.7.2 Contact positions. Letters shall be arranged to avoid confusion between contacts. All letters or numerals shall appear on the front and rear face of each insert. Lettering of the plug insert shall correspond with that of the mating receptacle insert.

3.8 Workmanship. The workmanship shall be in accordance with the requirements contained herein. Connectors shall meet the design and dimensional requirements of this specification. There shall be no evidence of poor molding or fabricating, damaged or improperly assembled contacts, peeling or chipping of the plating or finish, nicks and burrs of metal parts surfaces. The contacts shall be free from burrs or sharp corners, which would damage the plating of mating connectors.

4. VERIFICATION

4.1.1 Test equipment and inspection facilities. Test and measuring equipment and inspection facilities of sufficient accuracy, quality and quantity to permit performance of the required inspection shall be established and maintained by the contractor.

4.2 Classification of inspection. The inspections requirements specified herein are classified as follows:

- a. First article inspection (see 4.3).
- b. Quality conformance inspection (see 4.6).

4.3 First article inspection. First article inspection shall consist of materials inspection, all the tests in table IV (connectors), or table V (contacts) as applicable to the contact or purchase order, and examinations of this specification.

MIL-DTL-28731E

TABLE IV. First article inspection - Connectors.

Inspection	Requirement paragraph	Test method paragraph	Conditions
Visual and mechanical inspection	3.1, 3.3, 3.4, through 3.4.5, 3.5, 3.20, and 3.2	4.7.1	All connectors
Permeability	3.3.3	---	All connectors
Insulation resistance	3.6.1	4.7.2	Unmated
Temperature cycling	3.6.2	4.7.3	Mated
Dielectric withstanding voltage	3.6.3	4.7.4	Unmated
Contact retention	3.6.4	4.7.5	Unmated
Vibration	3.6.5	4.7.6	Unmated
Mechanical shock	3.6.6	4.7.7	Mated
Mating and unmating forces	3.6.7	4.7.8	Mated or unmated
Humidity	3.6.8	4.7.9	Unmated
Durability	3.6.9	4.7.10	Mated or unmated
Salt spray	3.6.10	4.7.11	Mated
Contact resistance	3.6.11	4.7.12	Mated
Resistance to soldering heat <u>1/</u>	3.6.16	4.7.16	Unmated

1/ For solder type termination's only.

TABLE V. First article inspection - contact test sequence.

Inspection	Requirement paragraph	Test method paragraph	Contact sample numbers									
			21-40 no. 26 or no. 30 AWG	1-20 no. 18 or no. 22 AWG	41-60 no. 18 or no. 22 AWG	61-80 no. 20 or no. 24 AWG	81-100 no. 22 or no. 26 AWG	101-120 no. 24 or no. 28 AWG	121-140 no. 26 or no. 30 AWG	141-150 no. 18 or no. 22 AWG	151-160 no. 26 or no. 30 AWG	1 - 20 unplated
<u>Group I (180 contacts)</u> Visual and mechanical inspection	3.1, 3.4 through 3.4.5, 3.20, and 3.21	4.7.1	X	X	X	X	X	X	X	X	X	X
<u>Group II (20 sets)</u> Salt spray (corrosion) Contact resistance Low level circuit resistance Visual and mechanical inspection	3.6.10 3.6.11 3.15 3.7	4.7.11 4.7.12 4.7.15 4.7.1		X X X							X	X
<u>Group III (50 sets)</u> Contact separating forces (plated contacts) Crimp tensile strength ^{1/} Crimp tensile strength ^{1/}	3.6.14 3.6.12 3.6.13	4.7.14 4.7.13 4.7.13.1			X X	X X	X X	X X	X X	X X		
<u>Group IV (20 contacts)</u> Contact separating forces (unplated)	3.6.14	4.7.14										X

^{1/} Not applicable to solder type contacts.

NOTE: Wire size 18 through 26 AWG are used with contacts having a wire range of 18 to 26 AWG and wire sizes 22 through 30 AWG are used with contacts having a wire range of 22 to 30 AWG.

MIL-DTL-28731E

4.3.1 Materials inspection. Materials inspection shall consist of certification supported by verifying data that the materials and finishes listed in paragraphs in 3.3.6, 3.3.7, 3.3.8, and 3.3.9, are used in fabricating the connectors, and shall be in accordance with the applicable referenced specifications or requirements prior to such fabrication.

4.4 Inspection conditions. Unless otherwise specified herein, all inspections shall be performed in accordance with the test conditions specified in the "GENERAL REQUIREMENTS" of MIL-STD-1344 and MIL-STD-202.

4.5 First Article inspection. First article inspection shall be performed at a laboratory acceptable to the Government (see 6.3).

4.5.1 Sample size and inspection routine.

4.5.1.1 Connectors - single part (first article inspection). Six each completely assembled plug or receptacle (2 of each type minimum) complete with guide pins, jackscrews, and with the insulator arrangement in accordance with specification sheet (see 3.1), shall be submitted for first article inspection. Mating plugs and receptacles shall be furnished. Contacts shall be installed in the insulator (see 4.5.2). The samples shall then be subjected to the inspection specified in table IV.

4.5.1.2 Connectors - group (first article testing). When submitting a group of connectors for first article inspection, samples from the applicable specification sheet, having the largest number of contacts, shall approve connectors listed on the other specification sheets having lesser contacts that are of the same design, construction, and materials. Completely assembled connectors (plugs and receptacles) with the maximum number of contacts and accessories to obtain an assembly with the maximum possible weight shall be subjected to the inspections specified in table IV. For connectors of the same family but with a smaller number of contacts, two plugs and receptacles for each connector with a smaller number of contacts shall be subjected to the inspections specified in table III. These samples shall be alternately equipped with available accessories (shields, clamps, jackscrews, etc.) so that each available feature is tested.

4.5.1.3 Contacts. One hundred and sixty (80 sets) plated and 20 unplated contacts shall be subjected to the inspection of table V groups I through IV, respectively, in the order shown.

4.5.2 Sample preparation.

4.5.2.1 Connectors. Connectors having crimp or solder type contacts shall be wired using number 22 AWG wire conforming to MIL-W-22759/9-22-*, for standard size contacts (MIL-C-28731/20 and /25) and 26 AWG wire conforming to MIL-W-22759/9-26-* for mini size contacts (MIL-C-28731/35).

4.5.2.2 Contacts - crimp type. Contacts shall be crimped with a tool conforming to MIL-C-22520/17 (see 3.4.2.2) to wire conforming to MIL-W-22759. The wire size shall conform to 4.5.2.1.

4.5.2.3 Contacts - solder type. Contacts shall be wired to wire conforming to MIL-W-22759. The wire size shall conform to 4.5.2.1.

4.5.2.4 Contacts - wrappost. Preparation not applicable see 3.4.2.5.

4.6 Quality conformance inspection.

4.6.1 Inspection of product for delivery. Inspection of product for delivery shall consist of table V (connectors), and table II (contacts).

4.6.1.1 Inspection lot. An inspection lot shall consist of all the connectors and associated fittings of the same PIN, produced under essentially the same conditions, and offered for inspection at one time.

4.7 Methods of inspection.

4.7.1 Visual and mechanical inspection. Connectors and associated fittings shall be inspected to verify that the design, construction, physical dimensions, interchangeability, marking, and workmanship are in accordance with the applicable requirements (see 3.1, 3.4 through 3.4.5 inclusive, 3.20 and 3.21).

MIL-DTL-28731E

4.7.2 Insulation resistance (see 3.6.1). The insulation resistance shall be measured between closest adjacent contacts and hardware in accordance with method 3003 of MIL-STD-1344. Any number of contacts may be tested simultaneously. The measurements shall be made with the contacts inserted into the molded insert. The test potential tolerance shall be 2 percent and the electrification time shall not exceed 1 minute.

4.7.3 Temperature cycling (see 3.6.2). Complete mated connectors shall be subjected to temperature cycling in accordance with method 1003, MIL-STD-1344. The temperature shall be -55°C to 125°C .

4.7.4 Dielectric withstanding voltage (see 3.6.3). The unmated connectors shall be tested in accordance with method 3001 of MIL-STD-1344. The connectors shall show no evidence of flashover when the specified voltage (see 3.1) is applied. The voltage shall be applied between contacts and hardware as connected for insulation resistance (see 4.7.2).

4.7.5 Contact retention (see 3.6.4). Connectors shall be tested in accordance with method 2007 of MIL-STD-1344. Axial loads shall be applied to individual contacts in unmated connectors in the normal removal direction. The load shall be applied uniformly at a rate of 1 pound per second. After 5 insertions and withdrawals from the same contact hole, the contacts shall withstand the specified axial load.

4.7.6 Vibration (see 3.6.5). Complete mated connectors shall be vibrated in accordance with test condition II, method 2005 of MIL-STD-1344. All contacts shall be wired in series with the appropriate size wire and connected to a suitable testing circuit. The mated connectors shall be held together only by the normal locking device. Strain relief shall be provided by the use of junction shells when applicable. Wires shall be supported on a stationary frame not closer than 12 inches from the connectors.

4.7.7 Mechanical shock (see 3.6.6). Either high impact shock or specified pulse shock testing shall be performed as applicable.

4.7.7.1 High-impact shock. Complete mated connectors shall be tested in accordance with method 207 of MIL-STD-202. All contacts shall be wired in series with the appropriate size wire and 100 milliamperes $+10/-0$, current flowing through the test contacts. The mated connectors shall be held together only by the normal locking device. Strain relief shall be provided by the use of junction shells where applicable. Wires shall be supported on a stationary frame not closer than 12 inches from the connectors.

4.7.7.2 Specified pulse shock. Complete mated connectors shall be tested in accordance with method 2004.1, test condition G, of MIL-STD-1344. All contacts shall be wired in series with appropriate size wire and 100 milliamperes $+10/-0$ of current maximum flowing through the test contacts. Wires shall be supported on a stationary frame not closer than 12 inches from the connectors. The mated connectors shall be held together only by the normal locking device. Strain relief shall be provided by the use of junction shells, where applicable. There shall be 18 shocks, 3 in each direction in each of the three perpendicular planes.

4.7.8 Mating and unmating forces (connector assembly) (see 3.6.7). Connectors shall be tested in accordance with method 2013 of MIL-STD-1344. Each connector with shields removed, if applicable, and a full complement of contact shall be mated and unmated. The insertion and withdrawal force and torque, applied gradually, shall be measured after 3 cycles.

4.7.9 Humidity (see 3.6.8). Unmated plugs and receptacles shall be tested in accordance with type II, method 1002 of MIL-STD-1344; however, steps 7A and 7B are not required. No measurements are required after initial conditioning, nor voltage applied to connectors during exposure. After completion of step 6 of the final cycle, the connectors shall be removed from the chamber. Excess moisture shall be shaken off surfaces. No mechanical wiping or forced drying shall be used. After the test, the following measurements shall be taken:

- a. Insulation resistance - Shall not be taken sooner than one-half and not later than 3 hours after removal from the chamber. If a measurement taken early in the specified time period results in a failure, the measurement may be taken once during the time period specified.
- b. Dielectric withstanding voltage - See 4.7.4.

MIL-DTL-28731E

4.7.10 Durability (see 3.6.9). The complete connector assemblies shall be subjected to 200 cycles of insertion and withdrawal at a rate not to exceed 100 cycles per hour. Tests shall be conducted using normal engaging hardware. The insertion and withdrawals shall be accomplished similar to that which the connectors shall be subjected to in service. After 200 cycles, the plug and receptacle assemblies shall be inspected.

4.7.11 Salt spray (corrosion) (see 3.6.10). The mated plugs and receptacles, along with 20 pairs of contacts, mounted in accordance with figure 1, shall be tested in accordance with method 1001, condition B of MIL-STD-1344. Immediately after exposure, the connectors shall be unmated and the exterior surfaces of the connectors and of the individual pairs of contacts shall be washed and dried for 12 hours maximum in a circulating air oven at a temperature of $38^{\circ}\text{C} \pm 3^{\circ}\text{C}$ ($100^{\circ}\text{F} \pm 5^{\circ}\text{F}$). After drying, the connectors shall be mated.

4.7.12 Contact resistance (see 3.6.11). Connectors shall be tested in accordance with method 3004 of MIL-STD-1344. The potential drop across each mated pair of contacts shall be measured at rated current as designated in table I. Potential drop readings shall be taken across the two points as shown on figure 2. For adapter to crimp contacts, figure 3 shall be used.

4.7.13 Crimp tensile strength (crimp contact) (see 3.6.12). The test shall be performed in accordance with method 2003 of MIL-STD-1344. Samples for test shall be placed in a standard tensile testing machine and the load applied at an approximate rate of 1 inch (25.4 mm) per minute to pull the wire out of the sample or break the wire sample (see table V).

4.7.13.1 Crimp tensile strength (adapter to crimp contact) (see 3.6.13). Provisions shall be made for mounting contacts in a suitable position of applying gradually increased loads during separation of the adapter and contact. Samples for test shall be placed in a standard tensile testing machine and the load applied at an approximate rate of 1 inch (25.4 mm) per minute to pull the adapter out of the contact.

4.7.14 Contact separating forces (contacts) (see 3.6.14). Provisions shall be made for mounting contacts in a suitable position of applying gradually increased loads during separation of the contact. The depth of the engagement shall be equal to the maximum length of the contact for the mating connector.

4.7.14.1 Contact separating forces (unplated contacts) (see 3.1). Separating forces of contacts when measured with the gauge shown on figure 4 shall be as specified.

4.7.14.2 Contact separating forces (plated contacts) (see 3.1). Separating forces of contacts when mated to each other shall be as specified.

4.7.15 Low level circuit resistance (contacts) (see 3.6.15). The low level circuit test shall be performed in accordance with method 3002 of MIL-STD-1344. For adapter to crimp contacts, figure 5 shall be used.

4.7.16 Resistance to soldering heat (see 3.6.16). All connectors with solder terminations shall be tested in accordance with MIL-STD-202, method 208 the following details shall apply:

- a. The applicable wire size properly prepared shall be inserted into the contact termination. A minimum of seven contacts shall be tested.
- b. An appropriately prepared resistance soldering iron with an appropriate tip shall be applied to the lower portion of the terminal configuration where the wire enters the termination.
- c. The solder shall be applied in the normal manner.
- d. The resistance soldering iron shall be applied to the system. The wattage shall be adjusted as to allow a proper solder fillet to be formed, or for a 4 second minimum time limit, whichever is more.
- e. After application, the soldering iron shall be removed and a visual and mechanical inspection performed.
- f. Visual inspection shall be a 1X, magnification. The connector shall show no evidence of distortion or damage to any area of the connector housing. The contact shall meet the contact retention requirements (4.7.5). The contact shall not interface with normal floating conditions as applicable and shall meet applicable location dimensions.

MIL-DTL-28731E

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirement shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Connectors and contacts covered by this specification are intended for use in airborne, ground support, and shipboard electrical and electronic equipment.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

- a. Title, number, and date of this specification.
- b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).
- c. Packaging requirements (see 5.1).
- d. Title, number, and date of the applicable specification sheet and the complete PIN (see 3.1).
- e. Level of preservation, packaging, packing and marking required (see section 5).
- f. Quantity of units per package, if other than one.

6.2.2 Removable contacts. Removable contacts are available for separate acquisition through specification sheets of this document (see 3.1).

6.3 First article. When first article inspection is required, the contracting officer should provide the specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a standard production item from the contractor's current inventory (see 4.5), and the number of items to be tested as specified in 4.5.1.1 or 4.5.1.3 as applicable. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval, of first article test results, and disposition of first articles. Invitations for bids should provide that the government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Definitions. For purposes of this specification, the following definitions shall apply:

6.4.1 Connector assembly. A complete connector assembly consists of a mated plug and receptacle.

6.4.2 Receptacle. A connector receptacle is that portion of the connector assembly which is normally "fixed", that is rigidly attached to a supporting surface.

6.4.3 Plug. A connector plug is that portion of the connector assembly, which is normally "removable".

MIL-DTL-28731E

6.5 Patent notice. Patent No. 3,248,686 owned by Elco Corporation. The Government has a royalty-free license under the above patent for the benefit of manufacturers of the items called for in this specification, either for the Government or for use in equipment to be delivered to the Government.

6.6 Copyright notice. Any portions of this specification and related documents, which may be covered by copyrights owned by Elco Corporation, are reprinted with the express permission of said copyright owner.

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.





FIGURE 1. Salt spray-contacts.

MIL-DTL-28731E



(NOT TO SCALE)




FIGURE 2. Contact resistance.




FIGURE 3. Contact crimp resistance.

MIL-DTL-28731E




FIGURE 4. Gauge tip, test fixture, contact separation for.




FIGURE 5. Low level circuit resistance.

MIL-DTL-28731E

6.8 Environmentally preferable material. Environmentally preferable materials should be used to the maximum extent possible that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. Table VI lists the Environmental Protection Agency (EPA) top seventeen hazardous materials targeted for major usage reduction. If any of these hazardous materials are required, it is recommended that it be used only when other materials cannot meet performance requirements.

TABLE VI. EPA top seventeen hazardous materials.

Benzene	Dichloromethane	Tetrachloroethylene
Cadmium and compounds	Lead and compounds	Toluene
Carbon Tetrachloride	Mercury and compounds	1,1,1 - Trichloroethane
Chloroform	Methyl Ethyl compounds	Trichloroethylene
Chromium and compounds	Methyl Isobutyl Ketone	Xylenes
Cyanide and compounds	Nickel and compounds	

6.9 Subject term (keyword listing).

Cadmium
 Contacts
 Crimp
 Current
 Dielectric
 Finish
 Heat
 Humidity
 Inspection
 Insulation displacement
 Lead
 Magnetic permeability
 Materials
 Mating force
 Nickel
 Sampling
 Socket
 Solderability

CONCLUDING MATERIAL

Custodians:
 Army - CR
 Navy - EC
 Air Force - 11
 DLA - CC

Preparing activity:
 DLA-CC
 (Project - 5935-3488)

Review activities:
 Army - AR, AT, MI
 Navy - AS, OS, SH
 Air Force - 11, 99

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-DTL-28731E	2. DOCUMENT DATE (YYYYMMDD) 20001011
3. DOCUMENT TITLE CONNECTORS, ELECTRICAL, RECTANGULAR, REMOVABLE CONTACT, FORMED BLADE, FORK TYPE (FOR RACK AND PANEL AND OTHER APPLICATIONS)		
4. NATURE OF CHANGE (<i>Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.</i>)		
5. REASON FOR RECOMMENDATION		
6. SUBMITTER		
a. NAME (<i>Last, First, Middle Initial</i>)		b. ORGANIZATION
c. ADDRESS (<i>Include zip code</i>)	d. TELEPHONE (<i>Include Area Code</i>) (1) Commercial (2) DSN (<i>if applicable</i>)	7. DATE SUBMITTED (YYYYMMDD)
8. PREPARING ACTIVITY		
a. NAME Defense Logistics Agency Defense Supply Center, Columbus		b. TELEPHONE (<i>Include Area Code</i>) (1) Commercial 614-692-0538 (2) DSN 850-0538
c. ADDRESS (<i>Include Zip Code</i>) DSCC-VAI P.O. Box 3990 Columbus, Ohio 43216-5000		IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6621 Telephone (703) 767-6888 DSN 427-6888