

INCH-POUND

MIL-DTL-38159C  
SUPPLEMENT 1  
27 January 2004

## DETAIL SPECIFICATION

CONNECTORS, ELECTRIC, RAMP POWER, 480/277 VOLTS,  
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-38159C, dated 27 January 2004

## SPECIFICATION SHEETS

MS27265	-	Connector, Plug, Electrical – Ramp Power, 416/277 Volts, Male
MS27266	-	Insert, Electrical Connector – Ramp Power, 416/240 Volts, Male
MS27267	-	Shell, Electrical Connector – Ramp Power, 416/240 Volts
MS27271	-	Grommet, Rubber – Plug Connector, Ramp Power, 416/240 Volts
MS27272	-	Cap-Plug, Protective Dust & Moisture Seal – Plug Connector, Ramp Power, 416/240 Volts
MS27282	-	Insert, Electrical Connector – Ramp Power, 416/240 Volts, Female
MS27283	-	Contact, Electrical-Plug Connector, Ramp Power, 416/240 Volts, Large, Female
MS27285	-	Connector, Plug, Electrical – Ramp Power, 416/277 Volts, Female
MS27567	-	Dummy Connector, Electrical, Male
MS27568	-	Dummy Connector, Electrical, Female

## CONCLUDING MATERIAL

Custodians:  
Air Force - 11  
DLA - CCPreparing activity:  
DLA - CC

(Project 5935-4602-000)

Review activity:  
Air Force - 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <http://www.dodssp.daps.mil>.