INCH-POUND

MIL-DTL-3922E SUPPLEMENT 1 18 April 2016

DETAIL SPECIFICATION

FLANGES, WAVEGUIDE, GENERAL PURPOSE, GENERAL SPECIFICATION FOR

This supplement forms a part of Detail Specification MIL-DTL-3922E, dated 18 April 2016.

SPECIFICATION SHEETS

MIL-DTL-3922/52	-	Flanges, Waveguide (Pressurizable Contact).
MIL-DTL-3922/53	-	Flanges, Waveguide (Cover) (Square 4 Hole) (Circular Back).
MIL-DTL-3922/54	-	Flanges, Waveguide (Cover) (Square, 4 Hole). (Inactive for new design)
MIL-DTL-3922/55	-	Flanges, Waveguide (Cover) (Round, 6 Hole). (Inactive for new design)
MIL-DTL-3922/56	-	Flanges, Waveguide (Cover) (Round, 8 Hole).
MIL-DTL-3933/57	-	Flanges, Waveguide (Cover) (Round, 8 Hole (2 Holes Centered Horizontally, 2 Holes Centered Vertically). (Inactive for new design)
MIL-F-3922/58	-	Flanges, Waveguide (Contact) (Rectangular, 10 Hole). (Inactive for new design)
MIL-DTL-3922/59	-	Flanges, Waveguide (Choke) (Square, 4 Hole).
MIL-DTL-3922/60	-	Flanges, Waveguide (Choke) (Round, 6 Hole). (Inactive for new design)
MIL-DTL-3922/61	-	Flanges, Waveguide (Choke) (Round, 8 Hole).
MIL-DTL-3922/62	-	Flanges, Waveguide (Choke) (Round, 8 Hole (2 Holes Centered Horizontally, 2 Holes Centered Vertically)).
MIL-DTL-3922/67	-	Flanges, Waveguide (Contact) (Round, 4 Hole) (Millimeter).
MIL-DTL-3922/68	-	Flanges, Waveguide Cover (Butt Mount) (Square, 4 Hole).
MIL-DTL-3922/70	-	Flanges, Waveguide (Cover) (Square, 4 Hole, Butt Mount). (Inactive for new design)
MIL-DTL-3922/75	-	Flanges, Waveguide, Reduced Height. (Inactive for new design)

AMSC N/A

FSC 5985



MIL-DTL-3922E SUPPLEMENT 1

Custodians: Army - CR Navy - EC Air Force - 85 DLA - CC Preparing activity: DLA - CC

(Project 5985-2016-012)

Review activities: Army - AR, AV, MI Navy - AS, MC, OS Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <u>https://assist.dla.mil/</u>.