

INCH-POUND

MIL-DTL-3933K  
SUPPLEMENT 1  
12 April 2011

## DETAIL SPECIFICATION

ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL  
GENERAL SPECIFICATION FOR

This supplement forms a part of Detail Specification MIL-DTL-3933K, dated 12 April 2011

## SPECIFICATION SHEETS

MIL-DTL-3933/10	-	ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL, COAXIAL LINE (SERIES N), FREQUENCY RANGE: DC TO 18 GHZ, CLASS III, MEDIUM POWER
MIL-DTL-3933/14	-	ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL, COAXIAL LINE (SMA CONNECTORS), FREQUENCY RANGE: DC TO 12.4 GHZ, CLASS IV, LOW POWER
MIL-DTL-3933/16	-	ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL COAXIAL LINE (SMA CONNECTORS), FREQUENCY RANGE: DC TO 18 GHZ, CLASS IV, LOW POWER
MIL-DTL-3933/17	-	ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL, COAXIAL LINE (TNC CONNECTORS), FREQUENCY RANGE: DC TO 18 GHZ, CLASS IV, LOW POWER
MIL-DTL-3933/18	-	ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL, COAXIAL LINE (SERIES N), FREQUENCY RANGE: DC TO 12.4 GHZ AND DC TO 18 GHZ, CLASS III, LOW POWER
MIL-DTL-3933/19	-	ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL, COAXIAL LINE (BNC CONNECTORS), FREQUENCY RANGE: DC TO 4.5 GHZ, CLASS III, LOW POWER
MIL-A-3933/23	-	ATTENUATORS, FIXED, TO-5 CONFIGURATION, CLASS IV, LOW POWER INACTIVE FOR NEW DESIGN
MIL-A-3933/24	-	ATTENUATOR, FIXED, COAXIAL LINE, (SMA CONNECTORS), BULKHEAD, CLASS IV, LOW POWER INACTIVE FOR NEW DESIGN
MIL-DTL-3933/25	-	ATTENUATORS, FIXED, MINIATURE, SPACE LEVEL, NON SPACE LEVEL, COAXIAL LINE (SMA CONNECTORS), FREQUENCY RANGE: DC TO 18 GHZ, CLASS IV, LOW POWER
MIL-DTL-3933/29	-	ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL, CHIP, (SURFACE MOUNT), 0-20 DB, FREQUENCY RANGE: DC TO 18 GHZ, CLASS IV
MIL-DTL-3933/30	-	ATTENUATORS, FIXED COAXIAL CONNECTOR SPACE LEVEL, NON SPACE LEVEL, TYPE 2.92 MM (SMK) FREQUENCY RANGE: DC TO 32 GHZ, CLASS III, LOW POWER

MIL-DTL-3933K  
SUPPLEMENT 1

- |                 |   |   |
|-----------------|---|---|
| MIL-DTL-3933/31 | - | ATTENUATORS, FIXED COAXIAL CONNECTOR,<br>SPACE LEVEL, NON SPACE LEVEL, CONNECTOR TYPE 3.5 MM<br>FREQUENCY RANGE: DC TO 28 GHZ, CLASS III, LOW POWER |
| MIL-DTL-3933/32 | - | ATTENUATORS, FIXED COAXIAL CONNECTOR,<br>SPACE LEVEL, NON SPACE LEVEL, TYPE 2.92 MM (SMK)<br>FREQUENCY RANGE: DC TO 42 GHZ, CLASS III, LOW POWER    |

Custodians:  
Army - CR  
Navy - EC  
Air Force - 85  
NASA - NA  
DLA - CC

Preparing activity:  
DLA - CC

Project (5985-2011-023)

Review activities:  
Army - MI  
Navy - AS, MC, SH  
Air Force - 71, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.daps.dla.mil>.