

MIL-DTL-3965G
AMENDMENT 1
28 October 2002

DETAIL SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM GENERAL
SPECIFICATION FOR

This amendment forms a part of MIL-DTL-3965G, dated 9 June 2000, and is approved for use by
all Departments and Agencies of the Department of Defense.

PAGE 4

Replace "(See supplement 1 list of associated specification sheets)." With the following.

"MIL-DTL-3965/1 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug) -
85°C (Voltage Derated to 125°C) Styles CL14 and CL16.

MIL-DTL-3965/19 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug) -
85°C (Voltage Derated to 125°C) Styles CL17 and CL18.

MIL-DTL-3965/20 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug) -
85°C (Voltage Derated to 125°C) Styles CL10 and CL13.

MIL-DTL-3965/21 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug) -
85°C (Voltage Derated to 125°C) Style CL55.

MIL-DTL-3965/24 - Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum (Polarized, Sintered Slug) -
85°C (Voltage Derated to 125°C) Styles CL66 and CL67."

PAGE 18

Paragraph 4.6.2.1 change the last sentence to read: Group C inspection shall be made on sample units which have
passed group A inspection, except that units which are to be subjected to tests of subgroup 5 shall be units which
have successfully passed subgroup 3 of table VIII (see 4.6.1.3.3).

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2200)

Review activities:
Navy - AS, MC, OS
Air Force - 19