

INCH - POUND
MIL-DTL-55302G
SUPPLEMENT 1
18 August 2011

DETAIL SPECIFICATION

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES

This supplement forms a part of MIL-DTL-55302G, dated 9 November 2009.

SPECIFICATION SHEETS 1/

| | |
|------------------|---|
| MIL-DTL-55302/1 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Right-Angle, for Printed Wiring Boards (.150 Spacing) |
| MIL-DTL-55302/2 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Straight-Thru, for Printed Wiring Boards (.150 Spacing) |
| MIL-DTL-55302/4 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Right-Angle, for Multilayered Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/5 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Straight-Thru, for Multilayered Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/6 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Straight-Thru, for Multilayered Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/7 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Right-Angle, for Multilayered Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/8 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Straight-Thru, for Multilayered Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/16 | Connectors, Printed Circuit Subassembly and Accessories: Pin, Right-Angle, for Printed Wiring Boards (.200 Spacing) |
| MIL-DTL-55302/17 | Connectors, Printed Circuit Subassembly and Accessories: Socket, Straight-Thru, for Printed Wiring Boards (.200 Spacing) |
| MIL-DTL-55302/18 | Connectors, Printed Circuit Subassembly and Accessories: Pin, Straight-Thru, for Printed Wiring Boards (.200 Spacing) |
| MIL-DTL-55302/19 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts Right-Angle, 41 Composite Contact, for Printed Wiring Boards (.150 Spacing) |
| MIL-DTL-55302/20 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contact, Straight-Thru, for Printed Wiring Boards (.150 Spacing) |
| MIL-DTL-55302/21 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contact, Right-Angle, 92 Composite Contact, for Multilayered Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/22 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Straight-Thru, for Multilayered Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/23 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Decade Increment 10 Thru 120, 150, 160 and 180 Contact Positions, for Printed Wiring Boards (.075 Spacing) |
| MIL-DTL-55302/24 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Decade Increment 10 Thru 110, Contact Positions, for Printed Wiring Boards (.075 Spacing) |
| MIL-DTL-55302/25 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, 120, 150, 160, and 180 Contact Positions, for Printed Wiring Boards (.075 Spacing) |
| MIL-DTL-55302/26 | Connectors, Printed Circuit Subassembly and Accessories: Plug, 30 Thru 140 Contact Positions, for Printed Wiring Boards (.100 Sq. Grid) |

MIL-DTL-55302G
SUPPLEMENT 1

| | |
|------------------|---|
| MIL-DTL-55302/27 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, 30 Thru 140 Contact Positions, for Printed Wiring Boards (.100 Sq. Grid) |
| MIL-DTL-55302/29 | Connectors, Printed Circuit Subassembly and Accessories: Gauge for Contact Separation Force Test Method |
| MIL-DTL-55302/30 | Connectors, Printed Circuit Subassembly and Accessories: Test Probe Fixture for Resistance to Test Probe Damage |
| MIL-DTL-55302/31 | Connectors, Printed Circuit Subassembly and Accessories: Keying Accessories |
| MIL-DTL-55302/32 | Connectors, Printed Circuit Subassembly and Accessories: Contacts, Solder |
| MIL-DTL-55302/38 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Electrical, Polarized Shell, Male, .100 Inch Contact Spacing Pin Terminal (Inactive) |
| MIL-DTL-55302/42 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Electrical, Polarized Shell, Female, .100 Inch Contact Spacing, Removable Crimp Contacts (Inactive) |
| MIL-DTL-55302/52 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Straight-Thru, Hermaphroditic Contact for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/53 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right-Angle, Hermaphroditic Contact for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/54 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Straight-Thru, Hermaphroditic Contact for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/55 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Socket Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/56 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Pin Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/57 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/58 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/59 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 90, 100 and 120 Contact Positions for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/60 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 90, 100 and 120 Contact Positions (.100 Spacing) |
| MIL-DTL-55302/61 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, and 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/62 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |

MIL-DTL-55302G
SUPPLEMENT 1

| | |
|------------------|---|
| MIL-DTL-55302/63 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/64 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/65 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/66 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Decade Increments 10 Thru 70 Contact Positions and Intermediate Positions of 14, 24, 44, 54 and 26, 36, 56, 66 for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/67 | Connectors, Printed Circuit Subassembly and Accessories: Pin, Right Angle Plug, Electrical, Polarized for Printed Wiring Boards (.090 Spacing) (Inactive) |
| MIL-DTL-55302/68 | Connectors, Printed Circuit Subassembly and Accessories: Socket, Receptacle, Electrical, Polarized (.090 Spacing) Removable Crimp Contacts (Inactive) |
| MIL-DTL-55302/69 | Connectors, Printed Circuit Subassembly and Accessories: Pin Plug, Electrical, Polarized (.090 Spacing) Removable Crimp Contacts (Inactive) |
| MIL-DTL-55302/70 | Connectors, Printed Circuit Subassembly and Accessories, Pin, Right Angle Plug, Electrical, Polarized for Printed Wiring Boards (.100 Spacing) (Inactive) |
| MIL-DTL-55302/71 | Connectors, Printed Circuit Subassembly and Accessories, Socket Receptacle, Electrical, Polarized Composite Contact (.100 Spacing) (Inactive) |
| MIL-DTL-55302/72 | Connectors, Printed Circuit Subassembly and Accessories: Socket Environmental Resistant, Receptacle, Electrical, Polarized (.150 Spacing), Removable Crimp Contacts (Inactive) |
| MIL-DTL-55302/73 | Connectors, Printed Circuit Subassembly and Accessories, Pin, Right Angle, Environmental Resistant, Plug, Electrical, Polarized for Printed Wiring Boards (.150 Spacing) (Inactive) |
| MIL-DTL-55302/74 | Connectors, Printed Circuit Subassembly and Accessories, Pin, Right Angle, Plug, Electrical, Polarized for Printed Wiring Boards (.100 Spacing) (Inactive) |
| MIL-DTL-55302/75 | Connectors, Printed Circuit Subassembly and Accessories: Socket Receptacle, Electrical, Polarized (.100 Spacing), Removable Crimp Contacts (Inactive) |
| MIL-DTL-55302/76 | Connectors, Printed Circuit Subassembly and Accessories, Socket Straight-Thru, Polarized for Multilayered Printed Wiring Boards (.100 Spacing) (Inactive) |
| MIL-DTL-55302/77 | Connectors, Printed Circuit Subassembly and Accessories, Pin, Right Angle, for Multilayered Printed Wiring Boards (.100 Spacing) (Inactive) |
| MIL-DTL-55302/78 | Connectors, Printed Circuit Subassembly and Accessories: Key, Polarizing, Connectors, Electrical Printed Wiring Boards (Inactive) |
| MIL-DTL-55302/82 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, 41, 66, 114 Contact Positions: for Printed Wiring Boards (.100 X .050 Offset Grid) (Inactive) |
| MIL-DTL-55302/83 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 41, 66, 114 Contact Positions: for Printed Wiring Boards (.100 X .050 Offset Grid) (Inactive) |
| MIL-DTL-55302/84 | Connectors, Printed Circuit Subassembly and Accessories: Contacts Crimp, Dip Solder Tail, Solder Turret, and Wirewrap (Inactive) |

MIL-DTL-55302G
SUPPLEMENT 1

| | |
|-------------------|--|
| MIL-DTL-55302/89 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, Hermaphroditic Contacts (.100 Spacing) |
| MIL-DTL-55302/90 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Right Angle, Hermaphroditic Contact (.100 Inch Spacing) |
| MIL-DTL-55302/91 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Straight-Thru, Hermaphroditic Contacts (.100 Inch Spacing) |
| MIL-DTL-55302/92 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Straight-Thru, Hermaphroditic Contacts (.100 Inch Spacing) |
| MIL-DTL-55302/93 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Insert (Insulator), Rectangular, Polarized, Removable Crimp Type, Hermaphroditic Contacts (.100 Inch Spacing) |
| MIL-DTL-55302/94 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Insert (Insulator), Rectangular, Polarized, Removable, Crimp Type Hermaphroditic Contacts (.100 Inch Spacing) |
| MIL-DTL-55302/95 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Composite Wrappost, Hermaphroditic Contacts (.100 Inch Spacing) |
| MIL-DTL-55302/96 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Wrappost (Removable) Hermaphroditic Contacts (.100 Inch Spacing) |
| MIL-DTL-55302/97 | Connectors, Printed Circuit Subassembly and Accessories: Contacts, Hermaphroditic, Crimp Removable for Wire (Stranded) |
| MIL-DTL-55302/98 | Connectors, Printed Circuit Subassembly and Accessories: Contact, Wrappost Removable Type |
| MIL-DTL-55302/99 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Straight Thru, Hermaphroditic Contact, Wrappost Removable, for Printed Wiring Boards (.100 Inch Spacing) (Inactive) |
| MIL-DTL-55302/102 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Straight-Thru, Hermaphroditic Contact, Crimp Removable, for Printed Wiring Boards (.100 Inch Spacing) (Inactive) |
| MIL-DTL-55302/110 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, 30 Thru 140 Contact Positions, For Printed Wiring Boards (.100 Sq. Grid) |
| MIL-DTL-55302/111 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, Straight-Thru, for Multilayered Printed Wiring Boards, (.100 Spacing) |
| MIL-DTL-55302/113 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Straight-Thru, 30 Thru 140 Contact Positions, Crimp Removable Contacts (.100 Sq. Grid) |
| MIL-DTL-55302/117 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, Decade Increment 20 Through 110 and 128 Contact Positions, for Printed Wiring Boards (.050 Spacing) |
| MIL-DTL-55302/118 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Decade Increment 20 Through 110 and 128 Contact Positions, for Printed Wiring Boards (.050 Spacing) |
| MIL-DTL-55302/119 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Decade Increment 20 Through 110 and 128 Contact Positions, for Printed Wiring Boards (.050 Spacing) |
| MIL-DTL-55302/120 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 128 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing) |
| MIL-DTL-55302/121 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contact, 128 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing) |
| MIL-DTL-55302/122 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 184 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing) |

MIL-DTL-55302G
SUPPLEMENT 1

| | |
|-------------------|---|
| MIL-DTL-55302/123 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contact, 184 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing) |
| MIL-DTL-55302/124 | Connectors, Printed Circuit Subassembly and Accessories: Keying Accessories |
| MIL-DTL-55302/125 | Connectors, Printed Circuit Subassembly and Accessories: Plug, 80 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing) |
| MIL-DTL-55302/126 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, 80 Contact Positions, for Printed Wiring Boards (.050 Inch Spacing) |
| MIL-DTL-55302/127 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Single Row, 2 Through 65 Contact Positions, for Printed Wiring Boards (.062 , .093 , .125) (.100 Spacing) |
| MIL-DTL-55302/128 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Double Row, 4 Through 130 Contact Positions, for Printed Wiring Boards (.062 , .093 , .125) (.100 Spacing) |
| MIL-C-55302/129 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, 90 Through 240 Contact Positions, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/130 | Connectors, Printed Circuit Subassembly and Accessories: Receptacles, 90 Through 240 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/131 | Connectors, Plug, Electrical, Printed Circuit Subassembly and Accessories: Right Angle, Pin Contacts, 64 or 96 Contact Position for Printed Wiring Boards (.100 Spacing) |
| MIL-C-55302/132 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle Socket Contacts, Straight Thru, 64 or 96 Contact Positions, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/133 | Connectors, Plug, Electrical, Printed Circuit Subassembly and Accessories: Right Angle, Pin Contacts, 32 or 64 Contact Position for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/134 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle Socket Contacts, Straight Thru 32 or 64 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/138 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin, 160 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/139 | Connectors, Printed Circuit Subassembly and Accessories: Receptacles, 160 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/140 | Connectors, Printed Circuit Subassembly and Accessories: Plug with Pin Contacts, 2 Keying Pins, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/141 | Connectors, Printed Circuit Subassembly and Accessories, Plug with Pin Contacts, 3 Keying Pins, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/142 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle With Socket Contacts, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/143 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle with Socket Contacts, 3 Keying Guides, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/144 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle With Pin Contacts, 2 Female Keying Guides, 1.516 Inches Length, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/145 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle With Pin Contacts, 2 Female Keying Guides, 2.114 Inches Length, for Printed Wiring Boards (.100 Inch Spacing) |

MIL-DTL-55302G
SUPPLEMENT 1

| | |
|-------------------|--|
| MIL-DTL-55302/146 | Connectors, Printed Circuit Subassembly and Receptacle With Pin Contacts, 2 Female Keying Guides, 2.717 Inches Length, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/147 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle With Pin Contacts, 2 Female Keying Guides, 3.315 Inches Length, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/148 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle With Pin Contacts, 2 Female Keying Guides, 3.917 Inches Length, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/149 | Connectors, Printed Circuit Subassembly and Accessories: Plug with Socket Contacts, 1.516 Inches Length, 2 Keying Pins, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/150 | Connectors, Printed Circuit Subassembly and Accessories: Plug with Socket Contacts, 2.114 Inches Length, 2 Keying Pins, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/151 | Connectors, Printed Circuit Subassembly and Accessories: Plug with Socket Contacts, 2.717 Inches Length, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/152 | Connectors, Printed Circuit Subassembly and Accessories: Plug with Socket Contacts, 3.315 Inches Length, 2 Keying Pins, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/153 | Connectors, Printed Circuit Subassembly and Accessories: Plug with Socket Contacts, 3.917 Inches Length, 2 Keying Pins, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/154 | Connectors, Printed Circuit Subassembly and Accessories, Mounting Hardware for Printed Wiring Boards |
| MIL-DTL-55302/155 | Connectors, Printed Circuit Subassembly and Accessories, Hood for Printed Wiring Boards |
| MIL-DTL-55302/156 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Right Angle, Decade Increments 10 Through 120, 150, 160 and 180 Contact Positions, for Printed Wiring Boards (.075 Spacing) |
| MIL-DTL-55302/157 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Straight Thru Contacts, 64 or 96 Contact Positions, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/158 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle Socket Contacts, 64 or 96 Contact Positions, for Printed Wiring Boards (.100 Inch Spacing) |
| MIL-DTL-55302/159 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle, 17, 29, 33, 41, 53, and 65 Contact Positions, for Printed Wiring Boards, 2.54 mm X 1.27 mm Offset Grid, Metric |
| MIL-DTL-55302/160 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle, 72, 84, 96, and 120 Contact Positions, for Printed Wiring Boards, 2.54 mm X 1.27 mm Offset Grid, Metric |
| MIL-DTL-55302/161 | Connectors, Printed Circuit Subassembly and Accessories, Receptacle, 160 Contact Positions, for Printed Wiring Boards, 2.54 mm X 1.27 mm Offset Grid, Metric |
| MIL-DTL-55302/162 | Connectors, Printed Circuit Subassembly and Accessories, Plug, 17, 29, 33, 41, 53, and 65 Contact Positions, for Printed Wiring Boards, 2.54 mm X 1.27 mm Offset Grid, Metric |
| MIL-DTL-55302/163 | Connectors, Printed Circuit Subassembly and Accessories, Plug, 72, 84, 96, and 120 Contact Positions, for Printed Wiring Boards, 2.54 mm X 1.27 mm Offset Grid, Metric |

MIL-DTL-55302G
SUPPLEMENT 1

| | |
|-------------------|---|
| MIL-DTL-55302/164 | Connectors, Printed Circuit Subassembly and Accessories, Plug and/or Receptacle, 160 Contact Positions, for Printed Wiring Boards, 2.54 mm X 1.27 mm Offset Grid, Metric |
| MIL-DTL-55302/166 | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Male Brush, Straight-Through, Polarized, for Multilayered Printing Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/167 | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Male Brush, Straight-Through, Polarized, with Wrappost Termination (.100 Spacing) |
| MIL-DTL-55302/168 | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Male Brush, Right Angle, Polarized, for Multilayered Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/169 | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Female Brush, Straight-Through, Polarized, (.100 Spacing) |
| MIL-DTL-55302/170 | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Female Brush, Right Angle, Polarized, for Multilayered Printed Wiring Board (.100 Spacing) |
| MIL-DTL-55302/171 | Connectors, Printed Circuit Subassembly and Accessories: Low Mating Force, Contact Brush |
| MIL-C-55302/172 | Connectors, Printed Circuit Subassembly and Accessories: Hardware, Coupling and Locking |
| MIL-DTL-55302/173 | Connectors, Printed Circuit Subassembly and Accessories: 2 Row, Pin Assemblies, 20 Through 150 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/174 | Connectors, Printed Circuit Subassembly and Accessories: 2 Row, Receptacle Assemblies, Right Angel, 20 Through 150 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/175 | Connectors, Printed Circuit Subassembly and Accessories: 2 Row, Pin Assemblies, Right Angle, 20 Through 150 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/176 | Connectors, Printed Circuit Subassembly and Accessories: 3 Row, Pin Assemblies, 75 Through 405 Contact Positions, For Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/177 | Connectors, Printed Circuit Subassembly and Accessories: 3 Row, Receptacle Assemblies, Right Angle, 75 Through 405 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/178 | Connectors, Printed Circuit Subassembly and Accessories: 3 Row, Pin Assemblies, Right Angle, 75 Through 405 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/179 | Connectors, Printed Circuit Subassembly and Accessories: 4 Row, Pin Assemblies, 100 Through 684 Contact Positions, for Printed Wiring Boards(.100 Spacing) |
| MIL-DTL-55302/180 | Connectors, Printed Circuit Subassembly and Accessories: 4 Row, Receptacle Assemblies, Right Angle, 100 Through 684 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/181 | Connectors, Printed Circuit Subassembly and Accessories: 4 Row, Pin Assemblies, Right Angle, 100 Through 684 Contact Positions, for Printed Wiring Boards (.100 Spacing) |
| MIL-DTL-55302/182 | Connectors, Printed Circuit Subassembly and Accessories: Guide Pins, Jackscrews and Mounting Ears |

MIL-DTL-55302G
SUPPLEMENT 1

| | |
|-------------------|--|
| MIL-DTL-55302/190 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, 100 Positions, Printed Wiring Boards (.075 Spacing) |
| MIL-DTL-55302/191 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 100 Positions, Printed Wiring Board (.075 Inch Spacing) |
| MIL-DTL-55302/192 | Connectors, Printed Circuit Subassembly and Accessories: Receptacle, Socket Contacts, 122 and 152 Positions, Printed Wiring Board (.075 Spacing) |
| MIL-DTL-55302/193 | Connectors, Printed Circuit Subassembly and Accessories: Plug, Pin Contacts, 122 and 152 Position, Printed Wiring Board (.075 Spacing) |

1/ See table I, selection chart, for further details on each specification sheet.

TABLE I. Selection chart.

| Specification sheet number | Status | Contact Spacing | Min Contacts | Maximum contacts | Contacts row | Contact force 1/ | Contact termination 1/ | Configuration 1/ | Plug or receptacle 1/ | Keying available 1/ | QPL 1/ |
|----------------------------|--------|-----------------|--------------|------------------|--------------|------------------|------------------------|------------------|-----------------------|---------------------|--------|
| MIL-DTL-55302/1 | A | 0.150 | 7 | 28 | 2 | NA | PC | ST | P | N | Y |
| MIL-DTL-55302/2 | A | 0.150 | 7 | 77 | 2 | --- | PC | ST | R | N | Y |
| MIL-DTL-55302/4 | A | 0.100 | 9 | 77 | 2 | NA | PC | RT | P | N | Y |
| MIL-DTL-55302/5 | A | 0.100 | 9 | 77 | 2 | NA | PC | ST | P | N | Y |
| MIL-DTL-55302/6 | A | 0.100 | 9 | 77 | 2 | --- | PC | ST | R | N | Y |
| MIL-DTL-55302/7 | A | 0.100 | 13 | 61 | 3 | NA | PC | RT | P | N | Y |
| MIL-DTL-55302/8 | A | 0.100 | 13 | 61 | 3 | --- | PC | ST | R | N | Y |
| MIL-DTL-55302/16 | A | 0.200 | 7 | 37 | 2 | NA | PC | RT | P | N | Y |
| MIL-DTL-55302/17 | A | 0.200 | 7 | 37 | 2 | --- | PC | ST | R | N | Y |
| MIL-DTL-55302/18 | A | 0.200 | 7 | 37 | 2 | NA | PC | ST | P | N | Y |
| MIL-DTL-55302/19 | A | 0.150 | 41 | 41 | 2 | NA | PC | RT | P | N | N |
| MIL-DTL-55302/20 | A | 0.150 | 41 | 41 | 2 | --- | PC | ST | R | N | N |
| MIL-DTL-55302/21 | A | 0.100 | 92 | 92 | 3 | NA | PC | RT | P | N | Y |
| MIL-DTL-55302/22 | A | 0.100 | 92 | 92 | 3 | --- | PC | ST | R | N | Y |
| MIL-DTL-55302/23 | A | 0.075 | 10 | 180 | 2 | NA | SS | ED | P | Y | Y |
| MIL-DTL-55302/24 | A | 0.075 | 10 | 110 | 2 | L | PC, SS | ED, ST | R | Y | Y |
| MIL-DTL-55302/25 | A | 0.075 | 120 | 180 | 2 | L | PC, SS | ED, ST | R | Y | Y |
| MIL-DTL-55302/26 | A | 0.100 | 30 | 110 | 2 | NA | SS | ED, ST | P | Y | Y |
| MIL-DTL-55302/27 | A | 1.000 | 30 | 110 | 2 | L | PC, SS, WW | ED, ST | R | Y | Y |
| MIL-DTL-55302/29 | A | NA | NA | NA | NA | | | | | NA | N |
| MIL-DTL-55302/30 | A | NA | NA | NA | NA | | | | | NA | N |
| MIL-DTL-55302/31 | A | NA | NA | NA | NA | | | | | NA | Y |
| MIL-DTL-55302/32 | A | NA | NA | NA | NA | | SW, WW | | | NA | Y |
| MIL-DTL-55302/38 | I | 0.100 | 11 | 35 | 2 | NA | PC | RT | P | N | N |
| MIL-DTL-55302/42 | I | 0.100 | 11 | 35 | 2 | --- | CR | ST | R | N | N |
| MIL-DTL-55302/52 | A | 0.100 | 18 | 72 | 2 | HE | PC | ST | R | Y | N |
| MIL-DTL-55302/53 | A | 0.100 | 18 | 72 | 2 | HE | PC | RT | P | Y | N |
| MIL-DTL-55302/54 | A | 0.100 | 18 | 72 | 2 | HE | PC | ST | P | Y | N |
| MIL-DTL-55302/55 | A | 0.100 | 10 | 70 | 2 | L, --- | PC, SW | ST | P-SC | N | Y |
| MIL-DTL-55302/56 | A | 0.100 | 10 | 70 | 2 | NA | PC, SW, WW | ST | R-PC | N | Y |
| MIL-DTL-55302/57 | A | 0.100 | 10 | 70 | 2 | NA | PC | RT | P-PC | Y | Y |
| MIL-DTL-55302/58 | A | 0.100 | 10 | 70 | 2 | L, --- | PC, SW, WW | ST | R-SC | Y | Y |
| MIL-DTL-55302/59 | A | 0.100 | 90 | 120 | 2 | NA | PC | RT | P-PC | Y | Y |
| MIL-DTL-55302/60 | A | 0.100 | 90 | 120 | 2 | L, --- | PC, SW, WW | ST | R-SC | Y | Y |
| MIL-DTL-55302/61 | A | 0.100 | 10 | 70 | 2 | NA | PC | RT | P-PC | N | Y |
| MIL-DTL-55302/62 | A | 0.100 | 10 | 70 | 2 | L, --- | PC, SW | ST | R-SC | N | Y |
| MIL-DTL-55302/63 | A | 0.100 | 10 | 70 | 2 | NA | PC, SW | ST | P-PC | Y | Y |
| MIL-DTL-55302/64 | A | 0.100 | 10 | 70 | 2 | L, --- | PC, SW, WW | ST | R-SC | Y | Y |
| MIL-DTL-55302/65 | A | 0.100 | 10 | 70 | 2 | L, --- | CR | ST | R-SC | Y | Y |
| MIL-DTL-55302/66 | A | 0.100 | 30 | 70 | 2 | L, --- | CR | ST | R-SC | N | Y |

See note at end of table.

MIL-DTL-55302G
SUPPLEMENT 1

TABLE I. Selection chart - Continued.

| Specification sheet number | Status | Contact Spacing | Min Contacts | Maximum contacts | Contacts row | Contact force 1/ | Contact termination 1/ | Configuration 1/ | Plug or receptacle 1/ | Keying available 1/ | QPL 1/ |
|----------------------------|--------|-----------------|--------------|------------------|--------------|------------------|------------------------|------------------|-----------------------|---------------------|--------|
| MIL-DTL-55302/67 | I | 0.100 | 30 | 49 | 3 | NA | PC | RT | P | N | Y |
| MIL-DTL-55302/68 | I | 0.100 | 30 | 49 | 3 | --- | CR | ST | R | N | Y |
| MIL-DTL-55302/69 | I | 0.100 | 61 | 49 | 3 | NA | CR | ST | P | N | Y |
| MIL-DTL-55302/70 | I | 0.100 | 61 | 61 | 3 | NA | PC | RT | P | N | Y |
| MIL-DTL-55302/71 | I | 0.100 | 40 | 61 | 3 | --- | CR, PC, WW | ST | R | N | Y |
| MIL-DTL-55302/72 | I | 0.150 | 40 | 76 | 3 | --- | CR | ST | R | Y | Y |
| MIL-DTL-55302/73 | I | 0.150 | 39 | 76 | 3 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/74 | I | 0.100 | 39 | 59 | 2 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/75 | I | 0.100 | 58 | 59 | 2 | --- | CR | ST | R | Y | Y |
| MIL-DTL-55302/76 | I | 0.100 | 58 | 87 | 2, 3 | --- | PC | ST | R | Y | Y |
| MIL-DTL-55302/77 | I | 0.100 | 58 | 87 | 2, 3 | NA | PC | ST | P | Y | Y |
| MIL-DTL-55302/78 | A | NA | NA | NA | NA | NA | | | | Y | Y |
| MIL-DTL-55302/82 | I | 0.100 | 41 | 114 | 2 | --- | CR, PC, WW | ST | R | N | N |
| MIL-DTL-55302/83 | I | 0.100 | 41 | 114 | 2 | NA | PC, WW | RT | P | N | N |
| MIL-DTL-55302/84 | I | NA | NA | NA | NA | --- | CR, SW, WW | | | NA | N |
| MIL-DTL-55302/89 | A | 0.100 | 24 | 96 | 2 | HE | PC | RT | P | Y | N |
| MIL-DTL-55302/90 | A | 0.100 | 24 | 96 | 2 | HE | PC | RT | R | Y | N |
| MIL-DTL-55302/91 | A | 0.100 | 24 | 96 | 2 | HE | PC, SS, WW | ST | P | Y | N |
| MIL-DTL-55302/92 | A | 0.100 | 24 | 96 | 2 | HE | PC, SS | ST | R | Y | N |
| MIL-DTL-55302/93 | A | 0.100 | 24 | 96 | 2 | HE | CR | ST | P | Y | N |
| MIL-DTL-55302/94 | A | 0.100 | 24 | 96 | 2 | HE | CR | ST | R | Y | N |
| MIL-DTL-55302/95 | A | 0.100 | 24 | 96 | 2 | HE | WW | ST | P | Y | N |
| MIL-DTL-55302/96 | A | 0.100 | 24 | 96 | 2 | HE | WW | ST | R | Y | N |
| MIL-DTL-55302/97 | A | NA | NA | NA | NA | HE | CR | | | NA | N |
| MIL-DTL-55302/98 | A | NA | NA | NA | NA | | WW | | | NA | N |
| MIL-DTL-55302/99 | I | 0.100 | 18 | 72 | 2 | HE | WW | ST | R | N | N |
| MIL-DTL-55302/102 | I | 0.100 | 18 | 72 | 2 | HE | CR | ST | R | N | N |
| MIL-DTL-55302/110 | A | 0.100 | 30 | 140 | 3 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/111 | A | 0.100 | 13 | 61 | 3 | --- | PC | ST | R | N | N |
| MIL-DTL-55302/113 | A | 0.100 | 30 | 140 | 2 | NA | PC | ST | P | N | Y |
| MIL-DTL-55302/117 | A | 0.050 | 20 | 128 | 2 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/118 | A | 0.050 | 20 | 128 | 2 | NA | SS | ST | P | Y | Y |
| MIL-DTL-55302/119 | A | 0.050 | 20 | 128 | 2 | --- | PC | ST | R | Y | Y |
| MIL-DTL-55302/120 | A | 0.050 | 128 | 128 | 2 | NA | WW | ST | P | Y | Y |
| MIL-DTL-55302/121 | A | 0.050 | 128 | 128 | 2 | --- | PC,SS | ED, ST | R | Y | Y |
| MIL-DTL-55302/122 | A | 0.050 | 184 | 184 | 2 | NA | WW | ST | P | Y | Y |
| MIL-DTL-55302/123 | A | 0.050 | 184 | 184 | 2 | --- | SS | ED, ST | R | Y | Y |
| MIL-DTL-55302/124 | A | NA | NA | NA | NA | | | | | NA | Y |
| MIL-DTL-55302/125 | A | 0.050 | 80 | 80 | 2, 4 | NA | PC | ST | P | Y | Y |
| MIL-DTL-55302/126 | A | 0.050 | 80 | 80 | 2, 4 | --- | PC | ST | R | Y | Y |

See note at end of table.

TABLE I. Selection chart - Continued.

| Specification sheet number | Status | Contact Spacing | Min Contacts | Maximum contacts | Contacts row | Contact force 1/ | Contact termination 1/ | Configuration 1/ | Plug or receptacle 1/ | Keying available 1/ | QPL 1/ |
|----------------------------|--------|-----------------|--------------|------------------|--------------|------------------|------------------------|------------------|-----------------------|---------------------|--------|
| MIL-DTL-55302/127 | A | 0.100 | 2 | 65 | 1 | --- | PC | RT | R | Y | Y |
| MIL-DTL-55302/128 | A | 0.100 | 4 | 130 | 2 | --- | PC | RT | R | Y | Y |
| MIL-C-55302/129 | A | 0.100 | 90 | 240 | 2, 3 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/130 | A | 0.100 | 90 | 240 | 2, 3 | --- | PC, WW | ST | R | Y | Y |
| MIL-DTL-55302/131 | A | 0.100 | 64 | 96 | 2, 3 | NA | PC | RT | P | N | Y |
| MIL-C-55302/132 | A | 0.100 | 64 | 96 | 3 | --- | PC, WW | ST | R | N | Y |
| MIL-DTL-55302/133 | A | 0.100 | 32 | 64 | 2 | NA | PC | RT | P | N | Y |
| MIL-DTL-55302/134 | A | 0.100 | 32 | 64 | 2 | --- | PC, WW | ST | R | N | Y |
| MIL-DTL-55302/138 | A | 0.100 | 160 | 160 | 3 | NA | PC | RT | P-PC | Y | Y |
| MIL-DTL-55302/139 | A | 0.100 | 160 | 160 | 3 | L, --- | PC, SW, WW | ST | R-SC | Y | Y |
| MIL-DTL-55302/140 | A | 0.100 | 17 | 65 | 2 | NA | CR, PC, SW, WW | ED, RT, ST | P | Y | N |
| MIL-DTL-55302/141 | A | 0.100 | 72 | 96 | 2 | NA | CR, PC, SS, WW | ED, RT, ST | P | Y | N |
| MIL-DTL-55302/142 | A | 0.100 | 17 | 65 | 2 | --- | CR, PC, WW | RT, ST | R | Y | N |
| MIL-DTL-55302/143 | A | 0.100 | 72 | 96 | 2 | --- | CR, PC, WW | RT, ST | R-PC | Y | N |
| MIL-DTL-55302/144 | A | 0.100 | 8 | 8 | Special | --- | CR, PC, WW | RT, ST | R-PC | Y | N |
| MIL-DTL-55302/145 | A | 0.100 | 11 | 11 | Special | --- | CR, PC, WW | RT, ST | R-PC | Y | N |
| MIL-DTL-55302/146 | A | 0.100 | 11 | 11 | Special | --- | CR, PC, WW | RT, ST | R-PC | Y | N |
| MIL-DTL-55302/147 | A | 0.100 | 11 | 11 | Special | --- | CR, PC, WW | RT, ST | R-PC | Y | N |
| MIL-DTL-55302/148 | A | 0.100 | 11 | 11 | Special | --- | CR, PC, WW | RT, ST | R-PC | Y | N |
| MIL-DTL-55302/149 | A | 0.100 | 8 | 8 | Special | --- | CR, PC, WW | RT, ST | P-SC | Y | N |
| MIL-DTL-55302/150 | A | 0.100 | 11 | 11 | Special | --- | CR, PC, SS, WW | ED, RT, ST | P-SC | Y | N |
| MIL-DTL-55302/151 | A | 0.100 | 11 | 11 | Special | --- | CR, PC, SS, WW | ED, RT, ST | P-SC | Y | N |
| MIL-DTL-55302/152 | A | 0.100 | 11 | 11 | Special | --- | CR, PC, SS, WW | ED, RT, ST | P-SC | Y | N |
| MIL-DTL-55302/153 | A | 0.100 | 11 | 11 | Special | --- | CR, PC, SS, WW | ED, RT, ST | P-SC | Y | N |
| MIL-DTL-55302/154 | A | NA | NA | NA | NA | | | | | NA | N |
| MIL-DTL-55302/155 | A | NA | NA | NA | NA | | | | | NA | N |
| MIL-DTL-55302/156 | A | 0.075 | 10 | 180 | 2 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/157 | A | 0.100 | 64 | 96 | 3 | NA | CP, WW | ST | P | N | Y |
| MIL-DTL-55302/158 | A | 0.100 | 64 | 96 | 3 | --- | PC | RT | R | N | Y |
| MIL-DTL-55302/159 | A | 0.100 | 17 | 65 | 2 | L, NA | CR, SW, PC, WW | RT, ST | P, R-M | Y | Y |
| MIL-DTL-55302/160 | A | 0.100 | 72 | 120 | 2 | L | CR, SW, PC, WW | RT, ST | R-M | Y | Y |
| MIL-DTL-55302/161 | A | 0.100 | 160 | 160 | 3 | L | PC, WW | ST | R-M | Y | Y |
| MIL-DTL-55302/162 | A | 0.100 | 17 | 65 | 2 | NA | CR, PC, SW, WW | RT, ST | P-M | Y | Y |

See note at end of table.

TABLE I. Selection chart - Continued.

| Specification sheet number | Status | Contact Spacing | Min Contacts | Maximum contacts | Contacts row | Contact force 1/ | Contact termination 1/ | Configuration 1/ | Plug or receptacle 1/ | Keying available 1/ | QPL 1/ |
|----------------------------|--------|-----------------|--------------|------------------|--------------|------------------|------------------------|------------------|-----------------------|---------------------|--------|
| MIL-DTL-55302/163 | A | 0.100 | 72 | 120 | 2 | NA | CR, PC, SW, WW | RT, ST | P-M | Y | Y |
| MIL-DTL-55302/164 | A | 0.100 | 160 | 160 | 3 | NA, L | CR, PC, SW, WW | RT, ST | P, P-M | Y | Y |
| MIL-DTL-55302/166 | A | 0.100 | 20 | 400 | 2, 3, 4 | NA | PC | ST | P | Y | Y |
| MIL-DTL-55302/167 | A | 0.100 | 20 | 400 | 2, 3, 4 | NA | WW | ST | P | Y | Y |
| MIL-DTL-55302/168 | A | 0.100 | 20 | 400 | 2, 3, 4 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/169 | A | 0.100 | 20 | 400 | 2, 3, 4 | L | CR, PC | ST | R | Y | Y |
| MIL-DTL-55302/170 | A | 0.100 | 20 | 400 | 2, 3, 4 | L | CR | ST | R | NA | Y |
| MIL-DTL-55302/171 | A | NA | NA | NA | NA | L | | | | NA | Y |
| MIL-C-55302/172 | A | NA | NA | NA | NA | | | | | | Y |
| MIL-DTL-55302/173 | A | 0.100 | 20 | 150 | 2 | NA | CP, PC, WW | ST | P | Y | Y |
| MIL-DTL-55302/174 | A | 0.100 | 20 | 150 | 2 | L | PC | RT | R | Y | Y |
| MIL-DTL-55302/175 | A | 0.100 | 20 | 150 | 2 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/176 | A | 0.100 | 75 | 405 | 3 | NA | CP, PC | ST | P | Y | Y |
| MIL-DTL-55302/177 | A | 0.100 | 75 | 405 | 3 | L | PC | RT | R | Y | Y |
| MIL-DTL-55302/178 | A | 0.100 | 75 | 405 | 3 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/179 | A | 0.100 | 100 | 684 | 4 | NA | CP, PC | ST | P | Y | Y |
| MIL-DTL-55302/180 | A | 0.100 | 100 | 684 | 4 | L | PC | RT | R | Y | Y |
| MIL-DTL-55302/181 | A | 0.100 | 100 | 684 | 4 | NA | PC | RT | P | Y | Y |
| MIL-DTL-55302/182 | A | NA | NA | NA | NA | | | | | | Y |
| MIL-DTL-55302/190 | A | 0.075 | 100 | 100 | 2 | L | PC, SW, WW | ST | R-SC | Y | Y |
| MIL-DTL-55302/191 | A | 0.075 | 100 | 100 | 2 | NA | PC | RT | P-PC | Y | Y |
| MIL-DTL-55302/192 | A | 0.075 | 122 | 152 | 3 | L | PC, SW, WW | ST | R-SC | Y | Y |
| MIL-DTL-55302/193 | A | 0.075 | 122 | 152 | 3 | NA | PC | RT | P-PC | Y | Y |

1/ Codes:

Contact force
HE = hermaphroditic
L = low
--- = standard
NA = not applicable

Contact termination
CR = crimp
CP = compliant pin
PC = printed circuit, solder dip and flexible circuit
SW = solder wire, solder cup and solder eyelet
SS = surface solder
WW = wire wrap

Configuration
ST – straight termination
RT – right angle
ED – edge board

Plug or receptacle
P = plug
R = receptacle
PC = pin contact
SC = socket contact
M = both pin and socket

Keying available
Y = yes
N = no
NA = not applicable

QPL
Y = yes
N = no

MIL-DTL-55302G
SUPPLEMENT 1

CONCLUDING MATERIAL

Custodians:

Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2009-175)

Review activities:

Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at <https://assist.daps.dla.mil>.