

INCH-POUND

MIL-DTL-7554G

22 JUNE 2003

SUPERSEDING

MIL-C-7554F

19 MAY 1993

DETAIL SPECIFICATION

CONTAINER KITS, AIRDROP

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a group of airdrop container kits required for use in the airdrop system.

1.2 Classification. Container kits for airdrop shall be of the following types and load capacities as specified. Specific components may be procured separately (see 6.2):

<u>Types</u>	<u>Load Capacity</u>
A-7A, Sling	500 pounds
A-21, Bag	500 pounds
A-22, Bag	2200 pounds
A-23, Container, High Altitude	2200 pounds

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are cited in sections 3 and 4 of this specification. These lists do not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of these lists, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data that may be of use in improving this document should be addressed to: Natick Soldier Center ATTN: AMSSB-RAD-AD(N), Natick, MA 01760-5017, using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

MIL-DTL-7554G

2.2.1 Specifications and standards. The following specifications and standards form a part of this document to the extent herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-DTL-32075 - Label: For Clothing, Equipage, and Tentage (General Use)

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 40, Philadelphia, PA 19111-5094)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

NATICK SOLDIER CENTER

11-1-2616 - Container, High Altitude, A-23 Assembly
51C6716 - Container, Kit Assembly-Sling Type A-7A, 500 lb. Capacity
51C6739 - Container Kit Assembly Bag, Cargo, Aerial Delivery Type A-21
500 lb. Capacity
50B7702 - Container Kit Assembly Bag, Cargo, Aerial Delivery Type A-22
2200 lb. Capacity

(Copies are available from the Natick Soldier Center, ATTN: AMSSB-RAD-AD(N) – CONFIGURATION MANAGER, Natick, MA 01760-5017.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to a first article inspection in accordance with 4.2.

MIL-DTL-7554G

3.2 Materials. Materials shall conform to the requirements of the applicable Technical Data Package (TDP), to subsidiary specifications and standards applicable thereto and as specified herein.

3.2.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided the materials meet or exceed the operational requirements, and promote economically advantageous life cycle costs.

3.3. Construction. The construction shall conform in all respects to the applicable drawings and all subsidiary drawings pertaining thereto and as specified herein.

3.3.1 Type 301 stitching. Ends of all type 301 stitching shall be backstitched or overstitched not less than ½ inch in accordance with the required stitch pattern.

3.3.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during the stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for box-x and W-W stitching) from the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch from the defective area, (1/2 inch for box-x and W-W stitching), continue over the defective area, and continue a minimum of 1 inch (1/2 inch for box-x and W-W stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.2 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met, and at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching.

3.4 Cotton tape and webbing.

3.4.1 Wax-dipping. All ends of cotton tape and webbing, which will be exposed in the finished item, shall be dipped a minimum of ½ inch in a 50-50 mixture of beeswax and paraffin. During the dipping operation, the temperature of the wax mixture shall be maintained at 180°F ± 20°F.

3.4.2 Searing. All exposed ends of nylon webbing and cord shall be seared smooth and even.

3.5 Marking. Unless otherwise specified herein or on the drawings, all marking on container kits or components shall conform to type IV, class 11 of MIL-DTL-32075, except that fastness to

MIL-DTL-7554G

accelerated laundering shall not apply. In lieu thereof, marking shall show fair fastness to weathering after 40 fading hours when tested in accordance with DDD-L-20.

3.6 Workmanship. All components and assemblies of the container kits shall be free from dirt, grease, oil or other foreign matter. External surfaces shall be free from sharp edges or burrs. Components shall not be fractured, cracked, buckled, loose, dented, missing, malformed or misaligned. Seams and stitching shall be free of needle damage (cuts or chews), omitted and unrelated stitching, open and broken seams and loose threads. The end item shall conform to the quality of product established by this specification.

4. VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

- a. First article inspection (see 4.2).
- b. Conformance inspection (see 4.3).

4.2 First article inspection. First article inspection shall be performed on one complete container assembly, unless otherwise stated in the contract, when a first article sample is specified (see 3.1). The inspection shall include the examinations of 4.3.1, 4.3.2, 4.4, and 4.5. Any defect or nonconformance shall be cause for rejection of the first article.

4.3 Conformance inspection. Conformance inspections shall include the examinations of 4.3.1, 4.3.2, 4.4 and 4.5. Sampling plans and acceptance/rejection criteria for 4.4 and 4.5 shall be as specified in the contract or purchase order. Assemblies which fail the acceptance criteria shall be cause for rejection of the lot.

4.3.1 Component and material inspection. Components and materials shall be inspected in accordance with all of the requirements of reference documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details and dimensional requirements, which cannot be examined in the finished product, are in accordance with specified requirements. The Government reserves the right to exclude from consideration of acceptance any material or service for which in-process inspection has indicated nonconformance.

4.4 End item visual examination. The end items shall be examined for the defects listed in table I. Any nonconformance to the Technical Data Package (TDP) shall be classified as a defect.

MIL-DTL-7554G

TABLE I. End Item Visual Defects

Examine	Defect	Classification	
		Major	Minor
Materials	Wrong color		201
Construction and assembly	Any component missing, loose or not securely retained	101	
Cleanliness	Dirt, grease, oil, or foreign matter		202
	Thread ends not trimmed throughout		203
Stitches and stitching	Not type of stitch specified	102	
	Stitching pattern not as specified	103	
	One stitch per inch under minimum specified		204
	Two or more stitches per inch under minimum specified	104	
	One stitch per inch over the maximum specified		205
	Two or more stitches per inch over maximum specified	105	
	NOTE: Variation in the number of stitches per inch cause by the operator speeding up the machine and pulling fabric to sew over heavy places, heavy seams, or in turning corners shall be classified as follows:		
	a. Within the major defect classification – Minor defect		
	b. Within the minor defect classification – No defect		
	Thread breaks and two or more consecutive skipped stitches not overstitched as specified		206
	Ends of stitching not secured as specified		207
	Any row of stitching missing	106	
	Needle damage (cuts or chews)	107	
	Stitch margin or gage not as specified		208
	Stitching runoffs not restitched in accordance with the applicable stitch pattern		209

MIL-DTL-7554G

TABLE I. End Item Visual Defects (cont'd)

Examine	Defect	Classification	
		Major	Minor
Stitches and stitching (con't)	Loose tension, resulting in loose top or bobbin thread; or tight tension resulting in tightness or puckering of material at stitch line		210
Cloth, webbing, tape, thread (as applicable)	Not type or size specified	108	
	Cut, hole, abrasion or frays, thin or weak area	109	
	Edge beaded or corded		211
	Exposed ends not waxed or seared, as specified		212
Hardware	Component fractured, malformed, bent or otherwise damaged; protective finish omitted; corroded areas, burrs or sharp edges	110	
	D-ring not assembled as specified	111	
	Snaphook not assembled as specified		213
	Adaptor assembled with protruding lip exposed		214
Plywood skid (when required)	Not grade or type specified	112	
	Surfaces not painted as required	113	
	Grain direction of top and bottom ply not as specified	114	
	Gaps and voids at edges and bevel not filled as specified	115	
	Plugged areas not sanded flush		215
Identification marking (including U.S. and special marking)	Missing, illegible, incorrect, wrong color, improper location or not applied as specified		216

4.5 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within

MIL-DTL-7554G

the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

6.1 Intended use. The container kits are intended for use in the airdrop of miscellaneous equipment and bulky supplies from aircraft in flight to ground.

6.2 Acquisition requirements. Acquisition documents should specify the following:

- a. Title, number, and date of this specification.
- b. Type of airdrop container kit required (see 1.2).
- c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).
- d. When a first article is required (see 3.1).
- e. Sampling plan (see 4.3).
- f. Packaging requirements (see 5.1).
- g. Components, when procured separately (see 6.3).

6.3 Components. The following components may be procured separately:

Quick release strap for: type A-21
Suspension webs for: type A-22 and A-23
Skids for: type A-22 and A-23
Covers for: type A-22 and A-23

6.4 Subject terms (key word) listing.

Air delivery
Equipment

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - GL2
Air Force - 99

Preparing Activity:
Army - GL2

(Project 1670-1043)

Review Activities:
Air Force - 11

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:

1. **DOCUMENT NUMBER**
MIL-DTL-7554G

2. **DOCUMENT DATE (YYYYMMDD)**
20030622

3. **DOCUMENT TITLE**
Container Kits, Airdrop

4. **NATURE OF CHANGE** (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. **REASON FOR RECOMMENDATION**

6. SUBMITTER

a. NAME (Last, First, Middle Initial)

b. ORGANIZATION

c. ADDRESS (Include Zip Code)

d. TELEPHONE (Include Area Code)
(1) Commercial
(2) DSN
(if applicable)

7. **DATE SUBMITTED**
(YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME
Natick Soldier Center

b. TELEPHONE (Include Area Code)
(508) 233-4258

c. ADDRESS (Include Zip Code)

AMSSB-RAD-AD(N), J. Riley
Natick, MA 01760-5017

IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: