

NOT MEASUREMENT SENSITIVE
------------------------------

MIL-DTL-81997C

10 October 2002

---

SUPERSEDING

MIL-P-81997B

30 September 1983

## DETAIL SPECIFICATION

POUCHES, CUSHIONED, FLEXIBLE,  
ELECTROSTATIC-PROTECTIVE, TRANSPARENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers flexible, electrostatic-protective, transparent pouches used in military preservation.

1.2 Classification. The types of pouches are as follows (see 6.2):

Type I     -     Double-walled electrostatic shielding reclosable pouches containing permanently encapsulated cushioning

Type II    -    Single-walled static dissipative pouches with cushioned inner walls

## 2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Air Warfare Center Aircraft Division (Code 414100B120-3), Highway 547, Lakehurst, NJ 08733-5100, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.
---

AMSC N/A

FSC 8105

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

## MIL-DTL-81997C

2.2 Government documents.

2.2.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (Do DISS) and supplement thereto, cited in the solicitation (see 6.2).

## SPECIFICATIONS

## FEDERAL

PPP-C-795 - Cushioning Material, Packaging (Flexible Closed Cell Plastic Film, for Long Distribution Cycles) (Inactive for New Design).

## DEPARTMENT OF DEFENSE

MIL-PRF-81705 - Barrier Materials, Flexible, Electrostatic Protective, Heat-Sealable.

## STANDARDS

## DEPARTMENT OF DEFENSE

MIL-STD-2073-1 - DoD Standard Practice for Military Packaging.

(Unless otherwise indicated, copies of the above specifications and standards are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

## AMERICAN SOCIETY FOR QUALITY CONTROL (ASQC)

ASQC-Z1.4 - Procedures, Sampling and Tables for Inspection by Attributes (DoD adopted).

(Application for copies should be addressed to the American Society for Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 53201-4606).

## MIL-DTL-81997C

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

### 3. REQUIREMENTS

3.1 First article. When specified (see 6.2), samples shall be subjected to first article inspection in accordance with 4.2.

#### 3.2 Material.

3.2.1 Type I. Type I pouches shall be constructed from a composite material consisting of two outer walls that encapsulate cushioning material conforming to PPP-C-795, class 2 (thin thickness). The outer walls shall be fabricated of material conforming to MIL-PRF-81705, type III.

3.2.2 Type II. Type II pouches shall be constructed solely of cushioning material conforming to PPP-C-795, class 2 (thin thickness).

3.3 Construction. Pouches shall be formed using two sheets of material, or by folding one sheet of material in half, and heat sealing along two sides and the bottom edge as required. The cushioning medium shall face toward the inside of all pouches. The side seams shall be parallel to each other and at right angles to the bottom seal or fold. The cushioning for type I pouches shall be sized to ensure a snug fit between layers of MIL-PRF-81705, type III, barrier material and shall not extend beyond the heat sealing area of the barrier material. The cushioning shall be encapsulated within the barrier material by sealing across the open or top edge of the pouch. The completed pouch shall thus contain only one opening for inserting the item.

3.3.1 Closure (type I only). The open end or top edge of type I pouches shall be provided with a reclosable zipper-type interlocking closure. The closure shall be effected by two strips – a rib element on one side of the pouch and a complementary groove element on the other side – that shall be heat sealed to the pouch. The zipper so formed shall be closable by applying finger pressure. The strips shall have a flange a minimum of 1/2 inch in width extending above the zipper closure. A colored line, approximately 1/4 inch above and parallel to the zipper track, shall be marked to indicate where the flange shall be pulled to open the zipper. The closure material shall be electrostatic protective and meet all requirements of MIL-PRF-81705, type III.

3.4 Dimensions and tolerances. The length and width of pouches shall be as specified in the contract or purchase order. For type I pouches, width shall be measured between the inside corners of the reclosable seal when open. For type II pouches, the width shall be measured from the inside edges of the side seams.

## MIL-DTL-81997C

For type I pouches, length shall be measured from the inside edge of the bottom seam or fold to the inside edge of the reclosable seal when closed. For type II pouches, length shall be measured from the inside edge of the bottom seam or bottom fold to the inside edge of the opening. Width and length tolerances shall be +1/4 inch and -1/8 inch. Common pouch stock sizes are listed in table I.

TABLE I. Common pouch sizes and designators.

Size designator	Inside dimensions (W x L) (inches)
01	2-1/2 x 3
02	2-1/2 x 6
03	3 x 5
04	4 x 6
05	4 x 8
06	4 x 12
07	6 x 6
08	6 x 8
09	8 x 12
10	10 x 10
11	10 x 12
12	10 x 13
13	12 x 12

3.5 Identification. Each pouch shall be identified with the following information: This specification number and revision; type; pouch manufacturer's name; month and year of pouch fabrication. When specified (see 6.2), the following additional cautionary markings shall be applied to or accompany each pouch:

ATTENTION  
 STATIC SENSITIVE DEVICES  
 HANDLE ONLY AT STATIC SAFE WORK STATIONS

The color and position of these markings is optional. A label or labels shall be secured to an outer face of the pouch using adhesive or any method that provides a secure attachment.

3.6 Seam continuity. Heat sealed seams and the reclosable closure for type I pouches shall be complete and unbroken around the perimeter of the pouch, as specified in 4.5.

3.7 Seam strength. Heat seals shall meet the requirements of MIL-STD-2073-1, Appendix G (see 4.6).

## MIL-DTL-81997C

3.8 Sealing recommendations (type II only). Each unit package containing type II pouches shall include a sheet legibly marked with the following heat-sealing information:

- a. Jaw type sealer (temperature, pressure and dwell).
- b. Band type sealer (temperature, pressure, and dwell).
- c. Rotary type sealer (preheat, pressure, and speed).

3.9 Workmanship. Pouches shall be free from any foreign matter, tears, cuts, splits, slits, creases, or other imperfections.

#### 4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

- a. First article inspection (see 4.2).
- b. Conformance inspection (see 4.3).

4.2 First article inspection. First article inspection shall consist of all the tests and examinations specified in this specification.

4.3 Conformance inspection. Conformance inspections shall consist of all the visual examinations listed in 4.4, the seam continuity test, and heat-sealed seam test specified in paragraphs 4.5 and 4.6, respectively.

4.3.1 Sampling for conformance inspection. For the purpose of determining the sample size in accordance with ASQC-Z1.4, the lot size (see 6.3) shall be expressed in number of bags produced in one production run and shall use an inspection level of S-1 for testing and S-3 for visual examination.

4.4 Visual examination of end item for defects in materials, construction, closure, dimensions and tolerance, identification, and sealing recommendations. The sample unit for the end item visual inspection shall be one pouch. The sample unit shall be visually inspected and measured to ensure it meets the requirements specified in 3.2, 3.3, 3.3.1, 3.4, 3.5, 3.8, and 3.9.

4.5 Seam continuity test. Water containing a dye such as methyl violet shall be poured into the pouch so that the water solution will cover an entire side of the pouch when laid on its side. The pouch shall be closed with a supplemental final heat seal or by closing the zipper closure, as applicable. Manually hold the pouch in a vertical attitude. Rotate the bag 360° in 90°

## MIL-DTL-81997C

increments so that each sealed edge is on the bottom for thirty seconds. Dye leakage through any original heat seal or the zipper closure indicates failure to meet the seam continuity requirement.

4.6 Heat-sealed seam test. Heat-sealed specimens shall be tested in accordance with the heat-sealed seam test specified in MIL-STD-2073-1, Appendix G, using a static load of 2-1/2 pounds. The number of specimens to be tested from each pouch shall be reduced when the size of the pouch precludes testing the prescribed number of specimens.

## 5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

## 6. NOTES

6.1 Intended use. Pouches covered by the requirements of this specification are intended for the packaging of electronic components, circuit boards, and assemblies sensitive to the damaging effect of electrostatic discharge. The pouches are designed for use as interior packages directly in contact with the contained part. Where additional cushioning, electromagnetic interference or electrostatic shielding, or watervaporproof barriers are required, they are to be used only outside the pouches, not inside them. The pouches may be used during assembly, handling, storage, and shipment of any electrostatic discharge sensitive item. There are no commercial equivalents that meet the physical, electrostatic protection, and corrosion requirements necessary to protect materiel that is exposed to the operational naval aviation environment. Specifically, specialized Method of Preservation GX of MIL-STD-2073-1C uses MIL-DTL-81997 to provide watervaporproof and electrostatic discharge protection for applicable items encountering the above conditions approved under MIL-STD-2073-1C.

6.2 Acquisition requirements. Acquisition documents must specify the following:

- a. Title, number, and date of this specification.
- b. Type of bag (see 1.2).
- c. Issue of DoDISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.2.1).

## MIL-DTL-81997C

- d. Size of pouches (inside length and width dimensions) (see 3.4 and table I).
- e. If additional pouch identification marking is required (see 3.5).
- f. If first article inspection is required (see 4.2).
- g. Packaging requirements (see 5.1).

6.3 Lot size. Inspection lot consists of all bags manufactured by the same process from the same raw material during one production run.

6.4 Specification part numbers. Specification part numbers may be used to identify pouches covered by this specification. This part number will definitize a given pouch in accordance with the following established system:

Specification Part Number: M81997-X YY

where X = the type of pouch (see 1.2)

YY = the pouch size designator (see table I)

For example, the specification part number for a pouch conforming to MIL-DTL-81997, type I, with dimensions of 6" x 6" would be:

M81997-1 07

6.5 Subject term (keyword) listing.

Bag  
Container  
Packaging material  
Preservation  
Reclosable

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes

MIL-DTL-81997C

CONCLUDING MATERIAL

Custodians:

Army – SM  
Navy – AS  
Air Force – 11  
DLA – DH

Preparing Activity:

Navy – AS  
  
(Project 8105-0383)

Review activities:

Army – AT, AV, EA, GL3, MI  
Navy – MC, OS, SA, SH



# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

## INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

<b>I RECOMMEND A CHANGE:</b>		<b>1. DOCUMENT NUMBER</b> MIL-DTL-81997C	<b>2. DOCUMENT DATE (YYYYMMDD)</b> 10 October 2002
<b>3. DOCUMENT TITLE</b> POUCHES, CUSHIONED, FLEXIBLE, ELECTROSTATIC-PROTECTIVE, TRANSPARENT			
<b>4. NATURE OF CHANGE</b> ( <i>Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.</i> )			
<b>5. REASON FOR RECOMMENDATION</b>			
<b>6. SUBMITTER</b>			
a. NAME ( <i>Last, First, Middle Initial</i> )		b. ORGANIZATION	
c. ADDRESS ( <i>Include ZIP Code</i> )		d. TELEPHONE ( <i>Include Area Code</i> ) (1) Commercial  (2) DSN ( <i>If applicable</i> )	<b>7. DATE SUBMITTED</b> (YYYYMMDD)
<b>8. PREPARING ACTIVITY</b>			
a. NAME COMMANDER NAVAL AIR WARFARE CENTER AIRCRAFT DIVISION		b. TELEPHONE ( <i>Include Area Code</i> ) (1) Commercial (732) 323-2947 (2) DSN 624-2947	
c. ADDRESS ( <i>Include ZIP Code</i> ) CODE 414100B120-3 HIGHWAY 547 LAKEHURST, NJ 08733-5100		<b>IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:</b> Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888	