

METRIC

MIL-DTL-83527B
SUPPLEMENT 1
5 August 2003

DETAIL SPECIFICATION

CONNECTORS, PLUG AND RECEPTACLE, ELECTRICAL, RECTANGULAR MULTIPLE INSERT TYPE, RACK TO PANEL, ENVIRONMENT RESISTING, 150°C TOTAL CONTINUOUS OPERATING TEMPERATURE, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-83527B, dated 15 July 2003.

SPECIFICATION SHEETS

- | | |
|---------------|---|
| MIL-C-83527/1 | - Connector, Plug, Electrical, Rectangular, Multiple Insert Type, Rack to Panel, Environment Resisting, 150°C Continuous Operating Temperature, Shell Size 2. |
| MIL-C-83527/2 | - Connector, Receptacle, Electrical, Rectangular, Multiple Insert Type, Rack to Panel, Environment Resisting, 150°C Continuous Operating Temperature, Shell Size 2. |
| MIL-C-83527/3 | - Connector, Plug, Electrical, Rectangular, Multiple Insert Type, Rack to Panel, Environment Resisting, 150°C Continuous Operating Temperature, Shell Size 3. |
| MIL-C-83527/4 | - Connector, Receptacle, Electrical, Rectangular, Multiple Insert Type, Rack to Panel, Environment Resisting, 150°C Continuous Operating Temperature, Shell Size 3. |
| MIL-C-83527/5 | - Connector, Plug, Electrical, Rectangular, Multiple Insert Type, Rack to Panel, Environment Resisting, 150°C Continuous Operating Temperature, Shell Size 4. |
| MIL-C-83527/6 | - Connector, Receptacle, Electrical, Rectangular, Multiple Insert Type, Rack to Panel, Environment Resisting, 150°C Continuous Operating Temperature, Shell Size 4. |
| MIL-C-83527/7 | - Connector, Plug, Electrical, Rectangular, Rack to Panel, Environment Resisting, 150°C Continuous Operating Temperature, Multiple Inserts. |
| MIL-C-83527/8 | - Connector, Receptacle, Electrical, Rectangular, Rack to Panel, Environment Resisting, 150°C Continuous Operating Temperature, Multiple Inserts. |

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4611-000)

Review activity:
Air Force - 99