

U. S. AIR FORCE
SPECIFICATION
NOTICE

MIL-E-5272A
Notice No. 1
16 November 1953

ENVIRONMENTAL TESTING, AERONAUTICAL AND
ASSOCIATED EQUIPMENT, (GENERAL SPECIFICATION FOR)

1. Specifications citing MIL-E-5272 issued prior to 16 September 1952 made reference to the test procedures of MIL-E-5272(USAF). In the revision of Specification MIL-E-5272(USAF) to Specification MIL-E-5272A, modifications were made which required renumbering of certain test procedures. Those test procedures of MIL-E-5272(USAF) which were renumbered are indicated in Table I. Therefore, when specifications dated prior to 16 September 1952 invoke the use of the tabulated tests, the substitution indicated will apply.

TABLE I

Procedure of MIL-E-5272 (USAF)	Procedure of MIL-E-5272A
High Temperature Tests Procedure II	High Temperature Tests Procedure I (Except that the temperature will be 85°C (185°F) in lieu of 71°C (160°F).
Low Temperature Tests Procedure III	Low Temperature Tests Procedure II
Altitude Tests Procedure III Procedure IV	Altitude Tests Procedure II Procedure II
Sand and Dust Tests Procedure II	Sand and Dust Tests Procedure I (utilizing 2300±500 feet per minute in lieu of 200±100 FPM.)
Immersion Tests Procedure II	Immersion Tests Procedure I

THIS NOTICE SHOULD BE FILED IN FRONT OF SPECIFICATION MIL-E-5272A.

(Copies of this notice may be obtained from the Commander, Wright Air Development
Center, Wright-Patterson Air Force Base, Ohio.)