

U. S. AIR FORCE  
SPECIFICATION  
NOTICE

MIL-E-5272A  
Notice No. 1

16 November 1953

ENVIRONMENTAL TESTING, AERONAUTICAL AND  
ASSOCIATED EQUIPMENT, (GENERAL SPECIFICATION FOR)

1. Specifications citing MIL-E-5272 issued prior to 16 September 1952 made reference to the test procedures of MIL-E-5272(USAF). In the revision of Specification MIL-E-5272(USAF) to Specification MIL-E-5272A, modifications were made which required renumbering of certain test procedures. Those test procedures of MIL-E-5272(USAF) which were renumbered are indicated in Table I. Therefore, when specifications dated prior to 16 September 1952 invoke the use of the tabulated tests, the substitution indicated will apply.

TABLE I

| Procedure of<br>MIL-E-5272 (USAF)               | Procedure of<br>MIL-E-5272A   |
|---|---|
| High Temperature Tests<br>Procedure II          | High Temperature Tests<br>Procedure I (Except that<br>the temperature will be<br>85°C (185°F) in lieu of<br>71°C (160°F). |
| Low Temperature Tests<br>Procedure III          | Low Temperature Tests<br>Procedure II   |
| Altitude Tests<br>Procedure III<br>Procedure IV | Altitude Tests<br>Procedure II<br>Procedure II  |
| Sand and Dust Tests<br>Procedure II             | Sand and Dust Tests<br>Procedure I (utilizing<br>2300±500 feet per minute<br>in lieu of 200±100 FPM.)                     |
| Immersion Tests<br>Procedure II                 | Immersion Tests<br>Procedure I  |

THIS NOTICE SHOULD BE FILED IN FRONT OF SPECIFICATION MIL-E-5272A.

(Copies of this notice may be obtained from the Commander, Wright Air Development  
Center, Wright-Patterson Air Force Base, Ohio.)